

# **HASviolet**

Installation and User Guide for RPI

Hudson Valley Digital Network

8 March 2021

v3.2

# Table of Contents

Introduction.....	3
Design.....	3
Hardware.....	4
Software.....	5
Operating System.....	5
Applications.....	5
Installation.....	5
Preparation.....	5
Remote Connectivity.....	6
Setup.....	7
Install.....	7
Using HASviolet RPi.....	8
Overview.....	8
Core Applications.....	9
HASviolet-config.py.....	9
HASviolet-beacon.py.....	9
HASviolet-chat.py.....	10
HASviolet-tx.py.....	10
HASviolet-rx.py.....	10
Libraries.....	11
HASvioletRF.py.....	11
HASvioletHID.py.....	11
Sensors.....	12
HASviolet-atmos.py.....	12
HASviolet-distance.py.....	12
HASviolet-gps.py.....	12
HASviolet-sensors.py.....	12
Appendices.....	13
XARPS.....	13
Payload Fields.....	13

# Introduction

Welcome to HASviolet!

Within Hudson Valley Digital Network (HVDN) we look at HASviolet as a project that is as much (if not more) about the journey as it is about the destination. The project's origins started with a member of HVDN sharing the idea "I've been wanting to do a "communicator" for a while. Something that someone could use over relatively short distances to send text messages back and forth. I have been looking for others to work on a project with too!"

After some investigation LoRa was something to consider since it "should play well with the hacker/maker crowd and possibly the IoT/computer science area." From this point we thought it was a good idea to take forward and started developing a concept around it.

We sifted through a number of existing published LoRa projects using Raspberry Pi and various microcontrollers. We found many github sites with code, libraries, and recommended hardware but most of them were just "proof of concepts", no demonstrations of use cases, or sharing of lessons learned whether as a "lone eagle" or part of a team.

Since we would be building new and flexing existing skillsets along the way our differentiation with this project would be sharing the journey through articles, videos, and (hopefully) good documentation.

This guide will help you get started with HASviolet beginning with required RPi hardware and Raspberry Pi OS installation. We will follow this with HASviolet installation, configuration, and the HASviolet application themselves. All references to "RPi" in this guide are to the Raspberry Pi Zero WH hardware.

## Design



When we embarked on the HASviolet project, we reviewed all the LoRa projects that were already out there. The vast majority of LoRa projects chose microcontrollers as their platform but we noticed many LoRa projects hit a roadblock after they reached basic objectives such as basic text chat between units. We came to the conclusion that unless a project is use-case driven and highlights the journey to a level of detail for others to build with you, the project just whithers over time especially with microcontroller based projects. We opted to lead the HASviolet project with a RPi solution first since it provides an optimal educational platform opportunity and would ease the "learning curve" as microcontroller options are included.

# Hardware

HASviolet consists of the following architecture components:

- Single board computer
- Display (OLED)
- Input (Pushbuttons)
- Network (WiFi)
- RF Module (LoRa)
- RF Antenna
- Power (2.5A)
  - Uses case requiring portable power find 1200mA H delivers ~7 hours of RF at low power when sent at 5 second intervals.

Tested hardware includes the following:

<p><u>Raspberry Pi Zero WH (Wireless with Headers)</u></p> <ul style="list-style-type: none"><li>• You will need to solder the 20-pin header to the board.</li></ul>	
<p><u>Adafruit LoRa Radio Bonnet with OLED – RFM95W @915Mhz</u></p> <ul style="list-style-type: none"><li>• Requires an antenna connected via a male U.FL connector</li></ul>	
<p><u>SanDisk Ultra 16GB RAM Class 10 MicroSD</u></p> <ul style="list-style-type: none"><li>• RPi require quality microSD cards at least Class 10</li></ul>	
<p><u>Power Source 5V @ 2.5A minimum</u></p> <ul style="list-style-type: none"><li>• The hardware can be powered via USB to PC as part of setup but for operation it needs to be on a standalone power source.</li></ul>	
<p><u>900 MHz Omnidirectional "stub" Antenna</u></p> <ul style="list-style-type: none"><li>• Our antenna</li></ul>	
<p><u>U.FL IPEX to SMA Connector</u></p> <ul style="list-style-type: none"><li>• Connect the omnidirectional antenna to the Adafruit LoRa Radio Bonnet</li></ul>	
<p>If you plan on connecting i2c sensors we recommend using the <u>Sparkfun Qwiic Connect System</u> adding the <u>Sparkfun Qwiic HAT for RPI</u> to your hardware stack.</p>	

# Software

## Operating System

The Raspberry Pi OS (32-bit) Lite image (RPi OS Lite) is chosen because it does not include desktop overhead and the unnecessary services and corresponding “bloat” on CPU and memory that go with it. HASviolet does not use the desktop.

## Applications

The HASviolet suite of applications are written in Python 3.7.X using [Visual Studio Code](#). Shell scripts ([Bash](#)) are used for creating the HASviolet installation environment.

## Installation

An overview of building HASviolet starts with:

- microSD card preparation
  - From a computer download and install RPi OS Lite on a microSD card.
  - Mount the microSD card and create/edit files so you can connect to the RPi
    - Connecting directly, WiFi, or USB
- RPi Setup
  - Insert microSD card into RPi and boot
  - Connect to RPi and run the Raspi-config tool to configure the RPi
- HASviolet Install
  - Reboot RPi, login as Pi, and clone the HASviolet repo
  - Run HASviolet install script then HASviolet config tool

## Preparation

Start with [downloading the RPi OS Lite](#) on a computer you will be connecting the microSD card to. Whether your computer is Windows, Linux, or OSX, the Raspberry Pi site provides you instructions and tools on [installing the image on the microSD card](#).

Once the image has been created on the microSD card, you will need to mount the card and create/edit files if you plan to remotely connect to the RPi via WiFi or USB. If you plan on using a directly connected monitor and keyboard you will require a mini HDMI adapter for your monitor and a USB OTG cable to attach a keyboard. If this is how you will connect to setup your Pi then you can jump to the RPi Setup section.



# Remote Connectivity

## Via IP through Wireless Connection

<ul style="list-style-type: none"><li>You can use this method if you wish to access the RPi via an existing WiFi network</li><li>Change to the <b>boot</b> directory on the SD card</li><li>Enable <b>ssh</b> access by creating a blank file named <b>ssh</b></li></ul>	cd /media/sd-card/boot touch ssh
<ul style="list-style-type: none"><li>Within the boot directory, create a file called <b>wpa_supplicant.conf</b> and edit</li></ul>	vi wpa_supplicant.conf
<ul style="list-style-type: none"><li>When you have opened the new file, add the configuration at right and save</li><li>Be sure to replace <b>SSID</b> with your local wireless network SSID</li></ul>	country=US ctrl_interface=DIR=/var/run/wpa_supplicant GROUP=netdev update_config=1 network={ ssid="MyWiFiNetwork" psk="aVeryStrongPassword" key_mgmt=WPA-PSK }
<ul style="list-style-type: none"><li>Change to your home directory, run <b>sync</b> as sudo, and unmount the SD card</li><li>Remove the SD card</li></ul>	cd ~ sudo sync umount /media/sd-card/root umount /media/sd-card/boot

## Via IP through USB connection

If WiFi is not available, using zero-configuration networking services may be an option if you are running OSX or Windows with Apple BonJour Services installed. Linux users will need to consult their distribution documentation on adding USB as an IP interface and any configuration changes to the installed Avahi software.

<ul style="list-style-type: none"><li>Change to the <b>boot</b> directory on the SD card</li><li>Edit the <b>config.txt</b> file</li></ul>	cd /media/sd-card/boot vi config.txt  Append the following line: dtoverlay=dwc2  Then save the file.
<ul style="list-style-type: none"><li>While in the boot directory, edit the <b>cmdline.txt</b> file, replace a line, then save file.</li></ul>	vi cmdline.txt  Replace with the following all as one continuous line:  dwc_otg.lpm_enable=0 console=serial0,115200 console=tty1 root=/dev/mmcblk0p2 rootfstype=ext4 elevator=deadline fsck.repair=yes rootwait modules-load=dwc2,g_ether quiet init=/usr/lib/raspi-config/init_resize.sh  Then save the file.
<ul style="list-style-type: none"><li>Remaining in the boot directory, enable <b>ssh</b> access by creating a blank file named <b>ssh</b></li></ul>	touch ssh

## Setup

• Insert SD card	If accessing via IP over USB, connect PC USB port to RPi USB Data port (next to mini-HDMI port)
• Connect RPi and Power on	ssh -l pi -o IdentitiesOnly=yes <yourpi>
• Log in with default pi:raspberry	If connecting via SSH for first time click <b>yes</b> to <b>accept fingerprint</b>
• Run Configuration tool	sudo raspi-config
• Navigate through each menu making selections as noted then exit tool	1. System Options S1 Wireless. LAN update (if using to connect) S2 Password. (change password) S4 Hostname. Change hostname to <b>your call + number [50-98] yourcall-50</b> S5 Boot/Auto Login select <b>B1</b> 2. Display Option ( <b>Nothing to do</b> ) 3. Interfacing options P2 SPI <b>Enable</b> P4 I2C <b>Enable</b> P5 I2C <b>Enable</b> 4. Performance Options P2 GPU Memory: <b>Set to 16</b> 5. Localization Options L1 Change Local to < <b>your-local</b> >.UTF-8 L2 Change Timezone L4 WLAN Country 7. Advanced Options A1 Expand filesystem 8. Update
• Run <b>sync</b> as sudo, and <b>reboot</b> (ignore errors)	sudo sync sudo reboot

## Install

• SSH into your Pi	sudo apt-get update sudo apt-get -y upgrade sudo sync sudo reboot
• Run OS update and upgrade	wget https://github.com/hudsonvalleydigitalnetwork/hasviolet.git
• Run sync and reboot	
• Log back in as pi and clone the HASviolet repo	
• Change directories to /home/pi/HASviolet	
• Run ./HASviolet_config.py	
• Change <b>NOCALL</b> to your call or handle	===== HASviolet Config Tool =====  1 Change my Call / Handle PURPLE 2 Change my SSID 50 3 Change my Beacon QRZ QRZ QRZ 4 Change dest Call / Handle BEACON 5 Change dest SSID 99  ----- 11 Change Radio RFM9X 12 Change Frequency (Hz) 911250000 13 Change Transmit Power 10 14 Change Modem 0 15 Change Bandwidth (Hz) 125000 16 Change Spread Factor 7 17 Change Coding Rate 8  ----- 40 Show current HASviolet.json 41 Generate ModemRegister settings  51 Write changes to hasVIOLET.json  99 About HASviolet-config 0 Exit program  Select menu item:
• Change <b>SSID</b> to a number 50 – 99	
• If needed increase <b>Transmit power</b> from 5 to as high as 20	
• Change <b>beacon</b> as you see fit	
• Save and exit	
• Installation is complete. Apps are run from /home/pi/ <b>HASviolet</b>	

**HASviolet is now installed!**

# Using HASviolet RPi

## Overview

HASviolet is a data communications application suite designed to be used on RF networks such as LoRa. The working directory for all applications is installed in **/home/pi/HASviolet**

The application suite is developed in Python and includes the following core applications;

- **HASviolet\_config.py** to configure your station with your call sign/handle
- **HASviolet\_BEACON.py** sends a repeating broadcast message
- **HASviolet\_chat.py** is a half-duplex messaging app
- **HASviolet\_TX.py** sends a message to another station
- **HASviolet\_RX.py** listens for messages from other stations
- **HASvioletRF.py** is a RF interface library used by all HASviolet applications to support abstraction from the variety of RF libraries/modules expected to be supported over time.
- **HASvioletHID.py** is a HID library (OLED, Buttons, etc) used by all HASviolet applications to support abstraction from the variety of modules/methods to be supported over time.
- **HASrf95.py** is a HOPE RFM95 library referenced by the **HASvioletRF** library
- **font5x8.bin** is a font file for OLEDs as used by the **HASvioletHID** library

Core and other applications have the dependency on the following config files stored in the **cfg/** directory;

- **HASviolet.json** is a configuration file generated by **HASviolet-config.py**
- **hvdn-logo.xbm** is a bitmap graphic file used by the **HASvioletHID** library

HASviolet includes a WebUI. Applications that support this include;

- **HASviolet\_websox.sh** is a script that can install, start, stop, and remove the HASviolet Web server as a daemon on startup
- **HASviolet\_websox.service** is a systemd file installed that starts **HASviolet\_websox.py**
- **HASviolet\_websox.py** is a web server that runs on RPi bootup and serves HTML, CSS, and Javascript files as the WebUI.
- **HASviolet.crt** is a certificate file for SSLv3/TLS used by **HASviolet\_web.py**
- **HASviolet.key** is a key file for SSLv3/TLS used by **HASviolet\_web.py**
- **HASviolet.pwf** is a password file used by **HASviolet\_web.py**
- **HASviolet\_account.py** is a ID/password management tool used for **HASviolet.pwf**

## Core Applications

### ***HASviolet\_config.py***

Configure your station. Updates HASviolet.json

```
Usage: HASviolet-config.py
```

### ***HASviolet\_BEACON.py***

Beacon a LoRa message

```
Usage: HASviolet_BEACON.py -c COUNT -t DELAY "message"
```

#### OPTIONS

```
-h, --help           show this help message and exit
-d DESTINATION, --destination DESTINATION
                    Destination
-m MESSAGE, --message MESSAGE
                    Message in quotes
```

## ***HASviolet\_CHAT.py***

Half-duplex LoRa messaging app

```
Usage: ./HASviolet_CHAT [-r] [-s]

OPTIONS
-h, --help      show this help message and exit
-r, --raw_data  Receive raw data
-s, --signal    Signal Strength
```

## ***HASviolet\_TX.py***

Send a LoRa message

```
Usage: HASviolet_TX.py -d DESTINATION "message"

OPTIONS
-h, --help      show this help message and exit
-d DESTINATION, --destination DESTINATION
                Destination
-m MESSAGE, --message MESSAGE
                Message in quotes
```

## ***HASviolet\_RX.py***

Listens for messages from other LoRa stations

```
Usage: ./HASviolet_rx.py -r -s

OPTIONS
-h, --help      show this help message and exit
-r, --raw_data  Receive raw data
-s, --signal    Signal Strength
```

# Libraries

For ease of development by end-users, HASviolet core applications in the previous release (Antigua) have been ported into two libraries to be used in your applications. The library names are **HASvioletRF.py** and **HASvioletHID.py**

## **HASvioletRF.py**

All RF functions are performed through this library. It has dependencies on RF specific modules that currently include **HASrf95.py** for the HOPE RFM95 module currently used on the Adafruit Radio bonnet. Support for the ST126X module is planned and will be referenced via the HASvioletRF.py. Some of the variables available to user applications include the following

Variable	Type	Description
self.radio	string	RF Modules used (RFM9X, Sx126X, etc)
self.modem	string	Modem string as standardized by Radiohead
self.frequency	string	Frequency in Hz
self.spreadfactor	string	LoRa Mode spreadfactor
self.codingrate4	string	LoRa Mode Coding Rate
self.bandwidth	string	LoRa Mode Bandwidth
self.spreadfactor	string	LoRa Mode spreadfactor
self.spreadfactor	string	LoRa Mode spreadfactor
self.txpwr	integer	Value from 5 to 23
self.mycall	string	Callsign or Handle (ie VIOLET)
self.myssid	integer	Recommended 50-99 (ie 50)

## **HASvioletHID.py**

All HID functions are performed through this library. This includes GPIO addressable buttons and OLED displays. This library has dependencies on the 128x32 SSD1306 display driver as available through the **adafruit\_ssd1306** library. Some of the methods available to user applications include the following

Variable	Type	Description
self.OLED	method	Frequency within 868 or 900 MHz bands in MHz (ie 911.25)
self.OLED.fill	method	Fill OLED screen
self.OLED.show	method	Show on OLED screen
self.btnLeft.value	method	Left Button position
self.btnMid.value	method	Middle Button position
self.btnRight.value	method	Right Button position
self.logo	method	Displays HVDN Logo on OLED

# Sensors

There are four interfaces that can be used to physically connect sensors and other devices to HASviolet. They are:

- **SPI** which we reserve for the RF module given speed and full-duplex support
- **i2c** which is our preference for use with sensors connected using the [Qwiic connect system](#).
- **microUSB** which we prefer for GPS devices
- **GPIO** as a last resort

The following sensor application “alpha code” is available in the **apps/sensors/** directory.

- **HASviolet-atmos.py** for use with the [Sparkfun BME280 Atmospheric sensor \(Qwiic\)](#)
- **HASviolet-distance.py** for use with the [Sparkfun Distance Sensor \(Qwiic\)](#)
- **HASviolet-gps.py** for use with [USB accessible GPS/GLONASS](#)
- **HASviolet-sensors.py** for use with all three of the aforementioned sensors simultaneously

## **HASviolet-atmos.py**

```
usage: HASviolet-atmos.py [-h] [-d DESTINATION]
HASviolet Atmos Sensor
-h, --help            show this help message and optional arguments:
-d DESTINATION, --destination DESTINATION
```

## **HASviolet-distance.py**

```
usage: HASviolet-distance.py [-h] [-d DESTINATION]
HASviolet Distance Sensor
-h, --help            show this help message and optional arguments:
-d DESTINATION, --destination DESTINATION
```

## **HASviolet-gps.py**

```
usage: HASviolet-gps.py [-h] [-d DESTINATION]
HASviolet GPS Sensor
-h, --help            show this help message and optional arguments:
-d DESTINATION, --destination DESTINATION
```

## **HASviolet-sensors.py**

```
usage: HASviolet-sensors.py [-h] [-d DESTINATION] [-a] [-f] [-g]
HASviolet Sensor TX
-h, --help            show this help message and optional arguments:
-d DESTINATION, --destination DESTINATION
-a, --atmosphere      Atmosphere Sensor
-f, --distance        Distance Sensor
-f, --distance        Distance Sensor
```

# Appendices

## XARPS

XARPS stands for eXtensible Amateur Radio Payload Specification. Referencing the Open Systems Interconnection model (OSI model), XARPS is an application layer protocol with link-level awareness for use by RF systems providing application level connectivity to other networked systems. ASCII (UTF-8) is used throughout the specification

### Payload Fields

Source	Destination	Options	Data Type	Data
9 bytes (string)	9 bytes (string)	1 byte (hex)	1 byte (hex)	235 bytes (string)

#### ***Source and Destination***

Each contain callsign/handle with SSID. Field size supports IARU decision for 7 character callsigns. Example source and destination data include W1FCC50, PURPLE53.

BEACON99 is a reserved word in the destination field for broadcast messages.

#### ***Options***

Value	Option	Description
0x00 - 0x05	Reserved	
0x06	ACK Response	Response to ACK Request
0x07	ACK Request	Used when positive verification is required that a payload was received

#### ***Data Type***

Value	Type	Description
0x00	Reserved	Reserved
0x01	Battery	Battery voltage update
0x02	Time	Current time payload
0x03	Position Update	GPS position update
0x04	Weather Update	Weather station data
0x05	Text Message	Text message between stations
0x06	Broadcast	Broadcast Message to all stations
0x07	Last Seen Stations	Digest of recent stations
0x08	Binary Data	Binary Data Transport
0x08 - 0x0F	Reserved	Reserved
0x46	Gopher	Gopher
0x50	HTTP	HTTP

Value	Type	Description
0x71	Ident	Ident
0x77	NNTP	NNTP
0x7B	NTP	NTP
0xC2	IRC	IRC

## 0x00 Reserved

Not used

## 0x01 Battery

This payload type provides battery voltage in ASCII numeric format, which may contain a floating point.

## 0x02 Time

This payload contains the time in epoch UTC

## 0x03 Position Update

This message is used to provide position updates, such as GPS locations of any station and is formatted as follows:

**[time in UTC],[latitude],[longitude],[altitude],[speed],[direction],[station type]**

Station types include:

Value	Type
0	handheld
1	pedestrian
2	car
3	truck
4	van
5	emergency vehicle
6	ambulance
7	fire truck
8	command vehicle
9	officer
10	aircraft
11	boat
12	quadcopter UAV
13	fixed wing UAV
14	balloon
15	float
16	landmark

Value	Type
17	road closed
18	accident
19	hazard
20	Perimeter Marker
21-255	reserved for future use

#### **0x04 Weather Update**

Weather updates are still in the definition process, but should utilize METAR format

#### **0x05 Text Message**

Free text field for text message between stations.

#### **0x06 Broadcast Message**

Broadcast and beacon messages. While BEACON99 is a reserved for any broadcast, it is recommended to BEACON and another SSID if you wish to send specific broadcast types like club bulletins, etc.

#### **0x07 Last Seen Stations**

Contains a comma delimited list of recently heard stations.

#### **0x08 Binary Data**

Binary Data transport

#### **0x0F Reserved**

Not used