

Assignment Questions: Linked List**Information:**

Program templates for questions 1 to 4 are provided as separate files: Q1_template_LL.c, Q2_template_LL.c, Q3_template_LL.c, and Q4_template_LL.c. You must utilize these templates to implement your functions. Each program includes a main () function containing a switch statement, which you will use to execute various functions that you are required to implement. These functions can be called multiple times, depending on the user's choice.

You are required to submit your code to HackerEarth (<https://www.hackerearth.com>). An email invitation for this will be sent to your school account. Additionally, even though we use HackerEarth for grading your assignment, please note that you must also submit your code to NTULearn.

The deadline for submissions on both HackerEarth and NTULearn is **February 9th, 2024 (Friday) at 11:59 PM.11:59 PM.**

Assignment Questions (1-4)

1. Write a C function insertSortedLL() that asks the user to input an integer, then inserts it into the linked list in ascending order. The function, insertSortedLL(), should not allow inserting an integer if it already exists in the current linked list. The function should return the index position where the new item was added; if the function could not complete successfully, it should return a value of -1. You can assume that the linked list is either a sorted linked list or an empty list.

The function prototype is given as follows:

```
int insertSortedLL(LinkedList *ll, int item);
```

If the current linked list is: **2 3 5 7 9**

Calling insertSortedLL() with a value of **8** will result in the following linked list:
2 3 5 7 8 9

The function should return the index position where the new item was added as follows:
The value 8 was added at index 4

If the current linked list is: **5 7 9 11 15**

Calling insertSortedLL() with a value of **7** will result in the following linked list:
5 7 9 11 15

The function does not complete successfully (does not insert the value of 7 to the linked list) hence it should return a value of -1:
The value 7 was added at index -1

Your function should print the contents of the linked list after it has been created. This function may be called multiple times for each time your program is running.

Some sample inputs and outputs are given as follows:

```
1: Insert an integer to the sorted linked list:
2: Print the index of the most recent input value:
3: Print sorted linked list:
0: Quit:
```

```
Please input your choice (1/2/3/0): 1
Input an integer that you want to add to the linked list: 2
The resulting linked list is: 2
```

```
Please input your choice (1/2/3/0): 1
Input an integer that you want to add to the linked list: 3
The resulting linked list is: 2 3
```

```
Please input your choice (1/2/3/0): 1
Input an integer that you want to add to the linked list: 5
The resulting linked list is: 2 3 5
```

```
Please input your choice (1/2/3/0): 1
Input an integer that you want to add to the linked list: 7
```

```

The resulting linked list is: 2 3 5 7
Input an integer that you want to add to the linked list: 9
The resulting linked list is: 2 3 5 7 9

Please input your choice (1/2/3/0): 1
Input an integer that you want to add to the linked list: 8
The resulting linked list is: 2 3 5 7 8 9

Please input your choice (1/2/3/0): 2
The value 8 was added at index 4

Please input your choice(1/2/3/0):3
The resulting sorted linked list is: 2 3 5 7 8 9

Please input your choice(1/2/3/0): 1
Input an integer that you want to add to the linked list: 5
The resulting linked list is: 5

Please input your choice(1/2/3/0): 1
Input an integer that you want to add to the linked list: 7
The resulting linked list is: 5 7

Please input your choice(1/2/3/0): 1
Input an integer that you want to add to the linked list: 9
The resulting linked list is: 5 7 9

Please input your choice(1/2/3/0): 1
Input an integer that you want to add to the linked list: 5
The resulting linked list is: 5 7 9

Please input your choice (1/2/3/0): 2
The value 5 was added at index -1

Please input your choice(1/2/3/0):3
The resulting sorted linked list is: 5 7 9

Please input your choice(1/2/3/0):

```

2. Write a C function `alternateMergeLinkedList()` which inserts nodes of the second list into alternate positions of the first list. The nodes of the second list should only be inserted when there are alternate positions available in the first list.

The function prototype is given as follows:

```
void alternateMergeLinkedList(LinkedList *l1, LinkedList *l2);
```

For an example, assume that given two linked lists are `LinkedList1` and

`LinkedList2`: `LinkedList1: 1 2 3`

`LinkedList2: 4 5 6 7`

The resulting linked lists

are: `LinkedList1: 1 4 2 5`

`3 6`

`LinkedList2: 7`

The second list should become empty when the first list is larger than the second list. For an example, assume that given two linked lists are `LinkedList1` and `LinkedList2`:

`LinkedList1: 1 5 7 3 9 11`

`LinkedList2: 6 10 2 4`

The resulting Linked Lists are: `LinkedList1: 1 6 5 10 7 2 3 4 9 11`

`LinkedList2: empty`

A sample input and output session is given below (if the current linked lists are `Linked list 1: 1 2 3` and `Linked list 2: 4 5 6 7`):

```

Linked list 1: 1 2 3
Linked list 2: 4 5 6 7

Please input your choice(1/2/3/0): 3
Linked list 1: 1 4 2 5 3 6
Linked list 2: 7

```

3. Write a C function `moveOddItemsToBack()` that moves all the odd integers to the back of the linked list.

The function prototype is given as follows:

```
void moveOddItemsToBack(LinkedList *ll);
```

Some sample inputs and outputs sessions are given

below: If the linked list is 2 3 4 7 15 18:

The resulting Linked List after moving odd integers to the back of the Linked List is: 2 4 18 3 7 15

If the linked list is 2 7 18 3 4 15:

The resulting Linked List after moving odd integers to the back of the Linked List is: 2 18 4 7 3 15

If the current linked list is 1 3 5:

The resulting Linked List after moving odd integers to the back of the Linked List is: 1 3 5

If the current linked list is 2 4 6:

The resulting Linked List after moving odd integers to the back of the Linked List is: 2 4 6

4. Write a C function `frontBackSplitLinkedList()` that splits the singly linked list into two sublists – one for the front half, and one for the back half. If the number of elements is odd, the extra element should go into the front list. The `frontBackSplitLinkedList()` prints two lists which contains `frontList` and `backList`.

The function prototypes are given as follows:

```
void frontBackSplitLinkedList(LinkedList *ll, LinkedList
*resultFrontList, LinkedList *resultBackList);
```

For example, assume that given linked list is: 2 3 5 6 7

The resulting Linked Lists, `frontList` and `backList` are:

`frontList`: 2 3 5

`backList`: 6 7

A sample input and output session is given below:

```

1: Insert an integer to the linked list:
2: Print the linked list:
3: Split the linked list into two linked lists, frontList and backList:
0: Quit:

```

```

Please input your choice(1/2/3/0): 1
Input an integer that you want to add to the linked list: 2
The resulting linked list is: 2

```

```

Please input your choice(1/2/3/0): 1
Input an integer that you want to add to the linked list: 3
The resulting linked list is: 2 3

```

```
Please input your choice(1/2/3/0): 1
Input an integer that you want to add to the linked list: 5
The resulting linked list is: 2 3 5

Please input your choice(1/2/3/0): 1
Input an integer that you want to add to the linked list: 6
The resulting linked list is: 2 3 5 6

Please input your choice(1/2/3/0): 1
Input an integer that you want to add to the linked list: 7
The resulting linked list is: 2 3 5 6 7

Please input your choice(1/2/3/0): 2
The resulting linked list is: 2 3 5 6 7

Please input your choice(1/2/3/0): 3
The resulting linked lists after splitting the given linked list
are: Front linked list: 2 3 5
Back linked list: 6 7
```