Home Support Calibration P1

Cured-state home test protocol and printable data record

Purpose. This screening run records end-to-end print survival and limited cured-state handling. It does not measure wet-green modulus, peel force, universal resin strength, or a safe support policy by itself.

Start here - non-negotiable boundary

Do not touch, measure, load, remove, straighten, or rescue resin-wet parts. Print, drain, wash, completely dry, and fully cure plate, stand, lever, and comb before separating anything. Use the resin maker's normal workflow and ordinary resin PPE, ventilation, containment, and waste practice. Record actual wash, dry, and cure settings and times.

	Before any handling
☐	Keep each carrier strip intact through wash, dry, and cure.
☐	Inspect wash basket and vat/film for detached material before scoring. A fractured terminal or catcher engagement is a failure.
☐	Open plate and fixture projects in ChituBox without repair, rescale, auto-support, or auto-repair. Record screenshots.
☐	Photograph clean build plate and release film before print; photograph full cured plate from top, +X, and +Y before separation.

Artifact identity

Artifact	Record
Actual printed plate	`H2-exact-grounded-full-plate.chitubox` - reviewed field-patched artifact, not generator output.
Plate SHA-256 / bytes	`a33b2e10c1293b322f89fe2910c79055fa59b2d8b7bf3b2d4df64c804a53a679` / `26101476`
Generator authority	`/private/tmp/plinth-home-calibration-plate`, commit `1541379c1063ca9a41ca2761a189779a8f715a2e`; its JSON and CSV identify 76 specimens. Generator commits `634abdb` and `1541379` are not claimed to have produced H2.
Fixture project	`/private/tmp/plinth-home-loading-fixture-inspection/home-support-loading-fixture.chitubox`, commit `1541379c1063ca9a41ca2761a189779a8f715a2e`
Fixture SHA-256 / bytes	`bef224e1d9634971827e0e989f50b7bbdc288f08dd244e301ad0d7ef27ba1e1f` / `56516`

The owner opened and sliced the fixture cleanly. It is a real reviewed project, but the cured printed fixture remains uncalibrated until the individual stand, lever, and comb are inspected and measured.

Cured inspection and scoring

For each of the 76 immutable IDs, score exactly one outcome: `present_intact`, `missing`, `cracked`, `permanently_bent`, `delaminated`, `brace_separated`, or `catcher_engaged`. A one-plate run is valid to screen and report. Three independently prepared plates are required only before promoting a tested cell into a measured engine constant.

Strip	IDs and condition
S1-VERTICAL	`V11 V12 V13 V14 V21 V22 V23 V24 V31 V32 V33 V34 V41 V42 V43 V44` - vertical, spans 6/12/18/24 mm x radii 0.30/0.50/0.70/0.90 mm.
S2-INCLINED-Y	`Y11 Y12 Y13 Y14 Y21 Y22 Y23 Y24 Y31 Y32 Y33 Y34 Y41 Y42 Y43 Y44` - 45 degrees toward project +Y; same matrix.
S3A-INCLINED-X	`X11 X13 X21 X23 X31 X33 X41 X43` - 45 degrees toward project +X; 0.30/0.70 mm radii.

Strip	IDs and condition
S3B-INCLINED-X	`X12 X14 X22 X24 X32 X34 X42 X44` - 45 degrees toward project +X; 0.50/0.90 mm radii.
S4-BRACED	`BX50 BX51 BX52 BX90 BX91 BX92 BY50 BY51 BY52 BY90 BY91 BY92` - 18 mm detachable; +X/+Y, radius 0.50/0.90 mm, brace none/single/X.
S5-TILES-CONTROLS	`T01 T02 T03 T04 T05 T06 T07 T08 CS1 CM1 CS2 CM2 CS3 CM3 CS4 CM4` - removal tiles; four strong CS and four marginal CM controls.

Fixture validation and safe loading

Wear eye protection. Place a clear shield or clear bag around the coupon and hanging mass. Never put hands or a caliper near a loaded brittle coupon or below the hanging mass.

1. After full cure, separate stand, lever, and 0.5/1.0/2.0 mm comb from their carriers. Place lever in stand.
2. Cut only a detachable coupon from its bridge. Seat its base in receiver `18` at x=58 mm for an 18 mm coupon, or receiver `24` at x=64 mm for a 24 mm coupon. Shaft points toward pivot; terminal crossbar sits at x=40 mm under the lever paddle.
3. Confirm the free lever moves without preload, binding, or unintended contact. Use a closed loop around the straight rooted mass peg. At x=-10 mm the hanging assembly pulls down and paddle applies the intended vertical load.
4. Caliper-measure pivot-to-mass arm `a_m` and pivot-to-contact arm `a_s` three times, unloaded. Nominal geometry is 10.0 mm / 40.0 mm, a 4:1 force reduction. Use actual ratio if different.
5. First validate with `CM1`, then `CS1`, recording both outcomes. Then test remaining controls and braced coupons in recorded geometry-matched pairs. Never reuse a damaged coupon.

Assembly mass	Effective load	Nominal force	Record
20 g	5 g	0.0490 N	exact complete assembly mass: object/container + loop/string
40 g	10 g	0.0981 N	weigh on kitchen scale; no coins
80 g	20 g	0.1961 N	record calculated force using measured arms
160 g	40 g	0.3923 N	10 s dwell, 30 s unloaded recovery, then ten cycles
320 g	80 g	0.7845 N	advance only if prior level survives

Force: `F_specimen_N = m_g / 1000 x 9.80665 x (a_m / a_s)` **Moment:** `M_base_Nmm = F_specimen_N x measured_base_to_contact_span_mm`

During load, use fixed perpendicular phone photos with the printed comb in the specimen plane at zero and at every mass. Only use the caliper unloaded: baseline and residual/recovery after 30 s. Treat changes under 0.10 mm as `unresolved`.

Stop at the first audible crack, visible whitening, brace separation, lever unseating, snap, or permanent set greater than 1.0 mm. Record the first stop. Later levels are `not_attempted`, never passes.

Printable record sheets

Print or copy these forms unchanged. A blank is not a pass.

A. Run metadata

Field	Record
Run ID / date / operator	
Printer / slicer version / profile digest	
Resin product / lot	
Print date / temperature window / actual	
PFA type / install-use state / inspection	
Wash equipment/settings/time	
Dry method/time and confirmation	
Cure equipment/settings/time and confirmation	
Basket inspection / vat-film inspection	
Plate visual gate and photo file	
Screening or descriptive-only reason	

B. 76-ID survival matrix

ID	Outcome/ photo	ID	Outcome/ photo	ID	Outcome/ photo	ID	Outcome/ photo
V11		V12		V13		V14	
V21		V22		V23		V24	
V31		V32		V33		V34	
V41		V42		V43		V44	
Y11		Y12		Y13		Y14	
Y21		Y22		Y23		Y24	
Y31		Y32		Y33		Y34	
Y41		Y42		Y43		Y44	
X11		X13		X21		X23	
X31		X33		X41		X43	
X12		X14		X22		X24	
X32		X34		X42		X44	
BX50		BX51		BX52		BX90	
BX91		BX92		BY50		BY51	
BY52		BY90		BY91		BY92	
T01		T02		T03		T04	
T05		T06		T07		T08	
CS1		CM1		CS2		CM2	
CS3		CM3		CS4		CM4	

C. Fixture inspection and arm measurements

Field	Record
Fixture opened/sliced clean; screenshot/file	
Stand, lever, comb washed/dried/ cured before separation	
Eye protection, clear shield/bag, no hands under mass	
Receiver, terminal x=40, shaft toward pivot, paddle contact	
Mass loop seated at rooted peg base	
Free lever movement/no preload	
Intended vertical load direction	
`a_m` readings 1 / 2 / 3 mm; selected	
`a_s` readings 1 / 2 / 3 mm; selected	
Actual `a_m / a_s` ratio; nominal 10.0/40.0 verified?	
Measured base-to-contact specimen span mm	
Fixture disposition: ready / fixture_unseated / fixture_invalid	

D. Per-coupon load sheet

Coupon ID:

Strip:

Receiver 18 or 24:

Unloaded baseline readings (mm):

/

/

Selected:

Zero-load perpendicular photo with comb:

Target g	Assembly g	Force N	10 s photo	Peak photo defl.	30 s readings	Recovery	10 cycles	Outcome/ stop
20								
40								
80								
160								
320								

First stop level:

Later levels: `not_attempted` if stopped.

E. T01-T08 removal and scar sheet

Tool order and removal direction fixed before first tile:

ID	Start/end	Time	Tile frac.?	Support frac.?	Remnant mm	Scar mm	Touch-up	Before/after photo
T01								

ID	Start/end	Time	Tile frac.?	Support frac.?	Remnant mm	Scar mm	Touch-up	Before/after photo
T02								
T03								
T04								
T05								
T06								
T07								
T08								

Report a scar/remnant below threshold as `<0.10 mm`.

F. Photo, file, deviation, and report-to-Codex checklist

	Item	File/path or note
☐	Build plate and release-film pre-print photo	
☐	Plate and fixture ChituBox inspections	
☐	Full cured plate top, +X, +Y photographs	
☐	Basket and vat/film detached-material photos	
☐	Fixture seating and arm-measurement photos	
☐	Zero and each loaded perpendicular-comb photo	
☐	T01-T08 before/after photos	
☐	Raw data, deviations, exclusions, and control disposition	
☐	Screening conclusion and limitations; no one-plate constant promotion	
☐	Final report package path sent to Codex	