




What data?

data size



Train: LONDON boroughs Validate: Santiago MAXAR? google earth engine complex, but API earthengine.google.com



test on Bristol google scholar: image segmentation roof deep learning

Found data:

MAXAR:

Precision3D Telco suite

osm: Huge free resource of map data

Other free data: ??

need research paper level labelled data to secure effectiveness





Stage 2 OSM etc London

OSM Polygons & Freely available satellite data



mirc





INPUT @ DEMO:

A: postcode area (e.g. se23) OR

B: London borough

Heatmap: denser colour = better [solar ROI or larger roofs or etc] Potential carbon savings & Where is the best installation?

Roof Space

suitability

Additional data on ROI or carbon saved etc if we have time Cached pre-tested results if need be

Scaled liveprocessing if plausible

OUTPUT @ DEMO:

1: imagery

&

2: data download

By postcode group (London) London is an assumption for now!

2 Use Cases

By London Borough





And the model?

## **U-Net model**

https://github.com/g oogle/earthengineapi/blob/master/pyt hon/examples/ipynb /UNET\_regression\_d emo.ipynb

Metric


Model for segment: U-Net

IoU loss function


## Intersection over Union loss

The accuracy metric can sometimes provide misleading results when the pixel class (PV) presence is small within the image, as the measure will be biased in mainly reporting how well the true negative cases (no-PV) are identified. A more suitable metric for image segmentation is the Intersection over Union (IoU), which consists of computing the common pixel area between the prediction and the ground-truth and dividing it by the area of union.

https://iopscience.iop.org/article/10.1088 /1742-6596/1343/1/012034/meta







arrive when you said you would

be kind and col (i more?

Remember ENJOY!

miro