Does External Data Improve Auckland House Price Prediction? An Explainable Machine Learning Study

Dominik Wecke, Huy Nguyen, Jiayi Du, Thao Nguyen, Xiang Yang
University of Auckland, Auckland, New Zealand

***Abstract*—House prices shape lending, rates and most families' biggest financial decision, yet free online valuation tools give a price without a reason. We build an explainable machine-learning pipeline for Auckland house prices and ask whether data about a home's surroundings improves prediction. From 92,010 Auckland Council sales (2024–2026), we use Splink probabilistic record linkage to give each property a LINZ coordinate, keep 59,708 market sales, and link 16 external features: location, 2023 Census and deprivation statistics, flood and noise exposure, and building activity. Under time-ordered five-fold cross-validation, adding these features to the same XGBoost model cuts RMSE from $343,718 to $212,678 and MAPE from 19.3% to 11.0%. A paired bootstrap shows the gain is significant, and a two-stage test shows the external features explain 29.3% of the error a property-only model leaves. Three importance methods agree that location drives most of the gain. XGBoost also beats four other models, including a hedonic regression (MAPE 15.7%), and SHAP explains each prediction in dollars. On 46 recent sales, however, homes.co.nz estimates recorded before each sale were more accurate (MAPE 6.0% vs 9.6%), pointing to the value of richer property data.**

***Index Terms*—house price prediction, explainable AI, SHAP, record linkage, Splink, gradient boosting, hedonic regression, Auckland**

I. Introduction

For most New Zealand households, a home is the largest thing they will ever buy. Its value matters to many people: buyers and sellers use it to set a price, banks use it to decide how much to lend, and Auckland Council uses it to set rates. In Auckland, these values are hard to predict. Homes differ a lot in size, age and condition, and so do the places they sit in. Some areas are close to the city centre or the coast, some neighbourhoods are much richer than others, and some homes sit in a flood plain or under a flight path. A model that only looks at the house itself will miss a large part of its price.

Free online valuation tools give buyers a number but not a reason. A buyer cannot see whether an estimate is high because of the house, its location or something else. This matters when the estimate feeds a decision worth a million dollars.

Past research has studied this problem from two sides. Hedonic studies of Auckland have measured the effect of one outside factor at a time, such as flood risk [1], school zones [2], leaky-building stigma [3] and social housing [4]. These models are easy to read, but they are built to explain one effect, not to predict new sales [5]. Machine learning models predict prices more accurately [6], [7], and SHAP [8] can show which features drive each prediction. However, we found no study that applies explainable machine learning to Auckland, and few that measure how much a *combined* set of outside data improves prediction on sales the model has not seen.

This paper answers two research questions:

- **RQ1:** Does adding Auckland-specific external features (location, neighbourhood, hazards and building activity) improve house price prediction compared with using only a property's own features?
- **RQ2:** How accurate and interpretable is our explainable model compared with a traditional hedonic model and free online valuation estimates for the same Auckland properties?

We test three hypotheses:

- **H1:** The same XGBoost model predicts sale prices with lower error when the external features are added, and the drop in error is statistically significant.
- **H2:** The external features contain information that the property features do not, so a model that sees *only* external features can predict part of the error left by a property-only model.
- **H3:** XGBoost predicts sale prices more accurately than a hedonic regression that uses the same features and the same test sales.

To test them, we built a data pipeline (Fig. 1). We start from the Auckland Council sales file, which has street addresses but no map coordinates. We link each property to the official LINZ address list with Splink [9], a tool for probabilistic record linkage, and keep 59,708 normal market sales of single homes. The coordinate then lets us attach 16 external features from public data. We train every model with time-ordered cross-validation, so it always learns from earlier sales and is tested on later ones. A paired bootstrap tests H1, a two-stage residual model tests H2, and a comparison on the same folds tests H3. Finally, three importance methods and SHAP show *which* external data matters and *why* the model gives a certain price.

Our main contributions are:

1) **A reproducible linked dataset.** We describe each step from the raw sales file to the model-ready data: record linkage, cleaning, and linking 16 external features from nine public sources.
2) **A fair test of external data.** We keep the model and its settings fixed and change only the features. External

data cuts RMSE by 38.1% and MAPE from 19.3% to 11.0%, and explains 29.3% of the error a property-only model leaves.

3) **Evidence on what drives the gain.** Location carries most of it. Neighbourhood statistics carry real signal but largely repeat location, and hazard and building-activity features add almost nothing at city scale.
4) **A comparison of five models with per-sale explanations.** XGBoost is the most accurate of five model types trained on the same inputs (MAPE 11.0% vs 15.7% for a hedonic regression). All five agree on the most important features, and SHAP gives each prediction a short explanation a buyer can read.
5) **An honest benchmark against an online tool.** On 46 recent sales, homes.co.nz estimates recorded before each sale beat our model (MAPE 6.0% vs 9.6%), even when our model is retrained up to the same date. This shows where public data runs out and what the explanation costs in accuracy.

The rest of the paper is organised as follows. Section II reviews related work. Section III describes the pipeline, the models and how we test each hypothesis. Section IV presents and discusses the results. Section V sets out the limitations, and Section VI concludes and suggests future work.

II. Related Work

A. Hedonic models and outside factors in Auckland

A hedonic model treats a house as a bundle of features, each with its own price, found by regressing sale price on those features [10]. These models are mainly used to *explain* the effect of each feature, not to predict new sales as well as possible [5]. Auckland studies show that factors outside the property matter. Adding valuer-defined submarkets improved a hedonic model more than switching to more complex spatial models [11]. Flood-prone homes on the North Shore sold for about 6.2% less before flood maps were published and 2.3% less afterwards [1]. A popular school zone raised prices [2], leaky-building stigma lowered them by about 5% [3], and nearby social housing lowered them by 1.7–23% [4]. Overseas work shows that ignoring the link between nearby sales can overstate an outside effect such as flooding [12]. Each of these studies looks at one factor in a linear model, so none shows how much a *combined* set of outside data improves prediction. We add 16 external features to one model at once and measure the change in error on unseen sales.

B. Machine learning versus hedonic models

Tree-based models learn curved effects and interactions from the data without the analyst choosing their shape. They usually predict prices better than hedonic regression: a random forest reached a MAPE of about 7% against 17% for regression on Ljubljana apartments [6], and an R^2 of 0.94 against 0.65 on Busan condominiums [7]. In Russia a random forest also won (MAPE 14.9% vs 18.3%), but its error was much higher for large apartments [13], so one overall number can hide weak spots. Gradient-boosted trees such as XGBoost [14] do similarly well. Soltani *et al.* [15] stressed that features and training data must only use sales that happened *before* the sale being predicted. Most comparisons change the model and the features at the same time, so it is unclear how much of the gain comes from better data. We change only one at a time: the features with the model fixed (H1), then the model with the features fixed (H3), always training on past sales only.

C. External data and explainable models

SHAP [8] splits each prediction into one contribution per feature, which makes machine learning models easier to read. In Lisbon, open data on the surroundings cut MAE by 8.24%, and SHAP ranked longitude and latitude among the top features [16]. In Sydney, SHAP showed that the effect of amenities changed with distance and amenity type [17], and in Beijing, location mattered most and other effects varied by area [18]. These studies rank features with SHAP alone. When features overlap, as coordinates and area statistics do, one ranking can mislead. We therefore test first whether external data helps, and then compare three importance methods that react differently to overlap.

D. Record linkage

Public sales data often has addresses but no coordinates. The Fellegi–Sunter model [19] links records with no shared key by weighing how strongly each field agrees. Splink [9] implements this model at scale and estimates it without labelled pairs. House price studies rarely report how their coordinates were obtained or how many sales were lost. We describe this step in full, because every external feature depends on it.

III. Methodology

All code is available online.[1] Fig. 1 gives an overview. Steps 1–4 build the dataset (Sections III-A–III-E); steps 5–8 train, test and explain the models (Sections III-F–III-J).

A. Auckland sales data

Our main data is the Auckland Council sales file [20]. It lists 92,010 property sales from January 2024 to August 2026, with 41 columns that describe the sale (price, date, sale type) and the property (land area, floor area, building age, condition, garages, and so on). Each property has a council valuation reference and a street address: a house number, an optional unit or letter, and a street name with a short road type (for example "St Michaels AV"). The file has no coordinates and no suburb, so on its own it cannot tell us *where* a home is.

B. Linking sales to coordinates with Splink

To place each property on the map, we linked it to the LINZ NZ Addresses list [21], which gives a coordinate for every official address in New Zealand. The two sources share no key, and the same address is often written differently (short forms, unit formats, missing letters or typing errors). An exact

[1] https://github.com/hugn456/COMPSCI_760_Group_3_Intelligent_Real_Estate_Price_Prediction_Model




Fig. 1. The full pipeline. Blue steps build the dataset; orange steps train, test and explain the models.

join on the address text would miss many homes and could not tell a near miss from a wrong address.

We therefore used probabilistic record linkage with Splink [9], [22], which implements the Fellegi–Sunter model [19]. For a candidate pair of records (one sale address, one LINZ address), the model compares several fields. Each comparison has a few ordered levels, such as exact agreement, close agreement by a string-similarity score, disagreement, and missing. For level ℓ of comparison k, the model learns two probabilities: $m_{k\ell}$, the chance of seeing that level when the two records are the same address, and $u_{k\ell}$, the chance of seeing it when they are not. It adds up the evidence from all comparisons into a match weight

$$w = \log_2 \frac{\lambda}{1-\lambda} + \sum_k \log_2 \frac{m_{k\gamma_k}}{u_{k\gamma_k}}, \qquad p = \frac{2^w}{1+2^w}, \tag{1}$$

where γ_k is the level seen for comparison k, λ is the prior chance that a random pair is a match, and p is the match probability. Agreement adds weight and disagreement removes it; the rarer an agreement is among non-matching pairs, the more weight it adds.

The model needs no hand-labelled pairs. The u values are estimated from random pairs, which are almost all non-matches, and the m values with the expectation–maximisation (EM) algorithm [9]. Splink can also adjust for term frequency, so that agreeing on a rare street name counts more than agreeing on a common one. To keep the number of pairs manageable, only pairs that pass a blocking rule are scored. [Blocking rules used, e.g. same street name, or same house number and first letters of the street name.] [Fields compared and their levels, e.g. house number (exact), unit/letter (exact or missing), street name (exact, Jaro–Winkler $\geq$ 0.9, else), road type; any cleaning applied first, such as lower-casing and expanding road-type short forms; whether term-frequency adjustment was used.]

Each valuation reference takes the LINZ address with the highest match weight, as long as the weight is above [threshold, as a match weight or match probability]. [Clerical review: how many pairs were checked by hand, in which match-weight bands, and the false-match rate found.] This links 81,363 of the 85,180 distinct properties in the sales file (95.5%) to one LINZ address and coordinate. A few LINZ addresses (72) are shared by two valuation references, for example two cross-leased homes at one street number. We join the coordinates back to the sales by valuation reference, built from the roll number, the assessment number and the lower-cased suffix that separates units under one assessment.

TABLE I
FILTERS APPLIED TO THE SALES DATA, IN ORDER

Filter	Sales left
All sales in the file	92,010
Residential, rural or lifestyle zoning	80,070
One unit of use	77,370
Freehold	76,395
One property per sale	74,112
Arm's-length market sale	61,244
Coordinate found by Splink	59,798
Exact duplicate records removed	59,711
Floor-area typos removed	59,708

C. Cleaning

We kept only sales that show a normal market price for one home. Table I lists the filters in the order we applied them.

The zoning and unit filters remove commercial properties and buildings with several homes. The tenure filter removes leasehold sales, which sell for less because the buyer does not own the land. The one-property filter matters most: when several properties are sold together, the record shows one combined price but the features of only one property, so the model cannot learn from it. The arm's-length filter removes sales between related parties, which may not reflect market value. Linkage found a coordinate for 97.6% of the remaining sales. We then removed records that repeat the same property, date and price, and three records whose building floor area is more than ten times the council's mass-appraisal floor area (for example 360,000 m^2 for an ordinary house), which are typing errors.

We also removed five columns that would leak the answer (data leakage). The net, chattels and other price columns add up to the sale price. The council's capital value and land value are themselves price estimates, so a model that used them would copy the council's valuation instead of learning from property and location data.

TABLE II
EXTERNAL FEATURES, THEIR SOURCES AND HOW EACH WAS LINKED

Feature	Source	Link
Latitude, longitude	LINZ [21]	Splink match
Distance to CBD	–	straight line
Distance to nearest school	MoE [23]	nearest point
Distance to coastline	LINZ [24]	nearest point
Walk to supermarket, bus stop	OSM [25], AT [26]	road network
NZDep2023 decile	Otago [27]	SA2 [28]
Median income, employment, unemployment, population, density	Census [29]	SA2
In flood plain, aircraft noise category	Auckland Council [30]	point in polygon
New dwellings consented (12 months)	Stats NZ [31]	SA2

TABLE III
FEATURE SETS

Group	Features
Baseline (11)	
Size	land area, building floor area
Building	age, condition, construction type, property type, off-street parking, garages under main roof, freestanding garages
Time	sale year, sale month
External (16)	
Location (7)	latitude, longitude, distance to CBD, distance to coastline, distance to nearest school, walking distance to supermarket, walking distance to bus stop
Neighbourhood (6)	NZDep2023 decile, median personal income, employment rate, unemployment rate, population, population density (all per SA2)
Hazards (2)	in flood plain, aircraft noise category
Building activity (1)	new dwellings consented in the SA2 (past 12 months)

D. Linking external features

With a coordinate for every sale, we attached 16 external features from nine public sources (Table II). All distances are measured in metres in the New Zealand Transverse Mercator projection (NZTM2000). We used three kinds of join:

- **Nearest distance.** Straight-line distance to a fixed CBD point (Queen Street, 174.7645°E, 36.8485°S), to the nearest of 2,564 open schools, and to the nearest point on the coastline. To make the coastline search fast, we placed a point every 20 m along the coast and found the nearest one with a k-d tree; this is within about 10 m of the exact distance. Walking distances to the nearest supermarket and bus stop follow the road network.
- **Point in polygon.** We found the 2025 Statistical Area 2 (SA2) that contains each home, and whether the home lies in a council flood plain or an aircraft noise area.
- **Area lookup.** Through the SA2, each home gets its area's NZDep2023 deprivation decile (1 = least deprived, 10 = most), 2023 Census statistics and the number of new dwellings consented in the past 12 months. Employment rate is employed people divided by people aged 15 and over; unemployment rate is unemployed people divided by the labour force; population density is the SA2 population divided by its land area.

Every sale found an SA2 and an NZDep2023 value. SA2 statistics are area-level values shared by every home in the same SA2.

E. Feature sets

We built two feature sets (Table III). The *baseline* set has 11 features that describe only the property and the sale date; it says nothing about location. The *augmented* set adds the 16 external features, for 27 in total. We group the external features into four groups, which we use later to measure importance.

Land area, floor area and the two walking distances are right-skewed (a few very large values), so we applied $\log(1+x)$ to them.

Removing near-copies. We dropped two features before modelling. Sale quarter is calculated from sale month, and the council's mass-appraisal floor area repeats the building floor area (Spearman $\rho = 0.96$). Both pairs had a variance inflation factor (VIF) of 17–18, well above the usual limit of 10. Dropping them cost XGBoost only \$212 of RMSE (0.1%), and afterwards no feature has a VIF above 7.3. This matters more for explanation than for accuracy: two copies of a feature share its SHAP credit and make both look less important than they are.

F. Training and testing over time

House prices change over time, so a model should only learn from sales that happened before the ones it predicts. Shuffling the data at random would let the model learn from the future, which makes results look better than they would be in practice [15].

We therefore sort the 59,708 sales by date and use five-fold expanding-window cross-validation (Fig. 2). The data is cut into six back-to-back time blocks of about 9,950 sales. In fold k, the model trains on blocks 1 to k and is tested on block $k+1$, so each fold learns from more history than the one before. Every sale after the first block is tested exactly once, by a model that has never seen it.

Inside each fold, all preprocessing is learned from the training blocks only and then applied to the test block: category codes (a category not seen in training gets its own code), the median used to fill missing walking distances (1.4–2.7% of sales), and the price limits below. Before training, we remove sales priced below the 1st or above the 99th percentile of the training prices (\$430,000–\$450,000 and \$4.2M–\$4.5M, depending on the fold), and apply the same limits to the test block. This stops a few extreme sales from dominating the error, but it means our results describe the middle 98% of the market. After this step, 48,777 test predictions remain across the five folds.

For n test sales with actual price y_i and predicted price $\hat{y}_i$,




Fig. 2. Five-fold expanding-window cross-validation. Each fold trains on all earlier sales and tests on the next period.

we report three error measures:

$$\mathrm{MAE} = \frac{1}{n}\sum_{i=1}^{n}|y_i - \hat{y}_i|, \tag{2}$$

$$\mathrm{RMSE} = \sqrt{\frac{1}{n}\sum_{i=1}^{n}(y_i - \hat{y}_i)^2}, \tag{3}$$

$$\mathrm{MAPE} = \frac{100}{n}\sum_{i=1}^{n}\frac{|y_i - \hat{y}_i|}{y_i}. \tag{4}$$

MAE is the typical error in dollars. RMSE gives more weight to large errors, which matter most for expensive homes. MAPE is the error as a percentage of price, so a \$100K miss on a \$600K home counts more than the same miss on a \$3M home. We pool the test predictions from all five folds and compute each measure once.

G. Models

Our main model is XGBoost [14], a gradient-boosted tree model that predicts the sale price in dollars. We chose it because it handles curved effects and mixed feature types well, and tree models beat linear regression in earlier house price studies [6], [7]. It uses 500 trees, maximum depth 6, learning rate 0.05, 80% of rows and of features sampled per tree, and random seed 42. To check that our results do not depend on one algorithm, we train four more models on exactly the same inputs:

- **Random forest** [32]: 150 trees, maximum depth 18, at least 2 sales per leaf.
- **CatBoost** [33]: 500 trees, depth 6, learning rate 0.05, set to match XGBoost. It gets the same integer category codes as the other models.
- **Neural network**: a multilayer perceptron with a learned embedding for each categorical feature and three hidden layers (256, 128 and 64 units, ReLU, dropout 0.1), trained with Adam [34] (learning rate 10^{-3}, batch 512) on the standardised log price. Training stops when the error on the latest 10% of the training period has not improved for 10 epochs. Inputs are clipped to the training 0.5th–99.5th percentiles.
- **Hedonic regression**, described next.

We do not tune any model. If each model were tuned separately, part of any difference could come from tuning rather than from the features or the algorithm. Fixed settings keep the comparisons fair, at the cost of slightly understating what each model could reach.

Hedonic regression. The traditional approach is a linear regression on the log of price,

$$\ln y_i = \beta_0 + \mathbf{x}_i^{\top}\boldsymbol{\beta} + \varepsilon_i, \tag{5}$$

fitted by ordinary least squares on the same 27 features. Each category is one-hot encoded, with its most common level as the reference, and any column that never changes in a fold's training data is dropped for that fold. As for the neural network, numeric inputs are clipped to the training 0.5th–99.5th percentiles, so one unusual value cannot produce an extreme price. Turning a log prediction back into dollars with $\exp(\cdot)$ underestimates the average price, so we multiply by Duan's smearing factor [35]:

$$\hat{y}_i = \exp\!\left(\hat{\beta}_0 + \mathbf{x}_i^{\top}\hat{\boldsymbol{\beta}}\right)\cdot\frac{1}{m}\sum_{j=1}^{m}e^{\hat{\varepsilon}_j}, \tag{6}$$

where $\hat{\varepsilon}_j$ are the m training residuals. The neural network uses the same correction.

H. Testing the hypotheses

H1: paired bootstrap. We train XGBoost on the baseline and the augmented feature set over the same folds. To check that the augmented model is better and not just lucky, we draw n test sales at random with replacement and compute

$$\Delta^{(b)} = M^{(b)}_{\text{base}} - M^{(b)}_{\text{aug}} \tag{7}$$

for each metric M [36]. Both models are scored on the same resampled sales, so the test is paired. We repeat this $B = 2{,}000$ times; the 2.5th and 97.5th percentiles of $\Delta^{(b)}$ give a 95% confidence interval. If it does not include zero, the improvement is statistically significant.

H2: two-stage residual test. H1 shows that external features help, but the model might only use them to relearn something the property features already contain. In stage 1, we take the baseline model's out-of-fold errors $r_i = y_i - \hat{y}_i^{\text{base}}$. In stage 2, a new XGBoost model sees *only* the 16 external features and predicts r_i, with its own five-fold expanding-window split over these sales in date order. The first block (8,132 sales) is training only, leaving 40,645 sales with a stage-2 prediction. Stage 2 never sees a property feature, so an out-of-fold R^2 above zero means the external features explain something the property features missed.

H3: same-fold comparison. All five models of Section III-G use the same features, folds, price limits and metrics, so any difference comes from the model alone. We compare their pooled errors and their errors in each fold.

I. Which external features matter

To see which external data drives the gain, we use fold 5: the model trains on all sales up to January 2026 and is tested on the 9,769 sales from January to August 2026. We study the four external groups of Table III with three methods:

- **Grouped permutation importance:** shuffle all features of a group together in the test set and measure the RMSE increase (average of 20 repeats).
- **SHAP:** the share of a group in the total mean absolute SHAP value, on 500 test sales.
- **Drop-group retraining:** retrain without the group (or without one feature) and measure the change in RMSE.

The three react differently when two groups carry similar information. Permutation breaks a group while the model still relies on it, so it shows how much the model *uses* the group, which can overstate how much it is *needed*. Drop-group retraining lets the model fall back on a similar group, so it shows what is *unique* to the group but can understate its value. SHAP splits the credit between similar features. Reading them together shows both use and uniqueness.

J. Explaining single predictions

SHAP values add up: for each sale, the model's average prediction plus the SHAP value of every feature equals the prediction. We use this to explain one held-out sale at a time. Starting from the average predicted price, each feature adds or removes a dollar amount. For a short summary, we add up the contributions within five themes (the four external groups plus "house and land"), which is valid because SHAP values are additive. A waterfall chart shows the largest single contributions with feature values in real units (square metres, kilometres, deciles). For the tree models we use exact TreeSHAP [8]; for the neural network and hedonic model we use SHAP's permutation explainer with 100 training sales as background.

K. Online valuation benchmark

To test the second half of RQ2, we compared our model with HomesEstimate, the free automated estimate on homes.co.nz [37]. Online estimates are updated after a sale, so an estimate looked up later may already reflect the sale price and make the online tool look better than it was. We avoid this by using estimates recorded on **9 July 2026**, before every sale in the sample.

We took the 50 most recent sales in our dataset (28 July to 18 August 2026), so each sold 19–40 days after its estimate was recorded. Two were outside the model's price limits (Section III-F) and two had no estimate, leaving **46 homes**. We compare two versions of our XGBoost model on these homes:

- **Ours (to 24 Jan):** the fold-5 prediction used in the rest of the paper, from a model trained on sales up to 24 January 2026.
- **Ours (to 9 Jul):** the same model retrained on all 58,223 sales before 9 July 2026, so that it knows the market up to the same day as the online estimates.

Besides MAE, RMSE and MAPE, we report the share of homes predicted within 5% and 10% of the sale price, a common way to judge automated valuations. With only 46 homes, we test the MAPE gap in two paired ways: a paired bootstrap (Eq. 7, 2,000 resamples) and a Wilcoxon signed-rank test [38] on the per-home absolute percentage errors, which does not assume the errors are normally distributed.

TABLE IV
H1: BASELINE (PROPERTY ONLY) VS. AUGMENTED (WITH EXTERNAL FEATURES), XGBOOST, POOLED OVER 5 FOLDS, $n = 48{,}777$

Model	Features	RMSE	MAE	MAPE
Baseline	11	$343,718	$223,224	19.3%
Augmented	27	$212,678	$127,983	11.0%




Fig. 3. Pooled error of the baseline and augmented XGBoost models.

IV. Experiments and Results

A. H1: Does external data help?

Table IV and Fig. 3 give the pooled error over all five folds. Adding the 16 external features cuts RMSE by $131,040, from $343,718 to $212,678 (38.1%), MAE by $95,242, and MAPE by 8.4 percentage points, from 19.3% to 11.0%. The paired bootstrap gives 95% confidence intervals of $126,988–$135,157 for the RMSE gain, $93,358–$97,194 for MAE and 8.2–8.5 points for MAPE. None includes zero, so **H1 is supported**. The gain is also steady over time: the augmented model wins in every fold, with RMSE between $191,483 and $238,373 against $320,862 to $370,069 for the baseline. Both models also improve in later folds, which have more training history.

What does this mean in practice? A typical error of $128,000 is still a lot of money, but it is about half of the $223,000 typical error of a model that only knows the house. Two homes with the same size, age and condition can differ in price by hundreds of thousands of dollars depending on where they are, and the baseline model has no way to see this.

B. H2: Do external features add new information?

A model could look like it needs external data only because the property features are weak. The two-stage test rules this out. A model that sees *only* the 16 external features explains 29.3% of the variance in what the property-only model gets wrong ($R^2 = 0.293$ on 40,645 held-out errors), and cuts the RMSE of those errors from $339,582 to $285,308. Since this model never sees a property feature, the 29.3% must be information the property features do not contain, so **H2 is supported**. The other 70.7% is not explained by our external data. It likely comes from things neither data source records, such as interior quality, views, renovations and the negotiation itself.

TABLE V

IMPORTANCE OF THE EXTERNAL FEATURE GROUPS ON FOLD 5. PERMUTATION: RMSE INCREASE WHEN THE GROUP IS SHUFFLED. SHAP: SHARE OF TOTAL MEAN |SHAP|. DROP-GROUP: RMSE CHANGE WHEN THE MODEL IS RETRAINED WITHOUT THE GROUP (NEGATIVE = SLIGHTLY BETTER WITHOUT IT).

Group	Permutation	SHAP	Drop-group
All external (16)	+171.2%	52.3%	+$129,379
Location (7)	+131.1%	35.1%	+$20,146
Neighbourhood (6)	+32.1%	16.1%	+$1,665
Hazards (2)	+0.3%	0.4%	+$370
Building activity (1)	+0.6%	0.6%	−$1,489

C. Which external features matter?

Table V compares the three methods on fold 5 (9,769 test sales, augmented RMSE $191,483). Together, the external features hold 52.3% of the model's total SHAP value, and dropping all of them raises RMSE by $129,379, in line with the five-fold result above.

Location matters most on all three measures. Distance to the CBD alone holds 15.5% of total SHAP, more than latitude (8.1%) or longitude (8.6%), and is second only to building floor area (21.0%) across all 27 features (Fig. 4). The SHAP plot shows the shape of this effect: being close to the CBD raises the price a lot, while beyond a certain distance further kilometres change little. A straight-line model cannot capture this shape.

Neighbourhood statistics mostly repeat location. The model clearly uses them: shuffling the group raises RMSE by 32.1%, and it holds 16.1% of SHAP, led by the deprivation decile (6.9%). Yet retraining without the group costs only $1,665, because the model recovers almost the same information from location. The reverse is not true: without the location group the model still loses $20,146, even though the neighbourhood statistics remain. Without all external features it loses $129,379, more than six times the sum of the four single-group losses. In plain terms, location and neighbourhood statistics describe much the same thing (how desirable an area is), and location describes it more fully. The same holds for single features: no external feature costs more than $3,752 when dropped alone (latitude), and for eight of them the model is slightly better without them, within noise. This is why one ranking method on its own would mislead.

Hazards and building activity add almost nothing at city scale. Only 6.4% of sales lie in a flood plain and 5.3% in an aircraft noise area. These features may matter for those homes, but they cannot explain much of the price variation across all of Auckland. The 12-month count of consents in an SA2 changes slowly and overlaps with location.

D. H3: Comparing five models

Table VI compares the five models on the same 48,777 test sales and the same 27 features. XGBoost is the most accurate on every metric (MAPE 11.0%), followed closely by CatBoost and random forest (11.6%), then the neural network (12.3%). The hedonic regression is clearly the least accurate (15.7%): its




Fig. 4. SHAP summary for the augmented XGBoost model on 500 fold-5 test sales (15 most important features). Each dot is one sale; colour shows the feature's value.

TABLE VI

H3: ALL MODELS ON THE SAME FEATURES AND FOLDS, POOLED, $n = 48{,}777$. TIME IS FOR TRAINING ALL FIVE FOLDS.

Model	RMSE	MAE	MAPE	Time
XGBoost	$212,678	$127,983	10.98%	4 s
CatBoost	$220,406	$135,087	11.61%	10 s
Random forest	$228,130	$134,876	11.55%	14 s
Neural network	$247,526	$148,230	12.29%	49 s
Hedonic (OLS, log)	$306,564	$186,708	15.72%	4 s

RMSE is 44% higher than XGBoost's, and it is worse in every one of the five folds (RMSE $288,480–$323,713 vs $191,483–$238,373). **H3 is supported.** All four machine learning models train all five folds in under a minute on a CPU, so the accuracy gain costs little.

Why do the tree models win? The hedonic model explains 72.9% of the variance in log price on fold 5's training data, so it is a reasonable model, but it gives each feature one straight-line effect for the whole city. Tree models can learn that the CBD distance matters a lot near the city and little far away, or that a large section is worth more in some areas than others. The neural network can learn such shapes too, but on tabular data of this size it trails the tree models, as is often seen on such data [39].

The models also agree on what matters. Table VII shows the SHAP share of the leading features in each model, on the same 500 fold-5 test sales. Building floor area is first and distance to the CBD second in all five models. The main difference is that the hedonic model leans more on SA2 income and building age: a linear model cannot learn sharp local patterns from latitude and longitude, so it relies on smoother area summaries instead. That five very different models agree on the top features makes these conclusions more trustworthy than any single model's ranking.

TABLE VII
SHARE OF TOTAL MEAN |SHAP| (%) FOR LEADING FEATURES, SAME 500 FOLD-5 TEST SALES. RF = RANDOM FOREST, NN = NEURAL NETWORK.

Feature	XGB	CatB	RF	NN	Hedonic
Building floor area	21.0	21.8	31.6	16.8	21.0
Distance to CBD	15.5	14.6	18.9	16.6	11.0
Land area	12.7	14.0	13.6	11.5	3.8
Latitude + longitude	16.7	17.2	19.1	13.6	11.2
Deprivation decile	6.9	8.1	3.7	7.0	3.4
Median income (SA2)	3.4	3.9	3.3	4.5	8.6
Building age	4.7	4.5	2.1	4.7	8.5

E. RQ2: Accuracy versus interpretability

The hedonic model's strength is that each coefficient has a one-sentence meaning that holds for every house. On fold 5, for example, each extra $10,000 of median personal income in the SA2 goes with 12.3% higher prices, each kilometre further from the CBD with 1.2% lower prices, each step up the deprivation decile with 1.3% lower prices, and a flood plain location with 1.8% lower prices, all else equal. XGBoost cannot give one number per feature, because a feature's effect changes from sale to sale. Instead, SHAP gives a dollar breakdown for each prediction (Section IV-F). This is the trade-off RQ2 asks about: the machine learning model gives up one global number per feature, but keeps a clear per-sale explanation while cutting the hedonic model's MAPE by about 30%.

F. Explaining a single prediction

Fig. 5 explains one held-out sale from fold 5's test period: a home sold in June 2026 for $1,285,000. The XGBoost model, trained only on sales up to January 2026, predicted $1,266,131 (1.5% below). Starting from the average prediction of $1,151,033:

- the *neighbourhood* adds $65,399, mostly from a low deprivation decile (2 of 10, +$71,055);
- *location* adds $41,119: the home's latitude (+$85,033) outweighs its 16.9 km distance from the CBD (−$63,763);
- the *house and land* add $26,184: a large floor area (172 m^2, +$84,080) more than offsets a small section (186 m^2, −$94,139);
- *market timing* (a 2026 sale) removes $19,070, and *hazards* change the price by only $1,469.

This is the kind of reason an online valuation tool does not give: a buyer can see that the price rests on the area and the size of the house, not on the section.

G. RQ2: Comparison with online valuation estimates

Table VIII compares our model with homes.co.nz on the same 46 homes. **homes.co.nz is clearly more accurate.** Its MAPE is 6.0% against 9.6% for our model, and half of its estimates are within 5% of the sale price, against 30% of ours. The gap is not luck: the paired bootstrap gives a 95% confidence interval of 1.3–6.0 points for the MAPE gap, and the Wilcoxon test gives $p = 0.012$. Our model is closer to the




Fig. 5. SHAP explanation of one held-out sale (XGBoost, fold 5). Bars run from the average prediction to the model's prediction; red raises the price and blue lowers it. Lines mark the average, predicted and actual price.

TABLE VIII
RQ2: OUR MODEL VS. HOMES.CO.NZ ON THE SAME 46 HOMES (SOLD 28 JULY – 18 AUGUST 2026; ONLINE ESTIMATES RECORDED 9 JULY 2026)

Predictor	MAPE	MAE	≤5%	≤10%
homes.co.nz	6.0%	$73,204	50%	76%
Ours (to 24 Jan)	9.6%	$125,769	30%	57%
Ours (to 9 Jul)	9.9%	$132,487	30%	61%

sale price on 17 of the 46 homes (37%), and Fig. 6 shows that when it loses, it often loses by a wide margin. On these homes our own error (9.6%) is close to its error on all test sales (11.0%), so the result reflects the online tool's strength, not an unlucky sample for our model.

The gap is not about timing. Our fold-5 model only knows sales up to January, about 5.5 months before the online estimates were recorded. Yet retraining it on all sales up to 9 July does not help (MAPE 9.9%; bootstrap interval 1.6–6.3 points, $p = 0.007$). The difference must therefore come from *information*, not from how recent the training data is.

Where does the extra information come from? Our largest misses are homes whose value depends on things the council file does not record: our model predicts 34% too high for one home and 25% too low for a $4.1M home near the top of our price range, where we have few sales to learn from (right end of Fig. 6). Where our model is closer (left end), its wins are usually smaller. An online tool can draw on richer property data, and by 9 July many of these homes were probably already listed for sale, with photos and descriptions that such a tool may use. A few online estimates land within 1% of the final price, which fits this picture. Our model, by design, uses only public council and area data and never sees a listing.

This answers the second half of RQ2. Our model is far more accurate than the traditional hedonic approach and explains every prediction in dollars, but it does not reach the accuracy of a commercial estimate built on richer data, and homes.co.nz gives no reason for its number. The 3.6-point MAPE gap is the current cost of building only on open data, and it shows




Fig. 6. Absolute error for each of the 46 homes, our model (to 24 Jan) vs. homes.co.nz (9 July). Homes are sorted from where our model does best relative to homes.co.nz (left) to where it does worst (right); the dashed line separates the 17 homes where ours is closer from the 29 where homes.co.nz is closer.

what to add next: better data about the house itself.

V. Limitations

Coverage. Our price filter keeps the middle 98% of each fold's training prices, so the results describe the typical Auckland home and may not hold for the cheapest or most expensive 1%. Record linkage placed 97.6% of the arm's-length single-home sales; if the missing 2.4% are different (for example new subdivisions not yet in LINZ), our results could be slightly off for that part of the market. The data also covers one city over 2024–2026, a fairly flat market, so the size of the gain may differ elsewhere or in a fast-rising market.

Area data. The neighbourhood features are 2023 Census and NZDep2023 values for the whole SA2. Every home in an SA2 shares them, they do not change over 2024–2026, and they describe the area, not the buyer. We had school locations but not enrolment zones, so we could not test school-zone effects.

Explanations are not causes. SHAP and the other methods show how the model uses a feature, not what causes prices to change: a large SHAP value for the deprivation decile does not mean deprivation *causes* a set dollar change in price. Because location and neighbourhood features overlap, the split of credit between them depends on the method, so no single number should be read as the "true" value of one feature.

Fixed settings. We fixed every model's settings for a fair comparison. A project that only cared about accuracy could tune each model and would likely do somewhat better than every number here.

Small online benchmark. The online comparison uses 46 homes from three weeks of sales, mostly in the middle of the market, and one online tool. The direction of the result is clear, but the exact size of the gap is uncertain, and other tools (such as propertyvalue.co.nz or OneRoof) may score differently.

VI. Conclusion and Future Work

This paper asked whether Auckland-specific external data improves house price prediction (RQ1), and how an explainable model built on it compares with a traditional hedonic model and free online valuations (RQ2). We built a pipeline from the Auckland Council sales file to a linked dataset: Splink record linkage gave each property a LINZ coordinate, and the coordinate let us attach 16 external features from nine public sources. We then tested the models with time-ordered cross-validation, so every prediction was made from past sales only.

For RQ1, the answer is yes, by a wide and significant margin. Adding the external features cuts XGBoost's RMSE by 38.1% and MAPE from 19.3% to 11.0% (H1), and a model that sees only external data explains 29.3% of the error a property-only model leaves (H2). The reason is simple: two similar houses in different places can sell for very different prices, and only the external features tell the model where a house is and what its area is like. For the first part of RQ2, XGBoost is the most accurate of five models and far more accurate than a hedonic regression on the same features (MAPE 11.0% vs 15.7%, H3), because it can learn curved and local effects. It still explains each prediction in dollars through SHAP. For the second part of RQ2, a free online estimate (homes.co.nz) recorded before each sale was more accurate on 46 recent sales (MAPE 6.0% vs 9.6%), even after we retrained our model up to the same date. Public council and area data take us most of the way, but not all the way, to a commercial estimate; the rest seems to need richer data about the house itself.

The clearest practical finding is that most of the value of external data is the value of *location*. Distance to the CBD and the coordinates carry the largest share; area census and deprivation statistics are useful but mostly repeat what location already says; and flood, noise and building-activity features add almost nothing to a city-wide model. For a team building a similar model with limited time, an accurate coordinate (here, good record linkage) and a few location measures are worth more than many extra area features.

The main drawbacks are that the model is less accurate for unusual homes, that area data is coarse and fixed in time, and that SHAP shows association, not cause. If this work continued as a master's project, we would: (1) repeat the online benchmark on a larger sample and several tools, recording estimates for homes as they are listed, and test whether listing data (photos, descriptions) closes the gap; (2) tune each model and add a prediction interval (for example with quantile regression or conformal prediction), so a buyer sees a range, not just one number; (3) test whether hazards matter more in the parts of Auckland where they are common, using location–feature interaction methods such as GeoShapley [40]; (4) add school enrolment zones and recent nearby sales, built only from earlier sales [15]; and (5) improve the record linkage to recover the 2.4% of sales without a coordinate and check whether they change our conclusions.

CONTRIBUTIONS

Dominik Wecke: Designed the methodology and project plan; prepared, filtered and cleaned the Auckland Council data; performed the Splink record linkage; contributed to the results analysis.

Huy Nguyen: Led the literature review; produced data visualisations; coded and trained the random forest model.

Jiayi Du: Prepared external data; analysed the data; coded and trained the CatBoost model; performed the error analysis.

Thao Nguyen: Built the data processing pipeline; prepared external features; trained the XGBoost model; compared the results with online estimates.

Xiang Yang: Prepared external features; experimented with the neural network; studied the hedonic model; analysed the results and produced the SHAP explanations.

REFERENCES

[1] O. Samarasinghe and B. Sharp, "Flood prone risk and amenity values: A spatial hedonic analysis," *Aust. J. Agricultural Resource Econ.*, vol. 54, no. 4, pp. 457–475, 2010.

[2] M. Rehm and O. Filippova, "The impact of geographically defined school zones on house prices in New Zealand," *Int. J. Housing Markets Anal.*, vol. 1, no. 4, pp. 313–336, 2008.

[3] M. Rehm, "Judging a house by its cover: Leaky building stigma and house prices in New Zealand," *Int. J. Housing Markets Anal.*, vol. 2, no. 1, pp. 57–77, 2009.

[4] V. Sequeira and O. Filippova, "Does concentration of social housing influence house prices? Evidence from New Zealand," *Int. J. Housing Markets Anal.*, vol. 14, no. 4, pp. 720–744, 2021.

[5] G. Shmueli, "To explain or to predict?" *Stat. Sci.*, vol. 25, no. 3, pp. 289–310, 2010.

[6] M. Čeh, M. Kilibarda, A. Lisec, and B. Bajat, "Estimating the performance of random forest versus multiple regression for predicting prices of the apartments," *ISPRS Int. J. Geo-Inf.*, vol. 7, no. 5, p. 168, 2018.

[7] S. An, Y. Song, H. Jang, and K. Ahn, "Toward transparent and accurate housing price appraisal: Hedonic price models versus machine learning algorithms," *Financial Innov.*, vol. 11, no. 1, p. 141, 2025.

[8] S. M. Lundberg and S.-I. Lee, "A unified approach to interpreting model predictions," in *Proc. Adv. Neural Inf. Process. Syst. (NeurIPS)*, vol. 30, 2017, pp. 4765–4774.

[9] R. Linacre, S. Lindsay, T. Manassis, Z. Slade, and T. Hepworth, "Splink: Free software for probabilistic record linkage at scale," *Int. J. Popul. Data Sci.*, vol. 7, no. 3, 2022. [Online]. Available: https://doi.org/10.23889/ijpds.v7i3.1794

[10] S. Rosen, "Hedonic prices and implicit markets: Product differentiation in pure competition," *J. Political Econ.*, vol. 82, no. 1, pp. 34–55, 1974.

[11] S. C. Bourassa, E. Cantoni, and M. Hoesli, "Spatial dependence, housing submarkets, and house price prediction," *J. Real Estate Finance Econ.*, vol. 35, no. 2, pp. 143–160, 2007.

[12] N. Bui, L. Wen, and B. Sharp, "House prices and flood risk exposure: An integration of hedonic property model and spatial econometric analysis," *J. Real Estate Finance Econ.*, vol. 69, no. 1, pp. 100–131, 2024.

[13] E. A. Antipov and E. B. Pokryshevskaya, "Mass appraisal of residential apartments: An application of random forest for valuation and a CART-based approach for model diagnostics," *Expert Syst. Appl.*, vol. 39, no. 2, pp. 1772–1778, 2012.

[14] T. Chen and C. Guestrin, "XGBoost: A scalable tree boosting system," in *Proc. 22nd ACM SIGKDD Int. Conf. Knowl. Discovery Data Mining*, 2016, pp. 785–794.

[15] A. Soltani, M. Heydari, F. Aghaei, and C. J. Pettit, "Housing price prediction incorporating spatio-temporal dependency into machine learning algorithms," *Cities*, vol. 131, p. 103941, 2022.

[16] F. Trindade Neves, M. Aparicio, and M. de Castro Neto, "The impacts of open data and eXplainable AI on real estate price predictions in smart cities," *Appl. Sci.*, vol. 14, no. 5, p. 2209, 2024.

[17] H. Lee, H. Han, and C. Pettit, "Capturing the distance decay effect of amenities on housing price using explainable artificial intelligence," *Appl. Geogr.*, vol. 174, p. 103486, 2025.

[18] Y. Chen, Y. Ye, X. Liu, C. Yin, and C. A. Jones, "Examining the nonlinear and spatial heterogeneity of housing prices in urban Beijing: An application of GeoShapley," *Habitat Int.*, vol. 162, p. 103439, 2025.

[19] I. P. Fellegi and A. B. Sunter, "A theory for record linkage," *J. Amer. Stat. Assoc.*, vol. 64, no. 328, pp. 1183–1210, 1969.

[20] Auckland Council, "District valuation roll and property sales data (DVR and DVRS files)," Auckland Council, Auckland, New Zealand, 2026, Extract dated Aug. 2026.

[21] Land Information New Zealand, "NZ addresses," LINZ Data Service, 2026, Accessed: Oct. 21, 2026. [Online]. Available: https://data.linz.govt.nz

[22] Ministry of Justice Analytical Services, "Splink: Probabilistic record linkage documentation," Accessed: Oct. 21, 2026. [Online]. Available: https://moj-analytical-services.github.io/splink/

[23] Ministry of Education, "New Zealand schools directory," Education Counts, 2026, Accessed: Oct. 24, 2026. [Online]. Available: https://www.educationcounts.govt.nz

[24] Land Information New Zealand, "NZ coastline," LINZ Data Service, 2026, Accessed: Oct. 24, 2026. [Online]. Available: https://data.linz.govt.nz

[25] OpenStreetMap contributors, "OpenStreetMap New Zealand extract," Geofabrik, 2026, Accessed: Oct. 21, 2026. [Online]. Available: https://download.geofabrik.de

[26] Auckland Transport, "GTFS static timetable data," Auckland Transport, 2026, Accessed: Oct. 21, 2026. [Online]. Available: https://at.govt.nz

[27] J. Atkinson, C. Salmond, and P. Crampton, "NZDep2023 index of deprivation," Department of Public Health, University of Otago, Wellington, New Zealand, Tech. Rep., 2024.

[28] Stats NZ, "Statistical area 2 2025 (generalised)," Stats NZ Geographic Data Service, 2025, Accessed: Oct. 24, 2026. [Online]. Available: https://datafinder.stats.govt.nz

[29] Stats NZ, "2023 Census totals by topic for individuals by Statistical Area 2," Stats NZ, 2024, Accessed: Oct. 24, 2026. [Online]. Available: https://datafinder.stats.govt.nz

[30] Auckland Council, "Flood plains, flood sensitive areas, and Unitary Plan base zone," Auckland Council Open Data, 2026, Accessed: Oct. 21, 2026. [Online]. Available: https://data-aucklandcouncil.opendata.arcgis.com

[31] Stats NZ, "Building consents issued," Stats NZ, 2026, Accessed: Oct. 21, 2026. [Online]. Available: https://www.stats.govt.nz

[32] L. Breiman, "Random forests," *Mach. Learn.*, vol. 45, no. 1, pp. 5–32, 2001.

[33] L. Prokhorenkova, G. Gusev, A. Vorobev, A. V. Dorogush, and A. Gulin, "CatBoost: Unbiased boosting with categorical features," in *Proc. Adv. Neural Inf. Process. Syst. (NeurIPS)*, vol. 31, 2018.

[34] D. P. Kingma and J. Ba, "Adam: A method for stochastic optimization," in *Proc. Int. Conf. Learn. Represent. (ICLR)*, 2015.

[35] N. Duan, "Smearing estimate: A nonparametric retransformation method," *J. Amer. Stat. Assoc.*, vol. 78, no. 383, pp. 605–610, 1983.

[36] B. Efron and R. J. Tibshirani, *An Introduction to the Bootstrap*. New York, NY, USA: Chapman & Hall, 1993.

[37] homes.co.nz, "HomesEstimate property value estimates," 2026, Accessed: Jul. 9, 2026. [Online]. Available: https://homes.co.nz

[38] F. Wilcoxon, "Individual comparisons by ranking methods," *Biometrics Bull.*, vol. 1, no. 6, pp. 80–83, 1945.

[39] L. Grinsztajn, E. Oyallon, and G. Varoquaux, "Why do tree-based models still outperform deep learning on typical tabular data?" in *Proc. Adv. Neural Inf. Process. Syst. (NeurIPS), Datasets and Benchmarks Track*, vol. 35, 2022.

[40] Z. Li, "GeoShapley: A game theory approach to measuring spatial effects in machine learning models," *Ann. Amer. Assoc. Geographers*, vol. 114, no. 7, pp. 1365–1385, 2024.