Documentation API
Tic Tac Toe Game

Author: Hugo Santos

Created at: March 21, 2019

Summary

Introduction

Api developed to Docler Holding to get data to Tic Tac Toe Game.

Url Base

<host>/docler-holding/api/public

Postman Collection

https://www.getpostman.com/collections/ce6f0df21871d65b6d11

API

POST: /tictactoe/move

Send a move to the Game Tic Tac Toe.

Header

```
Content-Type: application/json
```

Body

```json
{
    "boardState": [
        ["", "", ""],
        ["", "O", ""],
        ["", "", ""]
    ],
    "level": 1
}
```

Parameters

Parameter	Description	Type
boardState	The actual board game state REQUIRED.	Array
level	The level game can be Easy (0) or Medium (1). REQUIRED.	Int

Response

200: OK

```json
{
    "lastCPUMove": [1, 0, "X"],
    "gameStatus": 0,
    "boardState": [
        ["",  "", "" ],
        ["X", "O", "" ],
        ["",  "", "" ]
    ],
    "error": null,
    "success": true
}
```

POST: /tictactoe/game-status

Get the game status.

Header

```
Content-Type: application/json
```

Body

```
{
    "boardState": [
        ["X", "X", "O"],
        ["O", "O", "X"],
        ["X", "O", "X"]
    ]
}
```

Parameters

Parameter	Description	Type
boardState	The actual board game state. REQUIRED.	Array

Response

200: OK

```
{
    "gameStatus": 3,
    "error": null,
    "success": true
}
```

Status HTTP

200: Success

400: Bad Request

404: Not Found