

Docker MCP Gateway - CVE-2026-55887

Argument Injection Through OCI Image Label Metadata

Language: English

Date: 2026-06-28

Author: Security Lab

Classification: Defensive security research and local laboratory documentation

Contents

Abstract	3
Key Facts	3
Technical Root Cause	4
Impact	4
Laboratory Architecture	4
Scenario Evidence	5
Vulnerable Scenario	5
Fixed Scenario	5
Upstream Remediation	5
Defensive Guidance	5
References	6

Abstract

CVE-2026-55887 is a high-severity argument-injection vulnerability in Docker MCP Gateway / Docker MCP Plugin. The vulnerable behavior affects versions from 0.21.0 up to, but not including, 0.42.2. The flaw is triggered through attacker-controlled metadata stored in the `io.docker.server.metadata` OCI image label. In vulnerable versions, that label is parsed into a broad server configuration structure that includes runtime-shaping fields, allowing untrusted image metadata to influence the `docker run` arguments used to launch an MCP server container.

This report documents the vulnerability, the technical root cause, the local laboratory architecture, the exploitation chain reproduced inside the lab boundary, the upstream remediation in 0.42.2, and the defensive indicators that make the behavior observable.

Scope

The material is limited to defensive security research and local reproduction. The lab uses an isolated Docker-in-Docker victim daemon and does not require publishing malicious images to a public registry or exposing the real host Docker socket to the vulnerable gateway.

Key Facts

CVE	CVE-2026-55887
GitHub Advisory	GHSA-r2xf-7jw5-pjg6
ZDI Advisory	ZDI-26-363, ZDI-CAN-29539
Affected package	github.com/docker/mcp-gateway
Affected versions	>= 0.21.0, < 0.42.2
Fixed version	0.42.2
Weakness	CWE-88: argument delimiter neutralization failure
Reported severity	High
Reported scores	GitHub CVSS v4.0 8.7; GitLab CVSS v3.1 8.6; ZDI CVSS v3.0 8.6

Table 1: Consolidated vulnerability facts from public advisories.

Technical Root Cause

Docker MCP Gateway supports MCP server definitions carried through OCI image metadata. In vulnerable versions, the gateway parses the `io.docker.server.metadata` label as YAML into a broad server configuration structure. That structure contains descriptive fields, but it also contains fields that shape container runtime behavior.

The resulting issue is a mass-assignment style argument-injection flaw. Metadata controlled by the image publisher reaches fields reserved for trusted gateway configuration. Those fields then influence the Docker argument vector constructed by the gateway.

```
attacker-controlled OCI image
      ↓
io.docker.server.metadata label
      ↓
YAML parsed by vulnerable gateway
      ↓
runtime fields enter server configuration
      ↓
gateway builds docker run arguments
      ↓
container starts with attacker-influenced runtime options
```

The vulnerability is argument injection rather than classic shell injection. The dangerous values are inserted into Docker's argument vector rather than passed through a shell command string.

Impact

Public advisories describe impact paths where attacker-controlled metadata causes the gateway to start an MCP server container with dangerous Docker runtime options. Examples include host filesystem mounts, execution as UID 0, and exposure of the Docker socket to the launched container.

The trust boundary is bypassed at container creation time. Container hardening flags such as `no-new-privileges` do not neutralize this issue because the dangerous options are applied before code inside the container runs.

In a real environment, successful exploitation can lead to host compromise. In this lab, the host role is intentionally replaced by a disposable Docker-in-Docker victim daemon.

Laboratory Architecture

The lab reproduces the real vulnerable behavior while isolating the learner's machine from the impact. The gateway is the real upstream Docker MCP Gateway built from tagged releases. The vulnerable path uses `v0.42.1`; the fixed path uses `v0.42.2`.

```
real host
├─ docker compose lab
│   ├─ victim-docker          # isolated Docker daemon representing the victim host
│   ├─ vulnerable-gateway    # real docker/mcp-gateway built from v0.42.1
│   ├─ fixed-gateway         # real docker/mcp-gateway built from v0.42.2
│   ├─ local-registry        # local OCI registry used by the lab
│   ├─ attacker-workstation  # image construction and inspection environment
│   └─ observer              # Docker event and evidence collection helper
```

The gateway talks to the lab Docker daemon through `DOCKER_HOST=tcp://victim-docker:2375`. It does not mount `/var/run/docker.sock` from the real host. The local registry keeps all challenge images inside the lab boundary.

Scenario Evidence

Vulnerable Scenario

The vulnerable scenario uses Docker MCP Gateway v0.42.1, which is inside the affected version range. The challenge image carries crafted OCI metadata. When the gateway processes that image, runtime-shaping metadata reaches the container launch path and appears in Docker event evidence collected from victim-docker.

The scenario evidence focuses on:

- image label content;
- gateway logs showing image processing;
- Docker events from the isolated victim daemon;
- container mounts and user configuration;
- proof that the target is the fake victim host, not the real host.

Fixed Scenario

The fixed scenario uses Docker MCP Gateway v0.42.2. The same challenge image is processed through the patched metadata import path. Runtime-shaping fields from the label no longer produce the vulnerable Docker runtime behavior.

The comparison focuses on:

- gateway logs from v0.42.1 and v0.42.2;
- Docker events from both runs;
- container mounts and user configuration;
- access to fake host data;
- handling of suspicious runtime fields.

Upstream Remediation

Version 0.42.2 changes how metadata imported from OCI labels is parsed and trusted.

The upstream patch introduces `catalog.ImportedServer`, a narrower import schema for image-label metadata. This schema keeps descriptive metadata while excluding runtime-shaping fields such as `command`, `volumes`, `user`, `extra hosts`, `secrets`, `policy`, `remote settings`, and `tool container runtime configuration`. Imported environment declarations keep names only, not values. Imported tool definitions omit container runtime configuration.

The patch also removes the older `self-contained docker://` parsing path that loaded label metadata directly into a full server definition. OCI-derived server data now flows through the restricted import path. As defense in depth, Docker flag values added after `-v`, `-u`, and `--add-host` are checked; values starting with `-` are skipped to prevent leading-hyphen values from becoming additional Docker CLI options.

Defensive Guidance

Primary remediation is upgrading Docker MCP Gateway to 0.42.2 or later.

Operational controls include:

- treating MCP server images as executable software;
- allowing only trusted MCP image publishers and registries;
- pinning approved images by digest;
- avoiding Docker socket mounts in MCP server containers;

- avoiding broad host filesystem mounts;
- isolating experimental MCP workloads;
- monitoring Docker Engine events for unexpected mounts, users, command overrides, and container creation arguments.

References

- Docker / GitHub Security Advisory GHSA-r2xf-7jw5-pjg6. Primary upstream advisory for affected versions, severity, impact, and remediation.
<https://github.com/docker/mcp-gateway/security/advisories/GHSA-r2xf-7jw5-pjg6>
- GitLab Advisory Database CVE-2026-55887. Independent advisory entry for package, version range, CVSS v3.1 vector, and references.
<https://advisories.gitlab.com/golang/github.com/docker/mcp-gateway/CVE-2026-55887/>
- Trend Micro Zero Day Initiative ZDI-26-363. Coordinated disclosure entry with CVSS v3.0 score, timeline, and exploitation conditions.
<https://www.zerodayinitiative.com/advisories/ZDI-26-363/>
- Upstream fix diff v0.42.1...v0.42.2. Source diff used to verify the remediation details.
<https://github.com/docker/mcp-gateway/compare/v0.42.1...v0.42.2>
- Patched import schema. `catalog.ImportedServer` schema that restricts OCI label imports.
https://github.com/docker/mcp-gateway/blob/v0.42.2/pkg/catalog/import_spec.go
- Patched OCI metadata parsing path. Patched code path converting imported label metadata into a restricted server definition.
<https://github.com/docker/mcp-gateway/blob/v0.42.2/pkg/workingset/workingset.go>
- Patched Docker argument guard. Defense-in-depth checks for Docker flag values.
<https://github.com/docker/mcp-gateway/blob/v0.42.2/pkg/gateway/clientpool.go>
- MITRE CWE-88. Weakness classification for improper neutralization of argument delimiters.
<https://cwe.mitre.org/data/definitions/88.html>