Repaired DiD-BCF main rerun versus historical raw
48 cells, 100 paired datasets per cell

ATT RMSE change

Treated CATT surface RMSE change

ATT 95% interval coverage

B1_baseline N=200 d=1
B1_baseline N=200 d=2
B1_baseline N=200 d=3
B1_null N=200 d=1
B1_null N=200 d=2
B1_null N=200 d=3
B1_selection_obs N=200 d=1
B1_selection_obs N=200 d=2
B1_selection_obs N=200 d=3
B1_serial_corr N=200 d=1
B1_serial_corr N=200 d=2
B1_serial_corr N=200 d=3
B1_strong_confounder N=200 d=1
B1_strong_confounder N=200 d=2
B1_strong_confounder N=200 d=3
B2_sweep N=50 d=1
B2_sweep N=50 d=2
B2_sweep N=50 d=3
B2_sweep N=100 d=1
B2_sweep N=100 d=2
B2_sweep N=100 d=3
B2_sweep N=200 d=1
B2_sweep N=200 d=2
B2_sweep N=200 d=3
B2_sweep N=400 d=1
B2_sweep N=400 d=2
B2_sweep N=400 d=3
B2_sweep N=800 d=1
B2_sweep N=800 d=2
B2_sweep N=800 d=3
B2_sweep_serial N=50 d=1
B2_sweep_serial N=50 d=2
B2_sweep_serial N=50 d=3
B2_sweep_serial N=100 d=1
B2_sweep_serial N=100 d=2
B2_sweep_serial N=100 d=3
B2_sweep_serial N=200 d=1
B2_sweep_serial N=200 d=2
B2_sweep_serial N=200 d=3
B2_sweep_serial N=400 d=1
B2_sweep_serial N=400 d=2
B2_sweep_serial N=400 d=3
B2_sweep_serial N=800 d=1
B2_sweep_serial N=800 d=2
B2_sweep_serial N=800 d=3
D_staggered N=200 d=1
D_staggered N=200 d=2
D_staggered N=200 d=3

−8 −6 −4 −2 0 2 4 6 8
Change from historical raw (%)
Paired bootstrap 95% intervals

−2 −1 0 1 2 3 4 5
Change from historical raw (%)
Paired bootstrap 95% intervals

0.75 0.80 0.85 0.90 0.95 1.00
Observed coverage on matched datasets
Dashed line: nominal 0.95

Historical raw
Repaired earlier

All 5,100 repaired fits enter full metrics. This paired comparison uses 4,800 historical matches; 300 additional null replications are separate.