Hello Łukasz and team.

Edge Cases due to unreliable protocol:

1) Lost messages

| Case | Solution proposed in my code |
|----------|---|
| Dim Lost | We can detect this only if current DIM plus the value in the message are out of the interval [0,1]. In this case a dim message must have been lost. I have simply assured that if it the sums go out of this interval the code pulls it into the interval again. Possible solution: A double transmission and acknowledge messages could be implemented but only with access to the light system. |

I assumed the TurnOff messages were always received at the beginning and ending of the transmission as it was said on the exercise guide. I assumed also that EOF were always at start and beginning and weren't lost.

- 2) Duplicate messages Verification of equal timestamps. This means it is a duplicate message.
- 3) Out of order messages Made a list, sorted it and only after it calculates the consumption.

How to use:

I used VS Code for this project.

My maven project outputs the Jar executable file to \sim /energy-estimator/target and usually the name is energy-estimator-1.jar.

If you want an updated jar file you only have to run the Maven command 'mvn package' in the terminal, while on the folder ~/energy-estimator (where the pom.xml is).

The program can be tested by copying and pasting the set of commands by the smart light in the command line and clicking Enter. You can also enter them one by one but we have to be sure we enter them correctly, i.e. without any extra spaces.

Any doubts you can reach me at $\underline{\text{hglebre@gmail.com}}$. Thank you.

Best regards.

Hugo Lebre.