

# Exploring complex normal faulting systems through physics-based dynamic modeling.


H.-S. Sánchez-Reyes<sup>1</sup>, O. Scotti<sup>2</sup>, S. Hok<sup>2</sup>, A.-A. Gabriel<sup>3</sup> and T. Taufiqurrahman<sup>3</sup>

<sup>1</sup>Institut des Sciences de la Terre, IRD-UGA, BP 53, 38041 Grenoble Cedex 9, France

<sup>2</sup>Bureau d'Évaluation des Risques Sismiques pour la Sûreté des Installations, IRSN, 92260 Fontenay-aux-Roses, France

<sup>3</sup>Department of Earth and Environmental Sciences, Ludwig-Maximilians-Universitat, 80333 Munchen, Germany

## 1. Introduction




### Geological context:

The Apennine seismic belt in Italy is an extensional province characterized by multi-fault normal-faulting seismic activity. Earthquakes and/or seismic sequences occurring across multi-fault segments during a single event (e.g. 1980 Ms 6.9 Irpinia Bernard & Zollo (1989)) or sequences spanning a period of days (e.g. 2009 Mw 6.1 L'Aquila Valoroso et al (2013)) to


months (e.g. 2016 Amatrice-Visso-Norcia Improta et al. (2019)), are controlled by the physical complexities of the active normal fault system. Understanding rupture propagation across step-overs, breaking multiple fault segments during a single earthquake, is crucial to enhance the current SHA Bai and Ampuero (2017).

**Goal: Explore dynamic rupture parameters to better understand the physical condition promoting rupture jumps in normal faulting systems**

## 2. Geometry-Settings



## 3. Simulation-Results



Some cases did not break the second fault, due to the distance between faults (large offsets and gaps), effect enhanced by prestress state (large  $S$ , small stress). Overlap (Offset < 0) promotes the jump.


### Hanging/foot wall asymmetry:

Regarding the second fault location with respect to the main fault (hanging or foot wall), when the second fault is on the hanging wall (Gap < 0), the dynamically triggered rupture is more likely to be triggered and sustainable.

### Stress shadow:

The final energy released ( $M_w$ ) increases/decreases according to the distance between faults (offset & gap). Although the overlap increases the triggering effect, the stress shadow due to the fault proximity inhibits a large stress drop on the 2nd fault.

## 4. Jump ? How ? When ? Why ?



## 5. Conclusion & Discussion

- ☞ A static analysis seems insufficient to determine a “break-away” behavior across step-over jumps.
- ☞ A maximum **5 km** step-over distance can still be crossed and promote **break-away ruptures** when pre-stress levels are high enough ( $S = 0.1$ ) and no obstacles (geometry, SHmax direction, friction properties, etc.) are present.
- ☞ **Break-away** ruptures on the 2nd fault seem to be triggered by two  $S$  waves arriving simultaneously to the 2nd fault from the northern and bottom ends of the 1st fault.
- ☞ A positive  $\Delta CFF$  area on the 2nd fault is insufficient to determine if the rupture will be triggered.
- ☞ Triggered by coinciding arrival of several waves?

## References

- Bai, K. and Ampuero, J.-P. (2017). Effect of seismogenic depth and background stress on physical limits of earthquake rupture across fault step overs. *JGR Solid Earth*, 122(12):10–280.
- Bernard, P. and Zollo, A. (1989). The irpinia (italy) 1980 earthquake: detailed analysis of a complex normal faulting. *JGR Solid Earth*, 94(B2):1631–1647.
- Improta, L., Latorre, D., Margheriti, L., Nardi, A., Marchetti, A., Lombardi, A. M., Castello, B., Villani, F., Ciaccio, M. G., Mele, F. M., et al. (2019). Multi-segment rupture of the 2016 amatrice-visso-norcia seismic sequence (central italy) constrained by the first high-quality catalog of early after-shocks. *Sci. Rep.*, 9(1):1–13.
- Uphoff, C., Rettenberger, S., Bader, M., Madden, E. H., Ulrich, T., Wollherr, S., and Gabriel, A.-A. (2017). Extreme scale multi-physics simulations of the tsunamigenic 2004 sumatra megathrust earthquake. In *Proc. Int. HPC*, pages 1–16.
- Valoroso, L., Chiaraluce, L., Piccinini, D., Di Stefano, R., Schaff, D., and Waldhauser, F. (2013). Radiography of a normal fault system by 64,000 high-precision earthquake locations: The 2009 l'aquila (central italy) case study. *JGR Solid Earth*, 118(3):1156–1176.