



Exploring complex normal faulting systems through physics-based dynamic rupture modeling

Cycle Team Meeting

Hugo S.

Institut de Recherche pour le Développement IRD - ISTerre

O., Scotti, S., Hok, A.-A. Gabriel and T. Taufiqurrahman

ANR EQTIME Project

May 9, 2022

Motivation

Preliminary exploration

Preliminary conclusions & discussion

On going work and to dos!

Motivation

Seismic Hazard in Central Italy

IRSN





Figure 11. Comparison between the slip distributions imaged on the VBFS fault during the 24 August (red contours; Tinti et al., 2016) and the 30 October 2016 main shocks (blue contours; this study) projected on the same fault striking 155° and dipping 47° . The red and blue stars are the two main shocks hypocentral locations. The black line is the intersection of the N210° segment and the N155° fault.

Modified by O. Scotti from Scognamiglio et al. (2018)

Seismic Hazard in Central Italy

IRSN





Figure 11. Comparison between the slip distributions imaged on the VBFS fault during the 24 August (red contours; Tinti et al., 2016) and the 30 October 2016 main shocks (blue contours; this study) projected on the same fault striking 155° and dipping 47° . The red and blue stars are the two main shocks hypocentral locations. The black line is the intersection of the N 210° segment and the N 155° fault.

Modified by O. Scotti from Scognamiglio et al. (2018)

Seismic Hazard in Central Italy

IRSN





Figure 11. Comparison between the slip distributions imaged on the VBFS fault during the 24 August 2016 (red contours; Tinti et al., 2016) and the 30 October 2016 main shocks (blue contours; this study) projected on the same fault striking 155° and dipping 47° . The red and blue stars are the two main shocks hypocentral locations. The black line is the intersection of the N 210° segment and the N 155° fault.

Modified by O. Scotti from Scognamiglio et al. (2018)

Seismic Hazard in Central Italy

IRSN





Figure 11. Comparison between the slip distributions imaged on the VBFS fault during the 24 August 2016 (red contours; Tinti et al., 2016) and the 30 October 2016 main shocks (blue contours; this study) projected on the same fault striking 155° and dipping 47°. The red and blue stars are the two main shocks hypocentral locations. The black line is the intersection of the N210° segment and the N155° fault.

Modified by O. Scotti from Scognamiglio et al. (2018)

Rupture jump across step-overs





Figure 11. Comparison between the slip distributions imaged on the VBFS fault during the 24 August 2016 event (red contours; Tinti et al., 2016) and the 30 October 2016 main shocks (blue contours; this study) projected on the same fault striking 155° and dipping 47°. The red and blue stars are the two main shocks hypocentral locations. The black line is the intersection of the N210° segment and the N155° fault.

- Potential larger magnitudes?
- Conditions promoting this?
 - Geometry
 - Stress conditions
- To enhance SHA!


Investigate the physical conditions
promoting rupture jumps across step overs
regarding normal fault systems

Previous studies focused on strike-slip fault systems: Galis et al. (2015); Hu et al. (2016); Bai and Ampuero (2017); Li and Liu (2020); Oglesby (2008), and more ...

Preliminary exploration



(www.seissol.org; e.g., Wollherr et al., 2018; Ulrich et al., 2019)




Stress-Strength
dimensionless
ratio

$$S = \frac{\tau_p - \tau_o}{\tau_o - \tau_r}$$

Stress & medium conditions

- Stress levels explored
- $S = 0.1, 0.2, 0.4, 0.6, 0.8, 0.9$




Stress-Strength
dimensionless
ratio

$$S = \frac{\tau_p - \tau_o}{\tau_o - \tau_r}$$

Stress & medium conditions

- Stress levels explored
 $S = 0.1, 0.2, 0.4, 0.6, 0.8, 0.9$
- Linear Slip Weakening:
 $\mu_s=0.6, \mu_d=0.4, d_c=0.15$ m




Stress-Strength
dimensionless
ratio

$$S = \frac{\tau_p - \tau_0}{\tau_0 - \tau_r}$$

Stress & medium conditions

- Stress levels explored
 $S = 0.1, 0.2, 0.4, 0.6, 0.8, 0.9$
- Linear Slip Weakening:
 $\mu_s=0.6, \mu_d=0.4, d_c=0.15 \text{ m}$
- Slow rupture initiation

$\mu_s \xrightarrow{t \rightarrow 1} \mu_d$
at a $4 \times 4 \text{ km}^2$ patch




Stress-Strength
dimensionless
ratio

$$S = \frac{\tau_p - \tau_0}{\tau_0 - \tau_r}$$

Stress & medium conditions

- Stress levels explored
 $S = 0.1, 0.2, 0.4, 0.6, 0.8, 0.9$
- Linear Slip Weakening:
 $\mu_s=0.6, \mu_d=0.4, d_c=0.15$ m
- Slow rupture initiation
 $\mu_s \xrightarrow{t \rightarrow 1} \mu_d$
 at a 4×4 km² patch




Stress-Strength
dimensionless
ratio

$$S = \frac{\tau_p - \tau_0}{\tau_0 - \tau_r}$$

Stress & medium conditions

- Stress levels explored
 $S = 0.1, 0.2, 0.4, 0.6, 0.8, 0.9$
- Linear Slip Weakening:
 $\mu_s=0.6, \mu_d=0.4, d_c=0.15$ m
- Slow rupture initiation
 $\mu_s \xrightarrow{t \rightarrow 1} \mu_d$
 at a 4×4 km² patch
- σ_{zz} is fixed to 100 MPa
 (~ 3.6 km depth)
- Homogeneous half-space
 $V_p=6.3, V_s=3.6$ km/s,
 $\rho=2800$ kg/m³



Stress-Strength
dimensionless
ratio

$$S = \frac{\tau_p - \tau_o}{\tau_o - \tau_r}$$

Stress & medium conditions

- Stress levels explored
 $S = 0.1, 0.2, 0.4, 0.6, 0.8, 0.9$
- Linear Slip Weakening:
 $\mu_s=0.6, \mu_d=0.4, d_c=0.15 \text{ m}$
- Slow rupture initiation
 $\mu_s \xrightarrow{t \rightarrow 1} \mu_d$
at a $4 \times 4 \text{ km}^2$ patch
- σ_{zz} is fixed to 100 MPa
($\sim 3.6 \text{ km depth}$)
- Homogeneous half-space
 $V_p=6.3, V_s=3.6 \text{ km/s},$
 $\rho=2800 \text{ kg/m}^3$
- Faults share same stress level

For these cases: Gap = 1 km, Offset = 1 km

Only 1 fault segment breaks

S : 0.6

For these cases: Gap = 1 km, Offset = 1 km

Only 1 fault segment breaks Rupture is arrested after jumping

$S: 0.6$

$S: 0.4$

For these cases: Gap = 1 km, Offset = 1 km

Only 1 fault segment breaks

Rupture is arrested after jumping

S : 0.6

S : 0.4


Both segments break

S : 0.2


Preliminary exploration: 3 different cases

For these cases: Gap = 1 km, Offset = 1 km

Only 1 fault segment breaks



Rupture is arrested after jumping




Both segments break




Preliminary exploration: 3 different cases



- Only 1st fault breaks




- Rupture arrested on the 2nd fault



- Both faults break


3 Different cases

72 simulations: [4] Gap values \times [3] Offset values \times [6] Stress levels



Under this configuration:


72 simulations: [4] Gap values \times [3] Offset values \times [6] Stress levels



Under this configuration:

S depends only on the stress level and not on μ_s or μ_d .

72 simulations: [4] Gap values \times [3] Offset values \times [6] Stress levels




Under this configuration:

S depends only on the stress level and not on μ_s or μ_d .

Rupture is arrested mainly due to the pre-stress level of faults.

72 simulations: [4] Gap values \times [3] Offset values \times [6] Stress levels




Under this configuration:

S depends only on the stress level and not on μ_s or μ_d .

Rupture is arrested mainly due to the pre-stress level of faults.

Beyond > 1 km offset jumps might be expected only at low S -ratio levels.

72 simulations: [4] Gap values \times [3] Offset values \times [6] Stress levels



Under this configuration:



S depends only on the stress level and not on μ_s or μ_d .

Rupture is arrested mainly due to the pre-stress level of faults.

Beyond > 1 km offset jumps might be expected only at low S -ratio levels.

Stress shadow and hanging/foot wall asymmetry are observed.

Preliminary conclusions & discussion




Triggering potential:

When the 2nd fault is located on the hanging wall (with respect to the 1st fault) the dynamically triggered rupture is more likely to be self-sustainable (break away).

Stress shadow: Slip VS Fault Proximity

IRSN


For these cases: Gap = 0.5 km, $S = 0.1$



Slip VS Fault Proximity:

The final slip distribution (estimated energy) increases/decreases according to the distance between faults.

For these cases: Gap = 0.5 km, $S = 0.1$




Slip VS Fault Proximity:

The final slip distribution (estimated energy) increases/decreases according to the distance between faults.

Large overlap → Fault proximity → high triggering effect
but,

For these cases: Gap = 0.5 km, $S = 0.1$



Slip VS Fault Proximity:

The final slip distribution (estimated energy) increases/decreases according to the distance between faults.

Large overlap → Fault proximity → high triggering effect but,



Stress shadow → decreases slip distribution on 2nd fault

On going work and to dos!

Central Italy complex normal faulting system

IRSN

Mapped fault traces



Central Italy:

- ☞ Extensional regime
- ☞ Multi-segment normal faulting system
- ☞ Complex fault geometry
- ☞ Seismicity along one or several segments
 - 1980 Ms6.9 Irpinia
 - 2016 Amatrice-Visso-Norcia

Some steps to follow (little by little):

Some steps to follow (little by little):

- Complexify fault geometry, larger, rougher, ...

Some steps to follow (little by little):

- Complexify fault geometry, larger, rougher, ...
- Account for a stratified embedding medium

Some steps to follow (little by little):

- Complexify fault geometry, larger, rougher, ...
- Account for a stratified embedding medium
- More realistic stress field: regional, depth-dependent

Some steps to follow (little by little):


- Complexify fault geometry, larger, rougher, ...
- Account for a stratified embedding medium
- More realistic stress field: regional, depth-dependent
- Include topography

Some steps to follow (little by little):

- Complexify fault geometry, larger, rougher, ...
- Account for a stratified embedding medium
- More realistic stress field: regional, depth-dependent
- Include topography


While exploring for the physical properties
promoting rupture jumps across step overs

Complexifying the fault geometry




Events from Tan et al. (2021)


Complexifying the fault geometry



Events from Tan et al. (2021)



Initial shear stress along dip (Pa)



Summary:



- Stress levels explored $S = 0.1$
- Linear Slip Weakening: $\mu_s=0.6$, $\mu_d=0.4$, $d_c=0.15$
- Slow rupture initiation
 $\mu_s \xrightarrow[t \rightarrow 1]{} \mu_d$ at $16\pi \text{ km}^2$ patch
- $\sigma_{zz} = 100 \text{ MPa}$ ($\sim 3.6 \text{ km depth}$)
- Homogeneous half-space
 $V_p=6.3$, $V_s=3.6 \text{ km/s}$, $\rho=2800 \text{ kg/m}^3$
- Stress level affected by geometry

Cumulative slip
along dip (m)

Slip rate
along dip (m/s)


~20 seconds of rupture

From Tinti et al. (2021)




Initial exploration: complex geometry + layered me

IRSN




Initial exploration: complex geometry + layered me

IRSN



Initial exploration: complex geometry + layered me

IRSN



Slip rate along dip direction (m/s)

Cumulative slip along dip direction (m)

Differences compared to other studies:

- We deal with normal faulting systems
- Under our configuration, beyond > 1 km offset jumps might be expected only at low *S*-ratio levels
- Different ways to initiate the rupture

To dos:

- Improve our mesh ✓
- Account for stratified media ✓
- Explore depth-dependent and heterogeneous stress fields
- Include plasticity, topography, ...

Thanks for listening!

- Keep the exploration on this fault system
Jan. – Apr. : depth-dependent stress+topography+plasticity

- Interact with the new postdoc (if there is a replacement)
Apr. – Jun.

- Extend this research to other regions and fault systems
 - Libanon (Dead Sea Fault), Peru ?
Apr. – Jul.

- Prepare a publication related to this study
Mar. – ...

- Prepare a report/tutorial of what I have done
Mar. – Apr.

References

References

- Aochi, H. (2018). Dynamic asymmetry of normal and reverse faults due to constrained depth-dependent stress accumulation. *Geophysical Journal International*, 215(3):2134–2143.
- Bai, K. and Ampuero, J.-P. (2017). Effect of seismogenic depth and background stress on physical limits of earthquake rupture across fault step overs. *Journal of Geophysical Research: Solid Earth*, 122(12):10–280.
- Faure Walker, J., Boncio, P., Pace, B., Roberts, G., Benedetti, L., Scotti, O., Visini, F., and Peruzza, L. (2021). Fault2sha central apennines database and structuring active fault data for seismic hazard assessment. *Scientific data*, 8(1):1–20.
- Galis, M., Pelties, C., Kristek, J., Moczo, P., Ampuero, J.-P., and Mai, P. M. (2015). On the initiation of sustained slip-weakening ruptures by localized stresses. *Geophysical Journal International*, 200(2):890–909.
- Hu, F., Zhang, Z., and Chen, X. (2016). Investigation of earthquake jump distance for strike-slip step overs based on 3-d dynamic rupture simulations in an elastic half-space. *Journal of Geophysical Research: Solid Earth*, 121(2):994–1006.
- Li, G. and Liu, Y. (2020). Earthquake rupture through a step-over fault system: An exploratory numerical study of the leech river fault, southern vancouver island. *Journal of Geophysical Research: Solid Earth*, 125(11):e2020JB020059.
- Oglesby, D. (2008). Rupture termination and jump on parallel offset faults. *Bulletin of the Seismological Society of America*, 98(1):440–447.
- Scognamiglio, L., Tinti, E., Casarotti, E., Pucci, S., Villani, F., Cocco, M., Magnoni, F., Michelini, A., and Dreger, D. (2018). Complex fault geometry and rupture dynamics of the mw 6.5, 30 october 2016, central italy earthquake. *Journal of Geophysical Research: Solid Earth*, 123(4):2943–2964.
- Tan, Y. J., Waldhauser, F., Ellsworth, W. L., Zhang, M., Zhu, W., Michele, M., Chiaraluce, L., Beroza, G. C., and Segou, M. (2021). Machine-learning-based high-resolution earthquake catalog reveals how complex fault structures were activated during the 2016–2017 central italy sequence. *The Seismic Record*, 1(1):11–19.
- Ulrich, T., Vater, S., Madden, E. H., Behrens, J., van Dinther, Y., Van Zelst, I., Fielding, E. J., Liang, C., and Gabriel, A.-A. (2019). Coupled, physics-based modeling reveals earthquake displacements are critical to the 2018 palu, sulawesi tsunami. *Pure and Applied Geophysics*, 176(10):4069–4109.
- Wollherr, S., Gabriel, A.-A., and Uphoff, C. (2018). Off-fault plasticity in three-dimensional dynamic rupture simulations using a modal discontinuous galerkin method on unstructured meshes: implementation, verification and application. *Geophysical Journal International*, 214(3):1556–1584.