

CSSE2002/7023

Semester 2, 2021

Programming in the Large

Week 4.1: Collections continued

In this Session

- List
- Iterators
- Set
- Map
- Sets with custom classes

Lists

Lists hold items in sequential order, much like an array.

- Grow and shrink automatically
- No fixed size limit
- Walk along list
- Insert an item anywhere in the list
- Remove an item anywhere in the list
- Is item in the list?

Types of Lists

List is an interface

- Can declare a reference to a list: `List<String>`
- Can't create a list object: ~~`new List<String>`~~

Some possible classes:

- LinkedList – better for ops which modify the middle of the list
`LinkedList<String>`
- ArrayList – better for random access
`ArrayList<String>`
- Vector – Mostly for protecting data in concurrent applications¹
`Vector<String>`

ListDemo.java

¹<https://geeksforgeeks.org/vector-vs-arraylist-java/>

Iterators

Iterators are a more flexible way to move through a collection than a `for each` loop.

An iterator refers to a position/item in a collection without needing to use an index number.

Most collections support `.iterator()`.

`IteratorDemo.java`

Iterators

Iterators are a more flexible way to move through a collection than a `for each` loop.

An iterator refers to a position/item in a collection without needing to use an index number.

Most collections support `.iterator()`.

`IteratorDemo.java`

Items can be removed from collections via iterators.

`IteratorDemo2.java`

Iterators

Iterators are a more flexible way to move through a collection than a `for each` loop.

An iterator refers to a position/item in a collection without needing to use an index number.

Most collections support `.iterator()`.

`IteratorDemo.java`

Items can be removed from collections via iterators.

`IteratorDemo2.java`

Modifying one iterator, and then trying to use an older iterator, **fails fast**.


Types of Iterators

Iterator is an interface

- Subinterfaces, and their implementing classes, provide behaviour specific to a context.
 - e.g. `ListIterator`
- Collection objects create and return an iterator to access their items.
 - We don't need to create the iterator for the collection.


`ListIteratorDemo.java`

Iterators




List<Integer>


Iterators




Iterators




Iterators




Iterators




Iterators




Iterators



Iterators



Iterators



Iterators

- The `ListIterator.remove()` method depends on the last element returned
- The `ListIterator.remove()` method cannot be called twice, or after `ListIterator.add()`
- The `ListIterator` interface is well documented
 - <https://docs.oracle.com/en/java/javase/13/docs/api/java.base/java/util/ListIterator.html>
 - Get used to navigating and reading the JavaDoc for the standard libraries.

Dangerous Loops

```
List<Integer> l = new ArrayList<>();  
l.add(10);  
l.add(8);  
l.add(3);
```

1)

```
for (int i = 0; i < l.size(); i++) {  
    l.add(l.get(i) + 1);  
}
```

2)

```
for (Integer i : l) {  
    l.add(i + 1);  
}
```

3)

```
int size = l.size();  
for (int i = 0; i < size; i++) {  
    l.add(l.get(i) + 1);  
}
```

4)

```
ListIterator<Integer> li =  
    l.listIterator();  
while (li.hasNext()) {  
    l.add(li.next() + 1);  
}
```

Sets

Sets store unique items (no duplicates).

- Iterate over the set (don't assume ordering)
- Add item to set
- Remove item from set
- Is item in set?

Types of Sets

- `TreeSet<E>` — E needs to implement `Comparable`
- `HashSet<E>` — E to have sensible `hashCode()` and `equals()`

`SetDemo.java`

Map

Maps store key:value pairs (similar to a Python dictionary).

- Need to specify a type for each

```
Map<Integer, String>
```

- Integer keys and String values.

```
MapDemo.java
```

- Note use of `.entrySet()` to iterate over map contents.

Sets with Custom Classes

(This is largely common with Maps, but Sets are simpler).

CustSet1.java, ...

Sets with Custom Classes

(This is largely common with Maps, but Sets are simpler).

CustSet1.java, ...

It is not enough that interface functions exist, they need to be consistent with what the code expects.

See the documentation for Comparable and Map for example.

In summary:

$$x.equals(y) \Leftrightarrow y.equals(x)$$
$$x.equals(y) \Rightarrow x.hashCode() == y.hashCode()$$
$$x.compareTo(y) < 0 \Leftrightarrow y.compareTo(x) > 0$$

Some Things Not to Do

- **If** you use mutable objects as keys (this should be avoided), do not *change* them once they are in a Set or Map.
- Do not add a Map as a value inside itself.