【ODM/OEM·Shared Manufacturer】

ECB-250

Cost control Molded Case Circuit Breaker

Remote control

Terminal post function

Cost control function

Protective cover function

Cost control Molded Case Circuit Breaker ECB-		160	250	400/630	800	1250	1600
Rated frame current Inm (A)		160	250	400	800	1250	1600
Rated current In (A)		16A-160A	100A-250A	250A-400A 400A-630A	500A-800A	1000A-1250A	1250A-1600A
Rated working voltage Ue (V)		AC400V/AC230V					
Rated insulation voltage Ui (V)		1000					
Rated impulse withstand voltage Uimp (kV)		8					
Number of poles		3					
Rated ultimate short-circuit breaking capacity Icu (kA)	AC230V	25	25	25	65	65	100
	AC400V	20	20	20	40	40	75
Rated service short-circuit breaking capacity Ics (kA)	AC230V	25	25	25	65	65	85
	AC400V	20	20	20	40	40	65
Utilization category		B	B	B	B	B	B
Outline dimension	Length	155	208	337	418	418	340
	Width	90	105	168	238	238	210
	Height	117	115	155	168	168	229
Electrical life (times)		1000	1000	1000	500	500	500
Mechanical life	Maintenance free	7000	7000	4000	2500	2500	2500
	With maintenance	10000	10000	7000	5000	3500	3500