ECHSTM6

Thermomagnetic Molded Case Circuit Breaker

Small volume

Low temperature rise

Integration

Complete specifications

Thermomagnetic Molded Case Circuit Breaker STM6–		125				160				250			
Frame current In		10A~125A				16A~160A				100A~250A			
Number of poles		1P，2P，3P，4P				2P，3P，4P				3P，4P			
Rated insulation voltage Ui （V）：		1000V											
Rated impulse withstand voltage Uimp（kV):		8kV											
Rated working voltage Ue (V),AC:		230V;400V; 690V											
Short circuit breaking capacity code:		C	S	M	H	C	S	M	H	C	S	M	H
Rated service short-circuit breaking capacity Ics（kA）：	AC230V:	5	15	35	50	7	10	25	35	20	25	40	50
	AC400V:	5	13	18	50	10	13	18	35(2P) 50(3P4P)	10	15	35	50
	AC690V:	3	3	5	8	2	3	5	10	3	4	10	15
Rated ultimate short-circuit breaking capacity Icu（kA）：	AC230V:	8	30	36(2P) 50(3P4P)	50	10	20	30	50	30	50	65	70
	AC400V:	8	25	36	50	15	25	36	50	15	30	50	65
	AC690V:	5	6	10	15	8	6	10	15	5	8	15	20
Mechanical life (times)		8500				8500				7000			
Electrical life (times)		1500				1500				1000			
Outline dimension (mm) a–b–c–ca 	Number of poles	1P	2P	3P	4P	2P	3P	4P		3P	4P		
	Width	25	50	75	100	60	90	120		105	140		
	Length	130				155				165			
	Height（S/H）	68				68/82				68/88			
	Height（S/H）	94.5				94/108				96/116			

MCCB

Thermomagnetic Molded Case Circuit Breaker

thermomagnetic molded case circuit breaker STM6-		400			630		800		1250			2000	
Frame current In:		250A~400A			500A~630A		500A~800A		800A~1250A			1000A~2000A	
Number of poles:		3P，4P											
Rated insulation voltage Ui (V):		1000V											
Uimp(kV): Rated impulse withstand voltage Uimp (kV):		8kV											
Ue(V),AC: Rated working voltage Ue (V), AC:		230V;400V; 690V											
Short circuit breaking capacity code:		S	M	H	M	H	M	H	S	M	H	M	H
Rated service short-circuit breaking capacity Ics (% Icu);	AC230V:	25	40	50	40	50	65	70	40	65	70	–	–
	AC400V:	15	35	65	35	65	50	65	35	50	65	50	85
	AC690V:	4	10	12	10	12	15	20	10	15	20	20	20
Rated ultimate short-circuit breaking capacity Icu (kA):	AC230V:	50	65	70	30	50	80	85	65	80	85	–	–
	AC400V:	30	50	65	50	65	65	85	50	65	85	50	100
	AC690V:	8	20	25	10	20	25	35	20	25	35	20	25
Mechanical life (times)		4000			4000		2500		2500			2500	
Electrical life (times)		1000			1000		500		500			500	
outline dimension (mm) a-b-c-ca	Number of poles	3P		4P	3P	4P	3P	4P	3P		4P	3P	4P
	Width	140		184	140	184	210	280	210		280	210	280
	Length	257			257		275.5		275.5			340	
	Height	103			103		103		103			141	
	Height	152			152		152		152			244	