ECHSTM6ELY-250

Electronic Leakage LCD Molded Case Circuit Breaker

Dedicated for Southern Power Grid

Green and eco-friendly

Residual current protection function

Support remote communication

Electronic Leakage LCD Molded Case Circuit Breaker STM6ELY–		160	250	400	630	800	1000
Number of poles		4P（3P+N）					
Rated current (A)		40A-100A 50A-125A 63A-160A	50A-125A 100A-250A	160A-400A	252A-630A	252A-630A 320A-800A	320A-800A 400A-1000A
Rated voltage (V)		AC400V					
Rated insulation voltage (V)		AC1000V					
Rated impulse withstand voltage Uimp (kV)		8kV					
Short circuit breaking capacity (kA) Icu/Ics	M	35/25	50/35	50/50	50/50	50/50	50/50
	H	65/50	65/65	75/75	75/75	85/85	85/85
Rated short-term withstand current Icw (kA)		5kA/1s	10kA/1s	10kA/1s	10kA/1s	20kA/1s	20kA/1s
Number of operation cycles	Power-on	1500	1000	1000	500	500	500
	Power-off	8500	7000	4000	2500	2500	2500
Outline dimension (mm) b-a-ca	4P（3P+N）	150*120*108	165*140*116	257*184*155	257*184*155	275*280*155	275*280*155

Electrical motor device (MD)	●	External transmission operating handle	●	Automatic release device	Electronic type