ECHSTM6LY

Thermomagnetic Residual Current Molded Case Circuit Breaker

Thermomagnetic protection function

Green and eco-friendly

Residual current protection function

Residual current alarm without trip function optional

Thermomagnetic Adjustable Residual Current Circuit Breaker STM6LY-		125				160				250				400		630		800		1250	
Frame current In：		16A~125A				16A~160A				100A~250A				250A~400A		400A~630A		500A~800A		1000A~1250A	
Rated insulation voltage Ui（V）：		1000V																			
Rated impulse withstand voltage Uimp (kV)：		8kV																			
Rated working voltage Ue（V),AC：		400V																			
Number of poles：		3P、4P																			
Short circuit breaking capacity code：		C	S	M	H	C	S	M	H	C	S	M	H	M	H	M	H	M	H	M	H
Rated service short-circuit breaking capacity Ics (kA):	AC400V：	3	5	18	35	10	15	25	35	10	18	25	35	35	42	35	50	35	50	35	50
Rated ultimate short-circuit breaking capacity Icu (kA):	AC400V：	5	8	25	35	15	20	25	35	15	25	35	50	50	65	50	65	50	65	50	65
I△m：		12.5kA												16.25kA							
Rated residual operating current I△n (mA):		50mA、100mA、200mA、300mA、500mA、800mA、1000mA (Optional four adjustable gears)																			
Mechanical life (times)		8500				8500				7000				4000		4000		2500		2500	
Electrical life (times)		1500				1500				1000				1000		1000		500		500	
outline dimension (mm) a-b-c-ca	2P	130*50*68*94.5				155*60*68(82)*94(108)								/							
	3P	130*75*68*94.5				155*90*68(82)*94(108)				165*105*68(88)*96(116)				257*140*103*152		257*140*103*152		275.5*210*103*1 52		275.5*210*103*152	
	4P	130*100*68*94.5				155*120*68(82)*94(108)				165*140*68(88)*96(116)				257*184*103*152		257*184*103*152		275.5*280*103*152		275.5*280*103*152	