ECHSTM6ZY-250M

IoT Intelligent Circuit Breaker

Complete specifications

Data acquisition

Communication function

Modular design

IoT Intelligent Circuit Breaker STM6ZY-		250M		400M		630M		1000M	
Rated frame current Inm (A)		250		400		630		1000	
Rated current In (A)		125(50-125A) 250(100-250A)		400(160-400A)		630(252-630A)		630(252-630A) 800(320-800A) 1000(400-1000A)	
Rated working voltage Ue (V)		AC400V							
Rated insulation voltage Ui (V)		1000							
Rated impulse withstand voltage Uimp (kV)		8							
Number of poles		3P	4P	3P	4P	3P	4P	3P	4P
Rated ultimate short-circuit breaking capacity Icu (kA)	AC400V	50		50		50		50	
Rated service short-circuit breaking capacity Ics (kA)	AC400V	35		35		35		50	
Selective category		B		B		B		B	
ICW		5kA/1s		10kA/1s		10kA/1s		15kA/1s	
Electrical life (times)		1000		1000		500		500	
Mechanical life	Maintenance free	7000		4000		2500		2500	
	With maintenance	10000		7000		3500		2500	
Outline dimension (Lmm*Wmm*Hmm)		220*105*107	220*140*107	285*140*130	285*184*130	285*140*130	285*184*130	300*210*130	300*280*130