ECHSTMRT-1250

Thermomagnetic Dual Adjustable Circuit Breaker

Small volume

Low temperature rise

Multiple connectors

Complete specifications

Thermomagnetic Dual Adjustable Circuit Breaker STM6RT-		125				160				250				400		630		800		1250	
Frame current In:		16A~125A				25A~160A				100A~250A				250A~400A		400A~630A		500A~800A		1000A~1250A	
Rated insulation voltage (V)Ui (V):		1000V																			
Rated impulse withstand voltage Uimp (kV):		8kV																			
Rated working voltage Ue (V),AC:		400V																			
Number of poles:		3P、4P																			
Short circuit breaking capacity code: :		C	S	M	H	C	S	M	H	C	S	M	H	M	H	M	H	M	H	M	H
Rated service short-circuit breaking capacity Ics (kA) :	AC400V:	5	10	18	50	5	10	10	50	5	8	10	50	50	50	50	50	50	65	50	65
Rated ultimate short-circuit breaking capacity Icu (kA) :	AC400V:	10	20	36	50	8	20	20	50	8	15	20	50	50	50	50	50	65	85	65	85
Mechanical life (times)		8500				8500				7000				4000		4000		2500		2500	
Electrical life (times)		1500				1500				1000				1000		1000		500		500	
Overall dimension (mm) a-b-c-ca 	3P	130*75*68*94.5				155*90*68(82)*94(108)				165*105*68(88)*96(116)				257*140*103*152		257*140*103*152		275.5*210*103*152		275.5*210*103*152	
	4P	130*100*68*94.5				155*120*68(82)*94(108)				165*140*68(88)*96(116)				257*184*103*152		257*184*103*152		275.5*280*103*152		275.5*280*103*152	