

# Going deeper with convolutions

**Christian Szegedy**

Google Inc.

**Wei Liu**

University of North Carolina, Chapel Hill

**Yangqing Jia**

Google Inc.

**Pierre Sermanet**

Google Inc.

**Scott Reed**

University of Michigan

**Dragomir Anguelov**

Google Inc.

**Dumitru Erhan**

Google Inc.

**Vincent Vanhoucke**

Google Inc.

**Andrew Rabinovich**

Google Inc.

## Abstract

We propose a deep convolutional neural network architecture codenamed Inception, which was responsible for setting the new state of the art for classification and detection in the ImageNet Large-Scale Visual Recognition Challenge 2014 (ILSVRC14). The main hallmark of this architecture is the improved utilization of the computing resources inside the network. **This was achieved by a carefully crafted design that allows for increasing the depth and width of the network while keeping the computational budget constant.** To optimize quality, the architectural decisions were based on the Hebbian principle and the intuition of multi-scale processing. One particular incarnation used in our submission for ILSVRC14 is called GoogLeNet, a 22 layers deep network, the quality of which is assessed in the context of classification and detection.

## 1 Introduction

In the last three years, mainly due to the advances of deep learning, more concretely convolutional networks [10], the quality of image recognition and object detection has been progressing at a dramatic pace. One encouraging news is that most of this progress is not just the result of more powerful hardware, larger datasets and bigger models, but mainly a consequence of new ideas, algorithms and improved network architectures. No new data sources were used, for example, by the top entries in the ILSVRC 2014 competition besides the classification dataset of the same competition for detection purposes. Our GoogLeNet submission to ILSVRC 2014 actually uses  $12\times$  fewer parameters than the winning architecture of Krizhevsky et al [9] from two years ago, while being significantly more accurate. The biggest gains in object-detection have not come from the utilization of deep networks alone or bigger models, but from the synergy of deep architectures and classical computer vision, like the R-CNN algorithm by Girshick et al [6].

Another notable factor is that with the ongoing traction of mobile and embedded computing, the efficiency of our algorithms – especially their power and memory use – gains importance. It is noteworthy that the considerations leading to the design of the deep architecture presented in this paper included this factor rather than having a sheer fixation on accuracy numbers. For most of the experiments, the models were designed to keep a computational budget of 1.5 billion multiply-adds at inference time, so that they do not end up to be a purely academic curiosity, but could be put to real world use, even on large datasets, at a reasonable cost.

重要启发文献  
网中间  
1x1卷积降维-升维, Global Average pooling层取代全连接层

In this paper, we will focus on an efficient deep neural network architecture for computer vision, codenamed Inception, which derives its name from the Network in network paper by Lin et al [12] in conjunction with the famous “we need to go deeper” internet meme [1]. In our case, the word “deep” is used in two different meanings: first of all, in the sense that we introduce a new level of organization in the form of the “Inception module” and also in the more direct sense of increased network depth. In general, one can view the Inception model as a logical culmination of [12] while taking inspiration and guidance from the theoretical work by Arora et al [2]. The benefits of the architecture are experimentally verified on the ILSVRC 2014 classification and detection challenges, on which it significantly outperforms the current state of the art.

## 2 Related Work

Starting with LeNet-5 [10], convolutional neural networks (CNN) have typically had a standard structure – stacked convolutional layers (optionally followed by contrast normalization and max-pooling) are followed by one or more fully-connected layers. Variants of this basic design are prevalent in the image classification literature and have yielded the best results to-date on MNIST, CIFAR and most notably on the ImageNet classification challenge [9, 21]. For larger datasets such as Imagenet, the recent trend has been to increase the number of layers [12] and layer size [21, 14], while using dropout [7] to address the problem of overfitting.

Despite concerns that max-pooling layers result in loss of accurate spatial information, the same convolutional network architecture as [9] has also been successfully employed for localization [9, 14], object detection [6, 14, 18, 5] and human pose estimation [19]. Inspired by a neuroscience model of the primate visual cortex, Serre et al. [15] use a series of fixed Gabor filters of different sizes in order to handle multiple scales, similarly to the Inception model. However, contrary to the fixed 2-layer deep model of [15], all filters in the Inception model are learned. Furthermore, Inception layers are repeated many times, leading to a 22-layer deep model in the case of the GoogLeNet model.

虽然池化层丢失了空间像素精确信息，但我们依然能用CNN进行定位和目标检测

多尺度信息融合  
受神经科学研究成果启发

Network-in-Network is an approach proposed by Lin et al. [12] in order to increase the representational power of neural networks. When applied to convolutional layers, the method could be viewed as additional  $1 \times 1$  convolutional layers followed typically by the rectified linear activation [9]. This enables it to be easily integrated in the current CNN pipelines. We use this approach heavily in our architecture. However, in our setting,  $1 \times 1$  convolutions have dual purpose: most critically, they are used mainly as dimension reduction modules to remove computational bottlenecks, that would otherwise limit the size of our networks. This allows for not just increasing the depth, but also the width of our networks without significant performance penalty.

增加模型的代表能力

处罚

The current leading approach for object detection is the Regions with Convolutional Neural Networks (R-CNN) proposed by Girshick et al. [6]. R-CNN decomposes the overall detection problem into two subproblems: to first utilize low-level cues such as color and superpixel consistency for potential object proposals in a category-agnostic fashion, and to then use CNN classifiers to identify object categories at those locations. Such a two stage approach leverages the accuracy of bounding box segmentation with low-level cues, as well as the highly powerful classification power of state-of-the-art CNNs. We adopted a similar pipeline in our detection submissions, but have explored enhancements in both stages, such as multi-box [5] prediction for higher object bounding box recall, and ensemble approaches for better categorization of bounding box proposals.

候选框中包含真目标的比例提高

## 3 Motivation and High Level Considerations

提高模型性能的传统方法：  
1. 增加深度（层数）  
2. 增加宽度（卷积核个数），适用于大规模标注好的数据集

The most straightforward way of improving the performance of deep neural networks is by increasing their size. This includes both increasing the depth – the number of levels – of the network and its width: the number of units at each level. This is as an easy and safe way of training higher quality models, especially given the availability of a large amount of labeled training data. However this simple solution comes with two major drawbacks.

缺点

Bigger size typically means a larger number of parameters, which makes the enlarged network more prone to overfitting, especially if the number of labeled examples in the training set is limited. This can become a major bottleneck, since the creation of high quality training sets can be tricky

参数越多，越容易过拟合  
对小数据集和获取标注成本大的数据集不适用



Figure 1: Two distinct classes from the 1000 classes of the ILSVRC 2014 classification challenge.

and expensive, especially if expert human raters are necessary to distinguish between fine-grained visual categories like those in ImageNet (even in the 1000-class ILSVRC subset) as demonstrated by Figure 1.

Another drawback of uniformly increased network size is the dramatically increased use of computational resources. For example, in a deep vision network, if two convolutional layers are chained, any uniform increase in the number of their filters results in a quadratic increase of computation. If the added capacity is used inefficiently (for example, if most weights end up to be close to zero), then a lot of computation is wasted. Since in practice the computational budget is always finite, an efficient distribution of computing resources is preferred to an indiscriminate increase of size, even when the main objective is to increase the quality of results.

The fundamental way of solving both issues would be by ultimately moving from fully connected to sparsely connected architectures, even inside the convolutions. Besides mimicking biological systems, this would also have the advantage of firmer theoretical underpinnings due to the groundbreaking work of Arora et al. [2]. Their main result states that if the probability distribution of the data-set is representable by a large, very sparse deep neural network, then the optimal network topology can be constructed layer by layer by analyzing the correlation statistics of the activations of the last layer and clustering neurons with highly correlated outputs. Although the strict mathematical proof requires very strong conditions, the fact that this statement resonates with the well known Hebbian principle – neurons that fire together, wire together – suggests that the underlying idea is applicable even under less strict conditions, in practice.

On the downside, today's computing infrastructures are very inefficient when it comes to numerical calculation on non-uniform sparse data structures. Even if the number of arithmetic operations is reduced by  $100\times$ , the overhead of lookups and cache misses is so dominant that switching to sparse matrices would not pay off. The gap is widened even further by the use of steadily improving, highly tuned, numerical libraries that allow for extremely fast dense matrix multiplication, exploiting the minute details of the underlying CPU or GPU hardware [16, 9]. Also, non-uniform sparse models require more sophisticated engineering and computing infrastructure. Most current vision oriented machine learning systems utilize sparsity in the spatial domain just by the virtue of employing convolutions. However, convolutions are implemented as collections of dense connections to the patches in the earlier layer. ConvNets have traditionally used random and sparse connection tables in the feature dimensions since [11] in order to break the symmetry and improve learning, the trend changed back to full connections with [9] in order to better optimize parallel computing. The uniformity of the structure and a large number of filters and greater batch size allow for utilizing efficient dense computation.

This raises the question whether there is any hope for a next, intermediate step: an architecture that makes use of the extra sparsity, even at filter level, as suggested by the theory, but exploits our

能否在仍旧利用现有硬件进行密集矩阵运算的条件下，改进模型结构，哪怕只在卷积层水平改进，从而能够利用额外的稀疏性能呢？

细粒度  
计算效率问题：  
两个相连卷积层，两层同步增加  
卷积核个数，计算量将平方增加  
如果很多权重计算后接近0，那么  
这部分计算就被浪费了，  
不能不考虑计算效率，不计成本追求精度

用稀疏连接取代密集连接

真数、演算

神经网络

对称性

current hardware by utilizing computations on dense matrices. The vast literature on sparse matrix computations (e.g. [3]) suggests that clustering sparse matrices into relatively dense submatrices tends to give state of the art practical performance for sparse matrix multiplication. It does not seem far-fetched to think that similar methods would be utilized for the automated construction of non-uniform deep-learning architectures in the near future.

The Inception architecture started out as a case study of the first author for assessing the hypothetical output of a sophisticated network topology construction algorithm that tries to approximate a sparse structure implied by [2] for vision networks and covering the hypothesized outcome by dense, readily available components. Despite being a highly speculative undertaking, only after two iterations on the exact choice of topology, we could already see modest gains against the reference architecture based on [12]. After further tuning of learning rate, hyperparameters and improved training methodology, we established that the resulting Inception architecture was especially useful in the context of localization and object detection as the base network for [6] and [5]. Interestingly, while most of the original architectural choices have been questioned and tested thoroughly, they turned out to be at least locally optimal. 至少能达到局部最优

One must be cautious though: although the proposed architecture has become a success for computer vision, it is still questionable whether its quality can be attributed to the guiding principles that have lead to its construction. Making sure would require much more thorough analysis and verification: for example, if automated tools based on the principles described below would find similar, but better topology for the vision networks. The most convincing proof would be if an automated system would create network topologies resulting in similar gains in other domains using the same algorithm but with very differently looking global architecture. At 无论如何 very least, the initial success of the Inception architecture yields firm motivation for exciting future work in this direction.

## 4 Architectural Details

The main idea of the Inception architecture is based on finding out how an optimal local sparse structure in a convolutional vision network can be approximated and covered by readily available dense components. Note that assuming translation invariance means that our network will be built from convolutional building blocks. All we need is to find the optimal local construction and to repeat it spatially. Arora et al. [2] suggests a layer-by-layer construction in which one should analyze the correlation statistics of the last layer and cluster them into groups of units with high correlation. These clusters form the units of the next layer and are connected to the units in the previous layer. We assume that each unit from the earlier layer corresponds to some region of the input image and these units are grouped into filter banks. In the lower layers (the ones close to the input) correlated units would concentrate in local regions. This means, we would end up with a lot of clusters concentrated in a single region and they can be covered by a layer of  $1 \times 1$  convolutions in the next layer, as suggested in [12]. However, one can also expect that there will be a smaller number of more spatially spread out clusters that can be covered by convolutions over larger patches, and there will be a decreasing number of patches over larger and larger regions. In order to avoid patch-alignment issues, current incarnations of the Inception architecture are restricted to filter sizes  $1 \times 1$ ,  $3 \times 3$  and  $5 \times 5$ , however this decision was based more on convenience rather than necessity. It also means that the suggested architecture is a combination of all those layers with their output filter banks concatenated into a single output vector forming the input of the next stage. Additionally, since pooling operations have been essential for the success in current state of the art convolutional networks, it suggests that adding an alternative parallel pooling path in each such stage should have additional beneficial effect, too (see Figure 2(a)).

As these “Inception modules” are stacked on top of each other, their output correlation statistics are bound to vary: as features of higher abstraction are captured by higher layers, their spatial concentration is expected to decrease suggesting that the ratio of  $3 \times 3$  and  $5 \times 5$  convolutions should increase as we move to higher layers. 朴素原生版本

One big problem with the above modules, at least in this naïve form, is that even a modest number of  $5 \times 5$  convolutions can be prohibitively expensive on top of a convolutional layer with a large number of filters. This problem becomes even more pronounced once pooling units are added to the mix: their number of output filters equals to the number of filters in the previous stage. The merging of the output of the pooling layer with the outputs of convolutional layers would lead to an inevitable

用密集模块去近似出局部最优稀疏结构

设计思想

聚合相关性的特征  
输入到下一层

局部信息，由 $1 \times 1$ 卷积提取  
越靠前面的层越提取局部信息，  
大范围空间信息由大卷积核提取，  
越靠后面的层越提取大范围空间信息

patch对齐

池化分支

原生Inception模块的问题：  
通道数越来越多，计算量爆炸




Figure 2: Inception module

increase in the number of outputs from stage to stage. Even while this architecture might cover the optimal sparse structure, it would do it very inefficiently, leading to a computational blow up within a few stages.

This leads to the second idea of the proposed architecture: <sup>明智的</sup> judiciously applying dimension reductions and projections wherever the computational requirements would increase too much otherwise. This is based on the success of embeddings: even low dimensional embeddings might contain a lot of information about a relatively large image patch. However, embeddings represent information in a dense, compressed form and compressed information is harder to model. We would like to keep our representation sparse at most places (as required by the conditions of [2]) and compress the signals only whenever they have to be aggregated en masse. That is,  $1 \times 1$  convolutions are used to compute reductions before the expensive  $3 \times 3$  and  $5 \times 5$  convolutions. Besides being used as reductions, they also include the use of rectified linear activation which makes them dual-purpose. The final result is depicted in Figure 2(b).

太过密集压缩的嵌入式向量  
不便于模型处理  
只在 $3 \times 3$ 、 $5 \times 5$ 卷积层之前  
应用 $1 \times 1$ 卷积降维

In general, an Inception network is a network consisting of modules of the above type stacked upon each other, with occasional max-pooling layers with stride 2 to <sup>减半</sup> halve the resolution of the grid. For technical reasons (memory efficiency during training), it seemed beneficial to start using Inception modules only at higher layers while keeping the lower layers in traditional convolutional fashion. This is not strictly necessary, simply reflecting some infrastructural inefficiencies in our current implementation.

底层先用普通卷积层，后面用Inception模块堆叠

One of the main beneficial aspects of this architecture is that it allows for increasing the number of units at each stage significantly without an uncontrolled blow-up in computational complexity. The <sup>无处不在的</sup> ubiquitous use of dimension reduction allows for shielding the large number of input filters of the last stage to the next layer, first reducing their dimension before convolving over them with a large patch size. Another practically useful aspect of this design is that it aligns with the intuition that visual information should be processed at various scales and then aggregated so that the next stage can abstract features from different scales simultaneously.

在堆叠模块时计算量不会爆炸

视觉信息多尺度并行分开处理  
再融合汇总

The improved use of computational resources allows for increasing both the width of each stage as well as the number of stages without getting into computational difficulties. Another way to utilize the inception architecture is to create slightly inferior, but computationally cheaper versions of it. We have found that all the included the knobs and levers allow for a controlled balancing of computational resources that can result in networks that are  $2 - 3 \times$  faster than similarly performing networks with non-Inception architecture, however this requires careful manual design at this point.

增加模型宽度和深度

精心调整后可实现比相同  
精度普通网络快2-3倍

## 5 GoogLeNet

We chose GoogLeNet as our team-name in the ILSVRC14 competition. This name is an homage to Yann LeCuns pioneering LeNet 5 network [10]. We also use GoogLeNet to refer to the particular incarnation of the Inception architecture used in our submission for the competition. We have also used a deeper and wider Inception network, the quality of which was slightly inferior, but adding it to the ensemble seemed to improve the results marginally. We omit the details of that network, since our experiments have shown that the influence of the exact architectural parameters is relatively








Figure 3: GoogLeNet network with all the bells and whistles

- A  $1 \times 1$  convolution with 128 filters for dimension reduction and rectified linear activation.
- A fully connected layer with 1024 units and rectified linear activation.
- A dropout layer with 70% ratio of dropped outputs.
- A linear layer with softmax loss as the classifier (predicting the same 1000 classes as the main classifier, but removed at inference time).

A schematic view of the resulting network is depicted in Figure 3.

## 6 Training Methodology

Our networks were trained using the DistBelief [4] distributed machine learning system using modest amount of model and data-parallelism. Although we used CPU based implementation only, a rough estimate suggests that the GoogLeNet network could be trained to convergence using few high-end GPUs within a week, the main limitation being the memory usage. Our training used asynchronous stochastic gradient descent with 0.9 momentum [17], fixed learning rate schedule (decreasing the learning rate by 4% every 8 epochs). Polyak averaging [13] was used to create the final model used at inference time.

Our image sampling methods have changed substantially over the months leading to the competition, and already converged models were trained on with other options, sometimes in conjunction with changed hyperparameters, like dropout and learning rate, so it is hard to give a definitive guidance to the most effective single way to train these networks. To complicate matters further, some of the models were mainly trained on smaller relative crops, others on larger ones, inspired by [8]. Still, one prescription that was verified to work very well after the competition includes sampling of various sized patches of the image whose size is distributed evenly between 8% and 100% of the image area and whose aspect ratio is chosen randomly between  $3/4$  and  $4/3$ . Also, we found that the photometric distortions by Andrew Howard [8] were useful to combat overfitting to some extent. In addition, we started to use random interpolation methods (bilinear, area, nearest neighbor and cubic, with equal probability) for resizing relatively late and in conjunction with other hyperparameter changes, so we could not tell definitely whether the final results were affected positively by their use.

## 7 ILSVRC 2014 Classification Challenge Setup and Results

The ILSVRC 2014 classification challenge involves the task of classifying the image into one of 1000 leaf-node categories in the Imagenet hierarchy. There are about 1.2 million images for training, 50,000 for validation and 100,000 images for testing. Each image is associated with one ground truth category, and performance is measured based on the highest scoring classifier predictions. Two numbers are usually reported: the top-1 accuracy rate, which compares the ground truth against the first predicted class, and the top-5 error rate, which compares the ground truth against the first 5 predicted classes: an image is deemed correctly classified if the ground truth is among the top-5, regardless of its rank in them. The challenge uses the top-5 error rate for ranking purposes.

We participated in the challenge with no external data used for training. In addition to the training techniques aforementioned in this paper, we adopted a set of techniques during testing to obtain a higher performance, which we elaborate below.

1. We independently trained 7 versions of the same GoogLeNet model (including one wider version), and performed ensemble prediction with them. These models were trained with the same initialization (even with the same initial weights, mainly because of an oversight) and learning rate policies, and they only differ in sampling methodologies and the random order in which they see input images.
2. During testing, we adopted a more aggressive cropping approach than that of Krizhevsky et al. [9]. Specifically, we resize the image to 4 scales where the shorter dimension (height or width) is 256, 288, 320 and 352 respectively, take the left, center and right square of these resized images (in the case of portrait images, we take the top, center and bottom squares). For each square, we then take the 4 corners and the center  $224 \times 224$  crop as well as the

top1 :  
第一个猜测就是答案  
top5 :  
前五个猜测结果中包含答案



Team	Year	Place	Error (top-5)	Uses external data
SuperVision	2012	1st	16.4%	no
SuperVision	2012	1st	15.3%	Imagenet 22k
Clarifai	2013	1st	11.7%	no
Clarifai	2013	1st	11.2%	Imagenet 22k
MSRA	2014	3rd	7.35%	no
VGG	2014	2nd	7.32%	no
GoogLeNet	2014	1st	6.67%	no

Table 2: Classification performance

Number of models	Number of Crops	Cost	Top-5 error	compared to base
1	1	1	10.07%	base
1	10	10	9.15%	-0.92%
1	144	144	7.89%	-2.18%
7	1	7	8.09%	-1.98%
7	10	70	7.62%	-2.45%
7	144	1008	6.67%	-3.45%

Table 3: GoogLeNet classification performance break down

square resized to  $224 \times 224$ , and their mirrored versions. This results in  $4 \times 3 \times 6 \times 2 = 144$  crops per image. A similar approach was used by Andrew Howard [8] in the previous year’s entry, which we empirically verified to perform slightly worse than the proposed scheme. We note that such aggressive cropping may not be necessary in real applications, as the benefit of more crops becomes marginal after a reasonable number of crops are present (as we will show later on).

3. The softmax probabilities are averaged over multiple crops and over all the individual classifiers to obtain the final prediction. In our experiments we analyzed alternative approaches on the validation data, such as max pooling over crops and averaging over classifiers, but they lead to inferior performance than the simple averaging.

In the remainder of this paper, we analyze the multiple factors that contribute to the overall performance of the final submission.

Our final submission in the challenge obtains a top-5 error of 6.67% on both the validation and testing data, ranking the first among other participants. This is a 56.5% relative reduction compared to the SuperVision approach in 2012, and about 40% relative reduction compared to the previous year’s best approach (Clarifai), both of which used external data for training the classifiers. The following table shows the statistics of some of the top-performing approaches.

We also analyze and report the performance of multiple testing choices, by varying the number of models and the number of crops used when predicting an image in the following table. When we use one model, we chose the one with the lowest top-1 error rate on the validation data. All numbers are reported on the validation dataset in order to not overfit to the testing data statistics.

## 8 ILSVRC 2014 Detection Challenge Setup and Results

The ILSVRC detection task is to produce bounding boxes around objects in images among 200 possible classes. Detected objects count as correct if they match the class of the groundtruth and their bounding boxes overlap by at least 50% (using the Jaccard index). Extraneous detections count as false positives and are penalized. Contrary to the classification task, each image may contain

Team	Year	Place	mAP	external data	ensemble	approach
UvA-Eurovision	2013	1st	22.6%	none	?	Fisher vectors
Deep Insight	2014	3rd	40.5%	ImageNet 1k	3	CNN
CUHK DeepID-Net	2014	2nd	40.7%	ImageNet 1k	?	CNN
GoogLeNet	2014	1st	43.9%	ImageNet 1k	6	CNN

Table 4: Detection performance

Team	mAP	Contextual model	Bounding box regression
Trimps-Soushen	31.6%	no	?
Berkeley Vision	34.5%	no	yes
UvA-Eurovision	35.4%	?	?
CUHK DeepID-Net2	37.7%	no	?
GoogLeNet	38.02%	no	no
Deep Insight	40.2%	yes	yes

Table 5: Single model performance for detection

many objects or none, and their scale may vary from large to tiny. Results are reported using the mean average precision (mAP).

The approach taken by GoogLeNet for detection is similar to the R-CNN by [6], but is augmented with the Inception model as the region classifier. Additionally, the region proposal step is improved by combining the Selective Search [20] approach with multi-box [5] predictions for higher object bounding box recall. In order to cut down the number of false positives, the superpixel size was increased by  $2\times$ . This halves the proposals coming from the selective search algorithm. We added back 200 region proposals coming from multi-box [5] resulting, in total, in about 60% of the proposals used by [6], while increasing the coverage from 92% to 93%. The overall effect of cutting the number of proposals with increased coverage is a 1% improvement of the mean average precision for the single model case. Finally, we use an ensemble of 6 ConvNets when classifying each region which improves results from 40% to 43.9% accuracy. Note that contrary to R-CNN, we did not use bounding box regression due to lack of time.

与R-CNN区别：  
1、结合Selective Search和multi-box prediction，减少无用的候选框  
2、没有使用框回归直接对候选框分类  
3、使用Inception模型作为分类器

We first report the top detection results and show the progress since the first edition of the detection task. Compared to the 2013 result, the accuracy has almost doubled. The top performing teams all use Convolutional Networks. We report the official scores in Table 4 and common strategies for each team: the use of external data, ensemble models or contextual models. The external data is typically the ILSVRC12 classification data for pre-training a model that is later refined on the detection data. Some teams also mention the use of the localization data. Since a good portion of the localization task bounding boxes are not included in the detection dataset, one can pre-train a general bounding box regressor with this data the same way classification is used for pre-training. The GoogLeNet entry did not use the localization data for pretraining.

In Table 5, we compare results using a single model only. The top performing model is by Deep Insight and surprisingly only improves by 0.3 points with an ensemble of 3 models while the GoogLeNet obtains significantly stronger results with the ensemble.

## 9 Conclusions

Our results seem to yield a solid evidence that approximating the expected optimal sparse structure by readily available dense building blocks is a viable method for improving neural networks for computer vision. The main advantage of this method is a significant quality gain at a modest increase of computational requirements compared to shallower and less wide networks. Also note that our detection work was competitive despite of neither utilizing context nor performing bounding box

稀疏结构

regression and this fact provides further evidence of the strength of the Inception architecture. Although it is expected that similar quality of result can be achieved by much more expensive networks of similar depth and width, our approach yields solid evidence that moving to sparser architectures is feasible and useful idea in general. This suggest promising future work towards creating sparser and more refined structures in automated ways on the basis of [2].

## 10 Acknowledgements

We would like to thank Sanjeev Arora and Aditya Bhaskara for fruitful discussions on [2]. Also we are indebted to the DistBelief [4] team for their support especially to Rajat Monga, Jon Shlens, Alex Krizhevsky, Jeff Dean, Ilya Sutskever and Andrea Frome. We would also like to thank to Tom Duerig and Ning Ye for their help on photometric distortions. Also our work would not have been possible without the support of Chuck Rosenberg and Hartwig Adam.

## References

- [1] Know your meme: We need to go deeper. <http://knowyourmeme.com/memes/we-need-to-go-deeper>. Accessed: 2014-09-15.
- [2] Sanjeev Arora, Aditya Bhaskara, Rong Ge, and Tengyu Ma. Provable bounds for learning some deep representations. *CoRR*, abs/1310.6343, 2013.
- [3] Ümit V. Çatalyürek, Cevdet Aykanat, and Bora Uçar. On two-dimensional sparse matrix partitioning: Models, methods, and a recipe. *SIAM J. Sci. Comput.*, 32(2):656–683, February 2010.
- [4] Jeffrey Dean, Greg Corrado, Rajat Monga, Kai Chen, Matthieu Devin, Mark Mao, Marc’aurelio Ranzato, Andrew Senior, Paul Tucker, Ke Yang, Quoc V. Le, and Andrew Y. Ng. Large scale distributed deep networks. In P. Bartlett, F.c.n. Pereira, C.j.c. Burges, L. Bottou, and K.q. Weinberger, editors, *Advances in Neural Information Processing Systems 25*, pages 1232–1240. 2012.
- [5] Dumitru Erhan, Christian Szegedy, Alexander Toshev, and Dragomir Anguelov. Scalable object detection using deep neural networks. In *Computer Vision and Pattern Recognition, 2014. CVPR 2014. IEEE Conference on*, 2014.
- [6] Ross B. Girshick, Jeff Donahue, Trevor Darrell, and Jitendra Malik. Rich feature hierarchies for accurate object detection and semantic segmentation. In *Computer Vision and Pattern Recognition, 2014. CVPR 2014. IEEE Conference on*, 2014.
- [7] Geoffrey E. Hinton, Nitish Srivastava, Alex Krizhevsky, Ilya Sutskever, and Ruslan Salakhutdinov. Improving neural networks by preventing co-adaptation of feature detectors. *CoRR*, abs/1207.0580, 2012.
- [8] Andrew G. Howard. Some improvements on deep convolutional neural network based image classification. *CoRR*, abs/1312.5402, 2013.
- [9] Alex Krizhevsky, Ilya Sutskever, and Geoff Hinton. Imagenet classification with deep convolutional neural networks. In *Advances in Neural Information Processing Systems 25*, pages 1106–1114, 2012.
- [10] Y. LeCun, B. Boser, J. S. Denker, D. Henderson, R. E. Howard, W. Hubbard, and L. D. Jackel. Backpropagation applied to handwritten zip code recognition. *Neural Comput.*, 1(4):541–551, December 1989.
- [11] Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.
- [12] Min Lin, Qiang Chen, and Shuicheng Yan. Network in network. *CoRR*, abs/1312.4400, 2013.
- [13] B. T. Polyak and A. B. Juditsky. Acceleration of stochastic approximation by averaging. *SIAM J. Control Optim.*, 30(4):838–855, July 1992.
- [14] Pierre Sermanet, David Eigen, Xiang Zhang, Michaël Mathieu, Rob Fergus, and Yann LeCun. Overfeat: Integrated recognition, localization and detection using convolutional networks. *CoRR*, abs/1312.6229, 2013.

- [15] Thomas Serre, Lior Wolf, Stanley M. Bileschi, Maximilian Riesenhuber, and Tomaso Poggio. Robust object recognition with cortex-like mechanisms. *IEEE Trans. Pattern Anal. Mach. Intell.*, 29(3):411–426, 2007.
- [16] Fengguang Song and Jack Dongarra. Scaling up matrix computations on shared-memory manycore systems with 1000 cpu cores. In *Proceedings of the 28th ACM International Conference on Supercomputing, ICS '14*, pages 333–342, New York, NY, USA, 2014. ACM.
- [17] Ilya Sutskever, James Martens, George E. Dahl, and Geoffrey E. Hinton. On the importance of initialization and momentum in deep learning. In *Proceedings of the 30th International Conference on Machine Learning, ICML 2013, Atlanta, GA, USA, 16-21 June 2013*, volume 28 of *JMLR Proceedings*, pages 1139–1147. JMLR.org, 2013.
- [18] Christian Szegedy, Alexander Toshev, and Dumitru Erhan. Deep neural networks for object detection. In Christopher J. C. Burges, Léon Bottou, Zoubin Ghahramani, and Kilian Q. Weinberger, editors, *Advances in Neural Information Processing Systems 26: 27th Annual Conference on Neural Information Processing Systems 2013. Proceedings of a meeting held December 5-8, 2013, Lake Tahoe, Nevada, United States.*, pages 2553–2561, 2013.
- [19] Alexander Toshev and Christian Szegedy. Deeppose: Human pose estimation via deep neural networks. *CoRR*, abs/1312.4659, 2013.
- [20] Koen E. A. van de Sande, Jasper R. R. Uijlings, Theo Gevers, and Arnold W. M. Smeulders. Segmentation as selective search for object recognition. In *Proceedings of the 2011 International Conference on Computer Vision, ICCV '11*, pages 1879–1886, Washington, DC, USA, 2011. IEEE Computer Society.
- [21] Matthew D. Zeiler and Rob Fergus. Visualizing and understanding convolutional networks. In David J. Fleet, Tomás Pajdla, Bernt Schiele, and Tinne Tuytelaars, editors, *Computer Vision - ECCV 2014 - 13th European Conference, Zurich, Switzerland, September 6-12, 2014, Proceedings, Part I*, volume 8689 of *Lecture Notes in Computer Science*, pages 818–833. Springer, 2014.