

[별지 2] 판두께측정표(별표 4 제1호다목2) 관련)

검사원 : (서명)

측정장소		측정일자	
선명/공사번호		선박소유자	
선박제조사		측정자	

		L/3	L/2	2L/3	평균값	판두께측정 계산식 적용 값
td	우현				-	(a + b)/2
					-	
					-	
	최소 값				(a)	
	좌현				-	
					-	
					-	
	최소 값				(b)	
ts	우현				-	(c + d)/2
					-	
					-	
	최소 값				(c)	
	좌현				-	
					-	
					-	
	최소 값				(d)	
tb	우현				-	(e + f)/2
					-	
					-	
	최소 값				(e)	
	좌현				-	
					-	
					-	
	최소 값				(f)	

$$75 \cdot a \cdot W \cdot L \leq D \cdot \left(2 \cdot td \cdot Bd + \frac{1}{3} \cdot ts \cdot D \cdot \frac{2 \cdot tb \cdot B + ts \cdot D - 2 \cdot td \cdot Bd}{ts \cdot D + tb \cdot B} \right) \times 10^3$$

$$(1) 75 \cdot a \cdot W \cdot L \cdot \alpha \qquad (A) = \underline{\hspace{2cm}}$$

$$(2) \text{ (i) } td \cdot Bd = \underline{\hspace{2cm}}$$

$$\text{ (ii) } ts \cdot D = \underline{\hspace{2cm}}$$

$$\text{ (iii) } tb \cdot B = \underline{\hspace{2cm}}$$

$$\text{ (iv) } 2 \times (\text{ iii }) + (\text{ ii }) - 2 \times (\text{ i }) = \underline{\hspace{2cm}}$$

$$\text{ (v) } (\text{ ii }) + (\text{ iii }) = \underline{\hspace{2cm}}$$

$$\text{ (vi) } (\text{ ii }) \times (\text{ iv }) / (\text{ v }) / 3 = \underline{\hspace{2cm}}$$

$$\text{ (vii) } D \times (2 \times (\text{ i }) + (\text{ vi})) \times 10^3 \qquad (B) = \underline{\hspace{2cm}}$$

$$(A) \leq (B) \text{ --- 합격}$$

$$(A) > (B) \text{ --- 불합격}$$