



[별표 6] 와이어로프의 종류, 절단시험하중 및 질량(제24조제1항제2호 관련)

1. 와이어로프의 종류

호별		1호	2호	3호	4호	5호	6호	21호
단면								
구 성	스트랜드 소선수	7	12	19	24	30	37	36
	스트랜드의 수	6	6	6	6	6	6	6
	섬유심	중심	중심 및 스트랜드의 중심	중심	중심 및 스트랜드의 중심	중심 및 스트랜드의 중심	중심	중심
구성기호		(6×7)	(6×12)	(6×19)	(6×24)	(6×30)	(6×37)	(6×WS (36))

2. 와이어로프의 절단시험 하중 및 중량

호별	1호		2호		3호		4호		5호		6호		21호	
구성 기호	(6×7)		(6×12)		(6×19)		(6×24)		(6×30)		(6×37)		(6×WS(36))	
지름 (mm)	절단 하중 (kN)	1m의 중량 (kg)	절단 하중 (kN)	1m의 중량 (kg)	절단 하중 (kN)	1m의 중량 (kg)	절단 하중 (kN)	1m의 중량 (kg)	절단 하중 (kN)	1m의 중량 (kg)	절단 하중 (kN)	1m의 중량 (kg)	절단 하중 (kN)	1m의 중량 (kg)
10	52.4	0.371	33.3	0.273	47.9	0.364	45.5	0.332	41.1	0.310	48.9	0.359	50.5	0.396
12	75.4	0.534	48.0	0.393	71.6	0.524	65.5	0.478	59.1	0.446	70.5	0.517	72.8	0.570
14	103	0.727	65.3	0.535	97.4	0.713	89.1	0.651	80.5	0.607	96.2	0.704	99.0	0.776
16	134	0.950	85.2	0.699	127	0.932	117	0.850	105	0.793	126	0.920	129	1.01
18	170	1.20	108	0.885	161	1.18	147	1.08	133	1.00	159	1.16	164	1.28
20	210	1.48	133	1.09	199	1.46	181	1.33	164	1.24	195	1.44	202	1.58
22	253	1.80	161	1.32	240	1.77	221	1.61	199	1.50	237	1.74	244	1.92
24	302	2.14	192	1.57	286	2.10	262	1.91	236	1.79	281	2.07	291	2.28
26	354	2.51	225	1.85	336	2.47	308	2.24	278	2.10	330	2.43	341	2.68
28	411	2.91	261	2.14	389	2.85	357	2.60	322	2.43	382	2.82	396	3.10
30	472	3.34	300	2.46	447	3.28	410	2.99	369	2.79	439	3.23	454	3.56
32	536	3.80	341	2.80	509	3.73	466	3.40	421	3.17	501	3.68	517	4.06
34	605	4.29	385	3.16	575	4.21	526	3.84	475	3.58	566	4.16	583	4.58
36	679	4.81	432	3.54	644	4.72	589	4.30	533	4.02	634	4.66	654	5.13
38	756	5.36	481	3.94	718	5.26	657	4.79	593	4.48	707	5.19	730	5.72
40	838	5.93	533	4.37	795	5.82	728	5.31	657	4.95	782	5.75	808	6.34
42					877									
44					963									
46					1,050									
48					0									
50					1,150	9.10	1,150	8.30	1,020	7.74	1,230	8.98	1,260	9.90
52					0									
54					1,250									
56					0									
58					1,250									
60							1,640	12.0	1,470	11.1	1,760	12.9	1,810	14.3
62							1,750	12.8	1,580	11.9	1,880	13.8	1,940	15.2
65							1,920	14.0	1,740	13.1	2,070	15.2	2,140	16.7