

[별표 3]

두께측정 기록표

두께측정 기록표 - 갑판 / 선저외판 / 선측외판

TM1-T/DHT/BC/DSBC/GE*

Report on THICKNESS MEASUREMENT of ALL DECK PLATING / ALL BOTTOM SHELL PLATING / ALL SIDE SHELL PLATING*

Ship's Name :

Report No. :

STRAKE POSITION			Report No.															
PLATE POSITION	No. or Letter	Org. Thk. <i>mm</i>	Forward Reading						Aft Reading						Mean Diminution %		M.A.D	
			Gauged		Diminution P		Diminution S		Gauged		Diminution P		Diminution S		P	S		<i>mm</i>
			P	S	<i>mm</i>	%	<i>mm</i>	%	P	S	<i>mm</i>	%	<i>mm</i>	%				
13th forward																		
12th																		
11th																		
10th																		
9th																		
8th																		
7th																		
6th																		
5th																		
4th																		
3rd																		
2nd																		
1st																		
Amidships																		
1st aft																		
2nd																		
3rd																		
4th																		
5th																		
6th																		
7th																		
8th																		
9th																		
10th																		
11th																		
12th																		
13th																		

Operators Signature :

(NOTES)

- This report form should be used for recording the thickness measurement of :
All strength deck plating within the cargo (length) area
All keel, bottom shell plating and bilge plating within the cargo (length) area
Side shell plating including selected wind and water strakes outside cargo (length) area
All wind and water strakes within cargo (length) area
- The strake position is should be clearly indicated as follow :
2.1 For strength deck indicate the number of the strake of plating inboard from the stringer plate.
2.2 For bottom plating indicate the number of the strake of plating outboard from the keel plate.
2.3 For side shell plating give number of the strake of plating below sheerstrake and letter as shown on shell expansion.
- For the ships which have no wide cargo openings i.e oil tankers all deck plating strakes should be recorded, for the ships which have wide cargo openings i.e ore/oil ships and bulk carriers only the deck plating strakes outside line of openings should be recorded.
- Measurements should be taken at the forward and aft areas of all plates and where plates cross ballast and cargo tank/hold boundaries separate measurements for the area of plating in way of each type of tank/hold should be recorded.
- The single measurements recorded should represent the average of multiple measurements.
- The maximum allowable diminution could be stated in an attached document.

* : delete as appropriate
T : Oil Tankers and Chemical Tankers with ESP notation
DHT : Double Hull Oil Tankers with ESP notation
BC : Bulk Carriers with ESP notation
DSBC : Double Skin Bulk Carriers with ESP notation
GE : Others
M.A.D : Minimum Allowable Diminution

두께측정 기록표 (계속)

두께측정 기록표 - 현측후판 및 갑판(횡단면 계측 시)

TM2-T/DHT/BC/DSBC/GE(i)*

Report on THICKNESS MEASUREMENT OF SHEER STRAKE AND DECK PLATING AT TRANSVERSE SECTIONS
(one, two or three transverse sections)

Ship's Name :

Identity No. :

Report No. :

STRENGTH DECK AND SHEER STRAKE PLATING																									
		FIRST TRANSVERSE SECTION AT FRAME NUMBER :								SECOND TRANSVERSE SECTION AT FRAME NUMBER :								THIRD TRANSVERSE SECTION AT FRAME NUMBER :							
STRAKE POSITION	No. or Letter	Org. Thk.	M.A.D	Gauged	Diminution P		Diminution S		No. or Letter	Org. Thk.	M.A.D	Gauged	Diminution P		Diminution S		No. or Letter	Org. Thk.	M.A.D	Gauged	Diminution P		Diminution S		
		mm	mm	P	S	mm	%	mm		%	mm	mm	P	S	mm	%		mm	%	mm	mm	P	S	mm	%
Stringer Plate																									
1st strake inboard																									
2nd																									
3rd																									
4th																									
5th																									
6th																									
7th																									
8th																									
9th																									
10th																									
11th																									
12th																									
13th																									
14th																									
centre strake																									
sheer strake																									
TOPSIDE TOTAL																									

Operators Signature :

(NOTES)

- This report form should be used for recording the thickness measurements of :
 - Strength deck plating and sheer strake plating transverse sections :
One, two or three sections within the cargo (length) area comprising of the following structural items :
 - (1) Strength deck plating
 - (2) Stringer plate
 - (3) Sheerstrake
- For the ships which have no wide cargo openings i.e oil tankers all deck plating strakes should be recorded, for the ships which have wide cargo openings i.e ore/oil ships and bulk carriers only the deck plating strakes outside line of openings should be recorded.
- The topside area comprises deck plating, stringer plate and sheer strake (including rounded gunwales)
- The exact frame station of measurement should be stated.
- The single measurements recorded should represent the average of multiple measurements.
- The maximum allowable diminution could be stated in an attached document.

* : delete as appropriate

두께측정 기록표 (계속)

두께측정 기록표 - 선측외판 및 선저외판(횡단면 계측 시)

TM2-T/DHT/BC/DSBC/GE(ii)*

Report on THICKNESS MEASUREMENT OF SHELL AND BOTTOM PLATING AT TRANSVERSE SECTIONS
(one, two or three transverse sections)

Ship's Name :

Identity No. :

Report No. :

SHELL AND BOTTOM PLATING																									
STRAKE POSITION	FIRST TRANSVERSE SECTION AT FRAME NUMBER :								SECOND TRANSVERSE SECTION AT FRAME NUMBER :								THIRD TRANSVERSE SECTION AT FRAME NUMBER :								
	No. or Letter	Org. Thk.	M.A.D	Gauged		Diminution P		Diminution S	No. or Letter	Org. Thk.	M.A.D	Gauged		Diminution P		Diminution S	No. or Letter	Org. Thk.	M.A.D	Gauged		Diminution P		Diminution S	
		mm	mm	P	S	mm	%	mm		%	mm	mm	P	S	mm	%		mm	%	mm	mm	P	S	mm	%
1st below sheer strake																									
2nd																									
3rd																									
4th																									
5th																									
6th																									
7th																									
8th																									
9th																									
10th																									
11th																									
12th																									
13th																									
14th																									
15th																									
16th																									
17th																									
18th																									
keel strake																									
BOTTOM TOTAL																									

Operators Signature :

(NOTES)

- This report form should be used for recording the thickness measurements of :
 - Shell and bottom plating transverse sections :

One, two or three sections within the cargo (length) area comprising of the following structural items :

 - Side shell plating
 - Bilge plating
 - Bottom shell plating
 - Keel plate
- The bottom area comprises keel, bottom and bilge plating.
- The exact frame station of measurement should be stated.
- The single measurements recorded should represent the average of multiple measurements.
- The maximum allowable diminution could be stated in an attached document.

* : delete as appropriate

두께측정 기록표 - 종통부재 (횡단면 계측 시)

TM3-T/DHT/BC/DSBC/GE*

Report on THICKNESS MEASUREMENT OF LONGITUDINAL MEMBERS AT TRANSVERSE SECTIONS
(one, two or three transverse sections)

Ship's Name :

Identity No. :

Report No. :

[illegible]

Operators Signature :

(NOTES)

1. This report form should be used for recording the thickness measurements of :
 - Longitudinal members at transverse sections :
 - One, two or three sections within the cargo (length) area comprising of the following structural items :
 - (1) Deck longitudinals
 - (2) Deck girders
 - (3) Sheerstrake longitudinals
 - (4) Longitudinal bulkhead top strake
 - (5) Bottom longitudinals
 - (6) Bottom girders
 - (7) Bilge longitudinals
 - (8) Longitudinal bulkhead lower strake
 - (9) Side shell longitudinals
 - (10) Longitudinal bulkhead plating (remainder)
 - (11) Longitudinal bulkhead longitudinals
 - (12) Inner bottom plating
 - (13) Inner bottom longitudinals
 - (14) Topside tank sloping plating
 - (15) Topside tank sloping plating longitudinals
 - (16) Hopper side plating
 - (17) Hopper side longitudinals
 - (18) 2nd deck plating (including all lower decks)
 - (19) 2nd deck plating longitudinals (including all lower decks)
 - (20) 2nd deck girders (including all lower decks)
 - (21) Horizontal girders in wing ballast tanks
 - (22) Inner side plating
 - (23) Inner side longitudinals

2. The exact frame station of measurement should be stated.
3. The single measurements recorded should represent the average of multiple measurements.
4. The maximum allowable diminution could be stated in an attached document.

* : delete as appropriate

두께측정 기록표 (계속)

두께측정 기록표 - 횡구조부재(화물탱크(창) 및 평형수 탱크)

TM4-T/DHT/BC/DSBC/GE*

Report on THICKNESS MEASUREMENT OF TRANSVERSE STRUCTURAL MEMBERS in the cargo oil and water ballast tanks within the cargo tank length / in the double bottom, hopper side and topside water ballast tanks*

Ship's Name :

Identity No. :

Report No. :

[illegible]

Operators Signature :

(NOTES)

1. This report form should be used for recording the thickness measurements of transverse structural members comprising of the following structural items :

- (1) Deck transverses centre tank
- (2) Bottom transverses centre tank
- (3) Deck transverses wing tank
- (4) Side shell vertical webs
- (5) Longitudinal bulkhead vertical webs
- (6) Bottom transverses wing tank
- (7) Struts
- (8) Transverse web face plates
- (9) Double bottom tank floors
- (10) Topside tank transverses
- (11) Hopper side tank transverses
- (12) Vertical web in wing ballast tank
- (13) Longitudinal bulkhead vertical web
- (14) Cross ties

2. The single measurements recorded should represent the average of multiple measurements.
3. The maximum allowable diminution could be stated in an attached document.

* : delete as appropriate

두께측정 기록표 (계속)

두께측정 기록표 - 횡격벽 (화물탱크(창) 구역)

TM5-T/DHT/BC/DSBC/GE*

Report on THICKNESS MEASUREMENT OF W.T/O.T TRANSVERSE BULKHEADS within the cargo tanks or cargo hold spaces

Ship's Name : _____

Identity No. :

Report No. :

[illegible]

Operators Signature :

(NOTES)

1. This report form should be used for recording the thickness measurement of W.T / O.T transverse bulkheads or cargo hold transverse bulkheads including bulkhead stiffeners and internal stiffeners of upper and lower stools.
2. The single measurements recorded should represent the average of multiple measurements.
3. The maximum allowable diminution could be stated in an attached document.

* : delete as appropriate

두께측정 기록표 - 기타구조부재

TM6-T/DHT/BC/DSBC/GE*

Report on THICKNESS MEASUREMENT OF MISCELLANEOUS STRUCTURAL MEMBERS

Ship's Name : _____

Identity No. :

Report No. :

[illegible]

Operators Signature :

(NOTES)

1. This report form should be used for recording the thickness measurement of miscellaneous structural members including the following structural items :

- (1) Hatch coamings (including stiffeners)
- (2) Deck plating between hatches
- (3) Hatch covers (including stiffeners)
- (4) Inner bulkhead plating
- (5) Superstructure deck plating
- (6) Forepeak tank internal members
- (7) Aftpeak tank internal members

2. The single measurements recorded should represent the average of multiple measurements.
3. The maximum allowable diminution could be stated in an attached document.

* : delete as appropriate

Report No. :

두께측정 기록표 (계속)

두께측정 기록표 - 갑판 / 선저외판 / 선측외판

TM1-DHT/BC/DSBC*(CSR)

Report on THICKNESS MEASUREMENT of ALL DECK PLATING, ALL BOTTOM PLATING or SIDE SHELL PLATING

Ship's Name : IMO number : Class identity No. : Report No. :

STRAKE POSITION															
PLATE POSITION	No. or Letter	As-built thk. mm	Voluntary thickness addition mm	Renewal thickness mm (a)	Forward Reading				Aft Reading				Mean remaining corr. addition, mm [(c1)+(c2)]/2		
					Gauged thk. mm (b1)		Remaining corr. addition, mm (c1)=(b1)-(a)		Gauged thk. mm (b2)		Remaining corr. addition, mm (c2)=(b2)-(a)				
					P	S	P	S	P	S	P	S	P	S	
12th forward															
11th															
10th															
9th															
8th															
7th															
6th															
5th															
4th															
3rd															
2nd															
1st															
Amidships															
1st aft															
2nd															
3rd															
4th															
5th															
6th															
7th															
8th															
9th															
10th															
11th															
12th															

Operators Signature :

(NOTES)

1. This report should be used for recording the thickness measurement of :
1.1 All strength deck plating within the cargo length area
1.2 All keel, bottom shell plating and bilge plating within the cargo length area
1.3 Side shell plating that is all wind and water strakes within the cargo length area
1.4 Side shell plating that is selected wind and water strakes outside the cargo length area
2. The strake position should be clearly indicated as follow :
2.1 For strength deck indicate the number of the strake of plating inboard from the stringer plate.
2.2 For bottom plating indicate the number of the strake of plating outboard from the keel plate.
2.3 For side shell plating give number of the strake of plating below sheer strake and letter as shown on shell expansion.
3. Only the deck plating strakes outside line of openings should be recorded.
4. Measurements should be taken at the forward and aft areas of all plates and the single measurements recorded should represent the average of multiple measurements.
5. The remaining corrosion addition should be recorded with the result of the gauged thickness minus the renewal thickness. If the result is negative, the structure in way should be renewed, and the mark "R" should be indicated in the right-hand column. If the result is between 0 and 0.5 mm (0 included), the structure in way should be additionally gauged, and the mark "S" should be indicated in the right-hand column.

* : delete as appropriate

DHT : Double Hull Oil Tankers with ESP notation

BC : Bulk Carriers with ESP notation

DSBC : Double Skin Bulk Carriers with ESP notation

두께측정 기록표 (계속)

두께측정 기록표 - 외판 및 갑판(횡단면 계측 시)

TM2-DHT/BC/DSBC/*(CSR)(i)

Report on THICKNESS MEASUREMENT OF SHELL AND DECK PLATING(one, two or three transverse sections)

Ship's Name : IMO number : Class identity No. : Report No. :

STRENGTH DECK AND SHEER STRAKE PLATING																									
	FIRST TRANSVERSE SECTION AT FRAME NUMBER :								SECOND TRANSVERSE SECTION AT FRAME NUMBER :								THIRD TRANSVERSE SECTION AT FRAME NUMBER :								
STRAKE POSITION	No. or Letter	As- built thk. mm	Vol. thk. add. mm	Ren. thk. mm (a)	Gauged thk. mm (b)		Remaining corr. addition, mm (b)–(a)		No. or Letter	As- built thk. mm	Vol. thk. add. mm	Ren. thk. mm (a)	Gauged thk. mm (b)		Remaining corr. addition, mm (b)–(a)		No. or Letter	As- built thk. mm	Vol. thk. add. mm	Ren. thk. mm (a)	Gauged thk. mm (b)		Remaining corr. addition, mm (b)–(a)		
					P	S	P	S					P	S	P	S					P	S	P	S	
Stringer Plate																									
1st strake inboard																									
2nd																									
3rd																									
4th																									
5th																									
6th																									
7th																									
8th																									
9th																									
10th																									
11th																									
12th																									
13th																									
14th																									
centre strake																									
sheer strake																									
TOPSIDE TOTAL																									

Operators Signature :

(NOTES)

- This report should be used for recording the thickness measurements of :
 - Strength deck plating and sheer strake plating transverse sections :
 - One, two or three sections within the cargo length area comprising of the following structural items :
 - (1) Strength deck plating
 - (2) Stringer plate
 - (3) Sheerstrake
 - For BC/DSBC(CSR), only the deck plating strakes outside the line of openings should be recorded.
 - The topside area comprises deck plating, stringer plate and sheer strake (including rounded gunwales)
 - The exact frame station of measurement is to be stated.
 - The single measurements recorded should represent the average of multiple measurements.
 - The remaining corrosion addition should be recorded with the result of the gauged thickness minus the renewal thickness. If the result is negative, the structure in way should be renewed, and the mark "R" should be indicated in the right-hand column. If the result is between 0 and 0.5 mm (0 included), the structure in way should be additionally gauged, and the mark "S" should be indicated in the right-hand column.
- * : delete as appropriate

두께측정 기록표 (계속)

두께측정 기록표 - 외판 및 갑판(횡단면 계측 시)

TM2-T/DHT/BC/DSBC/*(CSR)(II)

Report on THICKNESS MEASUREMENT OF SHELL PLATING (one, two or three transverse sections)

Ship's Name : IMO number : Class identity No. : Report No. :

STRAKE POSITION		FIRST TRANSVERSE SECTION AT FRAME NUMBER :						SECOND TRANSVERSE SECTION AT FRAME NUMBER :						THIRD TRANSVERSE SECTION AT FRAME NUMBER :												
		No. or Letter	As- built thk. mm	Vol. thk. add. mm	Ren. thk. mm (a)	Gauged thk. mm (b)		Remaining corr. addition, mm (b)-(a)		No. or Letter	As- built thk. mm	Vol. thk. add. mm	Ren. thk. mm (a)	Gauged thk. mm (b)		Remaining corr. addition, mm (b)-(a)		No. or Letter	As- built thk. mm	Vol. thk. add. mm	Ren. thk. mm (a)	Gauged thk. mm (b)		Remaining corr. addition, mm (b)-(a)		
P	S					P	S	P	S					P	S	P	S					P	S	P	S	
1st below sheer strake																										
2nd																										
3rd																										
4th																										
5th																										
6th																										
7th																										
8th																										
9th																										
10th																										
11th																										
12th																										
13th																										
14th																										
15th																										
16th																										
17th																										
18th																										
19th																										
20th																										
Keel strake																										
BOTTOM TOTAL																										

Operators Signature :

(NOTES)

1. This report form should be used for recording the thickness measurements of :

- Shell plating transverse sections :

One, two or three sections within the cargo length area comprising of the following structural items :

- (1) Side shell plating
- (2) Bilge plating
- (3) Bottom shell plating
- (4) Keel plate

2. The bottom area comprises keel, bottom and bilge plating.

3. The exact frame station of measurement should be stated.

4. The single measurements recorded should represent the average of multiple measurements.

5. The remaining corrosion addition should be recorded with the result of the gauged thickness minus the renewal thickness. If the result is negative, the structure in way should be renewed, and the mark "R" should be indicated in the right-hand column. If the result is between 0 and 0.5 mm (0 included), the structure in way should be additionally gauged, and the mark "S" should be indicated in the right-hand column.

* : delete as appropriate

두께측정 기록표 - 종통부재 (횡단면 계측 시)

Report on THICKNESS MEASUREMENT OF LONGITUDINAL MEMBERS (one, two or three transverse sections)

[illegible]

(NOTES)

1. This report form should be used for recording the thickness measurements of :
 - Longitudinal members at transverse sections :
 One, two or three sections within the cargo length area comprising of the following structural items :

For BC/DSBC(CSR)

- | | |
|--|--|
| (1) Deck longitudinals | (1) Deck longitudinals |
| (2) Sheerstrake longitudinals | (2) Deck girders |
| (3) Side shell longitudinals | (3) Sheerstrake longitudinals |
| (4) Bilge longitudinals | (4) Topside tank sloping plate |
| (5) Bottom longitudinals | (5) Topside tank sloping plate longitudinals |
| (6) Deck girders | (6) Bottom longitudinals |
| (7) Horizontal girders in wing ballast tanks | (7) Bottom girders |
| (8) Bottom girders | (8) Bilge longitudinals |
| (9) Longitudinal bulkhead top strake | (9) Side shell longitudinals, if any |
| (10) Longitudinal bulkhead bottom strake | (10) Inner bottom plating |
| (11) Longitudinal bulkhead plating (remainder) | (11) Inner bottom longitudinals |
| (12) Longitudinal bulkhead longitudinals | (12) Hopper plating |
| (13) Inner side plating | (13) Hopper longitudinals |
| (14) Inner side longitudinals | (14) Inner side plating |
| (15) Hopper plating | Inner side longitudinals, if any |
| (16) Hopper longitudinals | Horizontal girders in wing ballast tanks |
| (17) Inner bottom plating | |
| (18) Inner bottom longitudinals | |
| (19) Topside tank plating | |
| (20) Topside tank longitudinals | |

2. The exact frame station of measurement should be stated.
3. The single measurements recorded should represent the average of multiple measurements.
4. The remaining corrosion addition should be recorded with the result of the gauged thickness minus the renewal thickness. If the result is negative, the structure in way should be renewed, and the mark "R" should be indicated in the right-hand column. If the result is between 0 and 0.5 mm (0 included), the structure in way should be additionally gauged, and the mark "S" should be indicated in the right-hand column.

* : delete as appropriate

두께측정 기록표 (계속)

두께측정 기록표 - 횡구조부재(화물탱크(창) 및 평형수 탱크)

TM4-DHT/BC/DSBC/*(CSR)

Report on THICKNESS MEASUREMENT OF TRANSVERSE STRUCTURAL MEMBERS in the double bottom, hopper side and topside water ballast tanks

Ship's Name : IMO number : Class identity No. : Report No. :

[illegible]

Operators Signature :

(NOTES)

1. This report form should be used for recording the thickness measurements of transverse structural members comprising of the following structural items :

For DHT(CSR)

- (1) Deck transverses - centre tank
- (2) Deck transverses - wing tank
- (3) Vertical web in wing ballast tank
- (4) Double bottom floors - wing tank
- (5) Double bottom floors - centre tank
- (6) Longitudinal bulkhead vertical webs
- (7) Cross ties

For BC/DSBC(CSR)

- (1) Double bottom tank floors
 - (2) Topside tank transverses
 - (3) Hopper side tank transverses
 - (4) Transverse web frame
- Ordinary transverse frame in double skin tank

2. The single measurements recorded should represent the average of multiple measurements.
3. The remaining corrosion addition should be recorded with the result of the gauged thickness minus the renewal thickness. If the result is negative, the structure in way should be renewed, and the mark "R" should be indicated in the right-hand column. If the result is between 0 and 0.5 mm (0 included), the structure in way should be additionally gauged, and the mark "S" should be indicated in the right-hand column.

* : delete as appropriate

두께측정 기록표 - 횡격벽 (화물탱크(창) 구역)

Report on THICKNESS MEASUREMENT OF cargo hold transverse bulkheads

TANK/HOLD DESCRIPTION :

FRAME NO:

Operators Signature :

1. This report form should be used for recording the thickness measurement of cargo hold and watertight/oiltight transverse bulkheads.
2. The single measurements recorded should represent the average of multiple measurements.
3. The remaining corrosion addition should be recorded with the result of the gauged thickness minus the renewal thickness. If the result is negative, the structure in way should be renewed, and the mark "R" should be indicated in the right-hand column. If the result is between 0 and 0.5 mm (0 included), the structure in way should be additionally gauged, and the mark "S" should be indicated in the right-hand column.

* : delete as appropriate

두께측정 기록표 - 기타구조부재

Report on THICKNESS MEASUREMENT OF MISCELLANEOUS STRUCTURAL MEMBERS

Ship's Name : IMO number : Class identity No. : Report No. :

[illegible]

(NOTES)

1. This report form should be used for recording the thickness measurement of miscellaneous structural members including the following structural items :
 - (1) Hatch coamings (including stiffeners)
 - (2) Deck plating between hatches
 - (3) Hatch covers (including stiffeners)
 - (4) Inner bulkhead plating
 - (5) Superstructure deck plating
 - (6) Forepeak tank internal members
 - (7) Aftpeak tank internal members
2. The single measurements recorded should represent the average of multiple measurements.
3. The remaining corrosion addition should be recorded with the result of the gauged thickness minus the renewal thickness. If the result is negative, the structure in way should be renewed, and the mark "R" should be indicated in the right-hand column. If the result is between 0 and 0,5 mm (0 included), the structure in way should be additionally gauged, and the mark "S" should be indicated in the right-hand column.

두께측정 기록표 (계속)

두께측정 기록표 - 화물창 횡능골

TM7-BC*(CSR)

Ship's Name : IMO number : Class identity No. : Report No. :

* : delete as appropriate