

[별표 12]

보조표지의 제작규격과 의미 및 적용기준

표지구분/종류	보조/방향및거리표지	번호	6-1																												
 <table border="1" data-bbox="713 927 908 1001"> <thead> <tr> <th></th> <th>A</th> <th>B</th> <th>C</th> <th>D</th> <th>E</th> <th>비율</th> </tr> </thead> <tbody> <tr> <td>30m</td> <td>420</td> <td>600</td> <td>300</td> <td>84</td> <td>103</td> <td>1</td> </tr> <tr> <td>50m</td> <td>700</td> <td>1000</td> <td>500</td> <td>140</td> <td>169</td> <td>1.67</td> </tr> <tr> <td>100m</td> <td>1360</td> <td>1950</td> <td>975</td> <td>273</td> <td>337</td> <td>3.25</td> </tr> </tbody> </table>					A	B	C	D	E	비율	30m	420	600	300	84	103	1	50m	700	1000	500	140	169	1.67	100m	1360	1950	975	273	337	3.25
	A	B	C	D	E	비율																									
30m	420	600	300	84	103	1																									
50m	700	1000	500	140	169	1.67																									
100m	1360	1950	975	273	337	3.25																									
○ 표지의 측면에 보조표지인 삼각형을 부착하고, 흑색 숫자를 표기하여 계류가 금지된 미터단위 거리를 나타냄																															