

TABLE III

PER-VIEW SUCCESS RATE (%) UNDER CAMERA STALENESS AND VIEW UNAVAILABILITY. FOR STALENESS, ONLY THE INDICATED CAMERA STREAM IS MADE STALE WHILE THE OTHER REMAINS CURRENT. FOR AVAILABILITY, ONLY THE INDICATED VIEW IS RETAINED AND THE OTHER IS REMOVED.

	Model	Normal	Staleness		Availability	
			Third	Wrist	Third	Wrist
VLA	OpenVLA-OFT	97.0	<u>37.15</u> $\downarrow 59.9$	10.90 $\downarrow 86.1$	<u>15.31</u> $\downarrow 81.7$	43.19 $\downarrow 53.8$
	π_0	92.5	32.85 $\downarrow 59.6$	<u>21.15</u> $\downarrow 71.3$	7.62 $\downarrow 84.9$	48.75 $\downarrow 43.8$
	$\pi_{0.5}$	97.2	21.35 $\downarrow 75.8$	19.70 $\downarrow 77.5$	2.19 $\downarrow 95.0$	<u>43.25</u> $\downarrow 54.0$
WAM	FastWAM	98.8	21.65 $\downarrow 77.2$	12.35 $\downarrow 86.5$	0.56 $\downarrow 98.2$	19.69 $\downarrow 79.1$
	LingBot-VA	97.0	55.75 $\downarrow 41.2$	13.25 $\downarrow 83.8$	1.38 $\downarrow 95.6$	40.62 $\downarrow 56.4$
	LaWAM	98.5	9.95 $\downarrow 88.5$	23.25 $\downarrow 75.2$	35.00 $\downarrow 63.5$	0.94 $\downarrow 97.6$