

CSC 4020 Fundamentals of Machine Learning:

K-Means


Baoyuan Wu

April 26/28

[Slide credit: Mengye Ren and Matthew MacKay]


Clustering

- Sometimes the data form clusters, where examples within a cluster are similar to each other, and examples in different clusters are dissimilar:



- Such a distribution is **multimodal**, since it has multiple **modes**, or regions of high probability mass.
- Grouping data points into clusters, with no labels, is called **clustering**
- E.g. clustering machine learning papers based on topic (deep learning, Bayesian models, etc.)

Clustering





- Assume the data $\{\mathbf{x}^{(1)}, \dots, \mathbf{x}^{(N)}\}$ lives in a Euclidean space, $\mathbf{x}^{(n)} \in \mathbb{R}^d$.
- Assume the data belongs to K classes (patterns)
- Assume the data points from same class are similar, i.e. close in Euclidean distance.
- How can we identify those classes (data points that belong to each class)?

K-means intuition

- K-means assumes there are k clusters, and each point is close to its cluster center (the mean of points in the cluster).
- If we knew the cluster assignment we could easily compute means.
- If we knew the means we could easily compute cluster assignment.
- Chicken and egg problem.
- It is NP hard.
- Very simple (and useful) heuristic - start randomly and alternate between the two.

K-means

- **Initialization:** randomly initialize cluster centers
- The algorithm iteratively alternates between two steps:
 - ▶ **Assignment step:** Assign each data point to the closest cluster
 - ▶ **Refitting step:** Move each cluster center to the center of gravity of the data assigned to it






Figure from Bishop

Simple demo: <http://syskall.com/kmeans.js/>

K-means Objective

What is actually being optimized?

K-means Objective:

Find cluster centers \mathbf{m} and assignments \mathbf{r} to minimize the sum of squared distances of data points $\{\mathbf{x}^{(n)}\}$ to their assigned cluster centers

$$\min_{\{\mathbf{m}\}, \{\mathbf{r}\}} J(\{\mathbf{m}\}, \{\mathbf{r}\}) = \min_{\{\mathbf{m}\}, \{\mathbf{r}\}} \sum_{n=1}^N \sum_{k=1}^K r_k^{(n)} \|\mathbf{m}_k - \mathbf{x}^{(n)}\|^2$$
$$\text{s.t. } \sum_k r_k^{(n)} = 1, \forall n, \quad \text{where } r_k^{(n)} \in \{0, 1\}, \forall k, n$$

where $r_k^{(n)} = 1$ means that $\mathbf{x}^{(n)}$ is assigned to cluster k (with center \mathbf{m}_k)

- **Optimization method** is a form of coordinate descent (“block coordinate descent”)
 - ▶ Fix centers, optimize assignments (choose cluster whose mean is closest)
 - ▶ Fix assignments, optimize means (average of assigned datapoints)

The K-means Algorithm

- **Initialization:** Set K cluster means $\mathbf{m}_1, \dots, \mathbf{m}_K$ to random values
- Repeat until convergence (until assignments do not change):
 - ▶ **Assignment:** Each data point $\mathbf{x}^{(n)}$ assigned to nearest mean

$$\hat{k}^n = \arg \min_k d(\mathbf{m}_k, \mathbf{x}^{(n)})$$

(with, for example, L2 norm: $\hat{k}^n = \arg \min_k \|\mathbf{m}_k - \mathbf{x}^{(n)}\|^2$)

and **Responsibilities** (1-hot encoding)

$$r_k^{(n)} = 1 \longleftrightarrow \hat{k}^{(n)} = k$$

- ▶ **Refitting:** Model parameters, means are adjusted to match sample means of data points they are responsible for:

$$\mathbf{m}_k = \frac{\sum_n r_k^{(n)} \mathbf{x}^{(n)}}{\sum_n r_k^{(n)}}$$

K-means for Vector Quantization





Figure from Bishop


K-means for Image Segmentation



- How would you modify k-means to get superpixels?

Why K-means Converges

- Whenever an assignment is changed, the sum squared distances J of data points from their assigned cluster centers is reduced.
- Whenever a cluster center is moved, J is reduced.
- **Test for convergence:** If the assignments do not change in the assignment step, we have converged (to at least a local minimum).




- K-means cost function after each assignment step (blue) and refitting step (red). The algorithm has converged after the third refitting step

Local Minima

- The objective J is non-convex (so coordinate descent on J is not guaranteed to converge to the global minimum)
- There is nothing to prevent k-means getting stuck at local minima.
- We could try many random starting points
- We could try non-local split-and-merge moves:
 - ▶ Simultaneously **merge** two nearby clusters
 - ▶ and **split** a big cluster into two

A bad local optimum



Soft K-means

- Instead of making hard assignments of data points to clusters, we can make **soft assignments**. One cluster may have a responsibility of .7 for a datapoint and another may have a responsibility of .3.
 - ▶ Allows a cluster to use more information about the data in the refitting step.
 - ▶ How do we decide on the soft assignments?

Soft K-means Algorithm

- **Initialization:** Set K means $\{\mathbf{m}_k\}$ to random values
- Repeat until convergence (until assignments do not change):
 - ▶ **Assignment:** Each data point n given soft “degree of assignment” to each cluster mean k , based on responsibilities

$$r_k^{(n)} = \frac{\exp[-\beta d(\mathbf{m}_k, \mathbf{x}^{(n)})]}{\sum_j \exp[-\beta d(\mathbf{m}_j, \mathbf{x}^{(n)})]}$$

- ▶ **Refitting:** Model parameters, means, are adjusted to match sample means of datapoints they are responsible for:

$$\mathbf{m}_k = \frac{\sum_n r_k^{(n)} \mathbf{x}^{(n)}}{\sum_n r_k^{(n)}}$$

Questions about Soft K-means

Some remaining issues

- How to set β ?
- What about problems with elongated clusters?
- Clusters with unequal weight and width

These aren't straightforward to address with K-means. Instead, next lecture, we'll reformulate clustering using a generative model.