

CSC 4020 Fundamental of Machine Learning: Bias-Variance Tradeoff

Baoyuan Wu
School of Data Science, CUHK-SZ

January 25/27, 2021

Bias-variance tradeoff

- We are provided by a training dataset $D = \{(\mathbf{x}_i, y_i)\}_{i=1}^n$, which is drawn i.i.d. from some distribution $P(\mathcal{X}, \mathcal{Y})$

Bias-variance tradeoff

- We are provided by a training dataset $D = \{(\mathbf{x}_i, y_i)\}_{i=1}^n$, which is drawn i.i.d. from some distribution $P(\mathcal{X}, \mathcal{Y})$
- The relationship between the input features \mathbf{x} and the output y is

$$y = h(\mathbf{x}) + e, \quad e \sim \mathcal{N}(0, \sigma^2), \quad (1)$$

$$p(y|\mathbf{x}) = \mathcal{N}(h(\mathbf{x}), \sigma^2 \mathbf{I}), \quad (2)$$

where $h(\mathbf{x})$ can be seen as the unknown target function and the mean of $p(y|\mathbf{x})$.

Bias-variance tradeoff

- We are provided by a training dataset $D = \{(\mathbf{x}_i, y_i)\}_{i=1}^n$, which is drawn i.i.d. from some distribution $P(\mathcal{X}, \mathcal{Y})$
- The relationship between the input features \mathbf{x} and the output y is

$$y = h(\mathbf{x}) + e, \quad e \sim \mathcal{N}(0, \sigma^2), \quad (1)$$

$$p(y|\mathbf{x}) = \mathcal{N}(h(\mathbf{x}), \sigma^2 \mathbf{I}), \quad (2)$$

where $h(\mathbf{x})$ can be seen as the unknown target function and the mean of $p(y|\mathbf{x})$.

- The goal of machine learning is to learn a hypothesis function based on the training dataset D using some learning algorithm \mathcal{A} , *i.e.*,

$$h_D = \mathcal{A}(D)$$

Bias-variance tradeoff

- **Expected hypothesis function** (given \mathcal{A}):

$$\bar{h} = E_{D \sim P^n}[h_D] = \int_D h_D p(D) dD$$

Bias-variance tradeoff

- **Expected hypothesis function** (given \mathcal{A}):

$$\bar{h} = E_{D \sim P^n}[h_D] = \int_D h_D p(D) dD$$

- Given a test pair $(\mathbf{x}, y) \sim P(\mathcal{X}, \mathcal{Y})$ and h_D , the **expected test error** is defined as

$$E_{(\mathbf{x}, y) \sim P}[(h_D(\mathbf{x}) - y)^2] = \int_{\mathbf{x}} \int_y (h_D(\mathbf{x}) - y)^2 p(x, y) d\mathbf{x} dy$$

Bias-variance tradeoff

- **Expected hypothesis function** (given \mathcal{A}):

$$\bar{h} = E_{D \sim P^n}[h_D] = \int_D h_D p(D) dD$$

- Given a test pair $(\mathbf{x}, y) \sim P(\mathcal{X}, \mathcal{Y})$ and h_D , the **expected test error** is defined as

$$E_{(\mathbf{x}, y) \sim P}[(h_D(\mathbf{x}) - y)^2] = \int_{\mathbf{x}} \int_y (h_D(\mathbf{x}) - y)^2 p(\mathbf{x}, y) d\mathbf{x} dy$$

- Given a test pair $(\mathbf{x}, y) \sim P(\mathcal{X}, \mathcal{Y})$ and \mathcal{A} , the **expected test error** is defined as

$$E_{(\mathbf{x}, y) \sim P, D \sim P^n}[(h_D(\mathbf{x}) - y)^2] = \int_D \int_{\mathbf{x}} \int_y (h_D(\mathbf{x}) - y)^2 p(\mathbf{x}, y) d\mathbf{x} dy dD$$

Bias-variance tradeoff

- **Expected hypothesis function** (given \mathcal{A}):

$$\bar{h} = E_{D \sim P^n}[h_D] = \int_D h_D p(D) dD$$

- Given a test pair $(\mathbf{x}, y) \sim P(\mathcal{X}, \mathcal{Y})$ and h_D , the **expected test error** is defined as

$$E_{(\mathbf{x}, y) \sim P}[(h_D(\mathbf{x}) - y)^2] = \int_{\mathbf{x}} \int_y (h_D(\mathbf{x}) - y)^2 p(x, y) d\mathbf{x} dy$$

- Given a test pair $(\mathbf{x}, y) \sim P(\mathcal{X}, \mathcal{Y})$ and \mathcal{A} , the **expected test error** is defined as

$$E_{(\mathbf{x}, y) \sim P, D \sim P^n}[(h_D(\mathbf{x}) - y)^2] = \int_D \int_{\mathbf{x}} \int_y (h_D(\mathbf{x}) - y)^2 p(x, y) d\mathbf{x} dy dD$$

- We are interested in evaluating the quality of a machine learning algorithm \mathcal{A} with respect to a data distribution $P(\mathcal{X}, \mathcal{Y})$. In the following we will show that this expression decomposes into three meaningful terms.

Bias-variance tradeoff

- The **expected test error** can be decomposed as follows

$$\begin{aligned} E_{(\mathbf{x},y),D} [(h_D(\mathbf{x}) - y)^2] &= E_{(\mathbf{x},y),D} [(h_D(\mathbf{x}) - \bar{h}(\mathbf{x})) + (\bar{h}(\mathbf{x}) - y)]^2 \\ &= E_{(\mathbf{x},y),D} [(h_D(\mathbf{x}) - \bar{h}(\mathbf{x}))^2] + 2E_{(\mathbf{x},y),D} [(h_D(\mathbf{x}) - \bar{h}(\mathbf{x}))(\bar{h}(\mathbf{x}) - y)] \\ &\quad + E_{(\mathbf{x},y),D} [(\bar{h}(\mathbf{x}) - y)^2] \end{aligned}$$

Bias-variance tradeoff

- The **expected test error** can be decomposed as follows

$$\begin{aligned} E_{(\mathbf{x},y),D} [(h_D(\mathbf{x}) - y)^2] &= E_{(\mathbf{x},y),D} [(h_D(\mathbf{x}) - \bar{h}(\mathbf{x})) + (\bar{h}(\mathbf{x}) - y)]^2 \\ &= E_{(\mathbf{x},y),D} [(h_D(\mathbf{x}) - \bar{h}(\mathbf{x}))^2] + 2E_{(\mathbf{x},y),D} [(h_D(\mathbf{x}) - \bar{h}(\mathbf{x}))(\bar{h}(\mathbf{x}) - y)] \\ &\quad + E_{(\mathbf{x},y),D} [(\bar{h}(\mathbf{x}) - y)^2] \end{aligned}$$

- We have

$$\begin{aligned} &E_{(\mathbf{x},y),D} [(h_D(\mathbf{x}) - \bar{h}(\mathbf{x}))(\bar{h}(\mathbf{x}) - y)] \\ &= E_{(\mathbf{x},y)} [E_D[(h_D(\mathbf{x}) - \bar{h}(\mathbf{x}))(\bar{h}(\mathbf{x}) - y)]] \\ &= E_{(\mathbf{x},y)} [(E_D[h_D(\mathbf{x})] - \bar{h}(\mathbf{x}))(\bar{h}(\mathbf{x}) - y)] = 0 \end{aligned}$$

Bias-variance tradeoff

- The **expected test error** can be decomposed as follows

$$\begin{aligned} E_{(\mathbf{x},y),D} [(h_D(\mathbf{x}) - y)^2] &= E_{(\mathbf{x},y),D} [(h_D(\mathbf{x}) - \bar{h}(\mathbf{x})) + (\bar{h}(\mathbf{x}) - y)]^2 \\ &= E_{(\mathbf{x},y),D} [(h_D(\mathbf{x}) - \bar{h}(\mathbf{x}))^2] + 2E_{(\mathbf{x},y),D} [(h_D(\mathbf{x}) - \bar{h}(\mathbf{x}))(\bar{h}(\mathbf{x}) - y)] \\ &\quad + E_{(\mathbf{x},y),D} [(\bar{h}(\mathbf{x}) - y)^2] \end{aligned}$$

- We have

$$\begin{aligned} &E_{(\mathbf{x},y),D} [(h_D(\mathbf{x}) - \bar{h}(\mathbf{x}))(\bar{h}(\mathbf{x}) - y)] \\ &= E_{(\mathbf{x},y)} [E_D[(h_D(\mathbf{x}) - \bar{h}(\mathbf{x}))(\bar{h}(\mathbf{x}) - y)]] \\ &= E_{(\mathbf{x},y)} [(E_D[h_D(\mathbf{x})] - \bar{h}(\mathbf{x}))(\bar{h}(\mathbf{x}) - y)] = 0 \end{aligned}$$

- Then, we have

$$E_{(\mathbf{x},y),D} [(h_D(\mathbf{x}) - y)^2] = E_{(\mathbf{x},y),D} [(h_D(\mathbf{x}) - \bar{h}(\mathbf{x}))^2] + E_{(\mathbf{x},y),D} [(\bar{h}(\mathbf{x}) - y)^2]$$

- We also have

$$\begin{aligned} E_{(\mathbf{x},y),D}[(\bar{h}(\mathbf{x}) - y)^2] &= E_{(\mathbf{x},y),D}[(\bar{h}(\mathbf{x}) - h(\mathbf{x})) + (h(\mathbf{x}) - y)]^2 \\ &= E_{\mathbf{x},y}[(h(\mathbf{x}) - y)^2] + E_{\mathbf{x},y}[\bar{h}(\mathbf{x}) - h(\mathbf{x}))^2] + 2E_{\mathbf{x},y}[(h(\mathbf{x}) - y)(\bar{h}(\mathbf{x}) - h(\mathbf{x}))] \\ &= E_{\mathbf{x},y}[(h(\mathbf{x}) - y)^2] + E_{\mathbf{x},y}[\bar{h}(\mathbf{x}) - h(\mathbf{x}))^2] \end{aligned} \quad (3)$$

Bias-variance tradeoff

- We also have

$$\begin{aligned} E_{(\mathbf{x},y),D}[(\bar{h}(\mathbf{x}) - y)^2] &= E_{(\mathbf{x},y),D}[(\bar{h}(\mathbf{x}) - h(\mathbf{x})) + (h(\mathbf{x}) - y)]^2 \\ &= E_{\mathbf{x},y}[(h(\mathbf{x}) - y)^2] + E_{\mathbf{x},y}[\bar{h}(\mathbf{x}) - h(\mathbf{x}))^2] + 2E_{\mathbf{x},y}[(h(\mathbf{x}) - y)(\bar{h}(\mathbf{x}) - h(\mathbf{x}))] \\ &= E_{\mathbf{x},y}[(h(\mathbf{x}) - y)^2] + E_{\mathbf{x},y}[\bar{h}(\mathbf{x}) - h(\mathbf{x}))^2] \end{aligned} \quad (3)$$

- Finally, we have

$$\begin{aligned} E_{(\mathbf{x},y),D}[(h_D(\mathbf{x}) - y)^2] \\ &= E_{(\mathbf{x},y),D}[(h_D(\mathbf{x}) - \bar{h}(\mathbf{x}))^2] + E_{(\mathbf{x},y)}[(\bar{h}(\mathbf{x}) - h(\mathbf{x}))^2] + E_{\mathbf{x},y}[(h(\mathbf{x}) - y)^2] \end{aligned}$$

Bias-variance tradeoff

- We also have

$$\begin{aligned} E_{(\mathbf{x},y),D}[(\bar{h}(\mathbf{x}) - y)^2] &= E_{(\mathbf{x},y),D}[(\bar{h}(\mathbf{x}) - h(\mathbf{x})) + (h(\mathbf{x}) - y)]^2 \\ &= E_{\mathbf{x},y}[(h(\mathbf{x}) - y)^2] + E_{\mathbf{x},y}[\bar{h}(\mathbf{x}) - h(\mathbf{x})]^2 + 2E_{\mathbf{x},y}[(h(\mathbf{x}) - y)(\bar{h}(\mathbf{x}) - h(\mathbf{x}))] \\ &= E_{\mathbf{x},y}[(h(\mathbf{x}) - y)^2] + E_{\mathbf{x},y}[\bar{h}(\mathbf{x}) - h(\mathbf{x})]^2 \end{aligned} \quad (3)$$

- Finally, we have

$$\begin{aligned} E_{(\mathbf{x},y),D}[(h_D(\mathbf{x}) - y)^2] \\ &= E_{(\mathbf{x},y),D}[(h_D(\mathbf{x}) - \bar{h}(\mathbf{x}))^2] + E_{(\mathbf{x},y)}[(\bar{h}(\mathbf{x}) - h(\mathbf{x}))^2] + E_{\mathbf{x},y}[(h(\mathbf{x}) - y)^2] \end{aligned}$$

- Above three terms are **variance**, **bias**, **noise**, respectively.

Bias-variance tradeoff

$$\begin{aligned} & E_{(\mathbf{x}, y), D} [(h_D(\mathbf{x}) - y)^2] \\ = & E_{(\mathbf{x}, y), D} [(h_D(\mathbf{x}) - \bar{h}(\mathbf{x}))^2] + E_{(\mathbf{x}, y)} [(\bar{h}(\mathbf{x}) - h(\mathbf{x}))^2] + E_{\mathbf{x}, y} [(h(\mathbf{x}) - y)^2] \end{aligned}$$

Bias-variance tradeoff

$$\begin{aligned} & E_{(\mathbf{x},y),D}[(h_D(\mathbf{x}) - y)^2] \\ = & E_{(\mathbf{x},y),D}[(h_D(\mathbf{x}) - \bar{h}(\mathbf{x}))^2] + E_{(\mathbf{x},y)}[(\bar{h}(\mathbf{x}) - h(\mathbf{x}))^2] + E_{\mathbf{x},y}[(h(\mathbf{x}) - y)^2] \end{aligned}$$

- **variance:** Captures how much your classifier changes if you train on a different training set. How "over-specialized" is your classifier to a particular training set (overfitting)? If we have the best possible model for our training data, how far off are we from the average classifier?

Bias-variance tradeoff

$$\begin{aligned} & E_{(\mathbf{x},y),D} [(h_D(\mathbf{x}) - y)^2] \\ = & E_{(\mathbf{x},y),D} [(h_D(\mathbf{x}) - \bar{h}(\mathbf{x}))^2] + E_{(\mathbf{x},y)} [(\bar{h}(\mathbf{x}) - h(\mathbf{x}))^2] + E_{\mathbf{x},y} [(h(\mathbf{x}) - y)^2] \end{aligned}$$


- **variance:** Captures how much your classifier changes if you train on a different training set. How "over-specialized" is your classifier to a particular training set (overfitting)? If we have the best possible model for our training data, how far off are we from the average classifier?
- **Bias:** What is the inherent error that you obtain from your classifier even with infinite training data? This is due to your classifier being "biased" to a particular kind of solution (*e.g.*, linear classifier). In other words, bias is inherent to your model.

Bias-variance tradeoff


$$\begin{aligned} & E_{(\mathbf{x}, y), D} [(h_D(\mathbf{x}) - y)^2] \\ = & E_{(\mathbf{x}, y), D} [(h_D(\mathbf{x}) - \bar{h}(\mathbf{x}))^2] + E_{(\mathbf{x}, y)} [(\bar{h}(\mathbf{x}) - h(\mathbf{x}))^2] + E_{\mathbf{x}, y} [(h(\mathbf{x}) - y)^2] \end{aligned}$$

- **variance:** Captures how much your classifier changes if you train on a different training set. How "over-specialized" is your classifier to a particular training set (overfitting)? If we have the best possible model for our training data, how far off are we from the average classifier?
- **Bias:** What is the inherent error that you obtain from your classifier even with infinite training data? This is due to your classifier being "biased" to a particular kind of solution (*e.g.*, linear classifier). In other words, bias is inherent to your model.
- **Noise:** How big is the data-intrinsic noise? This error measures ambiguity due to your data distribution and feature representation. You can never beat this, it is an aspect of the data.


Bias-variance tradeoff




Bias-variance tradeoff



Bias-variance tradeoff



Bias-variance tradeoff



Regime 1 (High Variance)

In the first regime, the cause of the poor performance is high variance.


Symptoms:

1. Training error is much lower than test error
2. Training error is lower than ϵ
3. Test error is above ϵ


Remedies:

- Add more training data
- Reduce model complexity -- complex models are prone to high variance

Bias-variance tradeoff



Bias-variance tradeoff



Regime 2 (High Bias)

Unlike the first regime, the second regime indicates high bias: the model being used is not robust enough to produce an accurate prediction.

Symptoms:

1. Training error is higher than ϵ

Remedies:

- Use more complex model (e.g. kernelize, use non-linear models)
- Add features

Bias-variance tradeoff

More details can be found at <https://www.cs.cornell.edu/courses/cs4780/2018fa/lectures/lecturenote12.html>