Driver / Carrier Mobile – API Endpoint Listing

Overview

This document lists all API endpoints required by the **Driver/Carrier Mobile Interface** and maps each one to its corresponding **database tables**.
These endpoints cover the main delivery operations and driver workflow features:

- Route assignment and daily delivery manifest management (US11)
- Real-time navigation and status updates (US12)
- Proof of Delivery (POD) capture (US13)
- Exception and failed delivery reporting (US14)

---

1. Driver Authentication & Profile

Method	Endpoint	Description	Main Tables
POST	`/auth/login`	Authenticate driver using email/phone and password; returns access token.	`users`, `drivers`
GET	`/drivers/me`	Retrieve logged-in driver profile and current status.	`drivers`, `users`, `carriers`
PATCH	`/drivers/me/status`	Update driver's availability or route status (`AVAILABLE`, `BREAK`, `ON_ROUTE`, `OFF_DUTY`).	`drivers`, `audit_logs`
PATCH	`/drivers/me/location`	Update driver's current GPS location (background sync).	`drivers`

2. Daily Route & Delivery Manifest Management

PROF

Method	Endpoint	Description	Main Tables
GET	`/routes/today`	Retrieve driver's assigned route for the current day, including total stops and progress.	`delivery_routes`, `drivers`
GET	`/routes/{id}`	Retrieve detailed route information (stops, sequence, ETA, metrics).	`delivery_routes`, `delivery_manifests`, `orders`
POST	`/routes/{id}/start`	Mark route as started (updates actual_start timestamp).	`delivery_routes`, `audit_logs`
POST	`/routes/{id}/complete`	Mark route as completed after last delivery (updates actual_end).	`delivery_routes`, `audit_logs`
POST	`/routes/{id}/optimize`	Request route re-optimization (e.g., for traffic or failed stops).	`delivery_routes`

3. Delivery Manifest Operations

Method	Endpoint	Description	Main Tables
GET	`/routes/{id}/deliveries`	List all delivery stops for a given route (sequence, address, status).	`delivery_manifests`, `orders`, `customers`
GET	`/deliveries/{id}`	Retrieve full delivery details for a specific stop (customer, package info, notes).	`delivery_manifests`, `orders`, `customers`
PATCH	`/deliveries/{id}/status`	Update delivery status (`EN_ROUTE`, `ARRIVED`, `DELIVERED`, `FAILED`).	`delivery_manifests`, `tracking_events`, `audit_logs`
POST	`/deliveries/{id}/arrived`	Confirm arrival at delivery location (GPS + timestamp).	`delivery_manifests`, `tracking_events`
POST	`/deliveries/{id}/skip`	Skip a stop (with justification or exception).	`delivery_manifests`, `delivery_attempts`, `tracking_events`

4. Proof of Delivery (POD)

Method	Endpoint	Description	Main Tables
POST	`/deliveries/{id}/pod/signature`	Upload digital signature for proof of delivery.	`delivery_manifests`, `shipping_documents`
POST	`/deliveries/{id}/pod/photo`	Upload delivery photo as evidence of drop-off.	`delivery_manifests`, `shipping_documents`
POST	`/deliveries/{id}/pod/delivery_note`	Add delivery note or special instructions from customer.	`delivery_manifests`, `shipping_documents`
POST	`/deliveries/{id}/complete`	Complete delivery with POD details (recipient name, relationship, GPS, notes).	`delivery_manifests`, `delivery_attempts`, `tracking_events`, `orders`
GET	`/deliveries/{id}/pod`	Retrieve proof of delivery data (photos, signatures).	`delivery_manifests`, `shipping_documents`

PROF

5. Exception & Failed Delivery Reporting

Method	Endpoint	Description	Main Tables
POST	`/deliveries/{id}/exception`	Report delivery issue or failure (damaged, absent, wrong address, etc.).	`delivery_exceptions`, `delivery_attempts`, `tracking_events`
POST	`/deliveries/{id}/exception/photos`	Upload supporting photos for the exception report.	`delivery_exceptions`
GET	`/deliveries/{id}/exceptions`	Retrieve all exceptions logged for a specific delivery.	`delivery_exceptions`
PATCH	`/deliveries/{id}/exception/{exception_id}`	Update or resolve exception (e.g., after redelivery or return).	`delivery_exceptions`, `audit_logs`
POST	`/deliveries/{id}/attempt`	Log a delivery attempt (success or failure) with GPS and timestamp.	`delivery_attempts`, `delivery_manifests`, `tracking_events`

PROF

6. Real-Time Tracking & Telemetry

Method	Endpoint	Description	Main Tables
POST	`/tracking/heartbeat`	Send periodic GPS + status updates for live tracking (background).	`drivers`, `tracking_events`
GET	`/tracking/{order_id}`	Retrieve tracking history for a specific order.	`tracking_events`, `orders`

Method	Endpoint	Description	Main Tables
POST	`/tracking/event`	Log a manual tracking event (e.g., “Out for Delivery”).	`tracking_events`

7. Notifications & Alerts

Method	Endpoint	Description	Main Tables
GET	`/notifications`	Retrieve driver’s pending notifications (new routes, customer messages).	`notification_logs`
PATCH	`/notifications/{id}/read`	Mark a notification as read.	`notification_logs`