

Domain Class	Responsibility
GroupAction	Controller / entry point. Handles the <i>Group Selection</i> command: checks <code>canGroup()</code> , clones the prototype group, builds an <code>UndoableEdit</code> , and performs the grouping. Also the base class for ungrouping.
UngroupAction	Controller for the <i>Ungroup Selection</i> command. Subclass of <code>GroupAction</code> configured to ungroup; reuses the grouping logic in reverse.
AbstractSelectedAction	Base behaviour for selection-based actions: provides <code>getView()</code> , <code>getEditor()</code> , selection-change listening, and <code>fireUndoableEditHappened()</code> .
DrawingEditor	Coordinates the editor and supplies the active <code>DrawingView</code> the action operates on.
DrawingView	View and selection manager. Exposes the current selection (<code>getSelectedFigures</code> , <code>getSelectionCount</code>), updates it (<code>clearSelection</code> , <code>addToSelection</code>), and provides the <code>Drawing</code> .
Drawing	Model / root container of all figures. Mutated during (un)grouping (<code>sort</code> , <code>indexOf</code> , <code>add</code> , <code>remove</code> , <code>basicAddAll</code> , <code>basicRemoveAll</code>); owns z-order.
CompositeFigure	Interface for a figure that contains child figures (<code>basicAdd</code> , <code>basicRemoveAllChildren</code> , <code>getChildren</code>), used to assemble and dissolve the group.
GroupFigure	Concrete <code>CompositeFigure</code> used as the prototype — the object the selected figures are placed into; manages the grouped children and their combined bounds.
Figure	Base interface for every drawable element. Each grouped/ungrouped figure receives <code>willChange()</code> / <code>changed()</code> so the canvas repaints and bounds recompute.
UndoableEdit / AbstractUndoableEdit	Undo/redo support: captures the operation so <code>undo()</code> reverses and <code>redo()</code> re-applies the group/ungroup.