

Package name	# of classes	Comments
org.jhotdraw.draw.action	3	Entry point of the change request — visited first and marked CHANGED . <code>GroupAction</code> , <code>UngroupAction</code> and their base <code>AbstractSelectedAction</code> start the feature from the <i>Group/Ungroup Selection</i> menu items.
org.jhotdraw.draw	10	Core model/view of the feature (CHANGED / PROPAGATES). Grouping moves figures between the drawing and a group: <code>Figure</code> , <code>AbstractFigure</code> , <code>CompositeFigure</code> , <code>AbstractCompositeFigure</code> , <code>GroupFigure</code> , <code>Drawing</code> , <code>AbstractDrawing</code> , <code>DefaultDrawing</code> , <code>DrawingView</code> , <code>DrawingEditor</code> .
org.jhotdraw.draw.event	7	Change/selection notifications fired while children move in or out of the group (PROPAGATES — listeners must stay consistent): <code>FigureEvent</code> , <code>FigureListener</code> , <code>FigureAdapter</code> , <code>CompositeFigureEvent</code> , <code>CompositeFigureListener</code> , <code>FigureSelectionEvent</code> , <code>FigureSelectionListener</code> .
org.jhotdraw.draw.handle	3	Selection handles rebuilt when the group becomes the selected figure (PROPAGATES): <code>Handle</code> , <code>BoundsOutlineHandle</code> , <code>TransformHandleKit</code> .
org.jhotdraw.draw.layouter	1	<code>Layouter</code> — optional auto-layout a composite figure can apply to its children after grouping. Visited, marked UNCHANGED .
org.jhotdraw.geom	2	Geometry for the group's combined bounds: <code>Geom</code> , <code>Dimension2DDouble</code> . Visited as neighbours, UNCHANGED .
org.jhotdraw.xml	3	Persistence so a saved group reloads with its children (PROPAGATES): <code>DOMStorable</code> , <code>DOMInput</code> , <code>DOMOutput</code> .
org.jhotdraw.util	2	Support used by the feature: <code>ResourceBundleUtil</code> (action labels) and <code>ReversedList</code> (child iteration order). UNCHANGED .
org.jhotdraw.app	1	<code>Disposable</code> — the lifecycle contract the action implements. UNCHANGED .
org.jhotdraw.beans	1	<code>WeakPropertyChangeListener</code> — lets the action track the active view without leaking memory. UNCHANGED .
javax.swing.undo (Java SE)	2	<code>UndoableEdit</code> , <code>AbstractUndoableEdit</code> — undo/redo of the group/ungroup. Visited but outside the project, so UNCHANGED .

Estimated Impact Set total: 35 classes visited across 11 packages (10 JHotDraw packages + 1 Java SE). The classes most likely to be modified for the change are concentrated in `org.jhotdraw.draw.action` and `org.jhotdraw.draw` ; the remaining packages were visited as neighbours and judged UNCHANGED or only PROPAGATES.