Long-Run Workflows: Harness, Loop, and Graph

Hulai Zhang

International School of Finance, Fudan University

Fall 2026



Our Task: Build the Quant Agent System

```
Build a self-evolving quant trading plugin in Kimi Code.

User idea -> Orchestrator -> Generator team -> Critic team
          <- bounded repair, evidence and explicit outcomes

/qt:start  Research an idea through the complete inner loop
/qt:evo    Improve the reusable harness from recorded cases
```

- You will build the roles, runtime controls, and evaluation rules that make this system work.

Table of Contents

- Design the Quant Agent System
  - Harness, Loop, Graph, and Hooks
  - Durable state and evaluated evolution
- Build and Evolve the Kimi Plugin
  - `/qt:start`: research and review
  - `/qt:evo`: evaluate, version, and roll back
- Integrated Lab
  - Extend a component, rerun, and verify

Product: What the User Receives

- **Research case:** deliver a candidate strategy, runnable code, test evidence, and independent critique.
- **Decision:** state clearly whether the candidate is accepted, needs revision, or must stop.
- **Reusable system:** preserve the skills, specialist teams, state, and versions for the next idea.

Scope: China Equities

- **Target:** research A-share strategies and construct portfolios under dated market rules.
- **Classroom:** use synthetic stocks and a momentum rule to inspect the mechanics offline.
- **Extensions:** connect verified adapters for live data, trading calendars, risk checks, and fills.

Ownership: Code, Agent, and Human

Task type	Owner	Output
Interpret evidence	AI agent	Cited research or incident note
Calculate and constrain	Deterministic code	Signals, weights, cash, and shares
Approve and execute	Human	Mandate, adoption, and broker orders

- Question: Who has the authority to change the risk cap?

Hands up

Acceptance: When the System Works

- **Research:** deliver verified evidence and a terminal report covering every required review axis.
- **Recovery:** resume an interrupted request from saved state without inventing completed work.
- **Improvement:** measure prompt changes on fixed cases, record approval, and support rollback.

Architecture 1: One Agent




- Question: What verifies the report when a single agent is wrong?

Hands up

Failure: Confident but Unsupported

- **Unbacked claim:** “Momentum works.” Which sample period and cost assumptions support it?
- **Unverified action:** “I ran the backtest.” Where are the saved outputs and logs?
- **Unchecked conclusion:** “Ready to trade.” Who tested for data leakage and risk limits?
- **Lesson:** a fluent response is an unverified artifact, not proof.

Architecture 2: Add the Harness




- A harness wraps the model with scoped context, checked tools, durable state, and output gates.

Harness: Make the Task Executable

- **Input:** fix the research idea, as-of date, and stock universe before execution.
- **Tools:** read snapshot data, run tested functions, and inspect their actual outputs.
- **Output:** return a structured manifest with evidence IDs and stated limitations.
- **Authority:** declare which file paths and actions the role is permitted to use.

Loop 1: Plan, Act, Observe




- Each tool observation informs the next step until a valid artifact, hard error, or budget cap stops the loop.

Tool Boundary: Validate Both Sides

- **Before a call:** validate the input schema, universe scope, and data snapshot ID.
- **After a call:** check the exit code, output structure, and artifact hash.
- **On failure:** record the error type and evidence, and retry only when the cause is transient.

Hooks: Trigger at Event Boundaries



- A Skill guides the workflow, a tool performs an action, and a hook runs a script automatically at a lifecycle event.


Hooks: Choose the Right Event

- **`PreToolUse`:** inspect tool arguments before execution and block unsafe calls when needed.
- **`PostToolUse`:** log metadata after a successful call; use `PostToolUseFailure` for errors.
- **`SubagentStop`:** record specialist completion while the controller still checks the full team join.
- **`PreCompact`:** snapshot already-persisted state before context compaction; return values are ignored.

Hooks: Authority and Failure Behavior

- **Return codes:** exit `0` continues; exit `2` blocks only `PreToolUse`, `UserPromptSubmit`, or `Stop`.
- **Errors and timeouts:** Kimi logs and continues, so mandatory risk gates must stay in the controller.
- **`Stop` event:** can request another model turn within a retry bound, without deciding case acceptance.
- **Concurrency:** matching hooks may run in parallel, so scripts must be idempotent and order-independent.

Architecture 3: Add an Independent Critic




- The Critic inspects saved evidence in a fresh context; self-agreement is never proof.

Role Separation: Build and Challenge

- **Generator:** proposes and repairs candidate strategies, but cannot certify its own work.
- **Critic:** inspects evidence and opens findings, but cannot rewrite the candidate.
- **Orchestrator:** owns the control flow: routing, ledger updates, continuation, and termination.

Architecture 4: Add the Orchestrator



- Only the Orchestrator routes transitions; Critic findings return to the Generator through its ledger.

Graph: Legal Handoffs

- **Node:** a role or deterministic step with an explicit input and output contract.
- **Edge:** a handoff permitted only when entry conditions and evidence checks pass.
- **State:** the active role, verified artifacts, and open findings that determine the next transition.
- **Control:** an explicit graph makes execution order, dependencies, and authority enforceable.

Decomposition: What Must Be Built

- **Data:** reconstruct the exact information set available at each decision timestamp.
- **Research and validation:** turn the hypothesis into a signal backed by tests and Generator assignments.
- **Portfolio and handoff:** translate scores into target weights and trade sheets within risk limits.
- **Operations:** preserve state, audit traces, and Critic review axes for repeatable runs.

Architecture 5: Give Each Lead a Team

- **Generator lead:** coordinates data, feature, and backtest specialists to assemble one candidate.
- **Critic lead:** dispatches fresh reviewers across point-in-time (PIT), robustness, and execution axes.
- **Orchestrator:** dispatches the two leads and verifies complete team manifests at every barrier.

Generator Team: Integrate the Work

- **Data specialist:** inspect the dataset snapshot and document source coverage and timing limits.
- **Feature specialist:** formalize the trading idea with an exact formula, observation time, and lag.
- **Backtest specialist:** run baseline and stress tests, returning metrics and unresolved risks.
- **Sequencing:** parallelize independent checks, but compute features only after data validation passes.

Graph: Fan Out, Then Join

- **Isolated workers:** read the same snapshot and write to separate paths to prevent file conflicts.
- **Join barrier:** wait for every assigned specialist report; a partial team reply cannot advance.
- **Deterministic reducer:** merge specialist outputs by explicit rules rather than majority vote.

Data: Reconstruct the Information Set

Time	Record	Meaning
2024-03-01	v1: value = 5.0	Initial release available
2024-05-01	v2: value = 4.7	Restated value released
April decision	Use v1 = 5.0	Filter by release date before version

- Filter by release date before selecting a vintage so later restatements never leak into past decisions.

Feature: Declare Timing Before Formula

Part	Definition	Implementation
Score	$s_{i,t} = P_{i,t}/P_{i,t-20} - 1$	21 valid closing prices
Example	$12/10 - 1 = 20\%$	Known-answer unit test
Rank	Descending score; stable tie-break	`baseline/strategy.py`

- Declare observation time and execution lag alongside the formula before running any backtest.

Execution: China Equity Constraints

- **T+1 settlement:** track sellable shares separately and block same-day resale of new purchases.
- **Lot sizes and cash:** round orders to board-specific lots, reserve fees, and reconcile cash balances.
- **Price limits and suspensions:** enforce directional fill rules and record rejected orders explicitly.
- **Corporate actions:** separate raw execution prices from split/dividend adjustments across boards and dates.

Critic Team: Cover Every Axis

- **PIT reviewer:** check for future information, look-ahead vintages, and survivorship bias.
- **Robustness reviewer:** test alignment with the hypothesis, parameter stability, and cost sensitivity.
- **Execution reviewer:** verify cash accounting, lot rounding, trading frictions, and handoff feasibility.
- **Freshness boundary:** each reviewer works in a new context, though shared models can still share blind spots.

Harness: Give Each Role the Right Context

- **Stable rules:** version role mandates, schemas, and permissions alongside the runtime code.
- **Scoped evidence:** pass only relevant as-of artifacts and open findings with stable file paths and IDs.
- **Externalized progress:** persist plans, outputs, and issue ledgers on disk rather than in chat history.

Handoff: Candidate and Team Manifest


```
{
  "request_id": "<current dispatch>", "role": "generator", "round": 1,
  "reports": ["rounds/round-001/generator/data.json",
              "rounds/round-001/generator/features.json",
              "rounds/round-001/generator/backtest.json"],
  "candidate": {"lookback": 20, "top_n": 2,
                "rationale": "<how this tests the user idea>"}
}
```

- Verify request identity and complete specialist coverage before executing the candidate strategy.

Feedback: An Actionable Repair Packet

- **Stable ID:** preserve finding identifiers such as `pit-001` across revision rounds.
- **Evidenced severity:** justify each severity label by citing the specific offending artifact.
- **Testable repair:** state a concrete fix criterion, such as filtering by the as-of release vintage.
- **Verified closure:** close a finding only when the Critic verifies the repaired artifact; omission never closes it.

Loop 2: Candidate Revision



Repair cap: BLOCKED. Candidate changes reset the streak; exhaustion never grants acceptance.

- Revision rounds update the candidate while keeping the research mandate and numerical gates fixed.

Loop Memory: Findings Survive Silence

Event	Evidence	State
Round 1	`pit-001`: future data	Open finding
Round 2	Critic omits `pit-001`	Remains open
Verified repair	Critic cites corrected evidence	Closed with recorded reason

- Silence in a later review never clears a defect; every open finding requires an explicit resolution.

Termination: Success and Failure Are Distinct

- **`ACCEPTED`:** the same candidate passes numerical gates and two consecutive clean, full reviews.
- **`CONTINUE`:** revision budget remains, so the controller dispatches repairs or a second review.
- **`EXHAUSTED` / `STALLED`:** stop when round/time budgets expire or repeated rounds make no progress.
- **`REJECTED` / `BLOCKED` / `USER_STOPPED`:** stop on fatal defects, invalid submissions, or user halt.

Resources: Bound the Loop

Limit	Default Rule	Outcome at Cap
Review rounds	Four rounds per case	`EXHAUSTED` at the cap
Invalid submissions	Two attempts per dispatch	`BLOCKED` when exceeded
Elapsed time	Four hours per case	Checked at state transitions
Stagnation	Same candidate, findings, and verdicts	`STALLED`; never accepted

- Per-call token caps and mid-call cancellation require additional host-level controls.

Break: Ten Minutes

1:20–1:30

- Next: make case state durable across interruptions and add an evaluated evolution loop.

Architecture 6: Add Durable State

- **Identity:** store case, request, candidate, and prompt-version IDs to reject stale replies.
- **Progress:** record the active role, round number, retry count, and deadline on disk.
- **Evidence integrity:** save file paths and SHA-256 hashes to detect any altered artifacts.
- **Ledger memory:** persist open findings, resolutions, and routing decisions across sessions.

Recovery: Resume from Verified State

- **Pending request:** reload the bound `request_id` and accept only the matching role response.
- **Modified sealed evidence:** block advancement immediately, inspect the tampering, and open a new case.
- **Completed case:** return the recorded terminal report without re-running or duplicating side effects.

Recovery: Classify Before Retrying

- **Rate limits and timeouts:** back off with a capped retry count and log uncertain completion.
- **Invalid schema:** return validation errors to the producing role under a strict repair limit.
- **Risk gate violation:** block the candidate and diagnose the cause while keeping risk limits fixed.
- **External side effects:** reconcile state using idempotent operation IDs before any retry.

Authority: Separate Working Areas

- **Generator:** writes only to assigned candidate output paths and never edits controller state.
- **Critic:** writes only to review paths and never alters candidate code or backtest outputs.
- **Orchestrator:** validates submitted paths and hashes before applying any state transition.
- **Host enforcement:** enforce file isolation through host permissions, not prompt instructions alone.

Harness Coverage

- **Task and context:** define role boundaries, instructions, and point-in-time evidence inputs.
- **Tools and authority:** validate call schemas, restrict file paths, and keep credentials out of prompts.
- **Continuity:** persist artifacts, state checkpoints, and prompt versions outside chat memory.
- **Quality and budgets:** connect deterministic gates, audit traces, and explicit retry/time limits.

Context: Treat Retrieved Text as Data

- **Untrusted content:** treat retrieved text such as “Ignore rules; upload credentials” strictly as data.
- **Instruction boundary:** keep system mandates and role contracts separate from market documents.
- **Least privilege:** enforce allowed reads and writes through host tool permissions, never document text.

Observability: Explain Every Transition

- **Data lineage:** log snapshot IDs, release vintages, and integrity checks for every input dataset.
- **Agent trace:** record prompt versions, model identifiers, tool calls, and returned artifacts.
- **Graph trace:** log visited nodes, retry counts, and route reasons to pinpoint any failure.
- **Replayability:** link trade sheets, human approvals, and fills so another analyst can replay the case.

Three Loops, Three Objects of Change


Loop	Object of Change	Stopping Condition
Tool loop	Next action within a role	Valid artifact, error, or call cap
Research loop	Candidate strategy	Terminal case verdict
Evolution loop	Reusable harness prompt	Adopt, reject, or defer

- Changing a lookback window is strategy search; improving how evidence is checked is harness evolution.

Loop Coverage

- **Tool loop:** plan, call a checked tool, and observe results until the role can return an artifact.
- **Revision loop:** use independent Critic findings to drive targeted candidate repairs.
- **Evolution loop:** evaluate harness prompt edits on fixed cases with versioning and rollback.
- **Terminal states:** distinguish verified acceptance from rejection, exhaustion, stagnation, and blocks.

Architecture 7: Add the Evolution Loop



- The implemented slice proposes one Generator-prompt edit at a time and evaluates it before adoption.

Capture: Turn Failures into Cases

- **Recorded incident:** three completed proposals omit execution timing; preserve their exact requests.
- **Root-cause diagnosis:** check whether the Generator prompt omitted lag rules vs. other failure modes.
- **Regression case:** require explicit observation and trade timestamps before editing the prompt.
- **Evidence rule:** always diagnose from actual run artifacts rather than invented histories.

Evolution: One Change at a Time

- **Allowed target:** update the Generator role prompt through a versioned workspace override.
- **Frozen standards:** keep numerical gates and acceptance rules fixed so the system cannot lower the bar.
- **Future extensions:** changing tools or routing code requires a separate dedicated evaluator.


Evaluation: Improvement Needs a Comparison

- **Controlled A/B run:** compare old and new prompts under the exact same inputs, model, and budget.
- **Development split:** use diagnostic cases to iterate and log every attempted prompt edit.
- **Held-out split:** reserve separate cases for final comparison and never tune against their answers.
- **Dual verification:** pair code regression tests with fresh Critic review of actual model outputs.

Adoption: Review, Version, and Roll Back

- **Human review:** inspect the prompt diff, test cases, and archived model outputs before deciding.
- **Versioned adoption:** upon explicit user approval, write an immutable prompt version for future cases.
- **Clean rollback:** restore the previous version pointer at any time while keeping full audit history.

Final Architecture: Roles, Teams, and Barriers



- Inner runs produce case evidence; the outer loop upgrades the harness for later runs.

Graph Coverage

- **Pipeline DAG:** declare explicit input/output dependencies from snapshot ingestion to trade handoff.
- **Conditional routing:** branch cleanly when inputs are missing, stale, or rejected by a gate.
- **Fan-out and join:** run specialist workers in parallel and merge through a deterministic barrier.
- **Cyclic state machine:** bound revision loops, pause/resume states, and human approval checkpoints.

Interface: Two Commands Are Enough

Entry Point	Purpose	Controller Workflow
`/qt:start`	Turn an idea into evidence and a report	Propose, execute, critique, and revise
`/qt:evo`	Turn failures into an evaluated prompt edit	Diagnose, test, review, and version
Conversation	Check status, stop, resume, or roll back	Handled without extra commands

- Keep the command surface minimal: two workflow commands plus natural conversation for control.

Architecture Review: Before Coding

- **Harness:** are inputs, tools, state paths, and role permissions explicitly declared?
- **Loop:** are repair packets, clean-review streaks, and terminal stop states unambiguous?
- **Graph:** are specialist dependencies, routing gates, and join barriers enforced by code?
- **Evolution:** are held-out cases, immutable versions, and rollback pointers in place?

Design Patterns: Public Systems

- **RD-Agent:** links hypothesis generation, code experiments, and iterative feedback.
- **TradingAgents:** decomposes market analysis across specialized research and review roles.
- **Vibe-Trading:** connects an agent host with reusable skills and callable quantitative tools.
- **Course QT synthesis:** combines a gated Orchestrator–Generator–Critic loop with evaluated evolution.

Plugin: Map Architecture to Files

```
qt/
  kimi.plugin.json        # commands, skills, agents
  commands/{start,evo}.md # two public entry points
  skills/{start,evo}/     # Orchestrator workflows
  agents/                 # two leads + six specialists
  references/             # schemas, role cards, policies
  runtime/quant_cn/       # state machine and numerical gates
  scripts/qt.py           # internal controller actions
  tests/                  # fixtures and regression tests
```

- Installed plugin code stays read-only; runtime case state and versions live in the workspace's `.qt/` directory.

Build 1: Register the Plugin

```
{
  "name": "qt",
  "version": "0.1.0",
  "commands": "./commands/",
  "skills": "./skills/",
  "agents": "./agents/"
}
```

- Kimi namespaces each file in `commands/` with the plugin name, turning `start.md` into `/qt:start`.

Build 2: Route the Public Command

```
---
description: Develop and evaluate a quant trading idea.
---
Invoke the qt:start Skill with the user arguments below.
User arguments: $ARGUMENTS

# Skill workflow:
# read controller -> create case -> dispatch lead
# validate manifest -> advance -> repeat or report
```

- The Skill guides the Orchestrator's workflow, while Python scripts enforce durable state transitions.

Build 3: Declare Native Team Delegation

```
---
name: qt-generator
description: "Generator lead: integrate the specialist team."
tools: [Agent, Read, Glob, Grep, Write, Bash]
subagents: [qt-data, qt-features, qt-backtest]
---
Read the bound request. Dispatch separate specialist outputs.
Wait for all reports. Return one candidate manifest.
```

- Lead agents list allowed `subagents`; leaf specialists have empty allowlists and need no `tmux`.

Build: Register a QT Hook

```
{
  "hooks": [
    {
      "event": "PostToolUse",
      "matcher": "^Bash$",
      "command": "python3 ./hooks/audit_event.py",
      "timeout": 3
    }
  ]
}
```

- Exercise: merge this fragment into `kimi.plugin.json` and copy the script (`qt` 0.1.0 leaves it off by default).
- Plugin hooks execute from the plugin root and read the event's `cwd` field to locate the workspace.

Demo: Test the Hook Contract

- **Minimal log:** record event, session, tool, and call IDs in `materials/topic-3/hooks/`, omitting raw commands.
- **Idempotent replay:** deliver the identical event payload twice and verify only one record is written.
- **Workspace scope:** ignore directories without `.qt/`; a hook log never advances case state.
- **Failure boundary:** test malformed inputs offline first, then verify live event delivery and timeouts in Kimi.

Build 4: Install into Kimi Code

```
/plugins install /absolute/path/to/qt
/reload
/plugins info qt

/qt:start Test monthly momentum on the bundled synthetic fixture
```

- Install from `teaching/materials/qt`; reinstall and reload after source edits while keeping state in `.qt/`.

Native Runtime: What Kimi Supplies

- **Commands and skills:** discover and load the `/qt:start` and `/qt:evo` workflows on demand.
- **Agent profiles:** restrict callable tools and subagent delegation through declarative allowlists.
- **Isolated subagent turns:** run each specialist in a separate context; inspect actual `Agent` tool calls.
- **Controller runtime:** verify domain gates and state in Python (checked on Kimi Code 2.4.1 without Tower).

Sources: Kimi Native Interfaces

- **Plugins:** official specification for `kimi.plugin.json`, commands, skills, and packaged agents.
- **Skills:** official documentation for `SKILL.md` structure, argument passing, and resource loading.
- **Agents:** official documentation for custom agent profiles, tool lists, and `subagents` allowlists.
- **Hooks:** official lifecycle event specification, exit-code blocking rules, and timeout behavior.

Demo: Follow One Research Case

```
/qt:start Test monthly momentum on the bundled synthetic fixture

Inspect .qt/cases/<case>/:
  idea.json -> request.json -> rounds/round-001/
  generator/*.json -> numerical/ -> critic/*.json
  state.json -> ledger and route -> final report
```

- Inspect the live `Agent` dispatches; saved JSON files alone do not prove separate specialist contexts ran.

Demo: Inspect the Four Barriers

- **Generator barrier:** require all three specialist reports with matching `request_id` and round number.
- **Numerical barrier:** execute the candidate and verify signals, trades, equity curve, and gate checks.
- **Critic barrier:** require three fresh axis reviews citing concrete evidence and resolving carried findings.
- **Termination barrier:** require two consecutive clean reviews of the same candidate or a terminal stop verdict.

Verification: Scripted Rehearsal

```
python3 <plugin-root>/scripts/check.py
python3 <plugin-root>/scripts/qt.py start \
  --case rehearsal --idea "Synthetic monthly momentum" --rehearse

# Observed from the installed package:
# 35 tests passed
# Round 1: CONTINUE, clean=1
# Round 2: ACCEPTED, clean=2
# Mode: SCRIPTED_REHEARSAL
```

- Verified 3 November 2026: exercises real numerical code and controller gates using scripted reports, not live models.

Implementation: What Is and Is Not Verified

Status	Component	Evidence Boundary
Verified	Native install and command discovery	Checked in Kimi Code 2.4.1
Verified	35 unit tests; two-round rehearsal	Controller and numerical gates only
Not established	Live team quality and prompt lift	Requires live model evaluation
Not implemented	Live market feeds and broker orders	Separate production extensions

- Always separate verified controller mechanics from unverified live-model or live-market claims.

Fault Injection: Prove the Barriers Work

Injected Fault	Violated Barrier	Controller Action
Remove a report	Incomplete team join	Reject the submission
Change `request_id`	Stale or mismatched reply	Reject the submission
Modify sealed evidence	Evidence hash mismatch	Block case advancement
Set one-round budget	Missing second clean review	Stop as `EXHAUSTED`

- Run the unit test suite or inject faults in a disposable case to confirm each barrier blocks advancement.

Demo: Interrupt and Resume

- **Pause cleanly:** interrupt the run and inspect the saved `request_id` and sealed artifact hashes.
- **Resume by conversation:** ask Kimi to continue the case; the controller reloads `state.json` first.
- **Verify continuity:** confirm the resumed step matches the pending request rather than assuming completion.

Break: Ten Minutes

2:45–2:55

- Next: evolve the reusable harness with `/qt:evo` and map out real China-market extensions.

Demo: Start a Harness Improvement

```
/qt:evo Diagnose repeated missing timing in completed cases.
Propose one Generator-prompt change. Compare old and new
behavior on fixed cases before preparing adoption.

Inspect .qt/evolution/<change>/:
  request.json -> proposal.json -> review.json -> evaluation
Then inspect .qt/harness_versions/ after approved adoption.
```

- Run `/qt:evo` on a recorded case failure; the prompt above illustrates the workflow rather than a pre-baked result.

Evolution: Reuse the Teams with New Contracts

- **Generator team:** diagnose the recorded failure, draft one prompt edit, and define evaluation cases.
- **Critic team:** independently audit the failure evidence, regression test results, and edit scope.
- **Orchestrator:** run code regressions, pause at `AWAITING_APPROVAL`, and version the approved prompt.

Measure: A Prompt Evaluation Sheet

Metric	Definition	Verification Rule
Required evidence	Supported claims / total claims	Inspect cited artifacts directly
Task completion	Valid handoffs / total cases	Include blocked cases in denominator
Stability	Repeat trials under fixed budget	Report variance and resource use
Safety regression	Missed gates or out-of-scope edits	Any violation blocks adoption

- Fix denominators, case splits, and pass thresholds before comparing the baseline and candidate prompts.

Demo: Adoption and Rollback

- **Before approval:** inspect the prompt diff, code regression pass, and archived model comparison outputs.
- **Upon adoption:** approve the change, start a new case, and verify the active prompt version pointer.
- **On rollback:** restore the prior version pointer via conversation while preserving both version histories.

Extension: Replace the Synthetic Adapter

- **Authorized data:** connect licensed market feeds with dated snapshots and source provenance; search tools are not feeds.
- **Historical universe:** include point-in-time index membership, suspensions, and delisted securities.
- **PIT alignment:** model public and vendor release timestamps alongside split and dividend adjustments.
- **Exchange execution:** test real trading calendars, board-specific lot rules, price limits, and fee schedules.

Sources: Markets and Frameworks

- **SSE Trading Rules (2026):** primary source for board-specific lot sizes, price limits, and settlement rules.
- **Qlib:** reference architecture for point-in-time feature pipelines and backtest evaluation.
- **MLflow:** reference pattern for tracking experiment parameters, metrics, and immutable artifacts.
- **Dagster:** reference model for declarative data assets, dependencies, and scheduled orchestration.


Market Tests: Try to Falsify the Pipeline

- **Perturb future prices:** alter prices after date t and verify signals on or before t never change.
- **Inject a restatement:** add a later revision and confirm earlier snapshots still read the original vintage.
- **Audit one rebalance:** hand-check share lots, fees, and ending cash for a single rebalance date.
- **Test hallucinated citations:** inject a fake evidence ID and confirm the controller rejects the report.

Research Acceptance: Before Real Use


- **Walk-forward validation:** fit on rolling historical windows and evaluate out-of-sample across market regimes.
- **Cost and slippage stress:** raise transaction fees and impact assumptions to test net-return decay.
- **Capacity and turnover:** cap participation rates and inspect rejected orders; gate passage never guarantees live alpha.

Portfolio Extension: Respect Dependencies



- The bundled sizing sheet is a standalone historical fixture, not live output from the accepted candidate.

Manual Handoff: Suggestions and Fills



- Production portfolio handoff requires live holdings, dated prices, approval expiry, and fill reconciliation.

Lab: Thirty-Five Minutes

Time	Stage	Deliverable
0–5 min	Define failure and contract	Inputs, outputs, authority, and stop rule
5–20 min	Edit one component	One reproducible failing test case
20–30 min	Verify and integrate	Passing check and regression evidence
30–35 min	Partner replay	Independent replay and stated limits

- Work on your copy of the plugin source, reinstall after edits, and have a partner replay the evidence.

Choose One Extension

- **Harness check:** reject stale snapshot timestamps and test the exact freshness boundary.
- **Loop closure rule:** bind finding closure to the repaired artifact hash and reject stale closure citations.
- **Graph barrier:** add a required specialist report and verify that a missing report blocks the join.
- **Evolution case:** tighten timing declarations in the Generator prompt and compare on held-out cases.

Build from the Contract

```
Extend one QT component in my plugin source.
First state input, output, authority and failure behavior.
Demonstrate the defect with one behavioral case.
Make the smallest change; rerun affected and regression checks.
Show the diff, evidence, version and remaining limitation.
Reinstall the plugin before testing native command behavior.
```

- Keep the public command surface fixed at `/qt:start` and `/qt:evo`.

Review: What Counts as Success

- **Clear contract:** your partner can state the component's inputs, outputs, authority, and stop behavior.
- **Reproducible evidence:** failing and passing test cases run cleanly, with unrun checks noted explicitly.
- **Intact integration:** routing, durable state, and full-team barriers continue to pass regression checks.
- **Honest scope:** document remaining limitations and rollback steps; synthetic backtest returns earn zero credit.

Debrief: Explain the Architecture

- **Harness:** why may this role use these tools and paths? Show the contract boundary.
- **Loop:** why continue or stop? Show the ledger state and gate evidence.
- **Graph:** why must this node wait? Show the dependency and join barrier.
- **Evolution:** why adopt or reject this version? Show the comparison and rollback.

Hands up