Anonymous block

↳ used while debugging by programmers.

Named vs Anonymv

↓

reusability

what stored means?

IN parameter (Normall c++/ java para meter)

↓

can't be modified.

ON param → Multiple

$$CGPA = \frac{\sum N_i C_i}{\sum C_i}$$

A+	4
A	3.75
A-	3.5
B+	3.25
B	3.00

A CSE 4110 → 2 cred
= 2 × 3.75
+

tot cred.

X number (4,2);

BEGIN

X = select

→ can't declare variable

X number(4,2);

BEGIN

Select name, CGPA

into x, y

From students

where ID = p_ID

end;

2 variables simultaneously

X x, y number

precision not allowed ~~in~~ even in return.

Customer

- ID
- name

Transaction

- ID
- CID
- Amount
- Type of Trans (1/0)
- Dt.

1. Deposit
0. withdrawal

write func to find the status of a

customer.

IF balance > 1000000
  Then ST = 'VIP'
ELSE
    ST = 'NORMAL'
END IF;

Soln:

CREATE OR REPLACE FUNCTION
GETSTATUS (PCID IN NUMBER)
  RETURN VARCHAR2

Nothing can be written

no precision allowed

→ Balance not in table. → Sum all depo - Sum all withdr

IS
  V_D NUMBER(10,2); → V_D NUMBER(10,2):=0
  V_W || || :=0;
  V_B
BEGIN

```
SELECT Sum(Amocent) into V_D
FROM Transaction
Where CID = P_CID
and TpTrans=1;

        into V_W;
FROM Transaction
Where CID = P_CID
and TpTrans=0;

V_B = V_D - V_W;
END;

IF V_B > 1000000
THEN ST='VIP';
ELSE ST ='NORMAL';
END IF;
```

IF 100 P.

Calling a Function

Select getstatus (1001) from Dual;

all employees of B.B branch.

```
SELECT C.Name, getStates(ID) STATUS
from Customer.
Where Branch = 'BB';
```

```
SELECT decode (Tp Trans , 1, 'Deposit',
                          1, 'withdraw', Others)
```

without yellow part → elseif → switch case.

RANK

Last placeholder → nth guy.