

OPEN SOURCE CONCEPT · PRIOR ART DISCLOSURE

Humanoid Workbench

A Specialized Workstation System for Humanoid Robots

Author Björn van der Valk	Website HumanoidWorkbench.com	Published June 2026	Version 1.0 — Public Domain
-------------------------------------	---	-------------------------------	---------------------------------------

This document is released into the public domain as a Defensive Publication. Its purpose is to establish prior art and prevent any party from claiming patent ownership over the general concept of specialized workstation systems designed for humanoid robots.

1. Executive Summary	1
Key Points	1
2. Market Context & Relevance	2
Why Tool Use Is the Critical Bottleneck	3
Deployment Scale	3
3. Definition	3
Scope	3
4. Core Philosophy.....	4
Design Principles.....	4
4.1 Tool Neutrality.....	4
4.2 Robot Capability Awareness.....	4
4.3 Solution Agnosticism	4
4.4 Scalability.....	5
4.5 Human-Robot Compatibility	5
5. Key Technical Challenges	5
6. Solution Space.....	6
6.1 Mechanical Interface Solutions	6
6.2 Workbench Surface Solutions	6
6.3 Sensing & Software Solutions	6
6.4 Hybrid & Novel Solutions.....	6
7. Prior Art & Related Work.....	6
8. Application Scenarios	7
8.1 Industrial Assembly	7

8.2 Maintenance & Repair 7

8.3 Construction Site 7

8.4 Small Workshop / SME 7

9. Public Domain Declaration..... 8

 Legal Basis..... 8

 Core Intent..... 8

 What This Does NOT Restrict 8

10. Document Versioning & Updates 9

1. Executive Summary

The Humanoid Workbench addresses one of the most pressing challenges in industrial robotics: how can humanoid robots use standard tools — designed for human hands — in practical working environments?

This document defines the concept, its scope, the key technical challenges it addresses, the potential solution space, relevant market context, and the reasoning behind its release as public domain prior art.

A Humanoid Workbench is a specialized workstation system optimized for the kinematic capabilities, grip patterns, reach envelopes, and physical characteristics of humanoid robots — enabling them to efficiently and reliably use standard, unmodified tools.

Key Points

- The concept is technology-agnostic — it does not prescribe specific solutions
- Standard tools remain unmodified — the workbench adapts to bridge the gap
- Addresses both hardware and workflow challenges in humanoid robot tool use
- Released as public domain to prevent patent monopolization of the general concept
- Applicable across manufacturing, maintenance, construction, and service industries

2. Market Context & Relevance

The humanoid robot industry is entering a period of rapid commercialization. Companies such as Tesla (Optimus), Figure AI, Agility Robotics, Boston Dynamics, and Apptronik are actively deploying or developing humanoid platforms for industrial use. A central challenge in nearly every deployment scenario is tool use.

Why Tool Use Is the Critical Bottleneck

Human workers have spent millennia co-evolving with their tools. Every screwdriver, drill, wrench, and power tool on the market today is designed around the human hand — its size, grip strength, dexterity, and proprioception. Humanoid robots face an immediate disadvantage:

- Hand geometry differs — even human-inspired robot hands have different dimensions and compliance
- Force modulation is imprecise — applying exactly the right torque or pressure is difficult
- Tactile feedback is limited — robots cannot yet feel slippage or resistance the way humans do
- Tool retrieval is unguided — picking up a loose screwdriver from a surface is surprisingly complex
- Battery and accessory changes require fine motor skills that exceed current robot dexterity

Deployment Scale

Analysts project that the humanoid robot market will grow from approximately \$1.5B in 2024 to over \$38B by 2035. Every deployed unit in an industrial setting will require some form of tool interface. The Humanoid Workbench concept addresses this at a systemic level — as infrastructure, not just as a per-robot adaptation.

Industry Sector	Primary Use Cases
Manufacturing	Assembly, fastening, quality inspection, maintenance
Automotive	Component installation, torque-critical fastening, paint prep
Construction	Drilling, cutting, measurement, material handling
Logistics & Warehousing	Packaging, sorting, labeling, pallet building
Maintenance & Repair	Infrastructure inspection, repair, tool-based servicing
Healthcare & Laboratories	Instrument handling, sample processing, sterile assembly

3. Definition

A Humanoid-Workbench is a specially designed workstation that is optimized for the kinematic capabilities, limitations, grip patterns, reach and physical characteristics of humanoid robots, allowing them to efficiently use standard or custom tools.

Scope

The concept encompasses any system — simple or complex — that bridges the gap between the physical capabilities of humanoid robots and the interface requirements of standard tools. This includes but is not limited to:

- Physical workbench surfaces with integrated features
- Tool storage, staging, and retrieval systems
- Docking stations and mechanical interfaces
- Force and torque absorption and guidance systems
- Vision and sensor-guided alignment systems
- Software and control systems that coordinate robot-tool interaction
- Hybrid human-robot shared workstations

Scope Boundary

The concept covers any system designed to provide an ergonomic and productive environment for a humanoid robot — including systems that enable effective use of standard tools, existing infrastructure, and real-world workflows. It does not apply to general-purpose industrial robot workcells, or standard human workbenches that have not been adapted or designed with humanoid robot use in mind. Systems that require tools to be fundamentally redesigned for robotic use also fall outside this scope.

4. Core Philosophy

The Humanoid Workbench concept starts from a simple insight: the most practical and scalable way to make humanoid robots productive is to design the environment around them — not to wait for perfect dexterity, and not to redesign every tool from scratch. A well-designed workbench makes a humanoid robot immediately useful in real workshops, on real work floors, with tools and infrastructure that already exist.

Design Principles

4.1 Tool Neutrality

Standard tools remain unmodified. A Humanoid Workbench works with existing tools — the drill from the hardware store, the socket set in the toolbox — rather than requiring proprietary robotic variants. This preserves cost-effectiveness and supply chain simplicity.

4.2 Robot Capability Awareness

Solutions are designed around the actual kinematic capabilities of humanoid robots — their reach envelopes, grip force profiles, joint limits, and sensory capabilities — rather than assuming human-equivalent performance.

4.3 Solution Agnosticism

The concept does not prescribe a single solution architecture. Mechanical adapters, software guidance, docking mechanisms, force absorption systems, and approaches not yet invented are all valid implementations. The goal is to define the problem space clearly and leave the solution space open.

4.4 Scalability

A Humanoid Workbench should be deployable at scale — from a single robot workstation in a small workshop to a large-scale industrial installation with multiple humanoid units operating in parallel.

4.5 Human-Robot Compatibility

Where possible, the workbench should remain usable by human workers as well — supporting hybrid environments where humans and humanoid robots share workspace and tools.

5. Key Technical Challenges

The following challenges represent the core problem space that a Humanoid Workbench system is designed to address. Each challenge is defined in terms of the gap between current humanoid robot capability and the requirements of standard tool use.

Challenge	Root Cause	Impact
Trigger & Switch Operation	Hand geometry mismatch, limited finger force	Cannot activate power tools reliably
Battery Exchange	Fine motor tolerance, visual alignment	Cordless tools become unusable mid-task
Accessory Changes	Chuck/socket release forces, small part grip	Cannot change drill bits or sockets
Fastener Handling	Picking small parts, maintaining orientation	Screws dropped, misaligned, cross-threaded
Workpiece Fixturing	Dual-hand coordination, compliance mismatch	Workpiece moves during operation
Force Control	Limited torque sensing, compliance in joints	Under/over-torquing, tool damage
Tool-Workpiece Alignment	Proprioception limits, visual system latency	Missed holes, surface damage
Tool Switching	Grasp release, re-grasp, storage coordination	Slow cycle times, task interruption
Tool Retrieval	Unguided pickup from flat surfaces	Reliably picking up flat or cylindrical tools from unstructured surfaces without guidance or pre-positioning
Two-Handed Operations	Coordination between both arms	Cannot perform operations requiring both hands

6. Solution Space

This document does not define specific solutions. It defines categories of solution approaches that fall within scope. Any implementation addressing the challenges in Section 5 through one or more of the following categories — or through novel approaches not listed here — constitutes a Humanoid Workbench.

6.1 Mechanical Interface Solutions

- Tool docking stations that present tools in a fixed, pre-aligned orientation
- Trigger and switch adapter mechanisms that translate robot grip into tool actuation
- Battery exchange fixtures that guide insertion and removal within robot tolerances
- Chuck and socket change systems with robot-compatible release mechanisms
- Fastener presentation systems (screw feeders, orientation fixtures, magnetic guides)

6.2 Workbench Surface Solutions

- Integrated fixturing and clamping systems operable by robot end-effectors
- Force and torque absorption surfaces for drilling and fastening operations
- Modular tool storage integrated into the work surface
- Guided approach channels for tool pickup and placement

6.3 Sensing & Software Solutions

- Vision-guided tool alignment systems (camera-based approach correction)
- Force-torque feedback integration for controlled fastening operations
- Task-level software coordination for tool selection and sequencing
- Digital twin integration for pre-planned tool interaction trajectories

6.4 Hybrid & Novel Solutions

- Human-robot collaborative fixturing (human holds workpiece, robot operates tool)
- Modular adapter ecosystems compatible across tool brands and robot platforms
- Solutions combining multiple categories above
- Approaches not yet conceived at the time of this publication

Important

This list is illustrative, not exhaustive. The purpose of defining solution categories is to establish the breadth of the prior art claim — not to limit implementations to only these approaches.

7. Prior Art & Related Work

The following related concepts exist in adjacent spaces. The Humanoid Workbench concept is distinct from each of these in its specific focus on humanoid robot tool use.

Related Concept	Distinction from Humanoid Workbench
Standard robot workcells	Designed for industrial arms, not humanoid kinematics or standard tools
Tool changers for robot arms	Proprietary end-effector swaps, not standard human tools
Human workbenches	Optimized for human ergonomics, not humanoid robot reach/grip
Cobots (collaborative robots)	Focus on safety in shared spaces, not tool interface optimization
Robot-specific tool designs	Redesigns the tool, not the workstation environment
Assembly jigs and fixtures	Workpiece-oriented, not tool-interface-oriented

To the best of the author's knowledge, no prior published concept, patent, or system specifically addresses the problem of workstation design optimized for humanoid robot tool use as a general category, as defined in this document.

8. Application Scenarios

8.1 Industrial Assembly

A humanoid robot performs multi-step assembly on a production line. The Humanoid Workbench provides pre-staged tools in robot-accessible positions, a fastener feed system, and fixturing for the workpiece — enabling the robot to complete the assembly cycle without human assistance or tool-specific custom programming.

8.2 Maintenance & Repair

A humanoid robot performs scheduled maintenance on industrial equipment. The workbench provides a tool staging area near the work site, with battery swap capability for cordless tools and guided retrieval for socket sets and torque wrenches.

8.3 Construction Site

Humanoid robots work alongside human crews on a construction site. Shared workbenches positioned throughout the site allow both human and robot workers to access and return tools — with robot-specific guidance features active when a robot is operating and inactive (or retracted) when a human approaches.

8.4 Small Workshop / SME

A small manufacturing business deploys a single humanoid robot for overnight work. A compact Humanoid Workbench occupies one corner of the workshop, providing the robot with everything it needs to operate standard tools through a full shift without human supervision.

9. Public Domain Declaration

This document constitutes a Defensive Publication — a formal mechanism for placing an inventive concept into the public domain in order to establish prior art and prevent future patent claims on the same general idea.

Legal Basis

Under patent law in most jurisdictions, a patent cannot be granted for an invention that was publicly disclosed before the patent application was filed. By publishing this document with a clear authorship, date, and public accessibility, the concept of the Humanoid Workbench enters the prior art record as of June 2026.

Any patent application filed after this date that claims the general concept of a workstation system specifically designed to enable humanoid robots to use standard tools should be challengeable on the basis of this prior art disclosure.

This document is released into the public domain. Anyone is free to implement, commercialize, build upon, or otherwise use the concepts described herein. No attribution is required, though it is appreciated. No permission is needed.

Core Intent

The explicit goal of this prior art disclosure is to keep the entire solution space open. Nobody should be able to patent the general concept of helping humanoid robots use standard tools or work within existing infrastructure — and thereby block others from building solutions in this space. This document is a deliberate act to ensure that remains the case.

Anyone — individuals, startups, companies, researchers — must remain free to develop, build, sell, and deploy any system that helps humanoid robots use standard tools or integrate into existing working environments. No permission, license, or royalty should ever be required for the general concept.

What This Does NOT Restrict

- Specific highly novel implementations with unique technical inventions may still be independently patentable — but the general concept cannot be
- Software, specific mechanical designs, and particular system architectures with genuine inventive step remain protectable

- Trademarks, branding, and trade secrets are unaffected by this disclosure
- Commercial development of Humanoid Workbench products is explicitly encouraged — this disclosure exists to enable that, not restrict it

10. Document Versioning & Updates

Version	Notes
1.0 — June 2026	Initial public release. Core definition, challenges, solution space, and prior art declaration.
Future versions	May include additional application scenarios, updated market context, or expanded solution categories as the field develops.

The latest version of this document is maintained at humanoidworkbench.com. All versions are archived and timestamped for prior art purposes.

Björn van der Valk

[HumanoidWorkbench.com](https://humanoidworkbench.com)

Published June 2026 · Version 1.0 · Public Domain