Temporal Knowledge-Graph Memory in a Partially Observable Environment

Taewoon Kim[1]
[1]HumemAI
taewoon@humem.ai

Vincent François-Lavet[2]
[2]Vrije Universiteit Amsterdam
vincent.francoislavet@vu.nl

Michael Cochez[3]
[3]ELLIS Institute Finland & Abo Akademi University
Michael.cochez@abo.fi

February 25, 2026

Abstract

Agents in partially observable environments require persistent memory to integrate observations over time. While KGs (knowledge graphs) provide a natural representation for such evolving state, existing benchmarks rarely expose agents to environments where both the world dynamics and the agent's memory are explicitly graph-shaped. We introduce the Room Environment v3, a configurable environment whose hidden state is an RDF KG and whose observations are RDF triples. The agent may extend these observations into a temporal KG when storing them in long-term memory. The environment is easily adjustable in terms of grid size, number of rooms, inner walls, and moving objects.

We define a lightweight temporal KG memory for agents, based on RDF-star-style qualifiers (`time_added`, `last_accessed`, `num_recalled`), and evaluate several symbolic baselines that maintain and query this memory under different capacity constraints. Two neural sequence models (LSTM and Transformer) serve as contrasting baselines without explicit KG structure. Agents train on one layout and are evaluated on a held-out layout with the same dynamics but a different query order, exposing train–test generalization gaps. In this setting, temporal qualifiers lead to more stable performance, and the symbolic TKG (temporal knowledge graph) agent achieves roughly fourfold higher test QA (question-answer) accuracy than the neural baselines under the same environment and query conditions. The environment, agent implementations, and experimental scripts are released for reproducible research at `https://github.com/humemai/agent-room-env-v3` and `https://github.com/humemai/room-env`.

1 Introduction

Agents operating in partially observable environments must infer and maintain structured information about the world as it evolves over time [20]. Because the world evolves according to structured dynamics, agents must store and update facts observed many steps earlier. Knowledge graphs (KGs) provide a natural representational substrate for such settings:

entities, relations, and qualifiers can express spatial structure, object locations, and temporal metadata in a uniform semantic framework [3, 11, 19, 33]. However, most benchmarks do not expose KG-shaped hidden states nor agents with explicitly modeled temporal KG memory (e.g., [1, 3, 8, 13–15, 30, 33]).

This paper introduces the Room Environment v3, a deterministic and fully configurable environment designed to fill this gap. The environment's hidden state is an RDF KG whose entities include rooms, objects, walls, and the agent, and whose relations encode spatial adjacency and object locations. At each timestep the agent receives a symbolic observation consisting of RDF triples describing the local room structure and the objects currently present. The environment is easily adjustable in terms of grid size, number of rooms, pattern of inner walls, and the number and motion patterns of moving objects. A further component of the environment is a query at each step requesting the current location of a named object. Accurate responses require maintaining an internal representation of the world that integrates partial observations over time.

While KGs and temporal KGs are widely used for representing evolving knowledge [10, 12, 19, 25], their application as *agent memory* in interactive environments remains underexplored. Prior work on gridworlds, symbolic environments, and relational reasoning benchmarks typically either (i) does not provide a KG-shaped hidden state, (ii) gives agents unstructured symbolic or text observations without a defined KG memory model, or (iii) uses neural representations that do not expose explicit triples or qualifiers for inspection [1, 3, 8, 13–16, 21, 30, 33]. As a result, there is limited understanding of how explicit temporal KGs function as internal state representations, how simple symbolic update rules perform relative to neural sequence models, and how temporal qualifiers influence generalization.

Recent work on long-term memory in artificial intelligence has increasingly focused on neural vector-based representations, where stored information is encoded in continuous embeddings rather than explicit symbolic structures [5, 13, 14, 16, 27, 30]. While such approaches are powerful, they often lack interpretability: the contents of memory and the basis of retrieved answers are not directly observable as explicit symbolic facts. One of the motivations for our contribution is to provide a setting where both the hidden state of the world and the agent's long-term memory are represented as explicit KGs. This enables interpretable memory inspection, deterministic updates, and transparent reasoning.

We propose a lightweight temporal KG memory model for agents that extends standard RDF triples with RDF-star-style qualifiers capturing `time_added`, `last_accessed`, and `num_recalled`. These qualifiers provide a simple but expressive mechanism for tracking the recency and usage of stored facts, enabling memory strategies that remain fully interpretable [23]. Based on this TKG framework, we implement several symbolic baselines that update and query their memory using deterministic rules, with optional capacity limits and simple eviction heuristics. To provide a contrasting perspective, we include two neural sequence models (LSTM and Transformer) that receive exactly the same symbolic observations but maintain memory as a fixed-length sequence queue buffer without explicit KG structure.

We evaluate all agents on two deterministic layouts: a training environment and a held-out test environment with identical dynamics but a different question order. This setup enables a controlled examination of train-to-test generalization and highlights the importance of structured temporal memory. Across capacities, temporal qualifiers contribute

to more stable behavior, and the symbolic TKG agent exhibits significantly higher test performance than the neural baselines under the same environment and query conditions. The environment, agent implementations, and full reproducibility material are publicly released in anonymized form.

Contributions

- We introduce the Room Environment v3, a deterministic and configurable environment whose hidden state and observations are expressed as RDF knowledge graphs.
- We define a lightweight temporal KG memory with RDF-star-style qualifiers and deterministic update rules.
- We compare symbolic TKG agents with neural sequence baselines under a shared interface and varying memory capacities.
- We release the full environment, agent implementations, and reproducibility scripts.

Code and environment. The main repository is at `https://github.com/humemai/agent-room-env-v3`; the Room Environment repository is at `https://github.com/humemai/room-env`.

Version history

This paper is a substantially revised and extended version of an earlier arXiv preprint on KG-based memory for partially observable environments. The present version introduces a new deterministic Room Environment v3, reformulates agent memory explicitly as a temporal knowledge graph using RDF-star qualifiers, adds symbolic baselines with interpretable update and eviction rules, and provides a controlled generalization analysis against neural sequence models. The earlier formulation is subsumed by this work, and citations to prior versions should be understood as referring to the present manuscript.

2 Background

2.1 RDF, RDF-star, and Knowledge Graph Representations

The Resource Description Framework (RDF) models facts as triples (s, p, o) with subject, predicate, and object drawn from IRIs or literals. An RDF graph therefore corresponds to a directed, edge-labeled multigraph in which relations capture structured connections between entities. This representation is well suited for spatially structured domains: rooms, objects, and adjacency relations can be expressed directly as triples without task-specific encodings.

RDF-star extends RDF with a concise syntax for *statements about statements*. An embedded triple $\ll s\ p\ o \gg$ can be used as the subject of further triples, e.g., $\ll s\ p\ o \gg$ `:time_added` 7. This allows qualifiers (timestamps, counters, provenance keys) to be attached directly to a base fact without the heavier reification vocabulary [17]. Because embedded triples behave like ordinary RDF terms, RDF-star offers a lightweight and standard-compatible way to represent temporal annotations in an agent's long-term memory.

2.2 Temporal Knowledge Graphs

Temporal knowledge graphs (TKGs) represent facts whose validity or relevance changes over time. Common approaches include interval-based, event-based, and update-based models, all of which associate each triple with temporal metadata reflecting when it was introduced or last observed. RDF-star can express such metadata by attaching qualifier key–value pairs to embedded triples, enabling fine-grained annotations such as `time_added`, `last_accessed`, or `num_recalled` [25]. Temporal KGs have been widely used in the Semantic Web to model evolving data, streaming updates [10], and temporally indexed knowledge sources.

In interactive settings, temporal qualifiers allow agents to track the recency and usage of stored information, to maintain evolving internal models, and to reason over past observations. These properties align naturally with the needs of partially observable environments, where an agent's internal state must integrate information gathered over many timesteps.

2.3 Symbolic Memory and Semantic State Tracking

Research on long-term memory for artificial agents has increasingly explored neural vector-based representations, where stored information is encoded implicitly in embeddings or hidden states [5, 13, 14, 16, 27, 30]. While effective for high-dimensional signals, such representations are typically opaque: the contents of memory cannot be inspected directly as noted in neural-symbolic systems [4], and the basis for retrieval is difficult to trace.

In contrast, symbolic memory systems store explicit facts that can be examined, queried, and updated deterministically. KGs offer a particularly suitable substrate for this purpose, as they represent entities and relations at a semantic level and support principled operations for insertion, deletion, and reannotation. When temporal qualifiers are incorporated, symbolic memory becomes fully transparent: each fact carries a clear history of when and how it was observed.

Heuristic update strategies such as recency-based selection, frequency-based selection, and simple eviction rules (e.g. FIFO, LRU, LFU) can operate directly over qualifiers attached to embedded triples. Such heuristics preserve interpretability while providing meaningful signals for deciding which facts to retain when memory capacity is limited.

2.4 Semantic Representations for Agents and Interactive Environments

Semantic Web research has long explored structured representations, logical reasoning, and knowledge-driven decision processes. Several interactive or agent-based settings use symbolic descriptions of the world, but the underlying environments are rarely expressed directly as KGs, and the agent's internal memory is typically not a temporal KG. Existing gridworld-style or relational reasoning benchmarks often provide symbolic observations without specifying how those observations should be integrated into a structured, evolving memory.

As a result, there is limited empirical understanding of how temporal KGs function as internal state representations for agents, how simple qualifier-driven heuristics compare to unstructured sequence-based memory, and how temporal metadata affects generalization in deterministic but partially observable domains. The environment and memory model introduced in this paper address these gaps by providing a setting in which both the hidden

state of the world and the agent's memory are explicit, inspectable knowledge graphs represented in standard RDF and RDF-star syntax.

3 Room Environment v3



Figure 1: Bird's-eye schematic of the hidden state at $t = 99$ ($s_{t=99}$), showing spatial layout and entity placement. This view is only a schematic for intuition: the actual environment state and agent-facing world are represented in the RDF knowledge-graph world (Figure 2). The agent does not directly observe s_t; its observation o_t is the induced RDF subgraph of the current room and visible adjacency relations.



Figure 2: Knowledge-graph view of the same hidden state at $t = 99$ ($s_{t=99}$), expressed as RDF structure.

The Room Environment v3 (Figures 1 and 2) is a configurable $g \times g$ grid world populated with named rooms, static and moving objects, and periodically changing inner walls. All environment components—hidden dynamics, observations, and the QA loop—are defined in RDF triples triples, making the environment a minimal but fully KG-shaped testbed for studying temporal memory.

The environment deliberately couples navigation and question answering. Because objects move and visibility is local, correct answers require exploration, accumulation of partial observations, and persistent memory of object trajectories. This design prevents trivial solutions: without navigation the task reduces to static KG lookup, and without

queries exploration has no semantic purpose. Their combination creates a controlled setting in which temporal memory is both necessary and measurable.

The environment generalizes the earlier setting introduced by Kim et al. [21]: instead of a single fixed layout, our version supports arbitrary grid sizes, heterogeneous wall schedules, multiple moving objects with independent motion rules, and exposes the entire hidden state as an RDF KG; when used as long-term memory inside the agent, this can be extended into a temporal KG via qualifiers.

3.1 Hidden State and Dynamics

At timestep t, the hidden state s_t consists of the on/off status of all inner walls, the positions of all static and moving objects, and the agent's current room.

Each room is a node, and cardinal directions are modeled as labeled edges (`north`, `east`, `south`, `west`). Walls are represented explicitly—e.g., `(room, north, wall)`—rather than by removing adjacency edges, allowing the environment to expose both potential adjacencies and their blocked status. Every moving object is equipped with a fixed, ordered preference list drawn from $\{\texttt{north}, \texttt{east}, \texttt{south}, \texttt{west}, \texttt{stay}\}$. At each step it executes the *first feasible* move in its list; if none are feasible, it remains in place. This rule, combined with wall schedules, makes object motion *deterministic*.

The inner walls follow fixed periodic schedules: if inner wall i has a pattern of length $|p_i|$, then the joint wall configuration repeats every $P_w = \mathrm{lcm}(|p_1|, \ldots, |p_W|)$ steps. Moving objects induce an additional period P_m. After an initial transient T_{settle}, the global state obeys

$$s_{t+P} = s_t, \qquad P = \mathrm{lcm}(P_w,\, P_m),$$

so the environment is a finite deterministic system with a compact periodic orbit.

Although deterministic, the state space is combinatorially large. With $R = g^2$ rooms, M moving objects, and W inner walls with pattern lengths $|p_1|, \ldots, |p_W|$, a coarse upper bound on the state space is

$$|\mathcal{S}| \;\leq\; R^M \prod_{i=1}^{W} |p_i|.$$

For our running configuration (g=7, R=49, M=18, W=36), this exceeds 6.6×10^{33}. Exact planning is infeasible; agents must instead reason over their own growing memory M_t.

The periodic wall schedule and deterministic object motion are intentional design choices: they ensure that the hidden state evolves in a structured but nontrivial way, making it impossible for an agent to answer location queries from the current observation alone. Because objects move and visibility is local, accurate question answering requires integrating partial observations over many steps. Periodicity keeps the environment fully deterministic and replayable while still enforcing genuine long-term memory demands.

A detailed description of the periodicity analysis, including closed-form bounds and deterministic replay examples, is provided in the public anonymous repository.

3.2 Observations as RDF Graph Fragments

At timestep t, the agent receives an observation o_t consisting of the RDF subgraph induced by its current room: the room node for the agent's location, any outgoing direction-labeled

edges to adjacent rooms that are not blocked by walls, and object–location triples for all objects currently in that room. This yields 5–6 triples per step. Observations contain no information beyond the agent's immediate neighborhood, so long-horizon queries require integrating partial observations over time.

Each timestep also issues a *location query* of the form: (X, `:at_location`, ?). The agent must identify the current room of the queried object [6]. This requires maintaining a temporal model of object motion as observed indirectly through partial glimpses, echoing aspects of KG-based QA (question-answer) [31].

3.3 Deterministic Question–Move Loop

At each timestep the agent first answers the query by returning the room of the specified object (reward +1 if correct, otherwise 0), and then executes a movement action chosen from {`north`, `east`, `south`, `west`, `stay`}.

Episodes last 100 steps, a length chosen to balance tractability with sufficient temporal depth. The full query sequence for each episode is pre-generated and fixed across all agents, ensuring strict comparability in evaluation.

3.4 Configurable Layouts and Test Split

The environment is fully parameterized by the grid length g, the number and placement of static and moving objects, the number and periodic patterns of inner walls, and the episode length.

We use two deterministic layouts: a training layout with fixed walls and object preferences, and a held-out test layout with identical dynamics but a different query order. This difference in question order yields a controlled train–test generalization setting in which agents must transfer their learned memory strategy rather than memorize a fixed query sequence.

3.5 Memory Interface (Agent-Agnostic)

The environment maintains only the hidden state s_t and the symbolic observation o_t emitted at each timestep. It does not prescribe any internal memory structure: agents may keep any private state they choose. The environment simply provides RDF observations, receives an action and an answer, and evaluates correctness against s_t.

In our experiments, we compare four agents. The *RDF-star agent* stores each observed fact as an RDF-star triple annotated with qualifiers (`time_added`, `last_accessed`, `num_recalled`). The *RDF agent* stores the same observations as plain RDF triples without qualifiers. The two *neural baselines* maintain fixed-length buffers of tokenized observations without explicit KG structure; one uses an LSTM encoder and the other uses a Transformer encoder. All agents operate in the same environment and query conditions.

3.6 Default Configuration

Unless stated otherwise, experiments use a `grid_length` of 7, with 18 static objects, 18 moving objects, 36 inner walls following periodic patterns, an episode length of 100, and a fixed query list shared across all agents. The reward is simply the number of correct queries

Agent	Memory repr.	Qualifiers	QA rule	Eviction
Symbolic–RDF	RDF triples	No	SPARQL	Random
Symbolic–TKG	RDF-star (TKG)	Yes	MRA/MRU/MFU	FIFO/LRU/LFU
Neural–LSTM	Obs. history	No	Prediction head	FIFO
Neural–Transformer	Obs. history	No	Prediction head	FIFO

Table 1: Agent comparison. MRA = most recently added, MRU = most recently used, MFU = most frequently used.

(maximum 100). All environment code, layouts, and deterministic replay scripts are included in the public anonymous repository for full reproducibility.

4 Agents

We evaluate four agents: two *symbolic* agents that store explicit KG structures, and two *neural* agents that store tokenized observation histories. All agents receive the same query sequence and operate in the same environment, but their exploration behaviors cause them to generate different observation histories. We evaluate them under memory capacities from 0 to 512 entries, which covers the range where capacity meaningfully constrains what can be stored. Table 1 summarizes the four agents.

4.1 Symbolic agents

Both symbolic agents store explicit triples. Their difference is whether they attach temporal qualifiers.

RDF agent (plain triples). Memory is a bounded set of RDF triples (s, p, o). Because these entries carry *no* timestamps or usage counts, the agent has no basis for ordering them. Therefore, when memory is full, the only principled choice is to evict a *uniformly random* triple.

QA rule. Answers are obtained by plain SPARQL pattern matching:

```
SELECT ?o WHERE { <s> <r> ?o . }
ORDER BY RAND() LIMIT 1
```

If multiple candidates match, tie-breaking is uniform because the agent lacks temporal metadata.

Exploration. The current map is reconstructed from the triples stored so far. The agent performs BFS (breadth-first search) to the nearest unvisited room. BFS is used because the memory itself is a graph and BFS is the simplest deterministic traversal aligned with that structure.

TKG agent (RDF-star with qualifiers). Each observed triple (s, r, o) is stored as an embedded triple $\ll s\ r\ o \gg$ annotated with:

`time_added`, `last_accessed`, `num_recalled`.

This creates a temporal knowledge graph M_t.

QA rules. Each query $(s_q, r_q, ?)$ is answered by selecting the object o whose qualifier is maximal:

$$\text{MRA} : \arg\max \texttt{time_added},$$
$$\text{MRU} : \arg\max \texttt{last_accessed},$$
$$\text{MFU} : \arg\max \texttt{num_recalled}.$$

Eviction. Using qualifiers permits structured removal: FIFO (oldest `time_added`), LRU (least recent `last_accessed`), LFU (smallest `num_recalled`).

Exploration. The agent ranks frontier rooms using MRA/MRU/MFU on edge triples and performs BFS to the top-ranked frontier.

SPARQL-star example (MRU).

```
SELECT ?o WHERE {
  << <s> <r> ?o >> :last_accessed ?t .
}
ORDER BY DESC(?t)
LIMIT 1
```

Thus, the TKG agent is entirely deterministic and fully traceable: every decision (answer, movement, eviction) is reproducible from M_t.

4.2 Neural agents

The neural agents store a fixed-length *tokenized observation history* without explicit graph structure. They differ only in the sequence encoder used.

Joint decision structure. Unlike the symbolic agents, which decompose question answering and exploration into two independent rules, the neural agents produce a *single joint operation* that simultaneously selects the answer and the movement. This results in a large option set (49 possible room answers $\times$ 5 movement choices) from which the prediction head chooses one element. Because answers referring to rooms that have not yet been observed are invalid, the option set is dynamically *masked* at each timestep so that only admissible answers remain. Consequently, the neural agents must learn end-to-end how to resolve queries and how to navigate, without access to explicit graph structure, qualifiers, or symbolic update rules. The neural agents learn this joint policy using a standard reinforcement-learning objective implemented via a Deep Q-Network (DQN) [24].

Tokenization. Each triple (s, p, o) is converted to an embedding vector

$$\mathbf{e}_i = W_{\text{emb}}\,[\,\text{emb}(s) \parallel \text{emb}(p) \parallel \text{emb}(o)\,],$$

and the last L such tokens form the memory buffer. When full, the oldest token is removed (FIFO), reflecting the queue structure of a fixed-length sequence buffer.

LSTM neural agent

The sequence $\mathbf{E} = [\mathbf{e}_1, \ldots, \mathbf{e}_L]$ is encoded by:

$$\mathbf{H} = \mathrm{LSTM}(\mathbf{E}).$$

Because LSTMs process data sequentially, temporal order is included implicitly [18].

Question-conditioned pooling. Given a question triple $(s_q, r_q, ?)$, embed it as $\mathbf{q}$ and compute attention weights:

$$\alpha_i = \frac{\exp(\mathbf{q}^\top \mathbf{h}_i)}{\sum_j \exp(\mathbf{q}^\top \mathbf{h}_j)}, \qquad \mathbf{c} = \sum_i \alpha_i \mathbf{h}_i.$$

A feedforward prediction head maps $\mathbf{c}$ to the 245 possible operation options (answer $\times$ movement).

Transformer neural agent

Here, $\mathbf{E}$ is fed to a Transformer encoder:

$$\mathbf{H} = \mathrm{Transformer}(\mathbf{E} + \mathrm{PE}),$$

where PE are sinusoidal positional encodings that supply the temporal order [29], enabling long-range temporal reasoning [9]. The same question-conditioned pooling and prediction head are used as in the LSTM agent.

Interpretability. Neural agents have no explicit triples, qualifiers, or traceable update rules, similar to episodic-control agents [5, 27]. Their internal state is an opaque vector, and only soft attention weights give partial insight into which past observations were influential. Symbolic agents, in contrast, expose every stored fact and every eviction decision.

5 Experiments

We evaluate all agents in the deterministic Room Environment v3 under varying long-term memory capacities, from 0 to 512. Each configuration is trained and tested on 5 random seeds, and we report the mean and standard deviation. All raw results, hardware specifications, and hyperparameters are provided in the anonymous repository.

Our evaluation focuses on three aspects:

1. **QA accuracy across memory capacities** (Figure 3)
2. **Coverage metrics over time** (Figure 4)
3. **Memory-state evolution for RDF-star** (Figure 5)

5.1 QA Accuracy Across Long-Term Memory Capacities

Figure 3 shows the train and test QA accuracy for all agents. Neural agents learn exploration and question answering jointly under a single end-to-end policy, yielding a large discrete action space and difficult credit assignment. As memory capacity increases, these agents also receive longer observation histories, making the underlying learning problem more computationally demanding; in principle, higher-capacity models may require substantially more training to benefit from the additional information. In our experiments, however, all memory-capacity settings were trained for the same number of episodes (200) to ensure a fair comparison, which likely contributes to the minimal performance gains observed in the higher-capacity regime.

Across almost all capacities, the Transformer agent slightly outperforms the LSTM agent, consistent with empirical trends in sequence modeling. However, neither architecture meaningfully exploits larger memory, and both exhibit substantial train–test gaps. In low-memory regimes (0–16), neural agents outperform symbolic ones—but this reflects random trial-and-error rather than informed reasoning: the agents often guess object locations without provenance and only gradually reinforce correct answers through reward.

Symbolic agents begin to outperform neural agents at capacity 32. Their accuracy increases with memory because operations such as BFS and graph queries add computation but not statistical difficulty. Neural agents, by contrast, must learn these structures from data and therefore require much more training and capacity to benefit from larger memory.

RDF-star achieves better QA accuracy in most memory capacities. The RDF-star agent family consists of 27 variants, arising from all combinations of three qualifier-based QA rules (MRA, MRU, MFU), three exploration priorities based on the same qualifiers, and three eviction heuristics (FIFO, LRU, LFU); these choices are independent because each stored fact carries the qualifiers `time_added`, `last_accessed`, and `num_recalled`. We report the best-performing variant, selected by training accuracy and evaluated identically at test time. Although the plain RDF agent can store more main triples under a fixed memory budget—since it stores triples rather than quadruples—the temporal qualifiers in RDF-star yield a more informative and expressive memory state, leading to stronger performance once capacity is sufficient to retain both facts and their associated temporal metadata.

At capacity 512, the best symbolic agent (RDF-star) reaches a QA accuracy of 46.52, whereas the best neural agent (LSTM) reaches 11.2, a four-fold difference. These results highlight that explicit symbolic memory is considerably more effective for long-horizon, partially observable semantic reasoning. Statistical variation is shown as shaded regions.

5.2 Coverage Metrics: Room and Triple Coverage

Figure 4 shows, for the long-term memory capacity of 512, the coverage metrics of the four agents: RDF, RDF-star, LSTM, and Transformer. Each subplot includes the cumulative number of unique rooms visited and the number of unique (s, p, o) triples stored in memory at each timestep. Raw values are provided in the anonymous repository.

Symbolic agents. Both symbolic agents achieve full coverage of all 49 rooms in the environment. Moreover, the RDF-star agent reaches full room coverage slightly earlier (timestep 70) than the RDF agent (timestep 74). The temporal qualifiers in RDF-star allow



Figure 3: Train–test QA accuracy for all agents across long-term memory capacities. Mean and standard deviation are computed across 5 seeds. Raw values can be found in the anonymous repository.

it to track time-varying wall configurations more accurately, yielding a more up-to-date inferred map of the environment and enabling more efficient exploration. Triple-coverage results follow the same pattern: symbolic agents accumulate nearly complete internal maps because they continue to explore until all reachable structure has been observed.

Neural agents. In contrast, the LSTM and Transformer agents stop increasing room coverage long before the end of the episode (around step 50 for the Transformer and step 30 for the LSTM). A plausible explanation is that neural policies must couple exploration and answering within a single high-cardinality action space. Once training converges to a locally rewarding but suboptimal behavior—such as repeatedly answering queries with moderate reward or oscillating among familiar states—the agents no longer discover new rooms. Because the reward signal is sparse and not explicitly tied to exploration, the policies collapse into low-entropy, non-exploratory behaviors. These plateauing exploration patterns also explain the limited triple coverage: neural agents simply encounter fewer states from which to build internal structure.



(c) RDF **(d) RDF-Star**

(a) Neural – LSTM **(b) Neural – Transformer**

Figure 4: Coverage metrics for the four agents, at the long-term memory capacity of 512. Neural agents halt exploration early, while symbolic agents visit all 49 rooms and accumulate nearly all unique triples. Raw values can be found in the anonymous repository.

5.3 Memory-State Evolution (RDF-Star)

To illustrate the expressive advantage of temporal symbolic memory, Figure 5 shows the RDF-star agent's long-term memory at timesteps $t = 0$, $t = 50$, and $t = 99$, using capacity 512. Each edge label includes the number of associated memories when more than one quadruple exists. Node colors correspond to semantic categories (rooms, static objects, moving objects, walls, and agent).

The graphs show the internal map becoming increasingly complete over time. Static objects (blue) appear prominently because the agent's deterministic BFS traversal guarantees that every room is visited at least once, and static objects never move; each one is therefore observed reliably when its room is first encountered. In contrast, moving objects (green) may leave a room before the agent arrives, their trajectories may intersect the traversal path only rarely, and their past locations may later be evicted under capacity pressure. As a result, moving objects are represented by far fewer stored triples—sometimes only a single observation—despite being present throughout the hidden state.

Full memory evolution images for all agents (from $t = 0$ to $t = 99$) are available in the anonymous repository.



Figure 5: Memory state of the RDF-star agent at $t = 0$, $t = 50$, and $t = 99$ (capacity 512). Counts in parentheses (e.g., "`at_location (3)`") indicate how many RDF-star memories share the same main triple but differ in their temporal qualifiers.

6 Related Work

Temporal and hyper-relational knowledge graphs. The Semantic Web stack provides a mature basis for representing structured data as RDF graphs and querying them with SPARQL [28]. RDF-star and SPARQL-star extend this model with *statements about statements*, allowing triples such as $\ll s\ p\ o \gg$ to be annotated with additional facts and queried directly [17]. Temporal and hyper-relational knowledge graphs build on these ideas by attaching time and other qualifiers to edges and have been extensively studied for tasks such as link prediction and event forecasting (e.g., [12]). In contrast, we use a temporal KG not primarily as a prediction target but as the *internal state* of an agent: every observation becomes a reified RDF-star statement with temporal qualifiers, and downstream decisions (answering and exploration) are implemented as queries and updates over this KG.

Memory under partial observability. In partially observable environments, agents must aggregate information over time. A large body of work uses neural memories to maintain an internal state proxy, including recurrent architectures, memory-augmented networks such as Neural Turing Machines and Differentiable Neural Computers [13, 14], and long-context models with compression or retrieval (e.g., MERLIN and related world-model agents [16, 30]). These approaches typically store history in dense vectors or key–value tensors, which makes it difficult to inspect what exactly is remembered at a given time. Our work instead treats the agent's long-term memory as an explicit temporal knowledge graph in RDF-star: each stored fact is a verifiable triple with qualifiers, and the effect of capacity limits or update rules on question answering can be inspected directly at the graph level. Alongside this, we include simple neural baselines that operate on observation histories without explicit KG structure, highlighting the behavioural differences between latent and symbolic memories [22].

Graph-structured environments and KG-based agents. Several interactive environments expose graph-structured or relational state [7], and neural architectures explicitly designed for graph-structured reasoning [32]. TextWorld and Jericho provide text-based games where an evolving symbolic world model can be extracted and used for control, leading to agents that query or learn over dynamic knowledge graphs [1, 8, 15, 26]. Agents with multiple KG-based memory stores have also been explored [21]. Other systems use KGs as world models for planning, question answering, or recommendation [6, 11, 19, 31]. Compared to these settings, our focus is deliberately narrow: we design the Room Environment v3 where (i) the hidden state and observations are *already* KGs, (ii) the question format is fixed, and (iii) the environment parameters (number of rooms, walls, objects, episode length) are easily adjusted. This allows us to isolate the role of temporal KG memory and to compare symbolic and neural baselines under controlled conditions rather than to optimize a full task pipeline.

Semantic Web, agents, and explainability. Within the Semantic Web community, KGs are increasingly used to support decision-making and explainable reasoning in multi-step processes, e.g., planning, data analytics, and interactive decision support. Traceability and provenance are central: KG representations allow one to link conclusions back to the

underlying facts [2]. Our design follows this line by making the agent's long-term memory itself a temporal KG; question answering is implemented as SPARQL-star-style retrieval over that memory, and memory contents can be visualized as graphs over time. This provides a compact testbed for studying how temporal qualifiers (e.g., recency and recall counts) interact with partial observability and capacity limits, and how symbolic KG memories compare to simple neural baselines in terms of generalization from training to held-out question orders.

7 Conclusion

We presented the Room Environment v3 in which both the hidden state and the agent's memory are represented as knowledge graphs, enabling a controlled study of temporal memory under partial observability. Using a lightweight RDF-star-based memory with temporal qualifiers, symbolic agents achieved full environment coverage and substantially higher QA accuracy than neural sequence baselines under the same environment and query conditions. The results highlight the effectiveness and interpretability of temporal knowledge graphs as agent memory, and provide a compact testbed for future work on semantic representations, temporal update rules, and neuro-symbolic memory models.

References

[1] Prithviraj Ammanabrolu and Matthew Hausknecht. Graph constrained reinforcement learning for natural language action spaces. In *International Conference on Learning Representations*, 2020. URL `https://openreview.net/forum?id=B1x6w0EtwH`.

[2] Kemafor Anyanwu and Amit Sheth. ρ-queries: enabling querying and ranking complex relationships.

[3] Peter W. Battaglia, Jessica B. Hamrick, Victor Bapst, Alvaro Sanchez-Gonzalez, Vinicius Zambaldi, Mateusz Malinowski, Andrea Tacchetti, David Raposo, Adam Santoro, Ryan Faulkner, Caglar Gulcehre, Francis Song, Andrew Ballard, Justin Gilmer, George Dahl, Ashish Vaswani, Kelsey Allen, Charles Nash, Victoria Langston, Chris Dyer, Nicolas Heess, Daan Wierstra, Pushmeet Kohli, Matt Botvinick, Oriol Vinyals, Yujia Li, and Razvan Pascanu. Relational inductive biases, deep learning, and graph networks, 2018. URL `https://arxiv.org/abs/1806.01261`.

[4] Tarek R. Besold, Artur d'Avila Garcez, Sebastian Bader, Howard Bowman, Pedro Domingos, Pascal Hitzler, Kai-Uwe Kuehnberger, Luis C. Lamb, Daniel Lowd, Priscila Machado Vieira Lima, Leo de Penning, Gadi Pinkas, Hoifung Poon, and Gerson Zaverucha. Neural-symbolic learning and reasoning: A survey and interpretation, 2017. URL `https://arxiv.org/abs/1711.03902`.

[5] Charles Blundell, Benigno Uria, Alexander Pritzel, Yazhe Li, Avraham Ruderman, Joel Z Leibo, Jack Rae, Daan Wierstra, and Demis Hassabis. Model-free episodic control, 2016. URL `https://arxiv.org/abs/1606.04460`.

[6] Antoine Bordes, Nicolas Usunier, Sumit Chopra, and Jason Weston. Large-scale simple question answering with memory networks, 2015. URL https://arxiv.org/abs/1506.02075.

[7] Devendra Singh Chaplot, Ruslan Salakhutdinov, Abhinav Gupta, and Saurabh Gupta. Neural topological slam for visual navigation, 2020. URL https://arxiv.org/abs/2005.12256.

[8] Marc-Alexandre Côté, Ákos Kádár, Xingdi Yuan, Ben Kybartas, Tavian Barnes, Emery Fine, James Moore, Ruo Yu Tao, Matthew Hausknecht, Layla El Asri, Mahmoud Adada, Wendy Tay, and Adam Trischler. Textworld: A learning environment for text-based games, 2019. URL https://arxiv.org/abs/1806.11532.

[9] Mostafa Dehghani, Stephan Gouws, Oriol Vinyals, Jakob Uszkoreit, and Łukasz Kaiser. Universal transformers, 2019. URL https://arxiv.org/abs/1807.03819.

[10] Daniele Dell'Aglio, Emanuele Della Valle, Frank van Harmelen, and Abraham Bernstein. Stream reasoning: A survey and outlook—a summary of ten years of research and a vision for the next decade. *Data Science*, 1(1-2):59–83, 2017. doi: 10.3233/DS-170006.

[11] Lisa Ehrlinger and Wolfram Wöß. Towards a definition of knowledge graphs. 09 2016.

[12] Alberto García-Durán, Sebastijan Dumancic, and Mathias Niepert. Learning sequence encoders for temporal knowledge graph completion. *CoRR*, abs/1809.03202, 2018. URL http://arxiv.org/abs/1809.03202.

[13] Alex Graves, Greg Wayne, and Ivo Danihelka. Neural turing machines. Technical report, arXiv preprint arXiv:1410.5401, 2014.

[14] Alex Graves, Greg Wayne, Malcolm Reynolds, Tim Harley, Ivo Danihelka, Agnieszka Grabska-Barwińska, Sergio Gómez Colmenarejo, Edward Grefenstette, Tiago Ramalho, Chris Dyer, et al. Hybrid computing using a neural network with dynamic external memory. *Nature*, 538:471–476, 2016.

[15] Xiaoxiao Guo, Mo Yu, Yupeng Gao, Chuang Gan, Murray Campbell, and Shiyu Chang. Interactive fiction game playing as multi-paragraph reading comprehension with reinforcement learning. In Bonnie Webber, Trevor Cohn, Yulan He, and Yang Liu, editors, *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 7755–7765, Online, November 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.emnlp-main.624. URL https://aclanthology.org/2020.emnlp-main.624/.

[16] David Ha and Jürgen Schmidhuber. World models. *CoRR*, abs/1803.10122, 2018. URL http://arxiv.org/abs/1803.10122.

[17] Olaf Hartig and Bryan Thompson. Foundations of an alternative approach to reification in rdf, 2021. URL https://arxiv.org/abs/1406.3399.

[18] Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural Computation*, 9(8):1735–1780, 1997. doi: 10.1162/neco.1997.9.8.1735.

[19] Aidan Hogan, Eva Blomqvist, Michael Cochez, Claudia D'amato, Gerard De Melo, Claudio Gutierrez, Sabrina Kirrane, José Emilio Labra Gayo, Roberto Navigli, Sebastian Neumaier, Axel-Cyrille Ngonga Ngomo, Axel Polleres, Sabbir M. Rashid, Anisa Rula, Lukas Schmelzeisen, Juan Sequeda, Steffen Staab, and Antoine Zimmermann. Knowledge graphs. *ACM Computing Surveys*, 54(4):1–37, July 2021. ISSN 1557-7341. doi: 10.1145/3447772. URL `http://dx.doi.org/10.1145/3447772`.

[20] Leslie Pack Kaelbling, Michael L. Littman, and Anthony R. Cassandra. Planning and acting in partially observable stochastic domains. *Artificial Intelligence*, 101(1):99–134, 1998. ISSN 0004-3702. doi: https://doi.org/10.1016/S0004-3702(98)00023-X. URL `https://www.sciencedirect.com/science/article/pii/S000437029800023X`.

[21] Taewoon Kim, Michael Cochez, Vincent François-Lavet, Mark Neerincx, and Piek Vossen. A machine with short-term, episodic, and semantic memory systems. In *Proceedings of the Thirty-Seventh AAAI Conference on Artificial Intelligence and Thirty-Fifth Conference on Innovative Applications of Artificial Intelligence and Thirteenth Symposium on Educational Advances in Artificial Intelligence*, AAAI'23/IAAI'23/EAAI'23. AAAI Press, 2023. ISBN 978-1-57735-880-0. doi: 10.1609/aaai.v37i1.25075. URL `https://doi.org/10.1609/aaai.v37i1.25075`.

[22] Daiki Kimura, Masaki Ono, Subhajit Chaudhury, Ryosuke Kohita, Akifumi Wachi, Don Joven Agravante, Michiaki Tatsubori, Asim Munawar, and Alexander Gray. Neuro-symbolic reinforcement learning with first-order logic, 2021. URL `https://arxiv.org/abs/2110.10963`.

[23] Paolo Missier, Khalid Belhajjame, and James Cheney. The w3c prov family of specifications for modelling provenance metadata. In *Proceedings of the 16th International Conference on Extending Database Technology*, EDBT '13, page 773–776, New York, NY, USA, 2013. Association for Computing Machinery. ISBN 9781450315975. doi: 10.1145/2452376.2452478. URL `https://doi.org/10.1145/2452376.2452478`.

[24] Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Alex Graves, Ioannis Antonoglou, Daan Wierstra, and Martin Riedmiller. Playing atari with deep reinforcement learning, 2013. URL `https://arxiv.org/abs/1312.5602`.

[25] Luc Moreau and P Missier. Prov-dm: The prov data model. 01 2012.

[26] Junhyuk Oh, Satinder Singh, and Honglak Lee. Value prediction network, 2017. URL `https://arxiv.org/abs/1707.03497`.

[27] Alexander Pritzel, Benigno Uria, Sriram Srinivasan, Adrià Puigdomènech, Oriol Vinyals, Demis Hassabis, Daan Wierstra, and Charles Blundell. Neural episodic control, 2017. URL `https://arxiv.org/abs/1703.01988`.

[28] Andy Seaborne and Steven Harris. SPARQL 1.1 query language. W3C recommendation, W3C, March 2013. https://www.w3.org/TR/2013/REC-sparql11-query-20130321/.

[29] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need, 2023. URL `https://arxiv.org/abs/1706.03762`.

[30] Greg Wayne, Chia-Chun Hung, David Amos, Mehdi Mirza, Arun Ahuja, Agnieszka Grabska-Barwinska, Jack W. Rae, Piotr Mirowski, Joel Z. Leibo, Adam Santoro, Mevlana Gemici, Malcolm Reynolds, Tim Harley, Josh Abramson, Shakir Mohamed, Danilo Jimenez Rezende, David Saxton, Adam Cain, Chloe Hillier, David Silver, Koray Kavukcuoglu, Matthew M. Botvinick, Demis Hassabis, and Timothy P. Lillicrap. Unsupervised predictive memory in a goal-directed agent. *CoRR*, abs/1803.10760, 2018. URL `http://arxiv.org/abs/1803.10760`.

[31] Wen-tau Yih, Ming-Wei Chang, Xiaodong He, and Jianfeng Gao. Semantic parsing via staged query graph generation: Question answering with knowledge base. In Chengqing Zong and Michael Strube, editors, *Proceedings of the 53rd Annual Meeting of the Association for Computational Linguistics and the 7th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 1321–1331, Beijing, China, July 2015. Association for Computational Linguistics. doi: 10.3115/v1/P15-1128. URL `https://aclanthology.org/P15-1128/`.

[32] Seongjun Yun, Minbyul Jeong, Raehyun Kim, Jaewoo Kang, and Hyunwoo J. Kim. Graph transformer networks, 2020. URL `https://arxiv.org/abs/1911.06455`.

[33] Vinicius Zambaldi, David Raposo, Adam Santoro, Victor Bapst, Yujia Li, Igor Babuschkin, Karl Tuyls, David Reichert, Timothy Lillicrap, Edward Lockhart, Murray Shanahan, Victoria Langston, Razvan Pascanu, Matthew Botvinick, Oriol Vinyals, and Peter Battaglia. Relational deep reinforcement learning, 2018. URL `https://arxiv.org/abs/1806.01830`.