What *Beamtime* adds

Experiment logging built around **hypotheses**, **agents** and **clusters**.

FEATURE	USUALLY · W&B, TENSORBOARD, MLFLOW	WITH BEAMTIME
Testable hypotheses *per run and per group*	Hypotheses live in your head or a doc; runs carry tags, not predictions.	**Proposals** with named **predictions**, frozen once a run records them; checked with t-intervals: `pass` · `fail`.
Agent-first by design *CLI and MCP over one operation set*	Built for people and scripts; agent access comes later, as a separate layer.	`note add` ↔ `note_add`: the same operations, small answers, ~100 ms a call; agent writes are **additive**.
Collaborative notes and memory *by people and agents, shown in the UI*	Free-text notes and reports next to the runs, detached from what was predicted.	Typed notes carry **verdicts** on predictions; **memory** compresses them. Every version kept, edited in the UI.
Views you fully control *reusable blocks; coding is not the bottleneck*	Dashboards clicked together per project, hard to diff, reuse or hand to an agent.	Agents write views as **YAML** from widgets and **custom blocks**; library blocks are pinned, validated, reused.
Plain files you own *no server, no database, no account*	Data sits on a server or in a database; TensorBoard writes binary event files.	A run is a folder of JSON and logs: `cat`, `grep`, `git diff`. The index is only a cache, rebuilt from the files.
Built for clusters *query over ssh, nothing synced*	Jobs need network to upload, or sync offline runs later; or forward a port per machine.	The laptop queries `@cluster/…` over ssh and only the answers travel. Compute nodes need no internet.

The research cycle
what the record keeps, run after run

