https://axiomwebdev.dpdns.org/

54	98	100	92	2/3
Performance	Accessibility	Best Practices	SEO	Agentic Browsing

54

Performance

Values are estimated and may vary. The performance score is calculated directly from these metrics. See calculator.

▲ 0–49 ■ 50–89 ● 90–100



METRICS Expand view

▲ First Contentful Paint
4.4 s

▲ Largest Contentful Paint
6.5 s

Total Blocking Time
510 ms

Cumulative Layout Shift
0

Speed Index
4.4 s



Show audits relevant to: All FCP LCP TBT CLS

INSIGHTS

Render-blocking requests — Est savings of 1,350 ms

Requests are blocking the page's initial render, which may delay LCP. Deferring or inlining can move these network requests out of the critical path. FCP LCP Unscored

Show 3rd-party resources (2)

URL	Transfer Size	Duration
fontshare.com	**2.8 KiB**	**930 ms**
/v2/css?f[]=cabinet-grotesk@800,700,500,400&display=swap (api.fontshare.com)	2.8 KiB	930 ms
Google Fonts Cdn	**1.2 KiB**	**930 ms**
/css2?family=... (fonts.googleapis.com)	1.2 KiB	930 ms
dpdns.org 1st Party	**7.4 KiB**	**210 ms**
/assets/index-Bkxoqrqg.css (axiomwebdev.dpdns.org)	7.4 KiB	210 ms

Forced reflow

A forced reflow occurs when JavaScript queries geometric properties (such as `offsetWidth`) after styles have been invalidated by a change to the DOM state. This can result in poor performance. Learn more about forced reflows and possible mitigations. Unscored

Top function call	Total reflow time
index-DdCCL6LV.js:76	249 ms

Source	Total reflow time
index-DdCCL6LV.js:265	0 ms
index-DdCCL6LV.js:265	1 ms
index-DdCCL6LV.js:265	0 ms
index-DdCCL6LV.js:265	0 ms
index-DdCCL6LV.js:75	248 ms
index-DdCCL6LV.js:75	1 ms
index-DdCCL6LV.js:344	31 ms
index-DdCCL6LV.js:258	4 ms
/assets/Sphere3D-Df_BUsNw.js:3873	0 ms

LCP breakdown

Each subpart has specific improvement strategies. Ideally, most of the LCP time should be spent on loading the resources, not within delays. LCP Unscored

Subpart	Duration
Time to first byte	80 ms
Element render delay	2,520 ms



p.max-w-md.text-lg.text-ink-muted.leading-relaxed.text-balance

Network dependency tree

Avoid chaining critical requests by reducing the length of chains, reducing the download size of resources, or deferring the download of unnecessary resources to improve page load. LCP Unscored

Maximum critical path latency: **865 ms**

Initial Navigation

- https://axiomwebdev.dpdns.org - **120 ms,** 2.20 KiB
  - /css2?family=... (fonts.googleapis.com) - **322 ms,** 1.16 KiB
    - ...v24/tDbv2o-fl....woff2 (fonts.gstatic.com) - **865 ms,** 30.73 KiB
    - ...v20/UcC73FwrK....woff2 (fonts.gstatic.com) - **864 ms,** 47.43 KiB
  - /v2/css?f[]=cabinet-grotesk@800,700,500,400&display=swap (api.fontshare.com) - **336 ms,** 2.80 KiB
    - ...TPYPKOYWF.../6QH2ALVTT....woff2 (cdn.fontshare.com) - **799 ms,** 20.64 KiB
    - ...N2ZXAXWEH.../NXM4Z4TDC....woff2 (cdn.fontshare.com) - **725 ms,** 20.77 KiB
    - ...B2O4O6V3J.../WN5274VQ3....woff2 (cdn.fontshare.com) - **723 ms,** 20.74 KiB
  - /assets/index-DdCCL6LV.js (axiomwebdev.dpdns.org) - **282 ms,** 180.48 KiB
    - /assets/Sphere3D-Df_BUsNw.js (axiomwebdev.dpdns.org) - **729 ms,** 222.36 KiB
  - /assets/index-Bkxoqrqg.css (axiomwebdev.dpdns.org) - **243 ms,** 7.41 KiB

Preconnected origins

preconnect hints help the browser establish a connection earlier in the page load, saving time when the first request for that origin is made. The following are the origins that the page preconnected to.

Origin	Source
https://fonts.googleapis.com/	link
https://fonts.gstatic.com/	link

Preconnect candidates

Add preconnect hints to your most important origins, but try to use no more than 4.

No additional origins are good candidates for preconnecting

Use efficient cache lifetimes — Est savings of 11 KiB

A long cache lifetime can speed up repeat visits to your page. Learn more about caching. FCP LCP Unscored

Request	Cache TTL	Transfer Size
Cloudflare Utility		**11 KiB**
/beacon.min.js/v4513226... (static.cloudflareinsights.com)	1d	11 KiB

Request	Cache TTL	Transfer Size
fontshare.com		**62 KiB**
…N2ZXAXWEH…/NXM4Z4TDC….woff2 (cdn.fontshare.com)	7d	21 KiB
…B2O4O6V3J…/WN5274VQ3….woff2 (cdn.fontshare.com)	7d	21 KiB
…TPYPKOYWF…/6QH2ALVTT….woff2 (cdn.fontshare.com)	7d	21 KiB

Optimize DOM size

A large DOM can increase the duration of style calculations and layout reflows, impacting page responsiveness. A large DOM will also increase memory usage. Learn how to avoid an excessive DOM size. Unscored

Statistic	Element	Value
Total elements		447
DOM depth	path	14
Most children	div.flex.animate-marquee.whitespace-nowrap.will-change-transform	30

3rd parties

3rd party code can significantly impact load performance. Reduce and defer loading of 3rd party code to prioritize your page's content. Unscored

3rd party	Transfer size	Main thread time
Cloudflare Utility	**11 KiB**	**12 ms**
/beacon.min.js/v4513226… (static.cloudflareinsights.com)	11 KiB	12 ms
Google Fonts Cdn	**79 KiB**	**0 ms**
…v20/UcC73FwrK….woff2 (fonts.gstatic.com)	47 KiB	0 ms
…v24/tDbv2o-fl….woff2 (fonts.gstatic.com)	31 KiB	0 ms
/css2?family=… (fonts.googleapis.com)	1 KiB	0 ms
fontshare.com	**65 KiB**	**0 ms**
…N2ZXAXWEH…/NXM4Z4TDC….woff2 (cdn.fontshare.com)	21 KiB	0 ms
…B2O4O6V3J…/WN5274VQ3….woff2 (cdn.fontshare.com)	21 KiB	0 ms
…TPYPKOYWF…/6QH2ALVTT….woff2 (cdn.fontshare.com)	21 KiB	0 ms
/v2/css?f[]=cabinet-grotesk@800,700,500,400&display=swap (api.fontshare.com)	3 KiB	0 ms

3rd party	Transfer size	Main thread time
unsplash.com	**1,030 KiB**	**0 ms**
/photo-155...-367ea4eb4db5?w=1600&q=80 (images.unsplash.com)	535 KiB	0 ms
/photo-144...-64674bd600d8?w=1600&q=80 (images.unsplash.com)	299 KiB	0 ms
/photo-155...-bebda4e38f71?w=1600&q=80 (images.unsplash.com)	196 KiB	0 ms

These insights are also available in the Chrome DevTools Performance Panel - record a trace to view more detailed information.

DIAGNOSTICS

▲ Reduce JavaScript execution time — 2.5 s

Consider reducing the time spent parsing, compiling, and executing JS. You may find delivering smaller JS payloads helps with this. Learn how to reduce Javascript execution time. TBT Unscored

Show 3rd-party resources (1)

URL	Total CPU Time	Script Evaluation	Script Parse
dpdns.org 1st Party	**5,431 ms**	**2,369 ms**	**5 ms**
/assets/index-DdCCL6LV.js (axiomwebdev.dpdns.org)	4,227 ms	1,859 ms	3 ms
https://axiomwebdev.dpdns.org	733 ms	45 ms	1 ms
/assets/Sphere3D-Df_BUsNw.js (axiomwebdev.dpdns.org)	471 ms	464 ms	1 ms
Unattributable	**1,173 ms**	**63 ms**	**0 ms**
`Unattributable`	1,173 ms	63 ms	0 ms
Cloudflare Utility	**76 ms**	**54 ms**	**5 ms**
/beacon.min.js/v4513226... (static.cloudflareinsights.com)	76 ms	54 ms	5 ms

▲ Minimize main-thread work — 6.7 s

Consider reducing the time spent parsing, compiling and executing JS. You may find delivering smaller JS payloads helps with this. Learn how to minimize main-thread work TBT Unscored

Category	Time Spent
Script Evaluation	2,493 ms
Other	2,233 ms
Style & Layout	1,584 ms
Rendering	354 ms
Garbage Collection	27 ms
Parse HTML & CSS	26 ms
Script Parsing & Compilation	10 ms

▲ Reduce unused JavaScript — Est savings of 179 KiB

Reduce unused JavaScript and defer loading scripts until they are required to decrease bytes consumed by network activity. Learn how to reduce unused JavaScript. FCP LCP Unscored

URL	Transfer Size	Est Savings
dpdns.org 1st Party	**400.4 KiB**	**179.1 KiB**
/assets/Sphere3D-Df_BUsNw.js (axiomwebdev.dpdns.org)	221.2 KiB	118.0 KiB
/assets/index-DdCCL6LV.js (axiomwebdev.dpdns.org)	179.3 KiB	61.1 KiB

○ Avoid long main-thread tasks — 12 long tasks found

Lists the longest tasks on the main thread, useful for identifying worst contributors to input delay. Learn how to avoid long main-thread tasks TBT Unscored

URL	Start Time	Duration
dpdns.org 1st Party		**1,508 ms**
/assets/index-DdCCL6LV.js (axiomwebdev.dpdns.org)	4,020 ms	618 ms

URL	Start Time	Duration
/assets/index-DdCCL6LV.js (axiomwebdev.dpdns.org)	7,103 ms	222 ms
/assets/index-DdCCL6LV.js (axiomwebdev.dpdns.org)	7,428 ms	159 ms
/assets/index-DdCCL6LV.js (axiomwebdev.dpdns.org)	4,670 ms	134 ms
/assets/Sphere3D-Df_BUsNw.js (axiomwebdev.dpdns.org)	7,325 ms	103 ms
https://axiomwebdev.dpdns.org	816 ms	81 ms
/assets/index-DdCCL6LV.js (axiomwebdev.dpdns.org)	4,909 ms	77 ms
/assets/index-DdCCL6LV.js (axiomwebdev.dpdns.org)	4,847 ms	62 ms
/assets/index-DdCCL6LV.js (axiomwebdev.dpdns.org)	3,963 ms	52 ms
Unattributable		**274 ms**
Unattributable	999 ms	149 ms
Unattributable	897 ms	72 ms
Unattributable	1,148 ms	53 ms

Avoid non-composited animations — 1 animated element found

Animations which are not composited can be janky and increase CLS. Learn how to avoid non-composited animations CLS Unscored

Element
main
Filter-related property may move pixels

More information about the performance of your application. These numbers don't directly affect the Performance score.

PASSED AUDITS (17) Hide

Layout shift culprits

Layout shifts occur when elements move absent any user interaction. Investigate the causes of layout shifts, such as elements being added, removed, or their fonts changing as the page loads. CLS Unscored

Document request latency

Your first network request is the most important. Reduce its latency by avoiding redirects, ensuring a fast server response, and enabling text compression. FCP LCP Unscored

- Avoids redirects
- Server responds quickly (observed 75 ms)
- Applies text compression

Duplicated JavaScript

Remove large, duplicate JavaScript modules from bundles to reduce unnecessary bytes consumed by network activity. FCP LCP Unscored

Font display

Consider setting `font-display` to `swap` or `optional` to ensure text is consistently visible. `swap` can be further optimized to mitigate layout shifts with font metric overrides. Unscored

Improve image delivery

Reducing the download time of images can improve the perceived load time of the page and LCP. Learn more about optimizing image size FCP LCP Unscored

INP breakdown

Start investigating how to improve INP by looking at the longest subpart. Unscored

LCP request discovery

Optimize LCP by making the LCP image discoverable from the HTML immediately, and avoiding lazy-loading Unscored

Legacy JavaScript

Polyfills and transforms enable older browsers to use new JavaScript features. However, many aren't necessary for modern browsers. Consider modifying your JavaScript build process to not transpile Baseline features, unless you know you must

support older browsers. Learn why most sites can deploy ES6+ code without transpiling FCP LCP Unscored

Modern HTTP

HTTP/2 and HTTP/3 offer many benefits over HTTP/1.1, such as multiplexing. Learn more about using modern HTTP. FCP LCP Unscored

Optimize viewport for mobile

Tap interactions may be delayed by up to 300 ms if the viewport is not optimized for mobile. Unscored

meta

Minify CSS

Minifying CSS files can reduce network payload sizes. Learn how to minify CSS. FCP LCP Unscored

Minify JavaScript

Minifying JavaScript files can reduce payload sizes and script parse time. Learn how to minify JavaScript. FCP LCP Unscored

Reduce unused CSS

Reduce unused rules from stylesheets and defer CSS not used for above-the-fold content to decrease bytes consumed by network activity. Learn how to reduce unused CSS. FCP LCP Unscored

Avoids enormous network payloads — Total size was 1,600 KiB

Large network payloads cost users real money and are highly correlated with long load times. Learn how to reduce payload sizes. Unscored

☑ Show 3rd-party resources (8)

URL	Transfer Size
unsplash.com	**1,030.3 KiB**
/photo-155...-367ea4eb4db5?w=1600&q=80 (images.unsplash.com)	535.2 KiB
/photo-144...-64674bd600d8?w=1600&q=80 (images.unsplash.com)	299.3 KiB

URL	Transfer Size
/photo-155...-bebda4e38f71?w=1600&q=80 (images.unsplash.com)	195.8 KiB
dpdns.org 1st Party	**402.8 KiB**
/assets/Sphere3D-Df_BUsNw.js (axiomwebdev.dpdns.org)	222.4 KiB
/assets/index-DdCCL6LV.js (axiomwebdev.dpdns.org)	180.5 KiB
Google Fonts Cdn	**78.2 KiB**
...v20/UcC73FwrK....woff2 (fonts.gstatic.com)	47.4 KiB
...v24/tDbv2o-fl....woff2 (fonts.gstatic.com)	30.7 KiB
fontshare.com	**62.1 KiB**
...N2ZXAXWEH.../NXM4Z4TDC....woff2 (cdn.fontshare.com)	20.8 KiB
...B2O4O6V3J.../WN5274VQ3....woff2 (cdn.fontshare.com)	20.7 KiB
...TPYPKOYWF.../6QH2ALVTT....woff2 (cdn.fontshare.com)	20.6 KiB

○ User Timing marks and measures

Consider instrumenting your app with the User Timing API to measure your app's real-world performance during key user experiences. Learn more about User Timing marks. Unscored

● Image elements have explicit `width` and `height`

Set an explicit width and height on image elements to reduce layout shifts and improve CLS. Learn how to set image dimensions CLS Unscored

● Page didn't prevent back/forward cache restoration

Many navigations are performed by going back to a previous page, or forwards again. The back/forward cache (bfcache) can speed up these return navigations. Learn more about the bfcache Unscored



Accessibility

These checks highlight opportunities to improve the accessibility of your web app. Automatic detection can only detect a subset of issues and does not guarantee the accessibility of your web app, so manual testing is also encouraged.

NAVIGATION

▲ Heading elements are not in a sequentially-descending order

Properly ordered headings that do not skip levels convey the semantic structure of the page, making it easier to navigate and understand when using assistive technologies. Learn more about heading order.

Failing Elements
h4.mb-6.text-xs.uppercase.tracking-widest.text-ink-muted

These are opportunities to improve keyboard navigation in your application.

ADDITIONAL ITEMS TO MANUALLY CHECK (10) Hide

○ Interactive controls are keyboard focusable

Custom interactive controls are keyboard focusable and display a focus indicator. Learn how to make custom controls focusable. Unscored

○ Interactive elements indicate their purpose and state

Interactive elements, such as links and buttons, should indicate their state and be distinguishable from non-interactive elements. Learn how to decorate interactive elements with affordance hints. Unscored

○ The page has a logical tab order

Tabbing through the page follows the visual layout. Users cannot focus elements that are offscreen. Learn more about logical tab ordering. Unscored

○ Visual order on the page follows DOM order

DOM order matches the visual order, improving navigation for assistive technology. Learn more about DOM and visual ordering. Unscored

- User focus is not accidentally trapped in a region

A user can tab into and out of any control or region without accidentally trapping their focus. Learn how to avoid focus traps. Unscored

- The user's focus is directed to new content added to the page

If new content, such as a dialog, is added to the page, the user's focus is directed to it. Learn how to direct focus to new content. Unscored

- HTML5 landmark elements are used to improve navigation

Landmark elements (`<main>`, `<nav>`, etc.) are used to improve the keyboard navigation of the page for assistive technology. Learn more about landmark elements. Unscored

- Offscreen content is hidden from assistive technology

Offscreen content is hidden with display: none or aria-hidden=true. Learn how to properly hide offscreen content. Unscored

- Custom controls have associated labels

Custom interactive controls have associated labels, provided by aria-label or aria-labelledby. Learn more about custom controls and labels. Unscored

- Custom controls have ARIA roles

Custom interactive controls have appropriate ARIA roles. Learn how to add roles to custom controls. Unscored

These items address areas which an automated testing tool cannot cover. Learn more in our guide on conducting an accessibility review.

PASSED AUDITS (19) Hide

- `[aria-*]` attributes match their roles

Each ARIA `role` supports a specific subset of `aria-*` attributes. Mismatching these invalidates the `aria-*` attributes. Learn how to match ARIA attributes to their roles.

- [aria-hidden="true"] is not present on the document <body>

  Assistive technologies, like screen readers, work inconsistently when aria-hidden="true" is set on the document <body>. Learn how aria-hidden affects the document body.

- [aria-*] attributes have valid values

  Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid values. Learn more about valid values for ARIA attributes.

- [aria-*] attributes are valid and not misspelled

  Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid names. Learn more about valid ARIA attributes.

- Buttons have an accessible name

  When a button doesn't have an accessible name, screen readers announce it as "button", making it unusable for users who rely on screen readers. Learn how to make buttons more accessible.

- Image elements have [alt] attributes

  Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. Learn more about the alt attribute.

- [user-scalable="no"] is not used in the <meta name="viewport"> element and the [maximum-scale] attribute is not less than 5.

  Disabling zooming is problematic for users with low vision who rely on screen magnification to properly see the contents of a web page. Learn more about the viewport meta tag.

- ARIA attributes are used as specified for the element's role

  Some ARIA attributes are only allowed on an element under certain conditions. Learn more about conditional ARIA attributes.

- [aria-hidden="true"] elements do not contain focusable descendents

  Focusable descendents within an [aria-hidden="true"] element prevent those interactive elements from being available to users of assistive technologies like screen readers. Learn how aria-hidden affects focusable elements.

- Elements use only permitted ARIA attributes

Using ARIA attributes in roles where they are prohibited can mean that important information is not communicated to users of assistive technologies. Learn more about prohibited ARIA roles.

- Background and foreground colors have a sufficient contrast ratio

Low-contrast text is difficult or impossible for many users to read. Learn how to provide sufficient color contrast.

- Document has a `<title>` element

The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. Learn more about document titles.

- `<html>` element has a `[lang]` attribute

If a page doesn't specify a `lang` attribute, a screen reader assumes that the page is in the default language that the user chose when setting up the screen reader. If the page isn't actually in the default language, then the screen reader might not announce the page's text correctly. Learn more about the `lang` attribute.

- `<html>` element has a valid value for its `[lang]` attribute

Specifying a valid BCP 47 language helps screen readers announce text properly. Learn how to use the `lang` attribute.

- Links have a discernible name

Link text (and alternate text for images, when used as links) that is discernible, unique, and focusable improves the navigation experience for screen reader users. Learn how to make links accessible.

- Lists contain only `<li>` elements and script supporting elements (`<script>` and `<template>`).

Screen readers have a specific way of announcing lists. Ensuring proper list structure aids screen reader output. Learn more about proper list structure.

- List items (`<li>`) are contained within `<ul>`, `<ol>` or `<menu>` parent elements

Screen readers require list items (`<li>`) to be contained within a parent `<ul>`, `<ol>` or `<menu>` to be announced properly. Learn more about proper list structure.

- Touch targets have sufficient size and spacing.

Touch targets with sufficient size and spacing help users who may have difficulty targeting small controls to activate the targets. Learn more about touch targets.

- Document has a main landmark.

  One main landmark helps screen reader users navigate a web page. Learn more about landmarks.

NOT APPLICABLE (43) Hide

- `[accesskey]` values are unique

  Access keys let users quickly focus a part of the page. For proper navigation, each access key must be unique. Learn more about access keys. Unscored

- `button`, `link`, and `menuitem` elements have accessible names

  When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn how to make command elements more accessible. Unscored

- Deprecated ARIA roles were not used

  Deprecated ARIA roles may not be processed correctly by assistive technology. Learn more about deprecated ARIA roles. Unscored

- Elements with `role="dialog"` or `role="alertdialog"` have accessible names.

  ARIA dialog elements without accessible names may prevent screen readers users from discerning the purpose of these elements. Learn how to make ARIA dialog elements more accessible. Unscored

- ARIA input fields have accessible names

  When an input field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more about input field labels. Unscored

- ARIA `meter` elements have accessible names

  When a meter element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn how to name `meter` elements. Unscored

- ARIA `progressbar` elements have accessible names

  When a `progressbar` element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn how to label `progressbar` elements. Unscored

- [role]s have all required [aria-*] attributes

  Some ARIA roles have required attributes that describe the state of the element to screen readers. Learn more about roles and required attributes. Unscored

- Elements with an ARIA [role] that require children to contain a specific [role] have all required children.

  Some ARIA parent roles must contain specific child roles to perform their intended accessibility functions. Learn more about roles and required children elements. Unscored

- [role]s are contained by their required parent element

  Some ARIA child roles must be contained by specific parent roles to properly perform their intended accessibility functions. Learn more about ARIA roles and required parent element. Unscored

- [role] values are valid

  ARIA roles must have valid values in order to perform their intended accessibility functions. Learn more about valid ARIA roles. Unscored

- Elements with the role=text attribute do not have focusable descendents.

  Adding role=text around a text node split by markup enables VoiceOver to treat it as one phrase, but the element's focusable descendents will not be announced. Learn more about the role=text attribute. Unscored

- ARIA toggle fields have accessible names

  When a toggle field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more about toggle fields. Unscored

- ARIA tooltip elements have accessible names

  When a tooltip element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn how to name tooltip elements. Unscored

- ARIA treeitem elements have accessible names

  When a treeitem element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more about labeling treeitem elements. Unscored

- The page contains a heading, skip link, or landmark region

Adding ways to bypass repetitive content lets keyboard users navigate the page more efficiently. Learn more about bypass blocks. Unscored

- `<dl>`'s contain only properly-ordered `<dt>` and `<dd>` groups, `<script>`, `<template>` or `<div>` elements.

When definition lists are not properly marked up, screen readers may produce confusing or inaccurate output. Learn how to structure definition lists correctly. Unscored

- Definition list items are wrapped in `<dl>` elements

Definition list items (`<dt>` and `<dd>`) must be wrapped in a parent `<dl>` element to ensure that screen readers can properly announce them. Learn how to structure definition lists correctly. Unscored

- ARIA IDs are unique

The value of an ARIA ID must be unique to prevent other instances from being overlooked by assistive technologies. Learn how to fix duplicate ARIA IDs. Unscored

- No form fields have multiple labels

Form fields with multiple labels can be confusingly announced by assistive technologies like screen readers which use either the first, the last, or all of the labels. Learn how to use form labels. Unscored

- `<frame>` or `<iframe>` elements have a title

Screen reader users rely on frame titles to describe the contents of frames. Learn more about frame titles. Unscored

- `<html>` element has an `[xml:lang]` attribute with the same base language as the `[lang]` attribute.

If the webpage does not specify a consistent language, then the screen reader might not announce the page's text correctly. Learn more about the `lang` attribute. Unscored

- Input buttons have discernible text.

Adding discernable and accessible text to input buttons may help screen reader users understand the purpose of the input button. Learn more about input buttons. Unscored

- `<input type="image">` elements have `[alt]` text

When an image is being used as an `<input>` button, providing alternative text can help screen reader users understand the purpose of the button. Learn about input image alt text. Unscored

- Form elements have associated labels

  Labels ensure that form controls are announced properly by assistive technologies, like screen readers. Learn more about form element labels. Unscored

- Links are distinguishable without relying on color.

  Low-contrast text is difficult or impossible for many users to read. Link text that is discernible improves the experience for users with low vision. Learn how to make links distinguishable. Unscored

- The document does not use `<meta http-equiv="refresh">`

  Users do not expect a page to refresh automatically, and doing so will move focus back to the top of the page. This may create a frustrating or confusing experience. Learn more about the refresh meta tag. Unscored

- `<object>` elements have alternate text

  Screen readers cannot translate non-text content. Adding alternate text to `<object>` elements helps screen readers convey meaning to users. Learn more about alt text for `object` elements. Unscored

- Select elements have associated label elements.

  Form elements without effective labels can create frustrating experiences for screen reader users. Learn more about the `select` element. Unscored

- Skip links are focusable.

  Including a skip link can help users skip to the main content to save time. Learn more about skip links. Unscored

- No element has a `[tabindex]` value greater than 0

  A value greater than 0 implies an explicit navigation ordering. Although technically valid, this often creates frustrating experiences for users who rely on assistive technologies. Learn more about the `tabindex` attribute. Unscored

- Cells in a `<table>` element that use the `[headers]` attribute refer to table cells within the same table.

  Screen readers have features to make navigating tables easier. Ensuring `<td>` cells using the `[headers]` attribute only refer to other cells in the same table may improve the experience for screen reader users. Learn more about the `headers` attribute. Unscored

- `<th>` elements and elements with `[role="columnheader"/"rowheader"]` have data cells they describe.

Screen readers have features to make navigating tables easier. Ensuring table headers always refer to some set of cells may improve the experience for screen reader users. Learn more about table headers. Unscored

- [lang] attributes have a valid value

Specifying a valid BCP 47 language on elements helps ensure that text is pronounced correctly by a screen reader. Learn how to use the lang attribute. Unscored

- <video> elements contain a <track> element with [kind="captions"]

When a video provides a caption it is easier for deaf and hearing impaired users to access its information. Learn more about video captions. Unscored

- autocomplete attributes are used correctly

The autocomplete attribute values must be valid and correctly applied for screen readers to function correctly. Learn more about valid autocomplete values. Unscored

- Elements with role="none" or role="presentation" do not have conflicts

There are certain cases where the semantic role of an element with role="none" or role="presentation" does not resolve to none or presentation. To ensure the element remains removed from the accessibility tree, you should not add any global ARIA attributes to the element or make it focusable. Learn more about presentation role conflict. Unscored

- SVG elements with an img role have an accessible text alternative

Ensures SVG elements with an img, graphics-document or graphics-symbol role have an accessible text alternative. Learn more about SVG alt text. Unscored

- Tables have different content in the summary attribute and <caption>.

The summary attribute should describe the table structure, while <caption> should have the onscreen title. Accurate table mark-up helps users of screen readers. Learn more about summary and caption. Unscored

- All heading elements contain content.

A heading with no content or inaccessible text prevent screen reader users from accessing information on the page's structure. Learn more about headings. Unscored

- Uses ARIA roles only on compatible elements

Many HTML elements can only be assigned certain ARIA roles. Using ARIA roles where they are not allowed can interfere with the accessibility of the web page. Learn more about ARIA roles. Unscored

- Image elements do not have `[alt]` attributes that are redundant text.

Informative elements should aim for short, descriptive alternative text. Alternative text that is exactly the same as the text adjacent to the link or image is potentially confusing for screen reader users, because the text will be read twice. Learn more about the `alt` attribute. Unscored

- Identical links have the same purpose.

Links with the same destination should have the same description, to help users understand the link's purpose and decide whether to follow it. Learn more about identical links. Unscored



Best Practices

TRUST AND SAFETY

- Ensure CSP is effective against XSS attacks

A strong Content Security Policy (CSP) significantly reduces the risk of cross-site scripting (XSS) attacks. Learn how to use a CSP to prevent XSS Unscored

Description	Directive	Severity
Host allowlists can frequently be bypassed. Consider using CSP nonces or hashes instead, along with `'strict-dynamic'` if necessary.	`script-src`	High
`'unsafe-inline'` allows the execution of unsafe in-page scripts and event handlers. Consider using CSP nonces or hashes to allow scripts individually.	`script-src`	High

- Ensure proper origin isolation with COOP

The Cross-Origin-Opener-Policy (COOP) can be used to isolate the top-level window from other documents such as pop-ups. Learn more about deploying the COOP header. Unscored

Description	Directive	Severity
No COOP header found		High

Mitigate DOM-based XSS with Trusted Types

The `require-trusted-types-for` directive in the `Content-Security-Policy` (CSP) header instructs user agents to control the data passed to DOM XSS sink functions. Learn more about mitigating DOM-based XSS with Trusted Types. Unscored

Description	Severity
No `Content-Security-Policy` header with Trusted Types directive found	High

BROWSER COMPATIBILITY

Baseline Features

Lists web features used on the page and their Baseline status as of 2026-05-01. Learn more about Baseline. Unscored

Web-features	Baseline Status	Source
dpdns.org 1st Party		
page-visibility-state	Limited Availability	(index):1
long-animation-frames	Limited Availability	(index):1
layout-instability	Limited Availability	(index):1
background-clip-text	Limited Availability	index-DdCCL6LV.js:75
requestidlecallback	Limited Availability	(index):1
zstd	Newly Available (2026-02-11)	(index):-1
http3	Newly Available (2024-09-16)	(index):-1
abortsignal-any	Newly Available (2024-03-19)	(index):1

Web-features	Baseline Status	Source
text-wrap	Newly Available (2024-10-17)	index-DdCCL6LV.js:75
backdrop-filter	Newly Available (2024-09-16)	index-DdCCL6LV.js:75
text-wrap-balance	Newly Available (2024-05-13)	index-DdCCL6LV.js:75
scrollend	Newly Available (2025-12-12)	index-DdCCL6LV.js:330
webgl2-color-management	Newly Available (2024-10-29)	/assets/Sphere3D-Df_BUsNw.js:3839
js-modules	Widely Available (2018-05-09)	(index):-1
nullish-coalescing	Widely Available (2020-09-16)	(index):1
aborting	Widely Available (2019-03-25)	(index):1
where	Widely Available (2021-01-21)	(index):-1
not	Widely Available (2021-01-21)	(index):-1
focus-visible	Widely Available (2022-03-14)	(index):-1
request-animation-frame	Widely Available (2015-07-29)	index-DdCCL6LV.js:337
intersection-observer	Widely Available (2019-03-25)	index-DdCCL6LV.js:75
ch	Widely Available (2015-07-29)	index-DdCCL6LV.js:75
will-change	Widely Available (2020-01-15)	index-DdCCL6LV.js:75
aspect-ratio	Widely Available (2021-09-20)	index-DdCCL6LV.js:75
flexbox	Widely Available (2015-09-30)	index-DdCCL6LV.js:75
grid	Widely Available (2017-10-17)	index-DdCCL6LV.js:75
individual-transforms	Widely Available (2022-08-05)	index-DdCCL6LV.js:344
web-animations	Widely Available (2020-09-16)	index-DdCCL6LV.js:75

Web-features	Baseline Status	Source
text-indent	Widely Available (2015-07-29)	index-DdCCL6LV.js:75
outline	Widely Available (2023-03-27)	index-DdCCL6LV.js:75
canvas	Widely Available (2015-07-29)	index-DdCCL6LV.js:40
weak-references	Widely Available (2021-04-26)	(index):1
webgl2	Widely Available (2021-09-20)	/assets/Sphere3D-Df_BUsNw.js:3839
offscreen-canvas	Widely Available (2023-03-27)	/assets/Sphere3D-Df_BUsNw.js:3815
Unattributable		
referrer-policy	Widely Available (2021-09-20)	

GENERAL

▲ Missing source maps for large first-party JavaScript

Source maps translate minified code to the original source code. This helps developers debug in production. In addition, Lighthouse is able to provide further insights. Consider deploying source maps to take advantage of these benefits. Learn more about source maps. Unscored

URL	Map URL
dpdns.org 1st Party	
/assets/Sphere3D-Df_BUsNw.js (axiomwebdev.dpdns.org)	
> Large JavaScript file is missing a source map	
/assets/index-DdCCL6LV.js (axiomwebdev.dpdns.org)	
> Large JavaScript file is missing a source map	

PASSED AUDITS (12) Hide

- Uses HTTPS

All sites should be protected with HTTPS, even ones that don't handle sensitive data. This includes avoiding mixed content, where some resources are loaded over HTTP despite the initial request being served over HTTPS. HTTPS prevents intruders from tampering with or passively listening in on the communications between your app and your users, and is a prerequisite for HTTP/2 and many new web platform APIs. Learn more about HTTPS.

- Avoids deprecated APIs

Deprecated APIs will eventually be removed from the browser. Learn more about deprecated APIs.

- Avoids third-party cookies

Third-party cookies may be blocked in some contexts. Learn more about preparing for third-party cookie restrictions.

- Allows users to paste into input fields

Preventing input pasting is a bad practice for the UX, and weakens security by blocking password managers.Learn more about user-friendly input fields.

- Avoids requesting the geolocation permission on page load

Users are mistrustful of or confused by sites that request their location without context. Consider tying the request to a user action instead. Learn more about the geolocation permission.

- Avoids requesting the notification permission on page load

Users are mistrustful of or confused by sites that request to send notifications without context. Consider tying the request to user gestures instead. Learn more about responsibly getting permission for notifications.

- Displays images with correct aspect ratio

Image display dimensions should match natural aspect ratio. Learn more about image aspect ratio.

- Serves images with appropriate resolution

Image natural dimensions should be proportional to the display size and the pixel ratio to maximize image clarity. Learn how to provide responsive images.

- Page has the HTML doctype

Specifying a doctype prevents the browser from switching to quirks-mode. Learn more about the doctype declaration.

- Properly defines charset

A character encoding declaration is required. It can be done with a `<meta>` tag in the first 1024 bytes of the HTML or in the Content-Type HTTP response header. Learn more about declaring the character encoding.

- No browser errors logged to the console

Errors logged to the console indicate unresolved problems. They can come from network request failures and other browser concerns. Learn more about this errors in console diagnostic audit

- No issues in the `Issues` panel in Chrome Devtools

Issues logged to the `Issues` panel in Chrome Devtools indicate unresolved problems. They can come from network request failures, insufficient security controls, and other browser concerns. Open up the Issues panel in Chrome DevTools for more details on each issue.

NOT APPLICABLE (4) Hide

- Redirects HTTP traffic to HTTPS

Make sure that you redirect all HTTP traffic to HTTPS in order to enable secure web features for all your users. Learn more. Unscored

- Use a strong HSTS policy

Deployment of the HSTS header significantly reduces the risk of downgrading HTTP connections and eavesdropping attacks. A rollout in stages, starting with a low max-age is recommended. Learn more about using a strong HSTS policy. Unscored

- Mitigate clickjacking with XFO or CSP

The `X-Frame-Options` (XFO) header or the `frame-ancestors` directive in the `Content-Security-Policy` (CSP) header control where a page can be embedded. These can mitigate clickjacking attacks by blocking some or all sites from embedding the page. Learn more about mitigating clickjacking. Unscored

- Detected JavaScript libraries

All front-end JavaScript libraries detected on the page. Learn more about this JavaScript library detection diagnostic audit. Unscored

92

SEO

These checks ensure that your page is following basic search engine optimization advice. There are many additional factors Lighthouse does not score here that may affect your search ranking, including performance on Core Web Vitals. Learn more about Google Search Essentials.

CRAWLING AND INDEXING

▲ robots.txt is not valid — 24 errors found

If your robots.txt file is malformed, crawlers may not be able to understand how you want your website to be crawled or indexed. Learn more about robots.txt.

Line #	Content	Error
62	<!doctype html>	Syntax not understood
63	<html lang="en" class="dark">	Syntax not understood
64	<head>	Syntax not understood
65	<meta charset="UTF-8" />	Syntax not understood
66	<link rel="icon" type="image/svg+xml" href="/favicon.svg" />	Syntax not understood
67	<meta name="viewport" content="width=device-width, initial-scale=1.0" />	Syntax not understood
68	<meta name="description" content="Axiom Web Builder — premium, custom-built websites and web apps for businesses worldwide. Fast, secure, and beautifully designed." />	Syntax not understood
69	<meta property="og:title" content="Axiom Web Builder — Premium Websites & Web Apps" />	Unknown directive
70	<meta property="og:description" content="Custom-built premium websites, web apps, and interactive experiences for businesses worldwide." />	Unknown directive

Line #	Content	Error
71	<meta property="og:site_name" content="Axiom Web Builder" />	Unknown directive
72	<meta property="og:type" content="website" />	Unknown directive
73	<meta name="theme-color" content="#0a0a0a" />	Syntax not understood
75	<link rel="preconnect" href="https://fonts.googleapis.com" />	Unknown directive
76	<link rel="preconnect" href="https://fonts.gstatic.com" crossorigin />	Unknown directive
77	<link href="https://fonts.googleapis.com/css2?family=Inter:wght@300;400;500;600;700;800&family=JetBrains+Mono:wght@400;500;700&display=swap" rel="stylesheet" />	Unknown directive
78	<link href="https://api.fontshare.com/v2/css?f[]=cabinet-grotesk@800,700,500,400&display=swap" rel="stylesheet" />	Unknown directive
80	<title>Axiom Web Builder — Premium Websites & Web Apps</title>	Syntax not understood
81	<script type="module" crossorigin src="/assets/index-DdCCL6LV.js"></script>	Syntax not understood
82	<link rel="stylesheet" crossorigin href="/assets/index-Bkxoqrqg.css">	Syntax not understood
83	</head>	Syntax not understood
84	<body>	Syntax not understood
85		Syntax not understood
86	</body>	Syntax not understood
87	</html>	Syntax not understood

To appear in search results, crawlers need access to your app.

ADDITIONAL ITEMS TO MANUALLY CHECK (1) Hide

- Structured data is valid

  Run the Structured Data Testing Tool to validate structured data. Learn more about Structured Data. Unscored

Run these additional validators on your site to check additional SEO best practices.

PASSED AUDITS (8) Hide

- Page isn't blocked from indexing

  Search engines are unable to include your pages in search results if they don't have permission to crawl them. Learn more about crawler directives.

- Document has a `<title>` element

  The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. Learn more about document titles.

- Document has a meta description

  Meta descriptions may be included in search results to concisely summarize page content. Learn more about the meta description.

- Page has successful HTTP status code

  Pages with unsuccessful HTTP status codes may not be indexed properly. Learn more about HTTP status codes.

- Links have descriptive text

  Descriptive link text helps search engines understand your content. Learn how to make links more accessible.

- Links are crawlable

  Search engines may use `href` attributes on links to crawl websites. Ensure that the `href` attribute of anchor elements links to an appropriate destination, so more pages of the site can be discovered. Learn how to make links crawlable

- Image elements have `[alt]` attributes

Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. Learn more about the `alt` attribute.

Document has a valid `hreflang`

hreflang links tell search engines what version of a page they should list in search results for a given language or region. Learn more about `hreflang`.

NOT APPLICABLE (1) Hide

Document has a valid `rel=canonical`

Canonical links suggest which URL to show in search results. Learn more about canonical links. Unscored

2/3

Agentic Browsing

These checks ensure high-quality, browsable websites for AI agents and validate the correctness of WebMCP integrations. This category is still under development and subject to change.

AGENT ACCESSIBILITY

llms.txt does not follow recommendations

If your llms.txt file does not follow recommendations, large language models may not be able to understand how you want your website to be crawled or used for training. The llms.txt file should be a Markdown file containing at least one H1 header.

Error
File is missing a required H1 header (e.g., "# Title").
File does not appear to contain any links.

These audits highlight best practices for improving the accessibility of the website for AI agents.

PASSED AUDITS (2) Hide

- Accessibility tree is well-formed — All audits passed

A well-formed accessibility tree helps AI agents to navigate and interact with the page.

- Cumulative Layout Shift — 0

Cumulative Layout Shift measures the movement of visible elements within the viewport. Learn more about the Cumulative Layout Shift metric.

NOT APPLICABLE (3) Hide

- WebMCP form coverage

Consider adding WebMCP annotations to the forms listed below. This helps AI agents identify and interact with these forms more reliably. Unscored

- WebMCP tools registered

Lists the WebMCP tools registered at the time of analysis. Unscored

- WebMCP schemas are valid

Valid WebMCP schemas are required for AI agents to understand and interact with tools correctly. Please fix any errors or warnings reported by the browser. Unscored

Captured at Jul 15, 2026, 7:08 PM GMT+5
Initial page load

Emulated Moto G Power with Lighthouse 13.3.0
Slow 4G throttling

Single page session
Using Chromium 150.0.0.0 with devtools

Generated by **Lighthouse** 13.3.0 | File an issue