

# LAPORAN TUGAS PEMROGRAMAN BERBASIS FRAMEWORK

## Modul 13

CRUD 1 dengan Backend Laravel dan Frontend ReactJS



Disusun Oleh :

Nama : Hunayn Risatayn

NIM : 1841720148

Kelas : TI-3E




Program Studi D-IV Teknik Informatika

Jurusan Teknologi Informasi

Politeknik Negeri Malang

Mei 2021

## Praktikum – Bagian 1: Instalasi Laravel 7

Langkah	Keterangan
1	<p>Untuk membuat project laravel v7 gunakan syntax berikut</p> <p><b>composer create-project --prefer-dist laravel/laravel:^7.0 hunayncrudlaravelreact</b></p>   <p>Silahkan buat database baru bernama <b>db_hunayncrudlaravelreact</b></p>  <p>Kemudian buka file <b>.env</b> yang ada di direktori <b>hunayncrudlaravelreact/.env</b></p> <p>Ubah source code pada file tersebut menjadi seperti dibawah ini</p>

```

9    DB_CONNECTION=mysql
10   DB_HOST=127.0.0.1
11   DB_PORT=3306
12   DB_DATABASE=db_hunayncrudlaravelreact
13   DB_USERNAME=root
14   DB_PASSWORD=
15

```

Masih di direktori project, ketik command berikut untuk membuat Model Article dan Migration-nya:

```

D:\data\Users\User\Documents\College\Framework Prog\framework_prog\13thWeek\hunayncrudlaravelreact>php artisan make:model Article --migration
Model created successfully.
Created Migration: 2021_05_24_041046_create_articles_table

D:\data\Users\User\Documents\College\Framework Prog\framework_prog\13thWeek\hunayncrudlaravelreact>

```

Sekarang buka file Article.php yang ada di dalam direktori app/Article.php dan modifikasi:

```

app > Article.php > ...
1  <?php
2
3  namespace App;
4
5  use Illuminate\Database\Eloquent\Model;
6
7  class Article extends Model
8  {
9      protected $table = "articles";
10     protected $fillable = ['title', 'content'];
11 }
12

```

Kemudian, buka file \*\*\*\*\*create\_articles\_table.php yang tersimpan di direktori database/migrations dan modifikasi seperti kode di bawah ini:

```

database > migrations > 2021_05_24_041046_create_articles_table.php > CreateArticlesTable > up
1  <?php
2
3  use Illuminate\Database\Migrations\Migration;
4  use Illuminate\Database\Schema\Blueprint;
5  use Illuminate\Support\Facades\Schema;
6
7  class CreateArticlesTable extends Migration
8  {
9      /**
10       * Run the migrations.
11       *
12       * @return void
13       */
14     public function up()
15     {
16         Schema::create('articles', function (Blueprint $table) {
17             $table->bigIncrements('id');
18             $table->string('title');
19             $table->string('content');
20             $table->timestamps();
21         });
22     }
23
24     /**
25      * Reverse the migrations.
26      *
27      * @return void
28      */
29     public function down()
30     {
31         Schema::dropIfExists('articles');
32     }
33
34     public function down()
35     {
36         Schema::dropIfExists('articles');
37     }
38 }
39

```

Activate Windows  
Go to Settings to activate Windows.

Kemudian jalankan command berikut ini agar table yang kita buat migrate ke database:

```
D:\data\Users\User\Documents\College\Framework Prog\framework_prog\13thWeek\hunayncrudlaravelreact>php artisan migrate
Migration table created successfully.
Migrating: 2014_10_12_000000_create_users_table
Migrated: 2014_10_12_000000_create_users_table (0.04 seconds)
Migrating: 2019_08_19_000000_create_failed_jobs_table
Migrated: 2019_08_19_000000_create_failed_jobs_table (0.03 seconds)
Migrating: 2021_05_24_041046_create_articles_table
Migrated: 2021_05_24_041046_create_articles_table (0.04 seconds)
D:\data\Users\User\Documents\College\Framework Prog\framework_prog\13thWeek\hunayncrudlaravelreact>
```

Jika berhasil dengan baik, maka di database db\_blog\_react akan muncul table seperti gambar di bawah ini:

Table	Action	Rows	Type	Collation	Size	Overhead
articles	Browse Structure Search Insert Empty Drop	0	InnoDB	utf8mb4_unicode_ci	16.0 KiB	-
failed_jobs	Browse Structure Search Insert Empty Drop	0	InnoDB	utf8mb4_unicode_ci	16.0 KiB	-
migrations	Browse Structure Search Insert Empty Drop	3	InnoDB	utf8mb4_unicode_ci	16.0 KiB	-
users	Browse Structure Search Insert Empty Drop	0	InnoDB	utf8mb4_unicode_ci	32.0 KiB	-
<b>4 tables</b>	<b>Sum</b>	<b>3</b>	<b>InnoDB</b>	<b>utf8mb4_general_ci</b>	<b>80.0 KiB</b>	<b>0 B</b>

Buka file routes/web.php dan silahkan modifikasi:

```
routes > web.php
1  <?php
2
3  use Illuminate\Support\Facades\Route;
4
5  /*
6  |-----
7  | Web Routes
8  |-----
9  |
10 | Here is where you can register web routes for your application. These
11 | routes are loaded by the RouteServiceProvider within a group which
12 | contains the "web" middleware group. Now create something great!
13 |
14 */
15
16 Route::view('/articles', 'app');
17 Route::view('/article/edit/{id}', 'app');
18 Route::view('/article/{id}', 'app');
19 Route::view('/', 'app');
20 Route::view('/{path}', 'app');
21
```

Kemudian buka file routes/api.php dan modifikasi menjadi:

```

routes > api.php
1  <?php
2
3  use Illuminate\Support\Facades\Route;
4
5  /*
6  |-----
7  | API Routes
8  |-----
9  |
10 | Here is where you can register API routes for your application. These
11 | routes are loaded by the RouteServiceProvider within a group which
12 | is assigned the "api" middleware group. Enjoy building your API!
13 |
14 */
15
16 Route::get('/articles', 'ArticleController@index');
17 Route::post('/article/store', 'ArticleController@store');
18 Route::get('/article/edit/{id}', 'ArticleController@getArticle');
19 Route::get('/article/{id}', 'ArticleController@getArticle');
20 Route::put('/article/{id}', 'ArticleController@update');
21 Route::delete('/article/delete/{id}', 'ArticleController@delete');
22

```

Ketik command di bawah ini untuk membuat controller baru bernama ArticleController

```

D:\data\Users\User\Documents\College\Framework Prog\framework_prog\13thWeek\hunayncrudlaravelreact>php artisan make:controller ArticleController
Controller created successfully.
D:\data\Users\User\Documents\College\Framework Prog\framework_prog\13thWeek\hunayncrudlaravelreact>

```

Sekarang buka file ArticleController.php yang terdapat di app/Http/Controllers.

Kemudian ketik kode berikut ini:

```

app > Http > Controllers > ArticleController.php > ...
1  <?php
2
3  namespace App\Http\Controllers;
4
5  use Illuminate\Http\Request;
6
7  class ArticleController extends Controller
8  {
9      public function index()
10     {
11         $articles = \App\Article::all();
12
13         return $articles->toJson();
14     }
15
16     public function store(Request $request)
17     {
18         $validatedData = $request->validate([
19             'title' => 'required',
20             'content' => 'required',
21         ]);
22
23         $project = \App\Article::create([
24             'title' => $validatedData['title'],
25             'content' => $validatedData['content'],
26         ]);
27
28         $msg = [
29             'success' => true,
30             'message' => 'Article created successfully!'
31         ];
32

```

Activate Windows  
Go to Settings to activate Windows.

```

33     return response()->json($msg);
34 }
35
36 public function getArticle($id) // for edit and show
37 {
38     $article = \App\Article::find($id);
39
40     return $article->toJson();
41 }
42
43 public function update(Request $request, $id)
44 {
45     $validatedData = $request->validate([
46         'title' => 'required',
47         'content' => 'required',
48     ]);
49
50     $article = \App\Article::find($id);
51     $article->title = $validatedData['title'];
52     $article->content = $validatedData['content'];
53     $article->save();
54
55     $msg = [
56         'success' => true,
57         'message' => 'Article updated successfully'
58     ];
59
60     return response()->json($msg);
61 }
62
63 public function delete($id)
64 {

```

Activate Windows  
Go to Settings to activate Windows.

```

60     return response()->json($msg);
61 }
62
63 public function delete($id)
64 {
65     $article = \App\Article::find($id);
66     if (!empty($article)) {
67         $article->delete();
68         $msg = [
69             'success' => true,
70             'message' => 'Article deleted successfully!'
71         ];
72         return response()->json($msg);
73     } else {
74         $msg = [
75             'success' => false,
76             'message' => 'Article deleted failed!'
77         ];
78         return response()->json($msg);
79     }
80 }
81 }
82

```

Jika Anda ingin menginstall package React Js, React Router Dom dan Sweet Alert, silahkan dimulai dari install package laravel ui dan laravel ui react berikut ini:

```

D:\data\Users\User\Documents\College\Framework Prog\framework_prog\13thWeek\hunayncrudlaravelreact>composer require laravel/ui "v2.0"
Warning from https://repo.packagist.org: You are using an outdated version of Composer. Composer 2 is now available and you should upgrade. See https://getcomposer.org/2
./composer.json has been updated
Loading composer repositories with package information
Warning from https://repo.packagist.org: You are using an outdated version of Composer. Composer 2 is now available and you should upgrade. See https://getcomposer.org/2
Updating dependencies (including require-dev)
Package operations: 1 install, 0 updates, 0 removals
 - Installing laravel/ui (v2.5.0): Downloading (100%)
Package fzaninotto/faker is abandoned, you should avoid using it. No replacement was suggested.
Package phpunit/php-token-stream is abandoned, you should avoid using it. No replacement was suggested.
Writing lock file
Generating optimized autoload files
> Illuminate\Foundation\ComposerScripts::postAutoloadDump
> @php artisan package:discover --ansi
Discovered Package: facade/ignition
Discovered Package: fideloper/proxy
Discovered Package: fruitcake/laravel-cors
Discovered Package: laravel/tinker
Discovered Package: laravel/ui
Discovered Package: nesbot/carbon
Discovered Package: nunomaduro/collision
Package manifest generated successfully.
66 packages you are using are looking for funding.
Use the `composer fund` command to find out more!
D:\data\Users\User\Documents\College\Framework Prog\framework_prog\13thWeek\hunayncrudlaravelreact>

```

Kemudian install react js:

```
D:\data\Users\User\Documents\College\Framework Prog\framework_prog\13thWeek\hunayncrudlaravelreact>php artisan ui react
React scaffolding installed successfully.
Please run "npm install && npm run dev" to compile your fresh scaffolding.

D:\data\Users\User\Documents\College\Framework Prog\framework_prog\13thWeek\hunayncrudlaravelreact>
```

Lalu install NodeJsnya:

```
C:\Windows\System32\cmd.exe
D:\data\Users\User\Documents\College\Framework Prog\framework_prog\13thWeek\hunayncrudlaravelreact>php artisan ui react
React scaffolding installed successfully.
Please run "npm install && npm run dev" to compile your fresh scaffolding.

D:\data\Users\User\Documents\College\Framework Prog\framework_prog\13thWeek\hunayncrudlaravelreact>npm install && npm run dev
npm WARN deprecated popper.js@1.16.1: You can find the new Popper v2 at @popperjs/core, this package is dedicated to the legacy v1
npm WARN deprecated chokidar@2.1.8: Chokidar 2 will break on node v14+. Upgrade to chokidar 3 with 15x less dependencies
npm WARN deprecated fsevents@1.2.13: fsevents 1 will break on node v14+ and could be using insecure binaries. Upgrade to fsevents 2.
npm WARN deprecated urix@0.1.0: Please see https://github.com/lydell/urix#deprecated
npm WARN deprecated resolve-url@0.2.1: https://github.com/lydell/resolve-url#deprecated
npm notice created a lockfile as package-lock.json. You should commit this file.
npm WARN optional SKIPPING OPTIONAL DEPENDENCY: fsevents@~1.2.7 (node_modules\chokidar\node_modules\fsevents):
npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: Unsupported platform for fsevents@1.2.13: wanted {"os":"darwin","arch":"any"} (current: {"os":"win32","arch":"x64"})
npm WARN optional SKIPPING OPTIONAL DEPENDENCY: fsevents@~2.3.1 (node_modules\watchpack\node_modules\chokidar\node_modules\fsevents):
npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: Unsupported platform for fsevents@2.3.2: wanted {"os":"darwin","arch":"any"} (current: {"os":"win32","arch":"x64"})
npm WARN optional SKIPPING OPTIONAL DEPENDENCY: fsevents@~2.3.1 (node_modules\sass\node_modules\chokidar\node_modules\fsevents):
npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: Unsupported platform for fsevents@2.3.2: wanted {"os":"darwin","arch":"any"} (current: {"os":"win32","arch":"x64"})

added 1129 packages from 500 contributors and audited 1133 packages in 57.034s

59 packages are looking for funding
  run npm fund for details

98% after emitting SizeLimitsPlugin

DONE Compiled successfully in 12386ms
11:44:18 AM

   Asset      Size  Chunks             Chunk Names
  /css/app.css 179 KiB  /js/app  [emitted]  /js/app
  /js/app.js   2 MiB  /js/app  [emitted]  /js/app

D:\data\Users\User\Documents\College\Framework Prog\framework_prog\13thWeek\hunayncrudlaravelreact>
```

Kemudian install react router dom nya:

```
D:\data\Users\User\Documents\College\Framework Prog\framework_prog\13thWeek\hunayncrudlaravelreact>npm install react-router-dom
npm WARN optional SKIPPING OPTIONAL DEPENDENCY: fsevents@1.2.13 (node_modules\fsevents):
npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: Unsupported platform for fsevents@1.2.13: wanted {"os":"darwin","arch":"any"} (current: {"os":"win32","arch":"x64"})
npm WARN optional SKIPPING OPTIONAL DEPENDENCY: fsevents@2.3.2 (node_modules\sass\node_modules\fsevents):
npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: Unsupported platform for fsevents@2.3.2: wanted {"os":"darwin","arch":"any"} (current: {"os":"win32","arch":"x64"})
npm WARN optional SKIPPING OPTIONAL DEPENDENCY: fsevents@2.3.2 (node_modules\watchpack\node_modules\fsevents):
npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: Unsupported platform for fsevents@2.3.2: wanted {"os":"darwin","arch":"any"} (current: {"os":"win32","arch":"x64"})

+ react-router-dom@5.2.0
added 11 packages from 6 contributors and audited 1144 packages in 11.302s

59 packages are looking for funding
  run `npm fund` for details

found 37 vulnerabilities (36 moderate, 1 high)
  run `npm audit fix` to fix them, or `npm audit` for details

D:\data\Users\User\Documents\College\Framework Prog\framework_prog\13thWeek\hunayncrudlaravelreact>
```

dan terakhir sweet alertnya:



```

D:\data\Users\User\Documents\College\Framework Prog\framework_prog\13thWeek\hunayncrudlaravelreact>npm i react-bootstrap-sweetalert
npm WARN optional SKIPPING OPTIONAL DEPENDENCY: fsevents@1.2.13 (node_modules\fsevents):
npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: Unsupported platform for fsevents@1.2.13: wanted {"os":"darwin","arch":"any"} (current: {"os":"win32","arch":"x64"})
npm WARN optional SKIPPING OPTIONAL DEPENDENCY: fsevents@2.3.2 (node_modules\sass\node_modules\fsevents):
npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: Unsupported platform for fsevents@2.3.2: wanted {"os":"darwin","arch":"any"} (current: {"os":"win32","arch":"x64"})
npm WARN optional SKIPPING OPTIONAL DEPENDENCY: fsevents@2.3.2 (node_modules\webpack\node_modules\fsevents):
npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: Unsupported platform for fsevents@2.3.2: wanted {"os":"darwin","arch":"any"} (current: {"os":"win32","arch":"x64"})

+ react-bootstrap-sweetalert@5.2.0
added 1 package from 1 contributor and audited 1145 packages in 12.137s

59 packages are looking for funding
  run `npm fund` for details

found 37 vulnerabilities (36 moderate, 1 high)
  run `npm audit fix` to fix them, or `npm audit` for details

D:\data\Users\User\Documents\College\Framework Prog\framework_prog\13thWeek\hunayncrudlaravelreact>

```

Buat file baru bernama App.js dan simpan di direktori resources/js/components.

```

resources > js > components > JS App.js
1  import React, { Component } from "react";
2  import ReactDOM from "react-dom";
3  import { BrowserRouter, Route, Switch } from "react-router-dom";
4  import Header from "../Header";
5  import ArticleIndex from "../ArticleIndex";
6  import ArticleCreate from "../ArticleCreate";
7  import ArticleShow from "../ArticleShow";
8  import ArticleEdit from "../ArticleEdit";
9
10 class App extends Component {
11   render() {
12     return (
13       <BrowserRouter>
14         <div>
15           <Header />
16           <Switch>
17             <Route exact path="/" component={ArticleIndex} />
18             <Route exact path="/create" component={ArticleCreate} />
19             <Route
20               path="/article/edit/:id"
21               component={ArticleEdit}
22             />
23             <Route path="/article/:id" component={ArticleShow} />
24           </Switch>
25         </div>
26       </BrowserRouter>
27     );
28   }
29 }
30
31 ReactDOM.render(<App />, document.getElementById("app"));
32

```

Activate Windows  
Go to Settings to activate Windows.

Buat lagi file baru bernama Header.js dan simpan di direktori resources/js/components.

```

resources > js > components > JS Header.js > ...
1  import React from "react";
2  import { Link } from "react-router-dom";
3
4  const Header = () => (
5    <nav className="navbar navbar-dark bg-dark">
6      <div className="container">
7        <Link className="navbar-brand" to="/">
8          Ilmu Coding
9        </Link>
10      </div>
11    </nav>
12  );
13
14 export default Header;
15

```

Buat lagi file baru bernama ArticleIndex.js dan simpan di direktori resources/js/components.



```
resources > js > components > JS ArticleIndex.js > ...
1 import axios from "axios";
2 import React, { Component } from "react";
3 import { Link } from "react-router-dom";
4 import SweetAlert from "react-bootstrap-sweetalert";
5
6 class ArticleIndex extends Component {
7   constructor() {
8     super();
9     this.state = {
10       articles: [],
11       msg: null,
12       type: null,
13       flash: false,
14       alert: null
15     };
16   }
17
18   hideAlert() {
19     this.setState({
20       alert: null
21     });
22   }
23
24   componentDidMount() {
25     axios.get("/api/articles").then(response => {
26       this.setState({
27         articles: response.data
28       });
29     });
30   }
31 }
```



Activate Windows

Buat lagi file baru bernama ArticleCreate.js dan simpan di direktori resources/js/components.

```
resources > js > components > JS ArticleCreate.js > ...
1 import axios from "axios";
2 import React, { Component } from "react";
3 import { Link } from "react-router-dom";
4 import SweetAlert from "react-bootstrap-sweetalert";
5
6 class ArticleCreate extends Component {
7   constructor(props) {
8     super(props);
9     this.state = {
10       title: "",
11       content: "",
12       alert: null,
13       errors: []
14     };
15     this.handleFieldChange = this.handleFieldChange.bind(this);
16     this.handleCreateNewArticle = this.handleCreateNewArticle.bind(this);
17     this.hasErrorFor = this.hasErrorFor.bind(this);
18     this.renderErrorFor = this.renderErrorFor.bind(this);
19   }
20
21   handleFieldChange(event) {
22     this.setState({
23       [event.target.name]: event.target.value
24     });
25   }
26
27   goToHome() {
28     const getAlert = () => (
29       <SweetAlert
30         success
31         title="Success!"
32         onConfirm={() => this.onSuccess()}

```



Activate Windows  
Go to Settings to activate Windows.

Buat lagi file baru bernama ArticleEdit.js dan simpan di direktori resources/js/components.

resources > js > components > JS ArticleEdit.js > ...

```
1 import axios from "axios";
2 import React, { Component } from "react";
3 import { Link } from "react-router-dom";
4 import SweetAlert from "react-bootstrap-sweetalert";
5
6 class ArticleEdit extends Component {
7   constructor(props) {
8     super(props);
9     this.state = {
10       title: "",
11       content: "",
12       alert: null,
13       message: "",
14       errors: []
15     };
16     this.handleFieldChange = this.handleFieldChange.bind(this);
17     this.handleUpdateArticle = this.handleUpdateArticle.bind(this);
18     this.hasErrorFor = this.hasErrorFor.bind(this);
19     this.renderErrorFor = this.renderErrorFor.bind(this);
20   }
21
22   handleFieldChange(event) {
23     this.setState({
24       [event.target.name]: event.target.value
25     });
26   }
27
28   componentDidMount() {
29     const articleId = this.props.match.params.id;
30
31     axios.get(`/api/article/edit/${articleId}`).then(response => {
32       this.setState({
```

Activate Windows  
Go to Settings to activate Windows.

Buat lagi file baru bernama ArticleShow.js dan simpan di direktori resources/js/components.

resources > js > components > JS ArticleShow.js > ...

```
1 import axios from "axios";
2 import React, { Component } from "react";
3 import { Link } from "react-router-dom";
4
5 class ArticleShow extends Component {
6   constructor(props) {
7     super(props);
8     this.state = {
9       article: {}
10     };
11   }
12
13   componentDidMount() {
14     const articleId = this.props.match.params.id;
15
16     axios.get(`/api/article/${articleId}`).then(response => {
17       this.setState({
18         article: response.data
19       });
20     });
21   }
22
23   render() {
24     const { article } = this.state;
25
26     return (
27       <div className="container py-4">
28         <div className="row justify-content-center">
29           <div className="col-md-8">
30             <div className="card">
31               <div className="card-header">
32                 Judul Artikel: {article.title}
```

Activate Windows  
Go to Settings to activate Windows.

Buat file baru bernama app.blade.php dan simpan di direktori resource/views.

```
resources > views > app.blade.php > html
1 <!DOCTYPE html>
2 <html lang="{{ app()->getLocale() }}">
3
4 <head>
5     <meta charset="utf-8">
6     <meta http-equiv="X-UA-Compatible" content="IE=edge">
7     <meta name="viewport" content="width=device-width, initial-scale=1">
8
9     <!-- CSRF Token -->
10    <meta name="csrf-token" content="{{ csrf_token() }}">
11
12    <title>React Laravel</title>
13
14    <!-- Styles -->
15    <link href="{{ asset('css/app.css') }}" rel="stylesheet">
16 </head>
17
18 <body>
19     <div id="app"></div>
20
21     <script src="{{ asset('js/app.js') }}"></script>
22 </body>
23
24 </html>
```

Silahkan buka file resources/js/app.js kemudian ubah source code menjadi seperti di bawah ini

```
9 /**
10  * Next, we will create a fresh React component instance and attach it to
11  * the page. Then, you may begin adding components to this application
12  * or customize the JavaScript scaffolding to fit your unique needs.
13  */
14
15 require(["./components/App"]);
16
```

Fungsinya agar antara file resources/js/app.js dan resources/js/components/App.js terhubung.

Ketik command berikut untuk menginstall perubahan yang terjadi:

```
C:\Windows\System32\cmd.exe
D:\data\Users\User\Documents\College\Framework Prog\framework_prog\13thWeek\hunayncrudlaravelreact>npm run dev
> @ dev D:\data\Users\User\Documents\College\Framework Prog\framework_prog\13thWeek\hunayncrudlaravelreact
> npm run development

> @ development D:\data\Users\User\Documents\College\Framework Prog\framework_prog\13thWeek\hunayncrudlaravelreact
> cross-env NODE_ENV=development node_modules\webpack\bin\webpack.js --progress --hide-modules --config=node_modules\laravel-mix\setup\webpack.config.js

13% building 25/29 modules 4 active ...velreact\node_modules\@babel\runtime\helpers\esm\objectWithoutPropertiesLoose.jsD
DEPRECATION WARNING: Using / for division is deprecated and will be removed in Dart Sass 2.0.0.

Recommendation: math.div($spacer, 2)

More info and automated migrator: https://sass-lang.com/d/slash-div

302 | $headings-margin-bottom:      $spacer / 2 !default;
    |                               ^^^^^^^^^^^
    |_
node_modules\bootstrap\scss\_variables.scss 302:31  @import
node_modules\bootstrap\scss\bootstrap.scss 9:9     @import
stdin 8:9                                          root stylesheet

DEPRECATION WARNING: Using / for division is deprecated and will be removed in Dart Sass 2.0.0.

Recommendation: math.div($input-padding-y, 2)

More info and automated migrator: https://sass-lang.com/d/slash-div

98% after emitting SizeLimitsPlugin

DONE Compiled successfully in 14349ms 12:02:08 PM


  Asset      Size  Chunks  Chunk Names
  /css/app.css 179 KiB  /js/app  [emitted]  /js/app
  /js/app.js  2.26 MiB  /js/app  [emitted]  /js/app

D:\data\Users\User\Documents\College\Framework Prog\framework_prog\13thWeek\hunayncrudlaravelreact>
```


Kemudian ketik command berikut:

```
D:\data\Users\User\Documents\College\Framework Prog\framework_prog\13thWeek\hunayncrudlaravelreact>php artisan serve
laravel development server started: http://127.0.0.1:8000
[Mon May 24 12:04:07 2021] PHP 7.4.9 Development Server (http://127.0.0.1:8000) started
```



Ketikkan localhost:8000 pada url browser maka project akan running



Tampilan pada localhost:8000/create yaitu menampilkan form untuk add data



## Data telah berhasil ditambahkan



Link GitHub : [https://github.com/hunaynr/framework\\_prog/tree/main/13thWeek](https://github.com/hunaynr/framework_prog/tree/main/13thWeek)

Link Youtube : <https://youtu.be/a9Xloep3yPQ>



