Available online at www.sciencedirect.com

ScienceDirect

Procedia Computer Science 00 (2026) 000–000

Procedia Computer Science

www.elsevier.com/locate/procedia

30th International Conference on Knowledge-Based and Intelligent Information & Engineering Systems (KES 2026)

EviR: Evidence-Guided Query Reformulation for Temporally Grounded VideoQA

Tan-Hung Nguyen[a,b], Gia-Hao Tran[a,b], Thanh Le[a,b,*]

[a] *Faculty of Information Technology, University of Science, Ho Chi Minh City, Vietnam*
[b] *Vietnam National University, Ho Chi Minh City, Vietnam*

Abstract

Grounded Video Question Answering (VideoQA) requires models to both predict correct answers and localize the temporal evidence supporting them. While recent advances in multimodal video reasoning have improved these capabilities, most existing methods assume that answer candidates can be directly used as retrieval queries. This assumption is often violated in multiple-choice grounded VideoQA, where answer candidates are abstract, incomplete, or poorly aligned with observable events. To address this limitation, we propose *EviR*, an evidence-guided framework that decomposes grounded VideoQA into query reformulation, temporal retrieval, evidence validation, and answer generation. EviR rewrites answer candidates into retrieval-friendly queries, retrieves candidate temporal spans, ranks them by evidence reliability, and predicts answers based on the most reliable evidence clip. Experiments on NExT-GQA and ReXTime demonstrate that EviR consistently improves performance under grounding-aware evaluation, improving IoU@0.5 by 5.77 and Acc@IoU=0.5 by 7.05 over the current state-of-the-art method, while maintaining comparable answer accuracy. These results highlight the importance of aligning answer formulation with temporal evidence retrieval for reliable grounded video reasoning.

© 2026 The Authors. Published by Elsevier B.V.
This is an open access article under the CC BY-NC-ND license (http://creativecommons.org/licenses/by-nc-nd/4.0/)
Peer-review under responsibility of the scientific committee of the KES International.

Keywords: Temporal video grounding; Grounded video question answering; Multimodal large language models; Video reasoning

1. Introduction

Reliable grounded VideoQA depends not only on predicting the correct answer, but also on identifying the temporal evidence that truly supports it. This requirement is central to grounded video understanding because answer correctness alone does not guarantee that a prediction is visually substantiated. *NExT-GQA* shows that strong answer accuracy can still arise from weak evidence alignment [1], while *ReXTime* further demonstrates that the required evidence may be temporally displaced from the question context, making grounded reasoning substantially harder [2].

* Corresponding author.
E-mail address: lnthanh@fit.hcmus.edu.vn (Thanh Le).

1877-0509 © 2026 The Authors. Published by Elsevier B.V.
This is an open access article under the CC BY-NC-ND license (http://creativecommons.org/licenses/by-nc-nd/4.0/)
Peer-review under responsibility of the scientific committee of the KES International.

These observations suggest that reliable grounded VideoQA depends not only on reasoning ability, but also on how effectively answer-relevant evidence is acquired and verified.

Recent Multimodal Large Language Models (MLLMs) have substantially improved video understanding [3, 4]. In temporal grounding, *VTimeLLM* enhances timestamp-sensitive modeling [5], *TimeChat* strengthens long-video temporal perception [6], and *Grounded-VideoLLM* improves fine-grained grounding through grounding-oriented training and architectural design [7]. In video reasoning, *SeViLA* decomposes answering into localization and language reasoning [8], *LLoVi* studies efficient long-range VideoQA with modular processing [9], and *VideoMind* introduces a role-based workflow with specialized planner, grounder, verifier, and answerer modules [10]. These methods show that temporal modeling and role specialization are effective design principles. However, they still leave a key challenge underexplored in grounded multiple-choice VideoQA. The language available for answer prediction is often not the language needed for temporal evidence retrieval.

The central hypothesis of this work is that grounded VideoQA benefits from explicitly separating *answer discrimination* from *evidence retrieval*. In multiple-choice VideoQA, answer candidates are written to distinguish options, not to describe visually localizable events. They are therefore often abstract, incomplete, or weakly visual. By contrast, temporal grounding requires retrieval queries that expose observable evidence. Directly grounding raw answer candidates can therefore produce segments that are temporally nearby but semantically weak, noisy, or only partially aligned with the evidence needed for answering. This mismatch is particularly harmful on benchmarks such as *NExT-GQA* and *ReXTime*, where prediction quality is evaluated together with evidence quality [1, 2].

This paper presents *EviR*, a modular framework for temporally grounded VideoQA that separates *evidence reformulation*, *evidence acquisition*, *evidence validation*, and *answer generation*. In the current multiple-choice instantiation, a Refiner rewrites each answer candidate into a grounding-friendly query, a Retriever localizes candidate temporal spans, a Validator scores and ranks the retrieved candidates by evidence reliability, and a Generator predicts the final answer from the highest-ranked evidence clip. This design follows the view that grounded answer prediction should be built on explicit evidence quality control rather than on direct end-to-end generation from the full video.

Evaluation on *NExT-GQA* and *ReXTime* shows that this design consistently improves strict grounding-aware metrics. EviR improves IoU@0.5 by 5.77 over the strongest prior baseline on *NExT-GQA* and improves Acc@IoU=0.5 by 7.05 on *ReXTime*, while also achieving the best or comparable answer accuracy. These results support the hypothesis that better alignment between answer formulation and temporal retrieval leads to more reliable grounded reasoning.

The main contributions are summarized below.

- A key mismatch in grounded VideoQA is identified between language formulation and temporal evidence retrieval. On current multiple-choice benchmarks, answer candidates are useful for discrimination but often unsuitable for evidence localization.
- *EviR* is presented as a modular framework that resolves this mismatch through evidence-guided query reformulation, temporal retrieval, explicit evidence validation, and grounded answer generation.
- Strong results are achieved on *NExT-GQA* and *ReXTime*, showing that improving evidence quality leads to more accurate and more reliable grounded VideoQA under strict grounding-aware evaluation.

The remainder of this paper is organized as follows. Section 2 reviews related work on temporal grounding, grounded VideoQA, and modular video reasoning. Section 3 presents the EviR framework and its components. Section 4 describes the experimental setup and reports the main results and ablations. Section 5 concludes the paper and discusses future directions.

2. Related Work

2.1. Temporal Video Grounding

Video Temporal Grounding (VTG) aims to localize the temporal segment in a video that corresponds to a language query. Recent progress in VTG increasingly leverages multimodal large language models (MLLMs), shifting from task-specific localization pipelines toward more unified video-language frameworks [4]. Representative methods such as VTimeLLM [5], TimeChat [6], and LITA [11] improve timestamp sensitivity, temporal representation,

and localization-oriented instruction tuning for video understanding. Grounded-VideoLLM further strengthens fine-grained localization through grounding-oriented architectural design and multi-stage training [7].

Beyond supervised grounding, training-free and post-training paradigms have also shown promising results. Training-free VTG methods demonstrate that large pre-trained models already contain useful temporal reasoning priors [12–14], while more recent approaches such as Time-R1 and TimeLens highlight the importance of grounding-specific post-training, stronger data curation, and more reliable optimization for precise temporal localization [15, 16]. Overall, these works substantially improve the ability of MLLMs to localize relevant temporal moments. However, they mainly study VTG in the conventional query-to-moment setting. In contrast, our work focuses on *multiple-choice grounded VideoQA*, where the input answer candidates are not naturally written as retrieval-friendly grounding queries, creating an additional mismatch between answer formulation and temporal evidence acquisition.

2.2. Grounded and Reasoning VideoQA

Conventional VideoQA primarily evaluates answer correctness, often without requiring the model to identify the evidence supporting its prediction. This limitation has motivated grounded VideoQA, where correct answering must be accompanied by faithful temporal evidence [1]. NExT-GQA is a representative benchmark in this direction, showing that strong answer accuracy does not necessarily imply grounded reasoning [1]. ReXTime complements this setting by emphasizing reasoning across time, where the evidence needed for answering may appear in a different temporal region from the question context [2]. More broadly, recent empirical studies in the LLM era also suggest that answer accuracy alone is insufficient for assessing genuine video understanding [17].

Several recent works attempt to connect temporal localization and answer prediction more explicitly. SeViLA decomposes the task into localization and answering stages, reducing reliance on dense temporal annotations through self-refinement [8]. For long-video reasoning, LLoVi, LangRepo, and VideoStreaming show that staged language-centric processing, memory-like representations, and streaming mechanisms can improve reasoning over temporally extended videos [9, 18, 19]. More recently, VideoExpert and VideoMind demonstrate that stronger temporal grounding and role specialization can further benefit grounded reasoning, especially in long-form and temporally complex settings [10, 20].

Our work is most closely related to this line of grounded reasoning methods, but differs in its task-specific focus. Existing approaches typically connect localization and answering more directly, whereas we target a distinct bottleneck in *multiple-choice* grounded VideoQA: answer options are designed for discrimination rather than temporal evidence retrieval. To address this mismatch, we explicitly introduce a refinement stage to transform answer candidates into retrieval-friendly queries and a validation stage to score and rank retrieved evidence before final answer generation.

3. Method

3.1. Overview

Given a video V, a question q, and a set of answer candidates $O = \{o_i\}_{i=1}^{N}$, temporally grounded VideoQA aims to predict not only the correct answer $\hat{y}$ but also the temporal evidence $\hat{s}$ that supports the prediction [1, 2]. In the current benchmark setting studied in this paper, the answer space is multiple-choice. EviR addresses a key mismatch in grounded VideoQA: the available language input for answering is written for discrimination, while temporal retrieval requires evidence-oriented queries. To bridge this gap, *EviR* decomposes the pipeline into four components: a *Refiner*, a *Retriever*, a *Validator*, and a *Generator*.

For each answer candidate, the Refiner first rewrites it into a grounding-friendly query. The Retriever then localizes top-K candidate temporal spans for each refined query. Next, the Validator evaluates all retrieved clips and assigns them validation scores. Finally, the Generator predicts the answer conditioned on the highest-ranked evidence rather than the entire video. In EviR, this decomposition separates evidence acquisition from evidence validation and answer generation, allowing each component to focus on a dedicated role. Although the present implementation is answer-candidate driven, the same framework structure can be extended to other grounded VideoQA settings by replacing the reformulation input.

3.2. Refiner

A key challenge in multiple-choice grounded VideoQA is that raw answer candidates are often not ideal temporal retrieval queries. They are typically written for answer discrimination rather than evidence localization, and may be too abstract, incomplete, or weakly visual to retrieve the correct temporal segment. This issue is particularly severe in grounded VideoQA, where answer correctness depends on accurate evidence localization [1, 2].

To address this problem, we introduce a query refinement stage. Given a question q and an answer candidate o_i, we use Gemini 2.5 Flash to rewrite the candidate into a grounding-friendly query:

$$r_i = \mathcal{F}_{\text{ref}}(q, o_i). \tag{1}$$

The goal of this step is to preserve the semantics of the answer candidate while making the underlying visual evidence more explicit. In practice, the Refiner transforms answer candidates from decision-oriented text into retrieval-oriented text, enabling the downstream Retriever to focus on visually localizable events rather than abstract answer semantics.

This design is especially helpful for causal and reasoning-across-time questions. In such cases, an answer candidate may refer to an inferred event or a temporally displaced consequence rather than a directly observable moment. Query refinement helps expose the visual evidence that should be retrieved before final answer generation. The Refiner is used as an off-the-shelf query rewriting module and is not further trained in our framework. The Refiner is a modular component and can be replaced by other LLMs.

3.3. Retriever

Given a refined query r_i, the Retriever localizes the top-K candidate temporal spans

$$\{s_{i,k}\}_{k=1}^{K} = \mathcal{F}_{\text{ret}}(V, r_i), \tag{2}$$

where each candidate span is represented as

$$s_{i,k} = [t_{i,k}^{s}, t_{i,k}^{e}], \tag{3}$$

with $t_{i,k}^{s}$ and $t_{i,k}^{e}$ denoting the predicted start and end timestamps. The corresponding retrieved clips are denoted by

$$c_{i,k} = V[s_{i,k}], \qquad k = 1, \ldots, K. \tag{4}$$

In our framework, the Retriever is initialized from Qwen3-VL-8B and fine-tuned for video temporal grounding on the TimeLens-100K dataset [16]. Following TimeLens, temporal information is injected through *interleaved textual timestamp encoding*, where timestamps are inserted as text tokens alongside the visual sequence. This design improves alignment between language queries and temporally grounded visual evidence.

The Retriever is trained with a three-stage pipeline. First, a supervised fine-tuning (SFT) warm-start is performed on 30K sampled instances from TimeLens-100K to initialize temporal grounding ability. Second, the SFT checkpoint is used to run offline inference on the full TimeLens-100K set, and the predicted spans are filtered according to temporal overlap quality. Third, the model is further optimized with GRPO under a thinking-free RLVR paradigm, where the reward is defined based on temporal localization quality. This training strategy improves the precision and reliability of temporal span prediction.

In our setting, the Retriever is applied to the refined queries produced from the answer candidates. For each refined query r_i, it returns candidate temporal spans that may serve as supporting evidence for answering the question. This design allows retrieval to operate on evidence-oriented reformulations rather than raw answer options, thereby improving the compatibility between temporal grounding and multiple-choice grounded VideoQA.

3.4. Validator

The Retriever returns a set of candidate evidence clips, but not every retrieved candidate is equally reliable for grounded reasoning. In grounded VideoQA, a candidate segment may be temporally close to the target event while still being weakly informative, noisy, or only partially aligned with the evidence required to answer the question. To improve the reliability of downstream reasoning, we introduce a *Validator* that verifies the retrieved candidates and assigns each one a score indicating how likely it is to serve as faithful evidence.

We denote the pool of candidate clips returned by the Retriever as

$$C = \{c_{i,k} \mid i = 1, \ldots, N;\ k = 1, \ldots, K\}, \tag{5}$$

where $c_{i,k}$ denotes the k-th candidate clip associated with the i-th query. Given a question q, the Validator assigns each candidate clip a validation score

$$\alpha_{i,k} = \mathcal{F}_{\text{val}}(q, c_{i,k}), \tag{6}$$

which measures how likely the candidate is to constitute faithful evidence for answering q. These scores induce a ranking over all retrieved candidates, which is then used by the Generator.

Our Validator follows the **verifier** design of VideoMind [10]. For each candidate clip, we adopt a *zoom-in* strategy by expanding its temporal boundaries by 50% on both sides and cropping the enlarged segment as input. Two special tokens, `<SEG-START>` and `<SEG-END>`, are inserted at the temporal positions corresponding to the original candidate boundaries, allowing the model to distinguish the hypothesized evidence span from its surrounding temporal context [10].

We formulate validation as a binary verification task. During training, each candidate is assigned a binary label according to its temporal overlap with the annotated evidence span: candidates with Intersection-over-Union (IoU) greater than 0.5 are treated as positive, and the others as negative, following [10]. The Validator is then fine-tuned to predict whether the highlighted segment should be accepted (`Yes`) or rejected (`No`) as valid evidence for the question.

During inference, for each candidate clip, we compute the logits of the `<Yes>` and `<No>` tokens under teacher forcing, denoted by L_y and L_n, respectively. The validation score is defined as

$$\alpha_{i,k} = \sigma(L_y - L_n), \tag{7}$$

where $\sigma(\cdot)$ is the sigmoid function. The resulting scores are used to rank all candidates before generation.

This validation stage is particularly important in grounded VideoQA, where answer prediction should rely on faithful evidence rather than merely plausible temporal proximity. By explicitly validating retrieved candidates before downstream reasoning, the Validator helps reduce the effect of near-miss retrievals and improves the robustness of grounded prediction [1, 10].

However, validation alone does not uniquely determine the correct answer. In practice, multiple answer candidates may correspond to visually similar or temporally overlapping events, making the evidence–answer alignment ambiguous. The highest-ranked clip therefore serves as grounded evidence for the subsequent Generator, which performs the final semantic reasoning over the candidate answers.

3.5. Generator

After validation, the Generator takes the highest-ranked evidence clip

$$\tilde{c} = c_{i^*,k^*}, \qquad (i^*, k^*) = \arg\max_{i,k} \alpha_{i,k}, \tag{8}$$

and predicts the final answer conditioned on the question, the answer candidates, and this selected evidence:

$$\hat{y} = \mathcal{F}_{\text{gen}}(q, \mathcal{O}, \tilde{c}). \tag{9}$$

While the Validator ranks the retrieved candidates by reliability, evidence ranking alone is not sufficient for final answer prediction. In grounded multiple-choice VideoQA, multiple answer candidates may correspond to visually similar or temporally overlapping events, so the highest-ranked evidence does not always map uniquely to a single answer option. The role of the Generator is therefore to resolve this ambiguity by performing semantic reasoning over the selected evidence together with the question and the candidate answers.

In our implementation, the Generator is based on **Qwen2-VL** [21] and is used without additional task-specific training. Unlike the Retriever and Validator, which are explicitly optimized for evidence acquisition and evidence validation, respectively, the Generator serves as the final multimodal reasoning module. Conditioning the Generator on the highest-ranked evidence rather than the full video encourages grounded prediction and reduces distraction from irrelevant visual context, which is particularly important for long-video reasoning and grounded VideoQA [1, 10].

4. Experiments

4.1. Experimental Setup

Benchmarks. We evaluate our framework on two temporally grounded VideoQA benchmarks, **NExT-GQA** [1] and **ReXTime** [2]. NExT-GQA emphasizes visually grounded answering, requiring the model to predict the correct answer while localizing the supporting temporal evidence [1]. ReXTime focuses on reasoning across time, where the evidence required for answering may lie in a temporal region different from that implied by the question context [2].

Evaluation metrics. For NExT-GQA, following prior work [1, 10], we report both IoP-based and IoU-based grounding metrics, including mIoP, IoP@0.3, IoP@0.5, mIoU, IoU@0.3, and IoU@0.5, together with Acc@GQA (IoP>0.5) and Acc@QA. For ReXTime, following the benchmark protocol [2], we report R@0.3, R@0.5, mIoU, Acc, and Acc@IoU=0.5.

Baselines. On NExT-GQA, we compare against representative grounded or temporally aware VideoQA methods, including FrozenBiLMNG+ [22], VTimeLLM [5], SeViLA [8], LangRepo [18], VideoStreaming [19], Grounded-VideoLLM [7], VideoExpert [20], VideoChat-TPO [23], LLoVi [9], HawkEye [24], DeVi [25], and VideoMind [10]. On ReXTime, we compare against VTimeLLM [5], TimeChat [6], LITA [11], and VideoMind [10]. Unless otherwise noted, all baseline results are taken from the corresponding original papers.

Implementation details. EviR consists of four modules: a Refiner, a Retriever, a Validator, and a Generator. The Refiner uses Gemini 2.5 Flash and is applied without additional training. The Retriever is initialized from Qwen3-VL-8B and fine-tuned on TimeLens-100K with a three-stage training pipeline consisting of SFT warm-start, offline filtering, and GRPO-based optimization. The Validator is built on Qwen2-VL-7B and trained with LoRA-based supervised fine-tuning following the verifier design of VideoMind [10]. The Generator is implemented with Qwen2-VL [21] and is used without additional fine-tuning. In all experiments, we set $K = 2$, where the Retriever generates two candidate temporal spans for each refined query, the Validator scores and ranks these candidates, and the Generator receives the highest-ranked clip for downstream reasoning. Table 1 summarizes the training configuration of the trainable modules.

Table 1. Training configuration of the trainable modules in our framework.

Module	Backbone	Training data	Training strategy
Retriever	Qwen3-VL-8B	TimeLens-100K	SFT → Filter → GRPO
Validator	Qwen2-VL-7B	DiDeMo, TACoS, QVHighlights	LoRA-based SFT

Table 2. Results on NExT-GQA. PT denotes trained/pretrained models, and TF denotes training-free models. Best results are in bold.

Method	Paradigm	mIoP	IoP@0.3	IoP@0.5	mIoU	IoU@0.3	IoU@0.5	Acc@GQA	Acc@QA
FrozenBiLMNG+ [22]	PT	24.2	28.5	23.7	9.6	13.5	6.1	17.5	70.8
VTimeLLM [5]	PT	27.9	30.3	23.8	18.3	27.7	14.1	12.7	–
SeViLA [8]	PT	29.5	34.7	22.9	21.7	29.2	13.8	16.6	68.1
LangRepo [18]	PT	31.3	–	28.7	18.5	–	12.2	17.1	–
VideoStreaming [19]	–	32.2	–	31.0	19.3	–	13.3	17.8	–
Grounded-VideoLLM [7]	PT	34.5	42.6	34.4	21.1	30.2	18.0	26.7	–
VideoExpert [20]	PT	34.6	45.3	29.3	27.9	41.0	22.4	21.6	71.1
VideoChat-TPO [23]	PT	35.6	47.5	32.8	27.7	41.2	23.4	25.5	–
LLoVi [9]	PT	37.3	–	36.9	20.0	–	15.3	24.3	–
HawkEye [24]	PT	–	–	–	25.7	37.0	19.5	–	–
DeVi [25]	TF	39.7	–	38.9	23.6	–	19.5	28.9	73.1
VideoMind [10]	PT	39.0	**56.0**	35.3	31.4	**50.2**	25.8	28.2	76.9
Ours	PT	**41.76**	54.13	**39.02**	**34.86**	49.88	**31.57**	**31.05**	**77.0**

Table 3. Results on ReXTime. FT indicates the fine-tuned setting reported by prior work. Best results are in bold.

Method	Size	FT	R@0.3	R@0.5	mIoU	Acc	Acc@IoU=0.5
VTimeLLM [5]	7B	✓	43.69	26.13	29.92	57.58	17.13
TimeChat [6]	7B	✓	40.13	21.42	26.29	49.46	10.92
VTimeLLM [5]	7B	–	28.84	17.41	20.14	36.16	–
TimeChat [6]	7B	–	14.42	7.61	11.65	40.04	–
LITA [11]	13B	–	29.49	16.29	21.49	34.44	–
VideoMind [10]	7B	–	38.22	25.52	27.61	**74.59**	20.20
Ours	8B	–	**46.91**	**35.94**	**36.99**	**74.59**	**27.25**

4.2. Main Results

As shown in Table 2, our method achieves the best overall performance among the compared methods on NExT-GQA, with particularly clear gains on strict grounding-aware metrics. Specifically, compared with the strongest prior baseline, VideoMind [10], our method improves mIoU by 3.46%, IoU@0.5 by 5.77%, and Acc@GQA by 2.85%, while also achieving the best mIoP and IoP@0.5.

A notable pattern is that our method performs slightly below VideoMind on the looser thresholds IoP@0.3 and IoU@0.3, but consistently outperforms it on the stricter thresholds IoP@0.5 and IoU@0.5. This suggests that the proposed framework improves precise temporal localization rather than only coarse overlap. Since NExT-GQA explicitly evaluates whether predicted answers are supported by correct temporal evidence [1], these results indicate better alignment between answer prediction and grounded temporal evidence.

As shown in Table 3, our method delivers the best grounding performance among the compared methods on ReXTime, achieving the highest R@0.3, R@0.5, and mIoU, while matching the best answer accuracy. In particular, compared with VideoMind [10], our method improves mIoU by 9.38% and Acc@IoU=0.5 by 7.05%.

This result is especially important on ReXTime, where answering correctly requires identifying temporally displaced evidence [2]. In this setting, answer accuracy alone is insufficient; the model must also retrieve the correct answer-supporting span. The gains on both retrieval metrics and Acc@IoU=0.5 therefore suggest that our framework is more effective at linking answer-relevant temporal evidence to final predictions. Taken together, the results on NExT-GQA and ReXTime show that our method is particularly effective under strict grounding-aware evaluation, where answer correctness and evidence quality must be satisfied jointly.

4.3. Ablation Study

We conduct ablations on ReXTime [2], which offers a particularly discriminative testbed due to its reasoning-across-time nature. Table 4 compares three variants: a Generator-only baseline, a Retriever–Validator–Generator pipeline without the Refiner, and the full model.

Table 4. Ablation results on ReXTime. Ref, Ret, Val, and Gen denote Refiner, Retriever, Validator, and Generator, respectively. The Generator-only variant does not produce temporal evidence spans, so grounding metrics are not reported.

Ref	Ret	Val	Gen	R@0.3	R@0.5	mIoU	Acc	Acc@IoU=0.5
–	–	–	✓	–	–	–	68.00	–
–	✓	✓	✓	33.01	25.19	27.17	73.24	19.22
✓	✓	✓	–	46.91	35.94	36.99	32.68	18.68
✓	✓	✓	✓	46.91	35.94	36.99	74.59	27.25

As shown in Table 4, the ablation study yields two clear observations. First, introducing explicit evidence retrieval and selection already provides a strong improvement over direct generation, raising answer accuracy from 68.00 to 73.24. This indicates that ReXTime cannot be solved reliably by generation alone, since correct answers often depend on evidence located at temporally displaced moments.

Second, the Refiner brings an additional and consistent gain across all reported metrics. Relative to the Retriever–Validator–Generator variant, the full model improves R@0.3 by 13.90%, R@0.5 by 10.75%, mIoU by 9.82%, and Acc@IoU=0.5 by 8.03%, while also increasing Acc from 73.24% to 74.59%. These results suggest that the Refiner improves the quality of the evidence supplied to downstream modules, resulting in more precise temporal grounding and stronger grounded question answering.

Overall, the ablation study confirms that the effectiveness of the full framework does not arise from generation alone, but from progressively improving evidence quality through the Refiner–Retriever–Validator–Generator pipeline.

5. Conclusion

In this paper, we propose *EviR*, a modular framework for temporally grounded VideoQA consisting of four components: a Refiner, a Retriever, a Validator, and a Generator. The framework is motivated by the observation that reliable grounded answer prediction depends not only on strong reasoning ability, but also on the quality of the temporal evidence provided to the final answer generator. In the present multiple-choice formulation, EviR uses the Refiner to rewrite answer candidates into grounding-friendly queries, then uses the Retriever to localize candidate evidence spans, the Validator to score and rank the retrieved evidence, and the Generator to produce the final answer based on the highest-ranked clip.

Experimental results on NExT-GQA and ReXTime show that our framework improves both temporal grounding quality and grounded question answering accuracy. In particular, the gains on stricter grounding-aware metrics indicate that the proposed pipeline is effective at producing more precise and reliable evidence, rather than merely retrieving roughly relevant moments. Our analysis further suggests that answer-aware refinement, explicit evidence selection, and evidence-conditioned generation all play important roles in achieving robust reasoning across time.

Overall, our findings show that temporally grounded VideoQA benefits from explicitly separating evidence refinement, retrieval, validation, and generation. Future work can extend EviR beyond multiple-choice supervision to question-only or open-ended settings, as well as to multi-span reasoning and more challenging long-form video scenarios where evidence may be sparse, compositional, or temporally distant.

Acknowledgements

We would like to thank our advisor for their guidance and support, as well as our team members for their collaboration and valuable discussions.

References

[1] J. Xiao, A. Yao, Y. Li, T.-S. Chua, Can i trust your answer? visually grounded video question answering, in: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, 2024, pp. 13204–13214.

[2] J.-J. Chen, Y.-C. Liao, H.-C. Lin, Y.-C. Yu, Y.-C. Chen, Y.-C. F. Wang, Rextime: A benchmark suite for reasoning-across-time in videos, Advances in Neural Information Processing Systems 37 (2024) 28662–28673.

[3] Y. Tang, J. Bi, S. Xu, L. Song, S. Liang, T. Wang, D. Zhang, J. An, J. Lin, R. Zhu, et al., Video understanding with large language models: A survey, IEEE Transactions on Circuits and Systems for Video Technology (2025).

[4] J. Wu, W. Liu, Y. Liu, M. Liu, L. Nie, Z. Lin, C. W. Chen, A survey on video temporal grounding with multimodal large language model, IEEE Transactions on Pattern Analysis and Machine Intelligence 48 (2) (2026) 1521–1541. doi:10.1109/TPAMI.2025.3615586.

[5] B. Huang, X. Wang, H. Chen, Z. Song, W. Zhu, Vtimellm: Empower llm to grasp video moments, in: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), 2024, pp. 14271–14280.

[6] S. Ren, L. Yao, S. Li, X. Sun, L. Hou, Timechat: A time-sensitive multimodal large language model for long video understanding, in: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, 2024, pp. 14313–14323.

[7] H. Wang, Z. Xu, Y. Cheng, S. Diao, Y. Zhou, Y. Cao, Q. Wang, W. Ge, L. Huang, Grounded-videollm: Sharpening fine-grained temporal grounding in video large language models, in: Findings of the Association for Computational Linguistics: EMNLP 2025, Association for Computational Linguistics, Suzhou, China, 2025, pp. 959–975. doi:10.18653/v1/2025.findings-emnlp.50.

[8] S. Yu, J. Cho, P. Yadav, M. Bansal, Self-chained image-language model for video localization and question answering, in: Advances in Neural Information Processing Systems 36 (NeurIPS 2023), Curran Associates, Inc., 2023, pp. 76749–76771.

[9] C. Zhang, T. Lu, M. M. Islam, Z. Wang, S. Yu, M. Bansal, G. Bertasius, A simple llm framework for long-range video question-answering, in: Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing, 2024, pp. 21715–21737.

[10] Y. Liu, K. Q. Lin, C. W. Chen, M. Z. Shou, Videomind: A chain-of-lora agent for temporal-grounded video reasoning, in: The Thirteenth International Conference on Learning Representations (ICLR), 2026.
URL https://openreview.net/forum?id=57EwidOnSf

[11] D.-A. Huang, S. Liao, S. Radhakrishnan, H. Yin, P. Molchanov, Z. Yu, J. Kautz, Lita: Language instructed temporal-localization assistant, in: Computer Vision – ECCV 2024, Vol. 15122 of Lecture Notes in Computer Science, Springer, 2024, pp. 202–218.

[12] M. Zheng, X. Cai, Q. Chen, Y. Peng, Y. Liu, Training-free video temporal grounding using large-scale pre-trained models, in: European Conference on Computer Vision, Springer, 2024, pp. 20–37.

[13] Y. Xu, Y. Sun, B. Zhai, M. Li, W. Liang, Y. Li, S. Du, Zero-shot video moment retrieval via off-the-shelf multimodal large language models, in: Proceedings of the AAAI Conference on Artificial Intelligence, Vol. 39, 2025, pp. 8978–8986.

[14] M. Qu, X. Chen, W. Liu, A. Li, Y. Zhao, Chatvtg: Video temporal grounding via chat with video dialogue large language models, in: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, 2024, pp. 1847–1856.

[15] Y. Wang, Z. Wang, B. Xu, Y. Du, K. Lin, Z. Xiao, Z. Yue, J. Ju, L. Zhang, D. Yang, X. Fang, Z. He, Z. Luo, W. Wang, J. Lin, J. Luan, Q. Jin, Time-r1: Post-training large vision language model for temporal video grounding, in: Advances in Neural Information Processing Systems (NeurIPS), 2025.
URL https://openreview.net/forum?id=gJ05Gm5VxQ

[16] J. Zhang, T. Wang, Y. Ge, Y. Ge, X. Li, Y. Shan, L. Wang, Timelens: Rethinking video temporal grounding with multimodal llms, in: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), 2026, accepted.

[17] J. Xiao, N. Huang, H. Qin, D. Li, Y. Li, F. Zhu, Z. Tao, J. Yu, L. Lin, T.-S. Chua, et al., Videoqa in the era of llms: An empirical study, International Journal of Computer Vision 133 (7) (2025) 3970–3993.

[18] K. Kahatapitiya, K. Ranasinghe, J. Park, M. S. Ryoo, Language repository for long video understanding, in: Findings of the Association for Computational Linguistics: ACL 2025, 2025, pp. 5627–5646.

[19] R. Qian, X. Dong, P. Zhang, Y. Zang, S. Ding, D. Lin, J. Wang, Streaming long video understanding with large language models, Advances in Neural Information Processing Systems 37 (2024) 119336–119360.

[20] H. Zhao, G.-P. Ji, R. Yan, H. Xiong, Z. Li, Videoexpert: Augmented llm for temporal-sensitive video understanding, IEEE Transactions on Circuits and Systems for Video TechnologyAccepted / in press (2026). doi:10.1109/TCSVT.2026.3653742.

[21] P. Wang, S. Bai, S. Tan, S. Wang, Z. Fan, J. Bai, K. Chen, X. Liu, J. Wang, W. Ge, et al., Qwen2-vl: Enhancing vision-language model's perception of the world at any resolution, arXiv preprint arXiv:2409.12191 (2024).

[22] A. Yang, A. Miech, J. Sivic, I. Laptev, C. Schmid, Zero-shot video question answering via frozen bidirectional language models, Advances in Neural Information Processing Systems 35 (2022) 124–141.

[23] Z. Yan, Z. Li, Y. He, C. Wang, K. Li, X. Li, X. Zeng, Z. Wang, Y. Wang, Y. Qiao, L. Wang, Y. Wang, Task preference optimization: Improving multimodal large language models with vision task alignment, in: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), 2025, pp. 29880–29892.

[24] Y. Wang, X. Meng, J. Liang, Y. Wang, Q. Liu, D. Zhao, Hawkeye: Training video-text llms for grounding text in videos, arXiv preprint arXiv:2403.10228 (2024).

[25] H. Qin, J. Xiao, A. Yao, Question-answering dense video events, in: Proceedings of the 48th International ACM SIGIR Conference on Research and Development in Information Retrieval, ACM, 2025, pp. 884–894. doi:10.1145/3726302.3729945.