

Stored Procedures and Triggers

Content

1. PostgreSQL Procedural Language
2. Types of functions
3. The PL/ pgSQL language

1. PostgreSQL Procedural Language (PL)

- PL = programming languages used by the database engine → manipulate and extract data
- PL **execute directly inside the database engine**, instead of remotely in a separate application program.
 - greatly **improve performance** by reducing the execution time of your application
 - provide a standard place to store functions that is **accessible to anyone who uses the database**

Procedural languages

- Standard PostgreSQL supports:
 - PL/pgSQL
 - PL/Tcl
 - PL/Perl
 - PL/Python
- additional procedural languages available but not included in the core distribution: PL/Java, PL/PHP, PL/sh, ...
- To use = installed PL on the system
- Default: PL/pgSQL is installed

PL/ pgSQL

- **NOT** a standard language - it is specific to PostgreSQL
- **NOT** portable to other database engines
- **HOWEVER:**
 - very close to Oracle's default procedural language, **PL/SQL**
 - very little effort is required to port functions created in PL/SQL to PL/pgSQL, and visa versa

<file:///C:/Program%20Files/PostgreSQL/9.4/doc/postgresql/html/plpgsql.html>

2. Types of functions

- 2 types of functions:
 - Stored procedures
 - Triggers
- Stored procedures:
 - instead of using individual SQL commands create a specialized stored procedure that performs **multiple SQL commands as one function**.
 - Each user can then **execute the stored procedure** as a **single function within a SQL command**

2. Types of functions

- Triggers:
 - are functions that are **executed directly by the database engine**, **based on an event** (insert, update, delete...) that occurs in a table.
 - often **used to update related data** in tables automatically when a table value is inserted or updated in a single table → allows you to **maintain data relations automatically**, **without having to worry about that in your application code**.

3. The PL/ pgSQL language

- Uses **standard SQL commands** to build programs (query, insert, modify, and delete) → easy to learn
- Uses **standard programming** statements:
 - define and evaluate variables
 - accept input values for the function
 - supply output values from the function
 - use control logic, such as conditional loops and IF/THEN statements
- *interpreted* PL = **NOT** compiled into a binary form, **EXECUTES** the text program lines one by one as the function is executed

<file:///C:/Program%20Files/PostgreSQL/9.4/doc/postgresql/html/plpgsql.html>

3. The PL/ pgSQL language

- The first time a PL/pgSQL program is run, an *execution plan* is prepared:
 - *keeps the plan* and *uses it every time* the function is called (during the PostgreSQL server session) → increases performance, as the PL/pgSQL code does not have to be interpreted each time the function is run
- **CAREFUL** when making dynamic changes to functions:
 - PostgreSQL detects if a function's code has changed, and creates a new execution plan when necessary
 - A function *A* call a function *B*, *B is changed*, **BUT** execution plan of *A* is not changed → **re-create A**

Creating a PL/pgSQL Function

- CREATE [OR REPLACE] FUNCTION *functionname* ([[*argmode*] [*argname*] *argtype* ,...]) [RETURNS *returntype*] AS \$\$

DECLARE <variable declarations>

BEGIN

<code section>

END;

\$\$

LANGUAGE *language*

[IMMUTABLE | STABLE | VOLATILE

| CALLED ON NULL INPUT | RETURNS NULL ON NULL INPUT |
STRICT

| SECURITY INVOKER | SECURITY DEFINER];

Creating PL/pgSQL Function - Explain

- *language*: procedural language used to create the function (eg. PL/pgSQL = plpgsql)
- *functionname*: unique name used to identify the function
- input and output arguments: *argmode argname argtype*
 - *argmode*: IN, OUT, INOUT
 - may define as many input and output variables as you need (each separated by a comma)
- for compatibility with previous versions, PostgreSQL 8 also **supports defining a single output variable** using the RETURNS keyword → The last line of code in the function must be a RETURN statement

Creating PL/pgSQL Function - Explain

- **\$\$**: signify the *start and end of the function code* text
- **DECLARE** section of the code is used to declare variables used within the function:
 - *variablename datatype [:= value];*
- Output:
 - RETURN → must RETURN in code
 - OUT

Simple example

- **Definition:**

```
CREATE FUNCTION store.test(IN val1 int4, IN val2 int4, out result  
int4) AS
```

```
$$DECLARE vmultiplier int4 := 3;
```

```
BEGIN
```

```
    result := val1 * vmultiplier + val2;
```

```
END; $$
```

```
LANGUAGE plpgsql;
```

- **Execute:** `select store.test(10, 5);`

Function parameters

- **IMMUTABLE:** indicates that the function cannot modify the database and always returns the same result when given the same argument values. Any call of the function with all-constant arguments can be immediately replaced with the function value.
- **STABLE:** indicates that the function cannot modify the database, and that within a single table scan it will consistently return the same result for the same argument values, but that its result could change across SQL statements.
- **VOLATILE** indicates that the function value can change even within a single table scan. DEFAULT

Function parameters

- **CALLED ON NULL INPUT:** the function will be called normally when some of its arguments are null. DEFAULT
- **RETURNS NULL ON NULL INPUT / STRICT:** indicates that the function always returns null whenever any of its arguments are null.
- **SECURITY INVOKER** indicates that the function is to be executed with the privileges of the user that calls it. DEFAULT
- **SECURITY DEFINER** specifies that the function is to be executed with the privileges of the user that created it.

Notification

- Must use the **GRANT SQL** command and grant the **EXECUTE** privilege to **Group or Login Roles** before other users can use the new stored procedure function
- When creating complex functions, create a text file that contains the complete **CREATE FUNCTION** command
- When rewriting a function, use the **CREATE OR REPLACE FUNCTION** format when creating your function code in the text file → any code updates will replace the function without you having to manually delete the function
- Must end the **CREATE FUNCTION** command with a semicolon
- When creating a function, use a graphical development environment that allows you to alter program code within an editing window

Creating a Stored Procedure Using pgAdmin III

- **Functions** Define functions that use the RETURNS keyword to return a single value
- **Procedures** Define functions that use the OUT keyword to return one or more values → **Functions** *in new version pgAdmin III*
- **Triggers** Define functions that are used to manipulate tables based on a table event
- pgAdmin III → graphic → ok
- Query Tool? psql?

PL/pgSQL Function Code

- Assigning Values to Variables:
 - *variable := expression;*
- The format of the SELECT INTO statement:
 - *SELECT INTO variable [, ...] column [, ...] clause;*
 - The variable must be declared using the table's %ROWTYPE table attribute
 - *customervar store."Customer"%ROWTYPE*
*SELECT INTO customervar * FROM store."Customer" where*
"CustomerID" = 'BLU001';
result := customervar."FirstName" || ' ' || customervar."LastName";

Condition Statements

- IF *condition* THEN
 <*statements1*>
ELSE
 <*statements2*>
END IF;

- IF *condition1* THEN
 <*statements1*>
ELSE IF *condition2* THEN
 <*statements2*>
ELSE
 <*statements3*>
END IF;

Loop Statements

- LOOP

<statements>

EXIT [WHEN *expression*];

END LOOP;

- WHILE *condition* LOOP

<statements>

END LOOP;

- FOR *variable* IN *select_clause* LOOP

<statements>

END LOOP;

```
customervar store."Customer"%ROWTYPE;  
FOR customervar IN SELECT * FROM store."Customer" LOOP  
    <statements>  
END LOOP;
```

Trapping errors

BEGIN

statements

EXCEPTION

WHEN *condition* [OR *condition* ...] THEN
handler_statements

[WHEN *condition* [OR *condition* ...] THEN
handler_statements ...]

END;

The *condition* names can be any of those shown in

[Appendix A](#)

Trapping errors

- When an error is caught by an **EXCEPTION** clause, the local variables of the PL/pgSQL function remain as they were when the error occurred, but all changes to persistent database state within the block are rolled back.

```
INSERT INTO mytab(firstname, lastname) VALUES('Tom', 'Jones');
BEGIN
    UPDATE mytab SET firstname = 'Joe' WHERE lastname = 'Jones';
    x := x + 1;
    y := x / 0;
EXCEPTION
    WHEN division_by_zero THEN
        RAISE NOTICE 'caught division_by_zero';
        RETURN x;
END;
```

Examples

- CREATE FUNCTION add(integer, integer) RETURNS integer AS

'select \$1 + \$2;'

LANGUAGE SQL

IMMUTABLE

RETURNS NULL ON NULL INPUT;

Examples

- CREATE OR REPLACE FUNCTION increment (i integer)
RETURNS integer AS

```
$$ BEGIN RETURN i + 1; END; $$
```

```
LANGUAGE plpgsql;
```


Examples

- `CREATE FUNCTION dup(in int, out f1 int, out f2 text) AS
$$ SELECT $1, CAST($1 AS text) || ' is text' $$
LANGUAGE SQL;`
- `SELECT * FROM dup(42);`

Examples

- `CREATE TYPE dup_result AS (f1 int, f2 text);`
- `CREATE FUNCTION dup(int) RETURNS dup_result AS
$$ SELECT $1, CAST($1 AS text) || ' is text' $$
LANGUAGE SQL;`
- `SELECT * FROM dup(42);`

Examples

- ```
CREATE FUNCTION extended_sales(p_itemno int)
RETURNS TABLE(quantity int, total numeric) AS $$
BEGIN
 RETURN QUERY SELECT s.quantity, s.quantity * s.price
 FROM sales AS s
 WHERE s.itemno = p_itemno;
END;
$$ LANGUAGE plpgsql;
```

# Examples

- ALTER FUNCTION sqrt(integer) RENAME TO square\_root;
- ALTER FUNCTION sqrt(integer) OWNER TO joe;
- ALTER FUNCTION sqrt(integer) SET SCHEMA maths;
- DROP FUNCTION sqrt(integer);

# Other examples

- <http://www.java2s.com/Code/PostgreSQL/CatalogPostgreSQL.htm>
- <file:///C:/Program%20Files/PostgreSQL/9.4/doc/postgresql/html/plpgsql.html>