Template Manual

Park HTML

Thank You :)

Thanks for purchasing template and for supporting our work. Park is our new fancy template. Responsive, clean and professional look with sleek design will satisfy all your needs.

You will need basic HTML, CSS, jQuery skills to edit Park HTML.
We will try to help you out with this documentation. If we fail here, you can always contact us on https://cocobasic.ticksy.com/ and our developers will try to solve your issue.

HTML Structure

Park consist several HTML files

- index.html - Home page
- about.html
- gallery.html
- gallery-full.html
- contact.html
- single.html
- portfolio.html
- portfolio-item1.html
- portfolio-item2.html
- portfolio-item3.html
- portfolio-item4.html
- portfolio-item5.html

Home section index.html

On Home page are placed several posts items, some of them are visible, some not. When you click on "Load more" the first 4 hidden items will be displayed. If you still have hidden items, the next 4 will be became visible after you click again on "Load more". If there are no more hidden items, the "Load more" button will become "No more". All visible items are created using code like this:

```html
<article class="animate relative blog-item-holder center-relative has-post-thumbnail">
                <div class="post-thumbnail">
                    <a href="single.html">
                        <img src="images/home_img_01.jpg" alt="" />
                    </a>
                </div>
                <div class="entry-holder">
                    <div class="entry-info">
                        <div class="cat-links">
                            <ul>
                                <li>
                                    <a href="#">Interior</a>
                                </li>
                            </ul>
                        </div>
                    </div>
                    <h2 class="entry-title">
            <a href="single.html">Contemporary, classic and inspiring <i>innovation</i> details</a>
                    </h2>
                    <div class="excerpt">
        <p>Take root and flourish dream of the mind's eye at the edge of forever shores of the cosmic</p>
                    </div>
                    <p class="read-more-arrow">
                        <a href="single.html">
```

```
                    <span class="fa fa-arrow-right" aria-hidden="true"></span>
                </a>
            </p>
        </div>
        <div class="clear"></div>
    </article>
```

Also, there are items which are not visible, like this:

```
<article class="hidden relative blog-item-holder center-relative has-post-thumbnail">
        <div class="post-thumbnail">
          <a href="single.html">
            <img src="images/home_img_05.jpg" alt="" />
          </a>
        </div>
        <div class="entry-holder">
        <div class="entry-info">
        <div class="cat-links">
        <ul>
        <li><a href="#">Architecture</a></li>
        </ul>
      </div>
     </div>
    <h2 class="entry-title">
      <a href="single.html">Fresh born ideas <i>growing</i> every day</a>
    </h2>
   <div class="excerpt">
   <p>The weeks are ham asked jokes. Neglected per made shy nay concluded. Not mile draw plan</p>
            </div>
            <p class="read-more-arrow">
             <a href="single.html">
                <span class="fa fa-arrow-right" aria-hidden="true"></span>
                </a>
            </p>
          </div>
        <div class="clear"></div>
    </article>
```

Code, which is showing the first 4 hidden items is placed in ***/js/main.js*** and looks like this:

```
jQuery('.blog-holder').find(".hidden").slice(0, 4).removeClass("hidden").addClass("animate loaded");
```

If you want, for example, to load 6 hidden items, you need to use code like this:

```
jQuery('.blog-holder').find(".hidden").slice(0, 6).removeClass("hidden").addClass("animate loaded");
```

Portfolio page

On Portfolio page are also placed several portfolio items and some of them are visible:

```
<div class="grid-item">
    <div class="item-wrapper animate">
        <div class="portfolio-thumbnail">
            <a href="portfolio-item4.html">
                <img src="images/home_img_01.jpg" alt="">
            </a>
        </div>
        <div class="entry-holder">
            <h2>
                <a href="portfolio-item4.html">Eight Stairs</a>
            </h2>
        </div>
    </div>
</div>
```

and some of them are hidden:

```
<div class="grid-item">
    <div class="item-wrapper hidden">
        <div class="portfolio-thumbnail">
            <a href="portfolio-item5.html">
                <img src="images/home_img_04.jpg" alt="">
            </a>
        </div>
        <div class="entry-holder">
            <h2>
                <a href="portfolio-item5.html">Dollar Sign</a>
            </h2>
        </div>
    </div>
</div>
```

"Load more" button works on same way like on Home page (read above for more info). Code, which is showing the first 4 hidden items is placed in **/js/main.js** and looks like this:

```
jQuery('#portfolio').find(".hidden").slice(0, 4).removeClass("hidden").addClass("animate loaded");
```

If you want, for example, to load 6 hidden items, you need to use code like this:

```
jQuery('#portfolio').find(".hidden").slice(0, 6).removeClass("hidden").addClass("animate loaded");
```

Single post - single.html

On Single post you will find code like this (image slider code):

```html
<script>
    var slider1_speed = "1200";
    var slider1_auto = "true";
    var slider1_hover = "true";
    var slider1_dots = "true";
</script>
<div class="image-slider-wrapper relative">
    <div id="slider1" class="image-slider slider animate">
        <div class="slick-slide">
            <img src="images/blog_img_02.jpg" alt="">
        </div>
        <div class="slick-slide">
            <img src="images/blog_img_03.jpg" alt="">
        </div>
        <div class="slick-slide">
            <img src="images/blog_img_04.jpg" alt="">
        </div>
    </div>
</div>
```

If you need one more slider, duplicate that code and change "**slider**" string on several places with new string, for example "**slider2**". So you will have "**slider2_speed**", "**slider2_auto**", id="**slider2**"...

Mail Configuration

Note: Do not remove any quote or double quote signs while doing this.

One notice: this will be functional only on your server, php file can not be executed on your local computer.

Just add your own email address here in your **config.php** file.

```
//SITE GLOBAL CONFIGURATION
$email = "your@email.here"; //<-- Your email
```

Element Animation

On Park are several elements which have fadeIn animation when the element comes in viewport. To add element animation, all you need to do is to add class "**animate**". For example:

```
<div id="slider1" class="image-slider slider animate">
    ...
```

Source & Credits

Special thanks to creators and contributors of these awesome libraries, we couldn't done this without them.

Images used in theme

https://unsplash.com

VIdeo used in template

https://www.youtube.com/watch?v=xEW_YXgRSIE

jQuery Isotope Plugin

http://isotope.metafizzy.co

Slick

http://kenwheeler.github.io

HTML5 Fallback Support

https://code.google.com/p/html5shiv

Respond JS

https://github.com/scottjehl/Respond

jQuery

http://jquery.com

Google Web Fonts

http://www.google.com/webfonts

Easing jQuery Plugin

http://gsgd.co.uk/sandbox/jquery/easing

Smart Menus

http://www.smartmenus.org/

Font Awesome

http://www.fontawesome.io/

FitVideo.js

http://fitvidsjs.com/

Justified Gallery

http://miromannino.github.io/Justified-Gallery/

We are sorry if we forgot to mention someone.

Questions?

We tried to help you out with this documentation. So please read carefully. If we fail here, you can always go to our support forum and post a new discussion in appropriate category. Our developers will try to solve your issue.

Thanks for understanding.