

2.4 Given the following signals

$$x(t) = 2\delta(t), \quad y(t) = 4u(t), \quad z(t) = e^{-2t}u(t),$$

Evaluate the following operations.

- (a) $x(t)*y(t)$
- (b) $x(t)*z(t)$
- (c) $y(t)*z(t)$
- (d) $y(t)*[y(t) + z(t)]$

2.14 The impulse response of a low-pass filter is $h(t) = e^{-t}u(t)$. Determine its step response, that is, the output when the input is a unit step.

2.24 Determine the overall impulse response for the system shown in Figure 2.34.




FIGURE 2.34 For Problem 2.24.

2.30 Given that $x[n] = \begin{cases} 1, & n = 0 \\ -1, & n = 1 \\ 0, & \text{otherwise} \end{cases}$, $h[n] = \begin{cases} 1, & n = 0 \\ 3, & n = 1 \\ 2, & n = 3 \\ 0, & \text{otherwise} \end{cases}$

- (a) Sketch $x[n]$ and $h[n]$.
- (b) Find $x[n]*h[n]$.

2.33 Two systems are described by

$$h_1[n] = (0.4)^n u[n], \quad h_2[n] = \delta[n] + 0.5\delta[n-1]$$

Determine the response to the input $x[n] = (0.4)^n u[n]$ if

- (a) The two systems are connected in parallel
- (b) The two systems are connected in cascade

2.36 The input $x[n] = [1 \ -1]$ to a system produces the output $y[n] = [4 \ 2 \ 5 \ 1]$. Determine the impulse response.

- 2.39** An LTI discrete system has the impulse response $h[n] = (0.6)^n u[n]$. Use MATLAB to calculate the response of the system to input $x[n] = u[n]$ and plot it.
- 2.40** Repeat the previous problem for $x[n] = \cos(n\pi/6)u[n]$.
- 2.41** Given that $x[n] = [1 \ -1 \ 2 \ 4]$ and $y[n] = [2 \ 6 \ 4 \ 0 \ 8 \ 5 \ 12]$, use MATLAB to find $h[n]$.
- 以recursive algorithm 求 $h[n]$
 - 手算或以deconv() 驗算