

Problem 1: Basic Java and Pseudocode (30 points)

1. **(4 points)** Evaluate the following expression and select the type and value of the result

`(int) 77.77`

- a. int, 77
- b. double, 77.77
- c. double, 77.0
- d. long, 77
- e. int, 78

2. **(4 points)** Evaluate the following expression and select the type and value of the result

`(6 != 6) || (2 == 2) && (3 == '3')`

- a. boolean, true
- b. boolean, false
- c. int, true
- d. Compile Error
- e. Runtime Error

3. **(4 points)** Evaluate the following expression and select the type and value of the result

`Boolean.parseBoolean("True") || (7 != (77/11))`

- a. boolean, true
- b. boolean, false
- c. int, true
- d. Compile error

4. **(7 points)** Examine the following pseudocode algorithm. What is the output and what is the total number of operations that are executed by this code?

Input : none

Output : ???????

Pre-condition : none

SET count TO 0

SET end TO 10

WHILE count < end

 DISPLAY count

 ADD 1 TO count

ENDWHILE

5. (6 points) Examine the following snippet of code:

```
int a = 4, b = 6, c = 0;
for (int i = 0; i < a; i++)
{
    c += a;
    for (int j = 0; j < b; j++) {
        c += b;
    }
}
StdOut.println(c);
```

What is the output?

6. (5 points) Given the code below add a line that prints the Numbers array to the screen in reverse.
Place your code where the XXX's are.

```
public class TestArrays
{
    public static void main (String[] args)
    {
        // Populate the array
        int numbers[] = {1, 2, 3, 4, 5, 6, 7};

        // Print from index 0 to N
        for (int i = 0; i < numbers.length; i++) {
            // Print the array item at index i
            StdOut.print(numbers[i]);
        }
        StdOut.print("\n");

        // Print the array in reverse
        XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX

    }
}
```

Problem 2: Functions (30 points)

1. (5 points) What does the following program do?

```
public static void negate (int value) {  
    value = -value;  
}  
  
public static void main (String[] args) {  
    int a = 43;  
    System.out.println(a);  
    negate(a);  
    System.out.println(a);  
}
```

- a) Prints the integer 43 twice
 - b) Prints the integers 43 and then -43
 - c) Prints the integer -43 twice
 - d) None of the above
2. (15 points) Write a static method `nearestInt()` that has one double parameter value and returns the nearest integer. Do not use any Math library function, instead use casting.

If the digit in the tenths place is less than 5, then **round down**, which means the units digit remains the same; if the digit in the tenths place is 5 or greater, then round up, which means you should increase the unit digit by one.

Examples:

```
nearestInt(2.5 ) returns 3  
nearestInt(2.49 ) returns 2  
nearestInt(-2.5 ) returns -3  
nearestInt(-2.49) returns -2
```

3. **(10 points)** Complete the method `anyTrue()` that takes an array of `boolean` values as its argument and returns `true` if any of the elements in the array is `true`, and `false` otherwise.

For example:

`anyTrue ([true,true,true,true])` returns `true`

`anyTrue ([false,false,false,true])` returns `true`

`anyTrue ([false,false,false,false])` returns `false`

```
public static boolean anyTrue (boolean[] a) {  
  
}
```

Problem 3: Recursion (35 points)

Questions 1 - 3 refer to the following three code segments (labeled A, B, and C).

A.

```
public static void myMethod(int n){
    if (n>0){
        myMethod(n-1);
    }
    System.out.println(n);
}
```

B.

```
public static void myMethod(int n){
    if (n>0){
        myMethod(n-1);
        System.out.println(n);
    }
}
```

C.

```
public static void myMethod(int n){
    if (n>0){
        myMethod(n-1);
    } else{
        System.out.println(n);
    }
}
```

1. **(5 points)** Which statement about methods A, B, and C above is true if the myMethod is called with a positive int parameter?
 - a. All three methods produce the same output.
 - b. All three methods produce different outputs.
 - c. Methods A and B produce the same output that is different from Method C.
 - d. Methods A and C produce the same output that is different from Method B.
 - e. Methods B and C produce the same output that is different from Method A.
2. **(6 points)** If the statement
 myMethod(5);
were executed, what is the output produced by code segment B?
3. **(5 points)** For this question, **consider Code Segment C only**. If the statement
 myMethod(5);
were executed, what is the total number of times myMethod is called (including the original call)?

4. (6 points) Given the recursive method surprise below:

```
public static String surprise(String s){
    if (s.length() <= 1){
        return s;
    }
    return s.charAt(s.length() - 1) + surprise(s.substring(0,s.length() - 2));
}
```

What is the printed when the following instruction is executed?
System.out.println(surprise("mathematics"));

5. Consider the recursive method magic below.

```
public static boolean magic(int[] a, int size){
    if (size == 1){
        return true;
    }
    return (a[size-1] > a[size - 2] && magic(a, size - 1) );
}
```

Suppose the following code segment is executed. Assume that args.length > 0.

```
int[] arr = new int[args.length];
for(int i = 0; i < args.length; i++){
    arr[i] = Integer.parseInt(args[i]);
}
System.out.println(magic(arr, arr.length));
```

- (3 points) Give a set of input values that would result in **true** being printed.
- (3 points) Give a set of input values that would result in **false** being printed.
- (3 points) Is there any set of values that would cause an endless loop?
- (3 points) Describe the intended purpose of the method magic?

Problem 4: OOP Using Data Types (35 points)

Suppose we have a String in the form "s1;s2;s3;...;sn;" where s1 to sn all have the form "name,id,gpa". Here, name, id and gpa separately represent a student's name, id and gpa. And the three pieces of information are separated by the character ',' and there is at least one character there for each kind of information. Note that the string always ends with one ';'.

The following code is a class defined to represent a student:

```
public class Student {
    private String name;
    private int id;
    private double gpa;

    public Student(String name, int id, double gpa) {
        this.name = name;
        this.id = id;
        this.gpa = gpa;
    }

    public String toString(){
        return "Name: " + this.name + "\nID: " + this.id + "\nGPA: " + this.gpa + "\n";
    }
}
```

Write a method that takes such a string and an integer n as inputs, where n represents the number of ';' in the string and returns a 1-D array containing n Student objects where each object is constructed using the information of si which is in the form of "name,id,gpa".

For example, if the parameters are {"Joy,101,3.45;Emily,102,3.56;Nancy,103,3.21;Jimmy,104,4.0;"} and 4, then the output would be a 1-D array whose length is 4 and has the following four Student objects:

```
Name: Joy
ID: 101
GPA: 3.45

Name: Emily
ID: 102
GPA: 3.56

Name: Nancy
ID: 103
GPA: 3.21

Name: Jimmy
ID: 104
GPA: 4.0
```

Use the provided String library methods to operate these string values. Here is the documentation for String: <https://docs.oracle.com/en/java/javase/11/docs/api/java.base/java/lang/String.html>

The method signature is given below:

```
public static Student[] convert(String str, int n)
```