6ED1052-2MD08-0BA2

Data sheet

Siemens

.........



LOGO! 12/24RCEO, logic module, power supply / I/O: 12/24 V DC/relay, 8 DI (4 AI)/4 DO, without display, memory 400 blocks, modularly expandable, Ethernet, integrated web server, data log, user-defined web pages, standard microSD card for LOGO! Soft Comfort V8.4 or higher, older projects executable cloud connection, MQTT in all LOGO! 8.4 basic units

Figure similar

C WHITE IN	
Installation type/mounting	
Mounting	on 35 mm DIN rail, 4 spacing units wide
Supply voltage	
Rated value (DC)	
• 12 V DC	Yes
• 24 V DC	Yes
permissible range, lower limit (DC)	10.8 V
permissible range, upper limit (DC)	28.8 V
Time of day	
Time switching clocks	
Number	400; Max. 400, function-specific
Power reserve	480 h
Digital inputs	
Number of digital inputs	8; Of which 4 can be used in analog mode (0 to 10 V)
Digital outputs	
Number of digital outputs	4; Relays
Short-circuit protection	No; external fusing necessary
Output current	
 for signal "1" permissible range for 0 to 55 °C, max. 	10 A
Relay outputs	
Switching capacity of contacts	
— with inductive load, max.	3 A
— with resistive load, max.	10 A
EMC	
Emission of radio interference acc. to EN 55 011	
Limit class B, for use in residential areas	Yes; Radio interference suppression according to EN55011, Limit Value Class B
Standards, approvals, certificates	
CE mark	Yes
CSA approval	No; covered by UL cert
UL approval	Yes
FM approval	Yes
developed in accordance with IEC 61131	Yes
according to VDE 0631	Yes
Marine approval	Yes; in preparation
Ecological footprint	

 environmental product declaration 	Yes	
Global warming potential		
— global warming potential, (total) [CO2 eq]	51.5 kg	
— global warming potential, (during production) [CO2 eq]	9.64 kg	
— global warming potential, (during operation) [CO2 eq]	42.1 kg	
— global warming potential, (after end of life cycle)[CO2 eq]	-0.364 kg	
Ambient conditions		
Ambient temperature during operation		
• min.	-20 °C; No condensation	
• max.	55 °C	
Ambient temperature during storage/transportation		
• min.	-40 °C	
• max.	70 °C	
Altitude during operation relating to sea level		
 Ambient air temperature-barometric pressure-altitude 	Tmin Tmax at 1 080 hPa 795 hPa (-1 000 m +2 000 m)	
Dimensions		
Width	71.5 mm	
Height	90 mm	
Depth	58 mm	

last modified: 10/9/2024 🖸