

Matching hieroglyphs through the Hausdorff distance

The dataset

- 2 sets of bitmaps (png format) are available in the folders 'hiero_01' and 'hiero_02'
 - hiero_01 has 22 bitmaps (01.png ... 22.png)
 - hiero_02 has 19 bitmaps (01.png ... 19.png)
- Each bitmap represents a hieroglyph, 0 pixel values corresponding to the foreground and 1 to the background

hiero_01




hiero_02




- The bitmaps do not have the same size

Project goal



- Define a procedure to compute the distance between two hieroglyphs through the Hausdorff distance
- Use the above procedure to compute a 19 x 22 matrix storing the distance of each hieroglyph in 'hiero_02' to each hieroglyph in 'hiero_01'

Guidelines




■ Read the bitmaps

```
> galleryNames = { 'hiero_01/01.png';  
'hiero_01/02.png';  
'hiero_01/03.png';  
'hiero_01/04.png';  
'hiero_01/05.png';  
'hiero_01/06.png';  
'hiero_01/07.png';  
'hiero_01/08.png'};
```

```
> img01 = imread(galleryNames{1});
```

Guidelines




- Represent each bitmap through the coordinates of foreground pixels

```
> galleryNames = { 'hiero_01/01.png';  
'hiero_01/02.png';  
'hiero_01/03.png';  
'hiero_01/04.png';  
'hiero_01/05.png';  
'hiero_01/06.png';  
'hiero_01/07.png';  
'hiero_01/08.png'};
```

```
> img01 = imread(galleryNames{1});
```

```
> [img01_I img01_J] = find(img01==0);
```


Guidelines



- Compute the Hausdorff distance between two pixel sets

????????????????

Guidelines



- Any idea to cope with the different size of the bitmaps?

????????????????