

## 实验二：MySQL 中表的创建与查询

22121630 汪江豪

1. 首先创建四张表，命令如下：

```
mysql> CREATE TABLE S
-> (SNO CHAR(4) NOT NULL,
-> SNAME CHAR(20) NOT NULL,
-> SADDR CHAR(20),
-> PRIMARY KEY(SNO));
Query OK, 0 rows affected (0.02 sec)

mysql> CREATE TABLE S
-> (SNO CHAR(4) NOT NULL,
-> SNAME CHAR(20) NOT NULL,
-> SADDR CHAR(20),
-> PRIMARY KEY(SNO));
Query OK, 0 rows affected (0.02 sec)

mysql> CREATE TABLE J
-> (JNO CHAR(4) NOT NULL,
-> JNAME CHAR(20),
-> JCITY CHAR(20),
-> BALANCE NUMERIC(7,2),
-> PRIMARY KEY(JNO));
Query OK, 0 rows affected (0.02 sec)

mysql> CREATE TABLE SPJ
-> (SNO CHAR(4) NOT NULL,
-> PNO CHAR(4) NOT NULL,
-> JNO CHAR(4) NOT NULL,
-> PRICE NUMERIC(7,2),
-> QTY SMALLINT,
-> PRIMARY KEY(SNO, PNO, JNO),
-> FOREIGN KEY(SNO) REFERENCES S(SNO),
-> FOREIGN KEY(PNO) REFERENCES P(PNO),
-> FOREIGN KEY(JNO) REFERENCES J(JNO),
-> CONSTRAINT C_QTY CHECK(QTY BETWEEN 0 AND 10000));
Query OK, 0 rows affected (0.03 sec)
```

2. 插入相应的数据。

3. 执行相应的查询。

- 3.1 检索供应零件编号为 J1 的工程的供应商编号 SNO。

```
mysql> SELECT DISTINCT SNO
-> from spj
-> where JNO = 'J1';
+-----+
| SNO |
+-----+
| S1 |
| S3 |
| S5 |
| S6 |
+-----+
4 rows in set (0.00 sec)
```

- 3.2 检索供应零件给工程 J1，且零件编号为 P1 的供应商编号 SNO。

```
mysql> SELECT SNO
-> FROM spj
-> where JNO = 'J1' AND PNO = 'P1';
+-----+
| SNO |
+-----+
| S1 |
+-----+
1 row in set (0.00 sec)
```

- 3.3 查询没有正余额的工程编号、名称及城市，结果按工程编号升序排列。

```
mysql> select JNO, JNAME, JCITY
-> FROM j
-> where BALANCE <= 0
-> order by JNO ASC;
+-----+-----+-----+
| JNO | JNAME           | JCITY   |
+-----+-----+-----+
| J1  | Dongfangmingzhu | Shanghai |
| J2  | Lianyouchang    | Changchun |
+-----+-----+-----+
2 rows in set (0.00 sec)
```

- 3.4 求使用零件数量为 100 到 1000 的工程编号、零件号和数量。

```
mysql> SELECT JNO, PNO, QTY FROM spj WHERE QTY BETWEEN 100 AND 1000;
+-----+-----+-----+
| JNO | PNO | QTY |
+-----+-----+-----+
| J1  | P3  | 100 |
| J5  | P3  | 100 |
+-----+-----+-----+
2 rows in set (0.00 sec)
```

3.5 查询上海的供应商名称，假设供应商关系 SADDR 列的值都以城市名开头。

```
mysql> select SNAME
-> FROM s
-> WHERE SADDR LIKE 'Shanghai%';
+-----+
| SNAME |
+-----+
| Company_B |
+-----+
1 row in set (0.01 sec)
```

3.6 检索使用了 P3 零件的工程名称。

```
mysql> select DISTINCT j.JNAME FROM spj join j on spj.JNO = j.JNO where spj.PNO = 'P3';
+-----+
| JNAME |
+-----+
| Dongfangmingzhu |
| Mingzhuxian |
| Lianyougongdi |
| Nanpudaqiao |
+-----+
4 rows in set (0.00 sec)
```

3.7 检索供应零件给工程 J1，且零件颜色为红色的供应商编号 SNO。

```
mysql> SELECT DISTINCT spj.SNO FROM spj join p on spj.PNO = p.PNO WHERE spj.JNO = 'j1' and p.COLOR = 'red';
+-----+
| SNO |
+-----+
| S1 |
| S5 |
| S6 |
+-----+
3 rows in set (0.00 sec)
```

3.8 检索至少使用了零件编号为 P3 和 P5 的工程编号 JNO。

```
mysql> select JNO
-> from spj
-> where PNO IN ('P3','P5')
-> GROUP BY JNO
-> HAVING COUNT(DISTINCT PNO) = 2;
+-----+
| JNO |
+-----+
| J1 |
| J4 |
| J6 |
+-----+
3 rows in set (0.00 sec)
```

3.9 检索不使用编号为 P3 零件的工程编号 JNO 和名称 JNAME。

```
mysql> select j.JNO, j.JNAME
-> from j
-> where j.JNO NOT IN (
-> select distinct spj.jno
-> from spj
-> where spj.PNO = 'P3'
-> );
+-----+-----+
| JNO | JNAME |
+-----+-----+
| J2 | Lianyouchang |
| J3 | MTR3 |
| J7 | Shuinichang |
+-----+-----+
3 rows in set (0.00 sec)
```