

实验三:Spark-SQL 分布式数据库部署

22121630 汪江豪

实验内容:

实验数据集记录了 2016 年以来 50 个州和华盛顿特区的出生率和相关数据。根据要求进行相关查询:

1. 按洲和年份分组查询, 出生婴儿的男女比例。
输出格式: (State, Year, MRatio, FRatio)
2. 按年份分组查询, 查询母亲受教育程度与平均生育年龄的关系。
输出格式: (Year, Education_Level_Code, Average_Age_of_Mother)
3. 按年份分组查询, 查询平均生育年龄与婴儿平均体重的关系。
输出格式: (Year, Average_Age_of_Mother, Average_Birth_Weight)

实验步骤:

1. 执行准备工作:

```
Sudo apt-get update; sudo apt-get upgrade  
Sudo apt-get install openssh-server vim  
Cd .ssh; ssh-keygen -t rsa -C "2814388011@qq.com"
```

2. 安装 java

```
Sudo apt-get install openjdk-8-jdk openjdk-8-jre
```

3. 为 java 设置环境变量

```
Sudo vim ~/.bashrc
```

在第一行添加

```
export JAVA_HOME=/usr/lib/jvm/java-8-openjdk-amd64
```

保存并退出后应用设置

```
Source ~/.bashrc
```

验证 java 安装成功

```
ubuntu@master:~$ echo $JAVA_HOME  
/usr/lib/jvm/java-8-openjdk-amd64  
ubuntu@master:~$ java -version  
openjdk version "1.8.0_432"  
OpenJDK Runtime Environment (build 1.8.0_432-8u432-ga~us1-0ubuntu2~20.04-ga)  
OpenJDK 64-Bit Server VM (build 25.432-bga, mixed mode)
```

4. 安装 hadoop 和 spark, 可以到官网下载, 或者将本地下载好的安装包通过 scp 命令远程传输到相应主机。

5. 解压到指定目录, 修改权限和名称, 方便后续访问

```
Sudo tar -zxvf Hadoop-2.7.1.tar.gz -C /usr/local  
Sudo tar -zxvf spark-2.1.0-bin-with-hive.tgz -C /usr/local  
Cd /usr/local  
Sudo chown -R ubuntu:root ./spark-2.1.0-bin-h2hive  
Sudo chown -R ubuntu:root ./Hadoop-2.7.1  
Mv spark-2.1.0-bin-h2hive spark  
Mv Hadoop-2.7.1 hadoop  
验证 hadoop 安装成功
```

```
ubuntu@master:/usr/local/hadoop$ bin/hadoop version
Hadoop 2.7.1
Subversion https://git-wip-us.apache.org/repos/asf/hadoop.git -r 15ecc87ccf4a0228f35af08fc56de536e6ce657a
Compiled by jenkins on 2015-06-29T06:04Z
Compiled with protoc 2.5.0
From source with checksum fc0a1a23fc1868e4d5ee7fa2b28a58a
This command was run using /usr/local/hadoop/share/hadoop/common/hadoop-common-2.7.1.jar
```

6. 配置 spark 环境并验证安装

`Cd ../spark/conf`

`Cp spark-env.sh.template spark-env.sh`

`Sudo vim spark-env.sh`

第一行添加

`export SPARK_DIST_CLASSPATH=$(/usr/local/hadoop/bin/hadoop classpath)`

保存并退出

`../bin/run-example SparkPi`

运行显示出圆周率计算结果，表明 spark 安装成功

7. 配置 hadoop 集群环境

`Cd ../hadoop/etc/Hadoop/`

修改相应的 `slaves`, `core-site.xml`, `hdfs-site.xml`, `mapred-site.xml` (要先将模板拷贝一份出来), `yarn-site.xml` 文件。至此，配置完成。保存实例，另外创建两个该实例作为 `slave01` 和 `slave02`。

8. 连接三台主机

三个主机，修改主机名，记录相互内网 ip，实现 ssh 免密访问

`Sudo vim /etc/hostname`，分别修改为 `master` `slave01`，`slave02` (主机名不可更改，否则会与之之前配置文件不符出错)

`Sudo vim /etc/hosts`，分别添加三台机器的内网 ip [主机名]

分别重启，应用配置。重启后分别输入 `ssh` 相互的主机名，验证三台机器之间可以互相实现免密登录。

9. 启动 hadoop 集群

在 master 主机中，`cd /usr/local/Hadoop`

先进行格式化：`bin/hdfs namenode -format`

再启动脚本：`sbin/start-all.sh`

验证 hadoop 集群是否成功启动，三台机器分别输入 `jps` 显示如下：

```
ubuntu@master:/usr/local/hadoop$ jps
2817 SecondaryNameNode
6227 Jps
2566 NameNode
2984 ResourceManager
ubuntu@slave01:~$ jps
4593 DataNode
4869 NodeManager
4999 Jps
ubuntu@slave02:~$ jps
4995 Jps
4852 NodeManager
4682 DataNode
```

表明 hadoop 集群成功启动。

10. 创建目录并上传数据集

先将数据集 `us_births_2016_2021.csv` 转换为 `.json` 格式文件 (各个表项之间不能有，否则导入数据库会出现异常)。Csv 转 json 的 python 脚本如下：

```
import csv
import json

# CSV文件路径
csv_file_path = "../us_births_2016_2021.csv"
# 输出的JSON文件路径
json_file_path = "../us_births_2016_2021.json"

# 初始化一个列表来保存所有的字典记录
data = []

# 读取CSV文件
with open(csv_file_path, mode="r", encoding="utf-8") as csv_file:
    csv_reader = csv.DictReader(csv_file)
    for row in csv_reader:
        # 将CSV记录转换为JSON对象
        data.append(json.dumps(row))

# 将JSON对象列表写入JSON文件, 每个对象占用一行
with open(json_file_path, mode="w", encoding="utf-8") as json_file:
    for json_obj in data:
        json_file.write(json_obj + "\n")
```

再通过 scp 从本地传到 master 主机，家目录下，命名为 us.json 再上传到 hdfs 系统
创建目录: bin/hdfs dfs -mkdir -p /user/ubuntu(目录名不能错)

上传数据集: bin/hdfs dfs -put ~/us.json

11. 启动 spark-sql 数据库

Cd ../spark

Bin/spark-sql

```
25/01/02 16:01:54 INFO HiveMetaStore.audit: ugi=ubuntu ip=unknown-ip-a
ddr cmd=get_database: global_temp
25/01/02 16:01:54 WARN metastore.ObjectStore: Failed to get database gl
obal_temp, returning NoSuchObjectException
25/01/02 16:01:54 INFO session.SessionState: Created local directory: /
tmp/1c19bd39-3717-4c72-a7ec-028964581295_resources
25/01/02 16:01:54 INFO session.SessionState: Created HDFS directory: /t
mp/hive/ubuntu/1c19bd39-3717-4c72-a7ec-028964581295
25/01/02 16:01:54 INFO session.SessionState: Created local directory: /
tmp/ubuntu/1c19bd39-3717-4c72-a7ec-028964581295
25/01/02 16:01:54 INFO session.SessionState: Created HDFS directory: /t
mp/hive/ubuntu/1c19bd39-3717-4c72-a7ec-028964581295/_tmp_space.db
25/01/02 16:01:54 INFO client.HiveClientImpl: Warehouse location for Hi
ve client (version 1.2.1) is file:/usr/local/spark/spark-warehouse/
spark-sql> |
```

显示如图，表明成功启动 spark-sql。

12. 导入 us.json 数据集

Create table us using org.apache.spark.sql.json options(path "us.json")

可以查看表是否创建成功: select * from us limit 50, 显示前 50 行

13. 开始 sql 查询:

(1) 按洲和年份分组查询，出生婴儿的男女比例

输出格式: (State, Year, MRatio, FRatio)

语句如下: (标识符有空格的要反引号`)

```
select State,
       Year,
       sum(case when Gender = "M" then `Number of Births` else 0 end) /
       sum(`Number of Births`) as MRatio,
       sum(case when Gender = "F" then `Number of Births` else 0 end) /
       sum(`Number of Births`) as FRatio
from us group by State, Year order by State, Year;
```

结果如图:

```

Wisconsin 2017 0.5108888033859177 0.48911119661408237
Wisconsin 2018 0.5129645230740428 0.4870354769259571
Wisconsin 2019 0.5111743322269638 0.4888256677730362
Wisconsin 2020 0.5108261544047266 0.48917384559527344
Wisconsin 2021 0.5101406581311406 0.4898593418688594
Wyoming 2016 0.5129975629569455 0.4870024370430544
Wyoming 2017 0.506156743444879 0.49384325655512096
Wyoming 2018 0.5144772935080768 0.4855227064919232
Wyoming 2019 0.5151561309977152 0.4848438690022848
Wyoming 2020 0.504079634464752 0.49592036553524804
Wyoming 2021 0.5281385281385281 0.47186147186147187
Time taken: 4.785 seconds, Fetched 306 row(s)
25/01/02 20:04:30 INFO CliDriver: Time taken: 4.785 seconds, Fetched 306 row(s)
spark-sql>

```

(2) 按年份分组查询，查询母亲受教育程度与平均生育年龄的关系

输出格式: (Year, Education_Level_Code, Average_Age_of_Mother)

语句如下:

```

select
Year,
`Education Level Code`
AVG(`Average Age of Mother (years)`) as Average_Age_of_Mother
from us group by Year, `Education Level Code`
order by Year, `Education Level Code`;

```

结果如图:

```

2020 6 31.313725490196067
2020 7 32.87745098039216
2020 8 33.82352941176472
2021 -9 29.789
2021 1 29.405882352941163
2021 2 25.336274509803918
2021 3 26.783333333333334
2021 4 28.483333333333333
2021 5 30.047058823529408
2021 6 31.377450980392158
2021 7 32.90980392156863
2021 8 33.83823529411765
Time taken: 1.265 seconds, Fetched 54 row(s)
25/01/02 20:19:52 INFO CliDriver: Time taken: 1.265 seconds, Fetched 54 row(s)
spark-sql>

```

(3) 按年份分组查询，查询平均生育年龄与婴儿平均体重的关系。

输出格式: (Year, Average_Age_of_Mother, Average_Birth_Weight)

语句如下:

```

select
Year,
AVG(`Average Age of Mother (years)`) as Average_Age_of_Mother,
AVG(`Average Birth Weight (g)`) as Average_Birth_Weight
from us group by Year order by Year;

```

结果如图:

```

2016 29.30087431693986 3261.675191256832
2017 29.40295081967215 3255.9590163934395
2018 29.533042529989117 3253.8970556161426
2019 29.6027262813522 3247.9850599781885
2020 29.699126637554578 3246.6778384279532
2021 29.774454148471595 3239.1487991266354
Time taken: 1.204 seconds, Fetched 6 row(s)
25/01/02 20:31:12 INFO CliDriver: Time taken: 1.204 seconds, Fetched 6 row(s)
spark-sql>

```