

Data Structures

Linked list, Queue, Stack

Definitions

Data structures – a combination of simple data types and structuration methods.

Standard operations on structured data types:

- 1. Definition
- 2. Initialization
- 3. Adding elements
- 3. Remove elements
- 4. Passing data structure

Types of linear data structures

Indexed structures – arrays. Already discussed.

Linked Lists - linear collections of data elements, whose order is not given by their physical placement in memory. Instead, each element points to the next. It is a data structure consisting of a collection of nodes which together represent a sequence.


ARRAY

18	34	16	-5	71	17
----	----	----	----	----	----


[0] [1] [2] [3] [4] [5]

16


LINKED LIST



A




B




Types of lists:
one-directional (A), circular (B)


Insertion




Passing the List



Add an element
(after selected)




Remove element



QUEUE





Definition

QUEUE from latin CAUDA (TAIL) – COADĂ



Queue is a collection in which the entities are kept in order and the principal (or only) operations on the collection are the addition of entities to the rear terminal position, known as enqueue, and removal of entities from the front terminal position, known as dequeue. This makes the queue a **First-In-First-Out (FIFO)** data structure

QUEUE

ADD

/

REMOVE






STACK

In computer science, a stack is an abstract data type that serves as a collection of elements, with two principal operations:

- **push**, which adds an element to the collection, and
- **pop**, which removes the most recently added element that was not yet removed.

Definition





STACK

ADD

/

REMOVE



Code example

```
#include <stdio.h>
#include <stdlib.h>

struct User {
    char name[20];
    char pass[20];
    char mail[50];
    struct User *next;
};

struct User* head = NULL;
```



List (stack & queue) traversal

```
void traverseList() {  
    struct User* current = NULL;  
    current = head;  
  
    while (current != NULL) {  
        printf("User: %s\n", current->name);  
        printf("Password: %s\n", current->pass);  
        printf("Email: %s\n\n", current->mail);  
  
        current = current->next;  
    }  
}
```

Add element

```
void addToList(char *name, char *pass, char *mail) {  
    struct User* item = NULL;  
    item = (struct User*)malloc(sizeof(struct User));  
  
    strcpy(item->name, name);  
    strcpy(item->pass, pass);  
    strcpy(item->mail, mail);  
  
    if (head != NULL) {  
        item->next = head;  
    }  
    else {  
        item->next = NULL;  
    }  
    head = item;  
}
```

Remove from stack

```
void removeFromListStack() {  
    struct User* current = NULL;  
    struct User* temp = NULL;  
  
    if (head == NULL) {  
        printf("No elements in list");  
        return;  
    }  
  
    current = head;  
  
    if (current != NULL) {  
        head = head->next;  
        free(current);  
    }  
}
```

Remove from queue

```
void removeFromListQueue() {
    struct User* current = NULL;
    struct User* temp = NULL;

    if (head == NULL) {
        printf("No elements in list");
        return;
    }

    if (head->next == NULL) {
        head = NULL;
        free(head);
        return;
    }

    current = head;
    while(current->next->next != NULL) current = current->next;

    temp = current->next;
    current->next = NULL;
    free(temp);
}
```



The entire program is
attached

Be carefull
with Stack and
Queue!



STACK GUN & QUEUE GUN