

[Home](#) [All Tutorials](#) [Java Core](#) [JSF](#) [Spring](#) [Hibernate](#) [Struts](#) [Android](#) [Others](#) 

# JSON Example With Jersey + Jackson



Posted on July 19, 2011 , Last modified : August 29, 2012

By [mkyong](#)

Jersey uses Jackson to convert **object to / form JSON**. In this tutorial, we show you how to convert a “Track” object into JSON format, and return it back to user.

## 1. Dependency

To make Jersey support JSON mapping, declares “**jersey-json.jar**” in Maven `pom.xml` file.

```
<dependency>
    <groupId>com.sun.jersey</groupId>
    <artifactId>jersey-server</artifactId>
    <version>1.8</version>
</dependency>

<dependency>
    <groupId>com.sun.jersey</groupId>
    <artifactId>jersey-json</artifactId>
    <version>1.8</version>
</dependency>
```

### Note

Review the downloaded dependencies in your project classpath, Jackson and related libraries are included.

### Recent Posts

# \$0.01 Web Hosting

Scalable, Secure Web Hosting. Try Our Award-Winning Service Now!



## 2. Integrate JSON with Jersey

In `web.xml`, declares "`com.sun.jersey.api.json.POJOMappingFeature`" as "`init-param`" in Jersey mapped servlet. It will make Jersey support JSON/object mapping.

```
<init-param>
  <param-name>com.sun.jersey.api.json.POJOMappingFeature</param-name>
  <param-value>true</param-value>
</init-param>
```

File : `web.xml` - full example.

```
<web-app ...>

  <servlet>
    <servlet-name>jersey-servlet</servlet-name>
    <servlet-class>com.sun.jersey.spi.container.servlet.ServletContainer</servlet-class>
    <init-param>
      <param-name>com.sun.jersey.config.property.packages</param-name>
      <param-value>com.mkyong.rest</param-value>
    </init-param>
    <init-param>
      <param-name>com.sun.jersey.api.json.POJOMappingFeature</param-name>
      <param-value>true</param-value>
    </init-param>
    <load-on-startup>1</load-on-startup>
  </servlet>

  <servlet-mapping>
    <servlet-name>jersey-servlet</servlet-name>
    <url-pattern>/rest/*</url-pattern>
  </servlet-mapping>
```



Ant - How to create a Java Project



Create a fat Jar file - Maven Assembly Plugin



Maven - Exclude log4j.properties in Jar file



Maven - Create a fat Jar file - One-JAR example



Java - Cron job to run a jar file

### Popular Tutorials



Android Tutorial



JSF 2.0 Tutorial



Spring Tutorial



Maven Tutorial



Hibernate Tutorial

&lt;/web-app&gt;

### 3. Simple Object

A simple “Track” object, later Jersey will convert it into JSON format.

```
package com.mkyong;

public class Track {

    String title;
    String singer;

    public String getTitle() {
        return title;
    }

    public void setTitle(String title) {
        this.title = title;
    }

    public String getSinger() {
        return singer;
    }

    public void setSinger(String singer) {
        this.singer = singer;
    }

    @Override
    public String toString() {
        return "Track [title=" + title + ", singer=" + singer + "]";
    }
}
```

```
}
```

## 4. JAX-RS with Jersey

Annotate the method with `@Produces(MediaType.APPLICATION_JSON)`. Jersey will use Jackson to handle the JSON conversion automatically.

```
package com.mkyong.rest;

import javax.ws.rs.Consumes;
import javax.ws.rs.GET;
import javax.ws.rs.POST;
import javax.ws.rs.Path;
import javax.ws.rs.Produces;
import javax.ws.rs.core.MediaType;
import javax.ws.rs.core.Response;

import com.mkyong.Track;

@Path("/json/metallica")
public class JSONService {

    @GET
    @Path("/get")
    @Produces(MediaType.APPLICATION_JSON)
    public Track getTrackInJSON() {

        Track track = new Track();
        track.setTitle("Enter Sandman");
        track.setSinger("Metallica");

        return track;

    }

    @POST
    @Path("/post")
    @Consumes(MediaType.APPLICATION_JSON)
    public Response createTrackInJSON(Track track) {
```

```
String result = "Track saved : " + track;  
return Response.status(201).entity(result).build();  
  
}  
  
}
```

## 5. Demo

See demo for GET and POST request.

### 1. GET method

When URI pattern “**/json/metallica/get**” is requested, the Metallica classic song “Enter Sandman” will be returned in JSON format.

```
{  
  "singer": "Metallica",  
  "title": "Enter Sandman"  
}
```



### 2. POST method

To test post request, you can create a RESTful client (refer to this [Jersey client APIs example](#)), and “post” the json format

string to URI pattern “[/json/metallica/post](#)”, the posted json string will be converted into “Track” object automatically.

## Download Source Code

Download it – [JSON-Support-Jersey-Example.zip](#) (7 KB)

## References

1. [Jackson Official Website](#)
2. [JSON Support in Jersey](#)

Tags : [integration](#) [jackson](#) [jax-rs](#) [jersey](#) [json](#)



[mkyong](#)

Founder of [Mkyong.com](#) and [HostingCompass.com](#), love Java and open source stuff. Follow him on [Twitter](#), or befriend him on [Facebook](#) or [Google Plus](#). If you like my tutorials, consider making a [donation to this charity](#), thanks.


## Related Posts

- ▶ [JSON example with RESTEasy + Jackson](#)
- ▶ [Jackson : was expecting double-quote to start field name](#)
- ▶ [Java JSON Tutorial](#)
- ▶ [Convert JSON string to Map – Jackson](#)
- ▶ [Jackson Streaming API to read and write JSON](#)

## Popular Posts

- ▶ [Top 8 Java People You Should Know](#)
- ▶ [Top 20 Java Websites](#)
- ▶ [Top 5 Free Java eBooks](#)
- ▶ [Top 10 Java Regular Expression Examples](#)
- ▶ [Top 5 Open Source Q&A Systems](#)

You might also like following tutorials :



71 Comments

Mkyong.com

Login ▾

Sort by Best ▾

Share  Favorite ★



Join the discussion...



**abhi** • a year ago

What is the “jersey-json.jar” version ?

i m facing an and error like

Jersey: No WebApplication provider is present

jersey-servlet is not able to intializate

wat is the version