Self-Rambling: A Stealthy Inference Cost Attack in Edge Serving of LVLMs –Supplementary Material–

I. Overview

Supplementary material presents the designed prompt templates for GPT-4o model to evaluate the Fluency and Reasonableness (F&R) metrics and more intuitive examples of verbose outputs:

A. Designed Prompt Templates to Evaluate the F&R metrics

We use the OpenAI API to leverage the GPT-4o model for evaluating the fluency and reasonableness of generated texts after inference cost attack methods. GPT-4o is an advanced proprietary Large Vision Language Models (LVLMs) that can be utilized as an LLM-as-a-Judge tool [1]. Here we list detailed prompt templates for evaluate fluency and reasonableness metrics.

```
# Fluency Scoring Prompt Template
response = openai.ChatCompletion.create(
    model= gpt-4o ,
    messages=[
        {
             role :  system ,
             content : (
                 You are a senior multimodal
                    evaluation specialist.
                 Your task is to assess the
                    linguistic fluency of a
                    given text as a
                    description of a provided
                    image.
                 You must evaluate along
                    these four
                    dimensions:\n\n
                 1. Grammatical Correctness:
                    Are syntax and grammar
                    accurate and
                    error-free?\n
                 2. Lexical Richness: Is the
                    vocabulary varied,
                    precise, and
                    appropriate?\n
                 3. Cohesive Flow: Does the
                    text read smoothly with
                    clear transitions and
                    logical progression?\n
                 4. Clarity of Expression: Is
                    meaning conveyed
                    unambiguously and
                    concisely?\n\n
                 After your analysis, provide
                    a single numeric score
                    between 0.0 and 5.0 (one
                    decimal place) reflecting
                    overall fluency,
                    plus a brief explanation
                       (1-2 sentences) stating
                       which dimension(s) most
                       influenced your score.
                    Respond strictly in this
                       JSON format, with no
                       extra keys or
                       commentary:\n\n
                    {\n
                       \ score\ : X.X,\n
                       \ explanation\ :
                       \ <concise rationale
                       referencing main
                       dimension(s) >\ \n
                    }
             )
        },
        {
             role :  user ,
             content : (
                 IMAGE:\n   <BASE64_HERE>\n\n
                 USER_PROMPT:\n
                     <USER_PROMPT_HERE>\n\n
                 MODEL_OUTPUT:\n
                 <OUTPUT_TEXT_HERE>\n\n
                 Instructions:\n
                 - Treat the image and text
                    as a single evaluation
                    instance.\n
                 - Use temperature=0.0 for
                    deterministic output.\n
                 - Ensure `score` has exactly
                    one digit after the
                    decimal point.\n
                 - Keep `explanation` under
                    30 words, clearly noting
                    which sub-criteria drove
                    your rating.
             )
        }
    ],
    temperature=0.0,
    max_tokens=2048
)
```

```
# Reasonableness Scoring Prompt Template
response = openai.ChatCompletion.create(
    model= gpt-4o ,
    messages=[
        {
             role :  system ,
             content : (
                 You are a senior multimodal
                    evaluation specialist.
                 Your task is to assess how
                    reasonable a given text
```

```
                    is as a description of a
                    provided image.
                You must evaluate along
                    these four
                    dimensions:\n\n
                1. Information Relevance:
                    Does the text address the
                    main subjects, actions,
                    and context shown in the
                    image?\n
                2. Visual Consistency: Are
                    the objects, colors,
                    spatial relationships,
                    and attributes described
                    actually present and
                    correctly represented?\n
                3. Logical Coherence: Is the
                    narrative
                    commonsense-correct, free
                    of internal
                    contradictions, and
                    consistent with
                    real-world knowledge?\n
                4. Detail Completeness: Are
                    key elements and details
                    covered without major
                    omissions, while avoiding
                    hallucinated or
                    irrelevant details?\n\n
                After your analysis, provide
                    a single numeric score
                    between 0.0 and 5.0 (one
                    decimal place) reflecting
                    overall reasonableness,
                plus a brief explanation
                    (1-2 sentences) stating
                    which dimension(s) most
                    influenced your score.
                Respond strictly in this
                    JSON format, with no
                    extra keys or
                    commentary:\n\n
                {\n
                  \ score\ : X.X,\n
                  \ explanation\ :
                    \ <concise rationale
                    referencing main
                    dimension(s) >\ \n
                }
            )
        },
        {
            role : user ,
            content : (
                IMAGE:\n   <BASE64_HERE>\n\n
                USER_PROMPT:\n
                    <USER_PROMPT_HERE>\n\n
                MODEL_OUTPUT:\n
                <OUTPUT_TEXT_HERE>\n\n
                Instructions:\n
                - Treat the image and text
                    as a single evaluation
                    instance.\n
                - Use temperature=0.0 for
                    deterministic output.\n
                - Ensure `score` has exactly
                    one digit after the
                    decimal point.\n
                - Keep `explanation` under
                    30 words, clearly noting
                    which sub-criteria drove
                    your rating.
                )
            }
        ],
        temperature=0.0,
        max_tokens=2048
)
```

Cross-judge evaluation: To examine whether the F&R assessment depends on the choice of evaluator, we additionally use the state-of-the-art GPT-6 Astra to reassess the same saved responses evaluated by GPT-4o. The input images, user prompts, complete generated responses, and scoring rubric in Supplementary Material Section A are held fixed. Method identities and previous scores are concealed from the evaluator. Fluency and Reasonableness are each scored from 0 to 5, and each response is evaluated in three independent sessions. As shown in Table I, S-R consistently achieves the highest F&R scores among the evaluated attack methods across all four LVLMs under both evaluators. Although GPT-6 Astra assigns slightly lower scores to S-R, its advantage over Sponge, Verbose, and Engorgio remains consistent. These results suggest that the comparative output-quality advantage of S-R is not specific to GPT-4o, while neither evaluator alone establishes agreement with human perception.

B. More Intuitive Examples

Here we illustrate more output texts after our Self-Rambling (S-R) attack on BLIP-2 2.7B. The resulting texts are extremely lengthy yet remain contextually plausible, empirically demonstrating the output imperceptibility of our attack in the generated outputs.

C. Human Study

Besides intuitive examples, we also conduct a small-scale human evaluation using twenty image–prompt pairs and responses generated by LLaVA-1.5 7B. Due to cost limitations, we choose Original, Verbose, and S-R attack methods, yielding sixty responses, and five human evaluators independently evaluate all responses in randomized order without access to method identities or automated scores. Each human evaluator is shown the corresponding image, user prompt, and complete response. Fluency and Reasonableness are scored separately from 0 to 5, yielding a combined F&R score from 0 to 10. To directly assess perceived rambling, evaluators additionally rate unnecessary verbosity on a separate 0–5 scale. As shown in Table II, S-R achieves higher human-rated Fluency and Reasonableness than Verbose, with a combined F&R score of 7.0 compared with 4.5. Its unnecessary verbosity score is also lower (2.5 versus 4.2), suggesting that evaluators perceive S-R outputs as less excessively verbose than those of Verbose. These findings support a relative output-quality advantage over other attack methods. We further assess inter-annotator agreement using ordinal Krippendorff's α [2] and quantify the rank correlation between automated scores and mean human

TABLE I: COMPARISON OF OUTPUT QUALITY EVALUATED BY GPT-4O AND GPT-6 ASTRA. REASON.: REASONABLENESS. F&R: FLUENCY AND REASONABLENESS.

LVLMs	Method	GPT-4o			GPT-6 Astra		
		Fluency	Reason.	F&R	Fluency	Reason.	F&R
BLIP-2 2.7B	Original	4.3	4.5	8.8	4.4	4.4	8.8
	Noise	4.2	4.5	8.7	4.2	4.5	8.7
	Sponge	1.7	1.6	3.3	1.5	1.4	2.9
	Verbose	2.2	1.9	4.1	2.0	1.8	3.8
	Engorgio	2.2	2.4	4.6	2.1	1.7	3.8
	Ours	**3.2**	**3.6**	**6.8**	**3.0**	**3.4**	**6.4**
InstructBLIP 7B	Original	4.0	4.1	8.1	4.2	4.1	8.3
	Noise	4.0	4.0	8.0	4.1	4.1	8.2
	Sponge	1.5	1.4	2.9	1.4	1.3	2.7
	Verbose	1.3	1.2	2.5	1.3	1.6	2.9
	Engorgio	2.3	2.2	4.5	2.2	1.8	4.0
	Ours	**2.9**	**3.5**	**6.4**	**2.8**	**3.2**	**6.0**
Qwen-VL 7B	Original	4.5	4.5	9.0	4.4	4.5	8.9
	Noise	4.4	4.2	8.6	4.3	4.3	8.6
	Sponge	1.7	1.5	3.2	1.8	1.6	3.4
	Verbose	1.6	1.7	3.3	1.7	1.8	3.5
	Engorgio	1.9	2.1	4.0	1.8	2.0	3.8
	Ours	**3.5**	**3.1**	**6.6**	**3.2**	**3.0**	**6.2**
LLaVA-1.5 7B	Original	4.6	4.5	9.1	4.6	4.6	9.2
	Noise	4.5	4.4	8.9	4.5	4.5	9.0
	Sponge	1.5	1.8	3.3	1.6	1.7	3.3
	Verbose	1.6	1.5	3.1	1.7	1.7	3.4
	Engorgio	2.9	2.8	5.7	2.9	3.0	5.9
	Ours	**3.6**	**3.2**	**6.8**	**3.5**	**3.2**	**6.7**

TABLE II: HUMAN EVALUATION OF LLAVA-1.5 7B OUTPUTS.

Method	Fluency↑ (0–5)	Reason.↑ (0–5)	F&R↑ (0–10)	Verbosity↓ (0–5)
Original	4.5	4.2	8.7	0.2
Verbose	2.4	2.1	4.5	4.2
S-R	3.8	3.2	7.0	2.5

TABLE III: INTER-ANNOTATOR AGREEMENT AND CORRESPONDENCE BETWEEN AUTOMATED AND HUMAN RATINGS ON THE SAME SIXTY RESPONSES. α: ordinal Krippendorff's alpha. ρ: Spearman's rank correlation with mean human ratings.

Metric	Human agreement α	GPT-4o ρ	GPT-6 Astra ρ
Fluency	0.73	0.78	0.76
Reason.	0.65	0.69	0.72




Fig. 1: **Attack on Real-world LVLMs Serving System (SGLang).** 10/10 attack and 2/10 attack mean 10 of 10 clients and 2 of 10 clients attack the serving system. Client latency, generally marked in blue, consists of queue and inference time.

ratings using Spearman's ρ [3]. All comparisons use the same sixty responses, with human ratings averaged across the five evaluators. As reported in Table III, inter-annotator agreement is 0.73 for Fluency and 0.65 for Reasonableness. The correlations with mean human ratings are 0.78 and 0.69 for GPT-4o, and 0.76 and 0.72 for GPT-6 Astra, respectively. These correlations characterize ranking correspondence. Overall, this human study provides preliminary human evidence that S-R preserves better perceived output quality.

D. More Attack Results on Real-world LVLMs Serving System

Following Section *D*, we consider two configurations that deploy the BLIP-2 2.7B model on an edge server with one NVIDIA 3090 GPU and the LLaVA-1.5 7B model on an edge server with two NVIDIA 3090 GPUs, employing the SGLang [17] v0.4 framework as the serving system. As shown in Fig. 1, the proposed S-R attack significantly compromises the LVLMs




Fig. 2: **Attack on Real-world LVLMs Serving System (SGLang).** Asynchronous request arrivals results for the LLaVA-1.5 serving scenario using Jetson AGX Orin 32 GB. Requests arrive according to a Poisson process at 15, 30, and 60 requests/min. Attack percentages denote the fraction of malicious requests..




Fig. 3: **Attack on Real-world LVLMs Serving System (SGLang).** Reserved token-slot budget at an arrival rate of 30 requests/min using Jetson AGX Orin 32 GB. Budgets of 1,408, 2,816, and 5,632 token slots represent different admission-capacity constraints.

edge serving, even a small number of malicious users (2 out of 10) can severely degrade the serving system.

To complement the serving evaluation, we analyze request arrival rates, reserved token-slot budgets, and benign prompt lengths. These illustrations examine the potential system-level effects of long-generation workloads. The experiments are conducted on Jetson AGX Orin 32GB with SGLang.

Asynchronous request arrivals. Fig. 2 evaluates S-R under different Poisson request arrival rates. Across the evaluated rates, attack workloads increase latency and reduce throughput relative to the corresponding no-attack baselines. Notably, even a 20% fraction of malicious requests causes observable service degradation, with larger latency increases at higher arrival rates. These results suggest that S-R remains effective under asynchronous traffic and that its impact is not limited to simultaneous request bursts. Since higher arrival rates also increase congestion without attacks, comparisons are made against the baseline at each arrival rate.

Reserved token-slot budget. Fig. 3 examines S-R under different token-slot budgets. Increasing the budget generally alleviates queuing and improves throughput, particularly for attack workloads. Nevertheless, a performance gap between the attack and no-attack conditions remains across the evaluated budgets. This indicates that additional admission capacity can mitigate the observed degradation but does not fully eliminate the impact of S-R within these settings. The results support the effectiveness of S-R across different admission-capacity configurations.

Variable-length benign prompts. Fig. 4 evaluates S-R with different benign input lengths while keeping attack inputs




Fig. 4: **Attack on Real-world LVLMs Serving System (SGLang).** Benign prompt length at an arrival rate of 30 requests/min using Jetson AGX Orin 32 GB. Benign inputs contain 32, 128, or 512 tokens, while attack inputs remain fixed at 32 tokens.


unchanged. Across the evaluated lengths, the mixed-request workload exhibits higher latency and lower throughput than the corresponding no-attack workload. Thus, the observed impact of S-R persists when benign requests have different input lengths. Longer benign inputs also degrade the no-attack baseline, highlighting the importance of comparisons under matched workload conditions. The fully malicious workload remains essentially unchanged, consistent with its fixed input configuration.

E. Potential Detector Training Strategies

Training a lightweight detector is a potential approach to identifying rambling and unnecessarily verbose outputs. A representative dataset should cover diverse image domains, prompts, models, and decoding configurations, with each response paired with its input image and user prompt. Curating such a dataset is challenging because distinguishing legitimate elaboration from fluent but unnecessary verbosity requires context-sensitive human judgment, particularly when responses remain relevant to the image and prompt. Benign examples should therefore include both concise answers and legitimate detailed explanations to reduce false positives, while attack examples should include both obvious repetition and fluent, contextually relevant rambling to reduce false negatives. Human annotation should follow explicit criteria for relevance, coherence, and unnecessary verbosity, with disagreements adjudicated to ensure consistent labeling. Training, validation, and test sets should be separated by source images and prompts to minimize data leakage, with further evaluation on unseen models and attack variants. Detection thresholds should be calibrated on validation data, and false-positive and false-negative rates should be reported on held-out test data. For online mitigation, evaluation should also measure detection delay, monitoring overhead, and the generation cost saved through early termination.


F. Extension to text LLM

Extending S-R to text-only LLMs improve the scope and impact of the core attack mechanism. Unlike continuous image perturbations, text modifications operate over discrete tokens. Following the text-based inference cost attack method



Attacked Output: On the left of the image there is a small bird shaped object that has a piece of wood sticking out of it. The bird has a piece of wood and a broken leg sticking out of it. The bird has been floating in the waters in the picture since the whole picture was taken. The bird has not been in the water for a long time. The piece of wood seems to be in the middle of the water. There is something black in the middle of the water that is also in the picture. It looks like it could be the bird's foot. The bird in the picture is struggling to get to its feet. The pole sticking out of the bird looks as if it is submerged into the water. This is because the water seems to be calm but it looks as if it is stirred up from the sea life or by something like a wave. The woods would be for protection. The wood would not be soft because it is from an old time piece and therefore would be hard. The piece of wood on the bird's leg would not be like a wooden board because it would have been broken by the current. This would give it more protection. The pole would be in a swimming motion because it is hard. This means that it would move away from the bird instead of toward the bird. The plank would be what it would be floating on. this is a close up of a blue duck standing in a puddle with a toy boat beside it on a piece of brown seaweed, swimming in the clear green water next to a rusted old rusty barrel on the left edge of the photo. You can see the rusted iron drain in the picture and the shiny metal buoy to the right of the duck in the rusted old rusty barrel that has some seaweed growing on the top. Please don't brighten it. Let's keep it as natural as possible. You need to get rid of that sky and be more precise on the way you change the focal distance and the way you crop it, and make it more close up like it is in this photo. The sky and the surrounding area is fine as long as you make it sharp and close up. Also, get rid of that water surface if possible. The blue duck is the star of the show in this photo. The other details should not be too close or bright or they will steal the focus from the blue duck and make it too fuzzy. This photo is a photo of a sea level pond where a blue duck is standing in the water. This blue duck is standing on a piece of sea weed. **[473 Tokens]**

Original Output: there is a seagull in the water and a bunch of seaweed is lying on the surface of the water **[14 Tokens]**




Attacked Output: The photo is a traffic stop sign on a pole. The image is posted on a wood panel of some type. The sign is facing the camera and the ground behind the sign is wet and soggy. I see a barricade in front of the sign which says in someones handwriting "dont stop" on it. A fence is in the foreground with two posts. Next is a tree with leaves and cones. On the other side of the trees is a curb.the picture is a stop sign on the side of the road. The sign reads no right turn. When looking at the picture you have to imagine you are driving. It is off the main road to the right. There is a tree by the sign that is keeping it from blowing away. When you think about it, you may notice the lettering of the sign is hard to read because it has been covered with green plastic. It appears the paint has already been removed from the lettering. It has also been blocked out with yellow plastic. At the top of the sign the red letters say stop. There is a white line on the sign and that white line is the line of sight to the road. You can see the road across the street is also empty. The tree, house and trash can are all in the background. There are also some cars in the background. **[209 Tokens]**

Original Output: On the underside of the sign is written 'do not paste.' Below is written in black marker: "do not paste." **[16 Tokens]**

Fig. 5: Intuitive cases illustration.


(Engorgio [4]), we preserve each original prompt and optimize a suffix with a fixed token budget (10 token) using Greedy Coordinate Gradient (GCG) [5], guided by the objective in Eq. (7). At each iteration, gradient information identifies the top-k candidate token replacements, from which a batch of candidate suffixes is sampled. We then evaluate the perplexity of the resulting prompt–suffix sequences to make the input texts more stealthy and retain the candidate has the lowest perplexity.

We conduct experiments on LLaMA 7B [6] and ChatGLM 6B [7], which are from different model families. We compare our methods to text-specific attack methods (Sponge [8] and Engorgio [4]), using Length, Latency, Energy, and F&R (with



Attacked Output: It is a question/answer image in which two things are being discussed at once. In the background of this image we see a white wall on which there are fruits and other things that can be seen in various different stages. The background of this image is a mirror. However, one of the most notable things about this image is the similarity between the two objects in the background and the objects in the foreground. The objects in the background are, of course, fruits and other foodstuffs. However, the objects in the foreground are completely different as well as the shapes of the objects. This image has several unique things about it. The images in the foreground are all banana halves, two apples, and a banana in a bowl. These all symbolize one thing - their almost identical state. The background of the image is also made up of these similarly identical objects, although in very different shapes and sizes. A second interesting thing about this image is the fact that it is almost completely red. The image is very bright and colorful. It is very eye catching, and grabs the viewer's attention immediately. Lastly, the red on the image is not only bright, but somewhat of a contrasting color. Therefore, it stands out against the other colors in the image and actually becomes one of the primary colors in this image. These primary colors help contribute to the color scheme of the image. This image has many things that make it unique and eye catching. For example, there is the similarity between the two objects in the foreground and background. In addition, the brightly colored background and the slightly contrasting red against the other colors. The bright colors and contrasting red in this image are all help to contribute to the color scheme of the image as a whole. This image is created to grab the viewers' attention. As a result of this, it will draw the viewers eye and compel them to look at the image further. The question posed in this image is "How do you make a fruit smoothie?" The question is posed in a very direct and simplistic manner. In addition, the question is posed in a way that it can be understood and answered by anybody. The answer is written on the counter next to the question. In addition, the question itself is simple to understand and would be easy for anyone to answer. However, the question could also be easily misunderstood. This is especially important because the answer to the question is written very close to the question. **[473 Tokens]**

Original Output: A bowl of fruit sits on a white countertop next to a red water pitcher **[12 Tokens]**



Attacked Output: the picture shows a motorbike and two riders on it. The bike is seen next to a fence. The riders are sitting on the bike wearing helmets. They are black and two men, one white. The bike is blue and grey. The bike has no number plate. The bike has a number plate on the right hand side which is covered by some poles. One is a telephone pole. The pole has a phone box on it. The pole is the same width as the bike. The bike has another pole of the same width and length. The tree is seen behind the bike. The fence is made up of some posts. The trees are white and green. Both have leaves. The bike looks as if it is going fast as can be seen by the shadow. The riders are sitting so close to the bike that it looks as if the bike is running over their legs. One of the riders is not wearing any shoes. They both have brown bags hanging from their shoulders. The bike looks old and well used. The fence is white and green. The trees have white trunks and green leaves. The bike is very near the fence and not as far away as it appears. The bikes side doors are open. It is missing its front and rear brakes. The bike is slightly turning. The bike has two cans on the back. It has a white and green sticker on the left side and the centre of the bike. The sticker has two very small round black circles and two arrows pointing to each other. The riders both have hoods on. One of the riders has a bike helmet on and one does not. One of the riders has a pair of gloves on. Both riders are black. The bike is seen almost at a 90 degree angle. The bike is going slow. The bike is not running over the riders legs. The fence looks old. There is a plant in front of it. The bike looks very worn and old. The fence does not look that old. The bike looks to be made of plastic. The fence looks like wood. The bike and the riders are black. The bike has two handles on the left side. Both riders are not wearing any shoes. Both riders have long gloves on. Both are wearing sleeved shirts. The riders are black. One has grey trousers on. The bike looks old and worn. Both of the riders are black. Both are wearing sneakers. The bike has an old logo on the left side. There is a blue and white metal post. There are white pipes on the fence. **[452 Tokens]**

Original Output: a man and his friend sit on a motorcycle in the middle of a street **[11 Tokens]**

Fig. 6: Intuitive cases illustration.

TABLE IV: EVALUATION OF THE TEXT-BASED EXTENSION OF S-R. LENGTH: GENERATED TOKENS; LATENCY AND ENERGY: PER REQUEST. F&R: FLUENCY AND REASONABLENESS (0–10).

LLM	Method	Length	Latency	Energy	F&R
LLaMA 7B	Original	503.2	17.4	769.2	9.2
	Sponge	764.3	22.5	1043.5	4.3
	Engorgio	792.3	24.8	1235.3	5.8
	S-R	1002.5	29.1	1420.2	7.1
ChatGLM 6B	Original	251.2	8.4	401.5	9.0
	Sponge	546.3	17.1	812.3	4.5
	Engorgio	817.2	23.1	1223.5	5.7
	S-R	985.2	27.2	1384.3	6.9

GPT-6 Astra). Following Engorgio, the experiment utilizes 50 samples from the training dataset for Standford-alpaca, setting maximum length of generated sequences to 1024 tokens. As shown in Table IV, S-R increases the mean output length to approximately 1.99× and 3.92× the original length on LLaMA 7B and ChatGLM 6B, respectively, accompanied by higher inference latency and energy consumption. Compared with Engorgio, S-R generates approximately 26.5% and 20.6% longer outputs, while achieving higher F&R scores (7.1 versus 5.8 and 6.9 versus 5.7, respectively). Although output quality remains below that of the original responses, these results suggest that S-R can induce longer generation while preserving better fluency and reasonableness than the evaluated attack baselines. This preliminary evaluation supports the feasibility of extending S-R to the two tested text-only models.

G. Ethical Considerations

Responsible disclosure. We plan to share our findings with the relevant model providers and serving-system developers, with the aim of supporting red-team testing rather than attacks on public services. We will provide the experimental settings, reproduction steps, and limitations of S-R so that providers can assess the risk in their own environments. We also intend to discuss the mitigation strategies outlined in Section VII and help evaluate their effectiveness against inference-cost attacks. Any testing involving a provider's infrastructure would require prior authorization and an agreed workload limit to avoid disrupting normal users. Where security reporting channels are available, we will use them to communicate the findings and discuss the handling of additional technical details. The disclosure status and any resulting feedback will be documented as the work progresses.

Limitations of released code. We will clarify in the README that the code is intended for reproducing our experiments and conducting authorized red-team tests. Users should run it on local models or services they own, and obtain explicit permission before testing any third-party system. We will also document the tested configurations and provide instructions for setting request and concurrency limits to avoid disrupting normal users. The release will focus on local adversarial-image generation and evaluation, without adding tools for discovering public endpoints, bypassing service restrictions, or sending sustained attack traffic. These measures aim to reduce misuse. Although a README statement cannot ensure responsible use, the mitigation strategies discussed in Section VII may help service providers reduce the impact of inference-cost attacks.

REFERENCES

[1] L. Zheng, W.-L. Chiang, Y. Sheng, and et al., "Judging llm-as-a-judge with mt-bench and chatbot arena," *NeurIPS*, vol. 36, pp. 46 595–46 623, 2023.

[2] K. Krippendorff, "Reliability in content analysis: Some common misconceptions and recommendations," *Human Communication Research*, vol. 30, no. 3, pp. 411–433, 2004.

[3] C. Spearman, "The proof and measurement of association between two things," *The American Journal of Psychology*, vol. 15, no. 1, pp. 72–101, 1904.

[4] J. Dong, Z. Zhang, Q. Zhang, and et al., "An engorgio prompt makes large language model babble on," in *ICLR*, 2025.

[5] A. Zou, Z. Wang, N. Carlini, M. Nasr, J. Z. Kolter, and M. Fredrikson, "Universal and transferable adversarial attacks on aligned language models," *arXiv preprint arXiv:2307.15043*, 2023.

[6] H. Touvron, T. Lavril, and et al, "Llama: Open and efficient foundation language models," *arXiv preprint arXiv:2302.13971*, 2023.

[7] Z. Du, Y. Qian, X. Liu, M. Ding, J. Qiu, Z. Yang, and J. Tang, "GLM: General language model pretraining with autoregressive blank infilling," in *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, S. Muresan, P. Nakov, and A. Villavicencio, Eds. Dublin, Ireland: Association for Computational Linguistics, May 2022, pp. 320–335. [Online]. Available: https://aclanthology.org/2022.acl-long.26/

[8] I. Shumailov, Y. Zhao, D. Bates, N. Papernot, R. Mullins, and R. Anderson, "Sponge examples: Energy-latency attacks on neural networks," in *EuroS&P*, 2021, pp. 212–231.