
Table of Contents

Introduction	1.1
2.2.9.1	1.2

CRM数据字典

CRM数据字典详细描述

2.2.9.1

数据库词典

= 数据库tables列表 =

- APP:base
 - base_app_content()
 - base_apps()
 - base_cache_expires()
 - base_files()
 - base_kvstore()
 - base_network()
 - base_queue()
 - base_rpcnotify()
 - base_rpcpoll()
 - base_task()
- APP:content
 - content_article_bodys(文章节点表)
 - content_article_indexs(文章主表)
 - content_article_nodes(文章节点表)
- APP:dbeav
 - dbeav_meta_register(meta关联表)
 - dbeav_meta_value_datetime(meta系统datetime类型存值表)
 - dbeav_meta_value_decimal(meta系统decimal类型)
 - dbeav_meta_value_int(meta系统int类型存值表)
 - dbeav_meta_value_longtext(meta系统text类型存值表)
 - dbeav_meta_value_text(meta系统text类型存值表)
 - dbeav_meta_value_varchar(meta系统varchar类型存值表)
 - dbeav_recycle()
- APP:desktop
 - desktop_filter()
 - desktop_flow(信息表)
 - desktop_hasrole()
 - desktop_menus()
 - desktop_recycle()
 - desktop_role_flow(信息表)
 - desktop_roles()
 - desktop_surveillance()
 - desktop_tag()
 - desktop_tag_rel()
 - desktop_user_flow(信息表)
 - desktop_users(商店后台管理员表)
- APP:ecgoods
 - ecgoods_brand(商品品牌)
 - ecgoods_buy_times(商品重复购买率)
 - ecgoods_group(商品分组)
 - ecgoods_shop_goods(商品表)
 - ecgoods_shop_goods_cat(类别属性值有限表)
 - ecgoods_shop_products()
- APP:ecorder
 - ecorder_api_log(api日志)
 - ecorder_chat_logs()
 - ecorder_credit_exchange()

- [ecorder_exchange_orders](#)(积分兑换订单)
- [ecorder_fx_order_items\(\)](#)
- [ecorder_fx_order_objects\(\)](#)
- [ecorder_fx_orders\(\)](#)
- [ecorder_gift_logs\(\)](#)
- [ecorder_gift_rule\(\)](#)
- [ecorder_gift_set_logs\(\)](#)
- [ecorder_logi_info](#)(订单物流数据)
- [ecorder_login_log\(\)](#)
- [ecorder_member_products\(\)](#)
- [ecorder_order_items\(\)](#)
- [ecorder_order_objects\(\)](#)
- [ecorder_order_pmt\(\)](#)
- [ecorder_orders\(\)](#)
- [ecorder_orders_manual](#)(手工订单表)
- [ecorder_point_set_logs\(\)](#)
- [ecorder_refunds](#)(支付记录)
- [ecorder_relate_products\(\)](#)
- [ecorder_shop\(\)](#)
- [ecorder_shop_agents\(\)](#)
- [ecorder_shop_analysis](#)(店铺分析表)
- [ecorder_shop_channel](#)(渠道分析)
- [ecorder_shop_credit\(\)](#)
- [ecorder_shop_gift\(\)](#)
- [ecorder_shop_lv](#)(店铺客户等级规则)
- [ecorder_shop_vcard\(\)](#)
- [ecorder_sms_sign\(\)](#)
- [ecorder_tb_refunds](#)(淘宝退款)
- [ecorder_trade_rates](#)(交易评价信息)
- [APP:ectools](#)
 - [ectools_analysis\(\)](#)
 - [ectools_analysis_logs\(\)](#)
 - [ectools_currency\(\)](#)
 - [ectools_order_bills\(\)](#)
 - [ectools_payments](#)(支付记录)
 - [ectools_refunds](#)(支付记录)
 - [ectools_regions\(\)](#)
- [APP:image](#)
 - [image_image\(\)](#)
 - [image_image_attach\(\)](#)
- [APP:market](#)
 - [market_active\(\)](#)
 - [market_active_abc](#)(营销活动效果评估abc拆分数据)
 - [market_active_assess\(\)](#)
 - [market_active_cycle\(\)](#)
 - [market_active_cycle_log\(\)](#)
 - [market_active_member\(\)](#)
 - [market_active_member_cycle\(\)](#)
 - [market_active_member_plan\(\)](#)
 - [market_active_plan\(\)](#)
 - [market_active_review](#)(营销活动监控)
 - [market_activity_edm_queue\(\)](#)
 - [market_activity_m_queue\(\)](#)

- `market_activity_m_queue_finished()`
- `market_api_log`(api日志)
- `market_callplan()`
- `market_callplan_members()`
- `market_coupon_ecstore()`
- `market_coupon_ecstore_sendlog()`
- `market_coupon_ecstore_sendlog_item`(优惠券发送记录明细)
- `market_coupon_ecstore_used()`
- `market_coupon_sent`(优惠券发送记录)
- `market_coupon_used()`
- `market_coupons()`
- `market_edm()`
- `market_edm_blacklist()`
- `market_edm_log()`
- `market_edm_tclass()`
- `market_edm_template_type()`
- `market_edm_templates()`
- `market_exchange_items`(可兑换物品)
- `market_exchange_order`(优惠券兑换日志)
- `market_fx_activity()`
- `market_fx_sms()`
- `market_fx_sms_log()`
- `market_sms()`
- `market_sms_blacklist()`
- `market_sms_deduction_record()`
- `market_sms_deduction_record_item()`
- `market_sms_log()`
- `market_sms_op_record()`
- `market_sms_order_log()`
- `market_sms_template_type()`
- `market_sms_templates()`
- `market_wx_bind_member_log`(手机号绑定会员日志)
- `market_wx_chat`(微信聊天记录表)
- `market_wx_due`(微信预约)
- `market_wx_due_orders`(微信预约订单)
- `market_wx_event`(微信客户事件表)
- `market_wx_integral_lottery()`
- `market_wx_integral_lotteryinfo()`
- `market_wx_integral_lotterylog()`
- `market_wx_join_log`(微信用户参与日志表)
- `market_wx_keywords`(微信用户关键字总表)
- `market_wx_keywords_autoreply`(微信用户关键字回复规则表)
- `market_wx_member`(微信客户关联表)
- `market_wx_msg_send_all`(微信群发消息)
- `market_wx_msg_send_all_log`(微信群发素材发送log)
- `market_wx_news`(图文素材)
- `market_wx_news_img`(图文图片)
- `market_wx_plugins`(微信用户互动插件规则表)
- `market_wx_point_log`(积分日志表)
- `market_wx_points_buy()`
- `market_wx_points_buylog()`
- `market_wx_sign_in_log`(微信客户签到日志表)
- `market_wx_store_subbranch()`

- [market_wx_survey](#)(问卷调查表)
- [market_wx_survey_items](#)(问卷调查题目)
- [market_wx_survey_log](#)(问卷调查快照)
- [market_wx_survey_result](#)(问卷调查结果)
- [market_wx_unbind_member_log](#)(手机号解绑会员日志)
- [market_wx_vote](#)(微信投票)
- [market_wx_vote_result](#)(微信投票结果)
- [market_wxautoreply](#)(微信用户规则表)
- [APP:marketcenter](#)
 - [marketcenter_cards](#)(卡券信息)
 - [marketcenter_consume_cards](#)(卡券核销)
 - [marketcenter_get_cards](#)(卡券领取)
- [APP:openapi](#)
 - [openapi_api_log](#)(api日志)
 - [openapi_setting](#)(开放数据接口配置表)
- [APP:pam](#)
 - [pam_account\(\)](#)
 - [pam_auth\(\)](#)
 - [pam_log\(\)](#)
- [APP:plugins](#)
 - [plugins_hits\(\)](#)
 - [plugins_log\(\)](#)
 - [plugins_orders\(\)](#)
 - [plugins_plugins\(\)](#)
 - [plugins_sms_logs\(\)](#)
 - [plugins_trades\(\)](#)
- [APP:taocrm](#)
 - [taocrm_all_points_log\(\)](#)
 - [taocrm_app\(\)](#)
 - [taocrm_app_members\(\)](#)
 - [taocrm_cache_area](#)(报表缓存(地域分析))
 - [taocrm_cache_dashboard](#)(首页缓存)
 - [taocrm_cache_hour](#)(报表缓存(购买时段))
 - [taocrm_cache_members](#)(报表缓存(客户相关报表))
 - [taocrm_cache_rfm](#)(报表缓存(购买时段))
 - [taocrm_cache_tree](#)(报表缓存(购买时段))
 - [taocrm_fx_member_group](#)(客户分组表)
 - [taocrm_fx_members](#)(分销客户表)
 - [taocrm_java_info\(\)](#)
 - [taocrm_member_all_analysis\(\)](#)
 - [taocrm_member_analysis\(\)](#)
 - [taocrm_member_analysis_day\(\)](#)
 - [taocrm_member_attr](#)(会员自定义属性)
 - [taocrm_member_benefits](#)(客户标签表)
 - [taocrm_member_benefits_item](#)(客户标签表)
 - [taocrm_member_benefits_log\(\)](#)
 - [taocrm_member_bind_queue](#)(客户去重任务)
 - [taocrm_member_card](#)(会员卡)
 - [taocrm_member_card_make_log](#)(会员卡生成记录)
 - [taocrm_member_card_template](#)(会员卡模板)
 - [taocrm_member_card_type\(\)](#)
 - [taocrm_member_caselog\(\)](#)
 - [taocrm_member_caselog_category\(\)](#)

- taocrm_member_contacts()
- taocrm_member_export()
- taocrm_member_export_log()
- taocrm_member_ext(会员扩展属性)
- taocrm_member_fav()
- taocrm_member_group(客户分组表)
- taocrm_member_import(导入客户表)
- taocrm_member_import_batch(导入客户分组批次表)
- taocrm_member_import_group(导入客户分组表)
- taocrm_member_import_sms(外部客户短信发送记录)
- taocrm_member_import_sms_log()
- taocrm_member_level(全局客户等级)
- taocrm_member_orders_day()
- taocrm_member_overall_property()
- taocrm_member_point_log()
- taocrm_member_point_type()
- taocrm_member_points()
- taocrm_member_property()
- taocrm_member_receivers()
- taocrm_member_tag(客户标签表)
- taocrm_member_to_tag(客户标签关联表)
- taocrm_members(客户表)
- taocrm_members_recommend(推荐表)
- taocrm_members_recommend_no()
- taocrm_members_rule_log(会员等级规则设置日志)
- taocrm_points_log(积分日志表)
- taocrm_rebate(返利发放记录表)
- taocrm_rebate_cycle(返利周期表)
- taocrm_rebate_rule(返点规则设置)
- taocrm_sms_log()
- taocrm_stored_value()
- taocrm_stored_value_log()
- taocrm_wangwang_shop()
- taocrm_wangwang_shop_chat_log()

app:base tables

base_app_content

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
content_id	content_id	mediumint(8) unsigned	N		Y
content_type	content_type	varchar(80)	Y		N
app_id	app_id	varchar(32)	Y		N
content_name	content_name	varchar(80)	N		N
content_title	content_title	varchar(100)	N		N

content_path	content_path	varchar(255)	N		N
ordernum	排序	smallint(4)	N	50	N
input_time	加载时间	int(10) unsigned	N		N
disabled	是否失效	enum('true','false')	N	false	N

- 索引

Key name	Column names	Unique	Comment
primary	content_id	Y	
idx_c_app_id	app_id	N	

base_apps

- 表结构


ColumnName	Comment	Type
app_id	程序目录	varchar(32)
app_name	应用程序	varchar(50)
debug_mode	调试模式	enum('true','false')
app_config	app_config	text
status	状态 installed: 已安装, 未启动;resolved: 已配置;starting: 正在启动;active: 运行中;stopping: 正在关闭;uninstalled: 尚未安装;broken: 已损坏;paused: 已暂停;	enum('installed','resolved','starting','active','stopping','uninstalled','broken')
webpath	webpath	varchar(20)
description	说明	varchar(255)
local_ver	当前版本	varchar(20)
remote_ver	最新版本	varchar(20)
author_name	author_name	varchar(100)
author_url	author_url	varchar(100)
author_email	author_email	varchar(100)
dbver	dbver	varchar(32)
remote_config	remote_config	longtext

- 索引

Key name	Column names	Unique	Comment

primary	app_id	Y
---------	--------	---

base_cache_expires



- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
type	type	varchar(20)	Y		N
name	name	varchar(255)	Y		N
expire	expire	int(10) unsigned	Y		N
app	app	varchar(50)	Y		N

- 索引

Key name	Column names	Unique	Comment
primary	type, name	Y	
ind_name	name	N	

base_files



- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
file_id	file_id	mediumint(8) unsigned	N		Y
file_path	file_path	varchar(255)	N		N
file_type	file_type private::public::	enum('private','public')	N	public	N
last_change_time	last_change_time	int(10) unsigned	N		N

- 索引

Key name	Column names	Unique	Comment
primary	file_id	Y	

base_kvstore



- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	mediumint(8) unsigned	N		Y
prefix	prefix	varchar(255)	Y		N
key	key	varchar(255)	Y		N

value	value	longtext	N		N
dateline	dateline	int(10) unsigned	N		N
ttl	ttl	int(10) unsigned	N	0	N

- 索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_prefix	prefix	N	
ind_key	key	N	

base_network

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
node_id	id	mediumint(8) unsigned	Y		Y
node_name	名称	varchar(255)	Y		N
node_url	网址	varchar(100)	Y		N
node_api	api地址	varchar(100)	Y		N
link_status	关联类型 active:正常;group:维护;wait:等待对方确认...;	enum('active','group','wait')	Y	wait	N
node_detail	说明	varchar(255)	N		N
token	验证码	varchar(32)	N		N

- 索引

Key name	Column names	Unique	Comment
primary	node_id	Y	

base_queue

- 表结构

ColumnName	Comment	Type	Not null	Default	Auto
queue_id	ID	mediumint(8) unsigned	Y		Y
queue_title	队列名称	varchar(50)	Y		N
	状态 running:运行中;hibernate:休眠				

	中;paused: 已暂停; failure:执行失败;				
worker	worker	varchar(200)	Y		N
start_time	任务产生时间	int(10) unsigned	Y		N
worker_active	上次运行时间	int(10) unsigned	N		N
total	队列长度	mediumint(8) unsigned	N		N
remaining	剩余任务	mediumint(8) unsigned	N		N
cursor_id	执行游标	varchar(255)	Y	0	N
runkey	runkey	char(32)	N		N
task_name	永久任务名称	varchar(50)	N		N
params	参数，通常就是filter	longtext	Y		N
errmsg	错误信息	varchar(255)	N		N

● 索引

Key name	Column names	Unique	Comment
primary	queue_id	Y	
ind_worker	worker	N	
ind_worker_active	worker_active	N	
ind_status	status	N	

base_rpcnotify

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	ID	bigint(20) unsigned	Y		Y
callback	API	varchar(200)	Y		N
rsp	状态 succ:成功;fail:失败;	enum('succ','fail')	Y		N
msg	信息	varchar(255)	Y		N
notifytime	通知时间	int(10) unsigned	Y		N
status	状态 true:已读;false:未读;	enum('true','false')	Y	false	N

● 索引

Key name	Column names	Unique	Comment
primary	id	Y	

ind_status	status	N
------------	--------	---

base_rpcpoll



• 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	序号	varchar(32)	N		N
process_id	进程序号	varchar(32)	N		N
type	类型 request:发出请求;response:接收的请求;	enum('request','response')	N		N
calltime	请求或被请求时间	int(10) unsigned	N		N
network	连接节点名称	mediumint(8) unsigned	N		N
method	同步的接口名称	varchar(100)	N		N
params	params	longtext	N		N
callback	回调地址	varchar(200)	N		N
callback_params	callback_params	text	N		N
result	请求响应的结果	text	N		N
fail_times	失败的次数	int(10)	Y	1	N
status	交互状态 succ:成功;failed:失败;	enum('succ','failed')	Y	failed	N

• 索引

Key name	Column names	Unique	Comment
ind_rpc_task_id	id, type, process_id	Y	
ind_rpc_response_id	process_id	N	
idx_c_network	network	N	

base_task



• 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
task	task	varchar(100)	N		N
minute	minute	int(10) unsigned	N		N
hour	hour	int(10) unsigned	N		N
day	day	int(10) unsigned	N		N

week	week	int(10) unsigned	N		N
month	month	int(10) unsigned	N		N

- 索引

Key name	Column names	Unique	Comment
primary	task	Y	

app:content tables

content_article_bodys

文章节点表

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	自增id	mediumint(8) unsigned	Y		Y
article_id	文章id	mediumint(8) unsigned	Y		N
tmpl_path	单独页模板	varchar(50)	N		N
content	文章内容	longtext	N		N
seo_title	SEO标题	varchar(100)	N		N
seo_description	SEO简介	mediumtext	N		N
seo_keywords	SEO关键字	varchar(200)	N		N
goods_info	关联产品	longtext	N		N
hot_link	热词	longtext	N		N
length	内容长度	int(10) unsigned	N		N
image_id	图片id	varchar(32)	N		N

- 索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_article_id	article_id	Y	
idx_c_article_id	article_id	N	

content_article_indexs

文章主表

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
article_id	文章ID	mediumint(8) unsigned	Y		Y

title	文章标题	varchar(200)	Y		N
type	文章类型 1:普通文章;2:单独页;3:自定义页面;	enum('1','2','3')	Y	1	N
node_id	节点	mediumint(8) unsigned	Y		N
author	作者	varchar(50)	N		N
pubtime	发布时间（无需精确到秒）	int(10) unsigned	N		N
uptime	更新时间（精确到秒）	int(10) unsigned	N		N
level	文章等级 1:普通;2:重要;	enum('1','2')	Y	1	N
ifpub	发布	enum('true','false')	Y	false	N
pv	pageview	int(10) unsigned	N	0	N
disabled	是否失效	enum('true','false')	Y	false	N

● 索引

Key name	Column names	Unique	Comment
primary	article_id	Y	
ind_node_id	node_id	N	
ind_ifpub	ifpub	N	
ind_pubtime	pubtime	N	
ind_level	level	N	
ind_disabled	disabled	N	
ind_pv	pv	N	
idx_c_node_id	node_id	N	

content_article_nodes

文章节点表

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
node_id	节点id	mediumint(8) unsigned	Y		Y
parent_id	父节点	mediumint(8) unsigned	Y	0	N
node_depth	节点深度	tinyint(1)	Y	0	N
node_name	节点名称	varchar(50)	Y		N
node_pagename	节点页面名	varchar(50)	N		N
node_path	节点路径	varchar(200)	N		N
seo_title	SEO标题	varchar(100)	N		N
seo_description	SEO简介	mediumtext	N		N

seo_keywords	SEO关键字	varchar(200)	N		N
has_children	是否存在子节点	enum('true','false')	Y	false	N
ifpub	发布	enum('true','false')	Y	false	N
hasimage	图	enum('true','false')	Y	false	N
ordernum	排序	mediumint(8) unsigned	Y	0	N
homepage	主页	enum('true','false')	N	false	N
uptime	修改时间	int(10) unsigned	N		N
tmpl_path	单独页模板	varchar(50)	N		N
list_tmpl_path	列表页模板	varchar(50)	N		N
content	文章内容	longtext	N		N
disabled	是否失效	enum('true','false')	Y	false	N

• 索引

Key name	Column names	Unique	Comment
primary	node_id	Y	
ind_disabled	disabled	N	
ind_ordernum	ordernum	N	

app:dbeav tables

dbeav_meta_register

meta关联表

• 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
mr_id	meta id	mediumint(8) unsigned	Y		Y
tbl_name	表名	varchar(100)	Y		N
pk_name	主表主键名	varchar(255)	Y		N
col_name	字段名	varchar(100)	Y		N
col_type	字段类型	varchar(255)	Y		N
col_desc	字段描述	longtext	Y		N

• 索引

Key name	Column names	Unique	Comment
primary	mr_id	Y	
idx_tbl_name	tbl_name	N	
idx_col_name	col_name	N	
idx_tbl_col	tbl_name, col_name	N	

dbeav_meta_value_datetime

meta系统**datetime**类型存值表

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
mr_id	关联表的id id	mediumint(8) unsigned	Y		N
pk	查询结果集定位基准	mediumint(8) unsigned	Y		N
value	meta值	datetime NOT NULL default '0000-00-00 00:00:00'	Y		N

- 索引

Key name	Column names	Unique	Comment
primary	mr_id, pk	Y	
ind_value	value	N	

dbeav_meta_value_decimal

meta系统**decimal**类型

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
mr_id	关联表的id id	mediumint(8) unsigned	Y		N
pk	查询结果集定位基准	mediumint(8) unsigned	Y		N
value	meta值	decimal(12,4) NOT NULL default '0.0000'	Y		N

- 索引

Key name	Column names	Unique	Comment
primary	mr_id, pk	Y	
ind_value	value	N	

dbeav_meta_value_int

meta系统**int**类型存值表

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
mr_id	关联表的id id	mediumint(8) unsigned	Y		N
pk	查询结果集定位	mediumint(8)	Y		N

pk	基准	unsigned	Y		N
value	meta值	int(11) NOT NULL default '0'	Y		N

- 索引

Key name	Column names	Unique	Comment
primary	mr_id, pk	Y	
ind_value	value	N	

dbeav_meta_value_longtext

meta系统text类型存值表

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
mr_id	关联表的id id	mediumint(8) unsigned	Y		N
pk	查询结果集定位基准	mediumint(8) unsigned	Y		N
value	meta值	longtext NOT NULL	Y		N

- 索引

Key name	Column names	Unique	Comment
primary	mr_id, pk	Y	

dbeav_meta_value_text

meta系统text类型存值表

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
mr_id	关联表的id id	mediumint(8) unsigned	Y		N
pk	查询结果集定位基准	mediumint(8) unsigned	Y		N
value	meta值	text NOT NULL	Y		N

- 索引

Key name	Column names	Unique	Comment
primary	mr_id, pk	Y	

dbeav_meta_value_varchar

meta系统varchar类型存值表

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
mr_id	关联表的id id	mediumint(8) unsigned	N		N
pk	查询结果集定位基准	mediumint(8) unsigned	Y		N
value	meta值	varchar(255) NOT NULL default ''	Y		N

- 索引

Key name	Column names	Unique	Comment
primary	mr_id, pk	Y	
ind_value	value	N	

dbeav_recycle

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
item_id	item_id	mediumint(8) unsigned	Y		Y
item_title	名称	varchar(200)	Y		N
item_type	类型	varchar(80)	Y		N
drop_time	删除时间	int(10) unsigned	Y		N
item_sdf	item_sdf	longtext	Y		N

- 索引

Key name	Column names	Unique	Comment
primary	item_id	Y	

app:desktop tables

desktop_filter

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
filter_id	filter_id	mediumint(8) unsigned	Y		Y
filter_name	筛选器名	varchar(20)	N		N
user_id	用户id	mediumint(8) unsigned	Y		N
model	表	varchar(100)	Y		N
filter_query	筛选条件	text	N		N

ctl	控制器	varchar(100)	Y		N
app	控制器	varchar(50)	Y		N
act	方法	varchar(50)	Y		N
create_time	建立时间	int(10) unsigned	Y	0	N

- 索引

Key name	Column names	Unique	Comment
primary	filter_id	Y	

desktop_flow

信息表

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
flow_id	序号	mediumint(8) unsigned	Y		Y
flow_from	发送者 user: 用户;system: 系统;internet: 站外;	enum('user','system','internet')	Y	system	N
from_id	from_id	mediumint(8) unsigned	N	0	N
subject	消息标题	varchar(50)	Y		N
flow_desc	消息描述	varchar(100)	Y		N
body	内容本体	text	Y		N
flow_ip	flow_ip	varchar(20)	Y		N
send_mode	send_mode direct:直送;broadcast:广播;fetch:收取;	enum('direct','broadcast','fetch')	Y	direct	N
flow_type	flow_type	varchar(32)	Y	default	N
send_time	send_time	int(10) unsigned	Y		N

- 索引

Key name	Column names	Unique	Comment
primary	flow_id	Y	

desktop_hasrole

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
user_id	user_id	mediumint(8) unsigned	Y		N

role_id	role_id	mediumint(8) unsigned	Y		N
---------	---------	-----------------------	---	--	---

- 索引

Key name	Column names	Unique	Comment
primary	user_id, role_id	Y	

desktop_menus

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
menu_id	menu_id	mediumint(8) unsigned	N		Y
menu_type	menu_type	varchar(80)	Y		N
app_id	app_id	varchar(32)	Y		N
workground	workground	varchar(200)	N		N
menu_group	menu_group	varchar(200)	N		N
menu_title	menu_title	varchar(100)	N		N
menu_path	menu_path	varchar(255)	N		N
disabled	是否失效	enum('true','false')	N	false	N
display	display	enum('true','false')	N	false	N
permission	permission	varchar(80)	N		N
addon	addon	text	N		N
target	target	varchar(10)	N		N
menu_order	menu_order	mediumint(8) unsigned	N	0	N

- 索引

Key name	Column names	Unique	Comment
primary	menu_id	Y	
ind_menu_type	menu_type	N	
ind_menu_path	menu_path	N	
ind_menu_order	menu_order	N	
idx_c_app_id	app_id	N	

desktop_recycle

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
item_id	item_id	mediumint(8) unsigned	Y		Y
item_title	名称	varchar(200)	N		N

item_type	类型	varchar(80)	Y		N
app_key	应用	varchar(80)	Y		N
drop_time	删除时间	int(10) unsigned	Y		N
item_sdf	item_sdf	longtext	Y		N

- 索引

Key name	Column names	Unique	Comment
primary	item_id	Y	

desktop_role_flow

信息表

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
role_id	role_id	mediumint(8) unsigned	Y		N
flow_id	flow_id	mediumint(8) unsigned	Y		N

- 索引

Key name	Column names	Unique	Comment
primary	role_id, flow_id	Y	

desktop_roles

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
role_id	工作组id	mediumint(8) unsigned	Y		Y
role_name	角色名	varchar(100)	Y		N
workground	工作场景	text	N		N

- 索引

Key name	Column names	Unique	Comment
primary	role_id	Y	

desktop_surveillance

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	mediumint(8)	Y		Y

id	id	unsigned	Y		Y
task_name	任务名	varchar(50)	Y		N
cycle	周期	varchar(20)	Y		N
begin_time	开始时间	int(10) unsigned	N	0	N
end_time	结束时间	int(10) unsigned	N	0	N
time_consuming	耗时(秒为单位)	mediumint(8) unsigned	Y	0	N
task_desc	任务描述	varchar(200)	Y		N

● 索引

Key name	Column names	Unique	Comment
primary	id	Y	

desktop_tag

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
tag_id	tag_id	mediumint(8) unsigned	Y		Y
tag_name	标签名	varchar(20)	Y		N
tag_mode	标签类型 normal:普通标签;filter:自动标签;	enum('normal','filter')	Y	normal	N
app_id	应用	varchar(32)	Y		N
tag_type	标签对象	varchar(20)	Y		N
tag_abbr	标签备注	varchar(150)	Y		N
tag_bgcolor	标签背景颜色	varchar(7)	Y		N
tag_fgcolor	标签字体颜色	varchar(7)	Y		N
tag_filter	标签条件	varchar(255)	Y		N
rel_count	rel_count	mediumint(8) unsigned	Y	0	N

● 索引

Key name	Column names	Unique	Comment
primary	tag_id	Y	
ind_type	tag_type	N	
ind_name	tag_name	N	

desktop_tag_rel

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
tag_id	tag_id	mediumint(8) unsigned	Y	0	N
rel_id	rel_id	varchar(32)	Y	0	N
app_id	应用	varchar(32)	Y		N
tag_type	标签对象	varchar(20)	Y		N

● 索引

Key name	Column names	Unique	Comment
primary	tag_id, rel_id	Y	

desktop_user_flow

信息表

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
user_id	user_id	mediumint(8) unsigned	Y		N
flow_id	flow_id	mediumint(8) unsigned	Y		N
unread	unread	enum('true','false')	Y	true	N
note	note	varchar(50)	N		N
has_star	has_star	enum('true','false')	Y	false	N
keep_unread	keep_unread	enum('true','false')	Y	false	N

● 索引

Key name	Column names	Unique	Comment
primary	user_id, flow_id	Y	

desktop_users

商店后台管理员表

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
user_id	用户名	mediumint(8) unsigned	Y		N
status	启用	enum('0','1')	Y	0	N
name	姓名	varchar(30)	N		N
lastlogin	最后登录时间	int(10) unsigned	Y	0	N
config	config	longtext	N		N
favorite	favorite	longtext	N		N
super	超级管理员	enum('0','1')	Y	0	N

lastip	lastip	varchar(20)	N		N
logincount	登陆次数	mediumint(8) unsigned	Y	0	N
disabled	是否失效	enum('true','false')	Y	false	N
op_no	编号	varchar(50)	N		N
memo	备注	text	N		N
customer_delete	客户删除权限	enum('0','1')	N	0	N

- 索引

Key name	Column names	Unique	Comment
primary	user_id	Y	
ind_disabled	disabled	N	

app:ecgoods tables

ecgoods_brand

商品品牌

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
brand_id	品牌ID	int(10) unsigned	Y		Y
brand_name	品牌名称	varchar(100)	Y		N
parent_id	父品牌ID	int(10) unsigned	N		N
cat_path	分类路径(从根至本节点的路径,逗号分隔,首部有逗号)	varchar(100)	N	,	N
is_leaf	是否叶子结点 (true: 是; false: 否)	enum('true','false')	N	false	N
disabled	是否失效	enum('true','false')	N	false	N
p_order	排序	mediumint(8) unsigned	N		N
goods_count	包含商品数	mediumint(8) unsigned	N	0	N
goods_id	商品ID	varchar(5000)	N		N
avg_price	平均价格	decimal(20,2)	N	0	N
total_num	销售数量	mediumint(8) unsigned	N	0	N
total_amount	销售金额	decimal(20,2)	N	0	N
buy_person	购买客户数	mediumint(8) unsigned	N	0	N
create_time	创建时间	int(10) unsigned	N		N
update_time	数据更新时间	int(10) unsigned	N		N

child_count	child_count	mediumint(8) unsigned	N	0	N
-------------	-------------	--------------------------	---	---	---

- 索引

Key name	Column names	Unique	Comment
primary	brand_id	Y	
ind_brand_name	brand_name	N	

ecgoods_buy_times

商品重复购买率

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	ID	int(10) unsigned	Y		Y
bn	商家编码	varchar(50)	N	0	N
name	商品名称	varchar(100)	N	0	N
one_times_person	购买单次客户	mediumint(8) unsigned	N	0	N
two_times_person	购买2次客户	mediumint(8) unsigned	N	0	N
two_times_days	购买2次周期(天)	mediumint(8) unsigned	N	0	N
thr_times_person	购买3次客户	mediumint(8) unsigned	N	0	N
thr_times_days	购买3次周期(天)	mediumint(8) unsigned	N	0	N
for_times_person	购买大于4次客户	mediumint(8) unsigned	N	0	N
for_times_days	购买大于4次周期(天)	mediumint(8) unsigned	N	0	N
update_time	数据更新时间	int(10) unsigned	N	0	N

- 索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_update_time	update_time	N	

ecgoods_group

商品分组

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement

group_id	ID	int(10) unsigned	Y		Y
group_name	分组名称	varchar(100)	Y		N
parent_id	父分组ID	int(10) unsigned	N		N
cat_path	分类路径(从根至本结点的ID路径,逗号分隔,首部有逗号)	varchar(100)	N	,	N
is_leaf	是否叶子结点（true：是； false：否）	enum('true','false')	N	false	N
disabled	是否失效	enum('true','false')	N	false	N
p_order	排序	mediumint(8) unsigned	N		N
goods_count	包含商品数	mediumint(8) unsigned	N		N
goods_id	商品ID	varchar(5000)	N		N
create_time	创建时间	datetime	N		N
child_count	child_count	mediumint(8) unsigned	N	0	N
avg_price	平均价格	decimal(20,2)	N	0	N
total_num	销售数量	mediumint(8) unsigned	N	0	N
total_amount	销售金额	decimal(20,2)	N	0	N
buy_person	购买客户数	mediumint(8) unsigned	N	0	N
update_time	数据更新时间	int(10) unsigned	N		N

- 索引

Key name	Column names	Unique	Comment
primary	group_id	Y	
ind_group_name	group_name	N	

ecgoods_shop_goods

商品表

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
goods_id	ID	int(10) unsigned	Y		Y
shop_id	来源店铺	varchar(32)	N		N
outer_id	外部ID	varchar(32)	N	0	N
code	商品唯一码	varchar(200)	N		N
bn	商品编号	varchar(200)	N		N
name	商品名称	varchar(200)	N		N
brand_id	品牌	int(10) unsigned	N		N

group_ids	商品分组	varchar(100)	N		N
store	库存（各仓库的库存总和）	mediumint(8) unsigned	N	0	N
c_id	淘宝分类	varchar(32)	Y	0	N
cat_id	分类	varchar(32)	Y	0	N
goods_type	销售类型 normal:普通商品;bind:捆绑商品;	enum('normal','bind')	Y	normal	N
mktprice	市场价	decimal(20,2)	N		N
cost	成本价	decimal(20,2)	N	0	N
price	销售价	decimal(20,2)	N	0	N
total_num	销售量	mediumint(8) unsigned	N	0	N
sale_money	销售金额	decimal(20,2)	N	0	N
buyperson	购买人数	mediumint(8) unsigned	N	0	N
marketable	上架	enum('true','false')	Y	true	N
weight	重量	decimal(20,2)	N		N
unit	单位	varchar(20)	N		N
score_setting	score_setting percent:百分比;number:实际值;	enum('percent','number')	N	number	N
score	积分	mediumint(8) unsigned	N		N
spec_desc	物品	longtext	N		N
params	params	longtext	N		N
uptime	上架时间	int(10) unsigned	N		N
downtime	下架时间	int(10) unsigned	N		N
last_modify	更新时间	int(10) unsigned	N		N
create_time	创建时间	int(10) unsigned	N		N
is_full_price	是否正价商品 1:正价商品;0:非正价商品;	enum('1','0')	Y	1	N
point_rule	积分规则 1:按金额给积分;2:给固定积分;3:不参与送积分;	enum('1','2','3')	Y	1	N
fixed_point_num	固定积分数	mediumint(8) unsigned	N	0	N
disabled	是否失效	enum('true','false')	Y	false	N
p_order	排序	mediumint(8) unsigned	Y	30	N
d_order	排序	mediumint(8) unsigned	Y	30	N
pic_url	商品主图	varchar(255)	N		N
info_url	商品描述链接	varchar(255)	N		N
spec	规格型号说明	varchar(255)	N		N

desc	商品其他描述	varchar(255)	N		N
p_1	p_1	mediumint(8) unsigned	N		N
p_2	p_2	mediumint(8) unsigned	N		N
p_3	p_3	mediumint(8) unsigned	N		N
p_4	p_4	mediumint(8) unsigned	N		N
p_5	p_5	mediumint(8) unsigned	N		N
p_6	p_6	mediumint(8) unsigned	N		N
p_7	p_7	mediumint(8) unsigned	N		N
p_8	p_8	mediumint(8) unsigned	N		N
p_9	p_9	mediumint(8) unsigned	N		N
p_10	p_10	mediumint(8) unsigned	N		N
p_11	p_11	mediumint(8) unsigned	N		N
p_12	p_12	mediumint(8) unsigned	N		N
p_13	p_13	mediumint(8) unsigned	N		N
p_14	p_14	mediumint(8) unsigned	N		N
p_15	p_15	mediumint(8) unsigned	N		N
p_16	p_16	mediumint(8) unsigned	N		N
p_17	p_17	mediumint(8) unsigned	N		N
p_18	p_18	mediumint(8) unsigned	N		N
p_19	p_19	mediumint(8) unsigned	N		N
p_20	p_20	mediumint(8) unsigned	N		N
p_21	p_21	varchar(255)	N		N
p_22	p_22	varchar(255)	N		N
p_23	p_23	varchar(255)	N		N
p_24	p_24	varchar(255)	N		N
p_25	p_25	varchar(255)	N		N
p_26	p_26	varchar(255)	N		N
p_27	p_27	varchar(255)	N		N
p_28	p_28	varchar(255)	N		N
month3_paid_amount	近3个月付款 金额	decimal(20,2)	N	0	N
month3_paid_num	近3个月付款 数量	mediumint(8) unsigned	N	0	N
no_use	不参与统计	tinyint(4)	N	0	N

- 索引

Key name	Column names	Unique	Comment
primary	goods_id	Y	
ind_bn	bn	N	

ind_outer_id	outer_id	N	
ind_month3_paid_num	month3_paid_num	N	
ind_name	name	N	
idx_c_brand_id	brand_id	N	

ecgoods_shop_goods_cat

类别属性值有限表

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
cat_id	分类ID	int(10) unsigned	Y		Y
outer_id	外部ID	varchar(32)	N	0	N
outer_parent_id	外部父ID	varchar(32)	N	0	N
parent_id	父分类ID	int(10) unsigned	N		N
cat_path	分类路径(从根至本结点的 路径,逗号分隔,首部有 逗号)	varchar(100)	N	,	N
is_leaf	是否叶子结点 (true: 是; false: 否)	enum('true','false')	Y	false	N
type_id	类型序号	mediumint(9)	N		N
cat_name	分类名称	varchar(100)	Y		N
disabled	是否失效	enum('true','false')	Y	false	N
p_order	排序	mediumint(8) unsigned	N		N
goods_count	商品数	mediumint(8) unsigned	N		N
create_time	创建时间	int(10) unsigned	N		N
child_count	子分类数	mediumint(8) unsigned	Y	0	N

- 索引

Key name	Column names	Unique	Comment
primary	cat_id	Y	
ind_cat_path	cat_path	N	
ind_disabled	disabled	N	

ecgoods_shop_products

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement

product_id	货品ID	mediumint(8) unsigned	Y		Y
goods_id	商品ID	int(10) unsigned	Y		N
shop_id	来源店铺	varchar(32)	Y		N
outer_id	外部ID	varchar(32)	Y		N
outer_sku_id	外部SKU-ID	varchar(32)	Y		N
bn	商品货号	varchar(32)	N		N
name	商品名称	varchar(64)	N		N
store	库存	mediumint(8) unsigned	N	0	N
price	单价	decimal(20,2)	N	0	N
good_ranks	好评数	mediumint(8) unsigned	Y	0	N
bad_ranks	差评数	mediumint(8) unsigned	N	0	N
neutral_ranks	中评数	mediumint(8) unsigned	N	0	N
total_amount	销售总金额	decimal(20,2)	N	0	N
total_num	销售总数	mediumint(8) unsigned	N	0	N
refund_num	退货总数	mediumint(8) unsigned	N	0	N
create_time	创建时间	int(10) unsigned	N	0	N
update_time	更新时间	int(10) unsigned	Y	0	N
status	货品状态	varchar(16)	N		N

索引

Key name	Column names	Unique	Comment
primary	product_id	Y	
ind_bn	bn	N	
ind_outer_sku_id	outer_sku_id	N	

app:ecorder tables

ecorder_api_log

api日志

表结构

ColumnName	Comment	Type	Not null	Default	
log_id	日志编号	varchar(32)	Y		↑
task_id	业务ID	varchar(50)	N		↑
task_name	任务名称	varchar(255)	N		↑
status	状态 running:运行中;success:成功;fail:失败;sending:发	enum('running','success','fail','sending')	Y	sending	↑

	起中;				
worker	api方法名	varchar(200)	Y		↑
params	params	text	N		↑
msg	msg	text	N		↑
api_type	同步类型 response:响应; request:请求;	enum('response','request')	Y	request	↑
error_lv	错误级别 normal:正常; system:系统级; application:应用级; warning:警告;	enum('normal','system','application','warning')	Y	normal	↑
marking_value	marking_value	varchar(80)	N		↑
marking_type	marking_type	varchar(32)	N		↑
memo	memo	text	N		↑
msg_id	msg_id	varchar(60)	N		↑
retry	重试次数	mediumint(8) unsigned	Y	0	↑
createtime	发起同步时间	int(10) unsigned	N		↑
last_modified	最后重试时间	int(10) unsigned	N		↑

● 索引

Key name	Column names	Unique	Comment
primary	log_id	Y	
ind_status	status	N	
ind_createtime	createtime	N	
ind_task_id	task_id	N	

ecorder_chat_logs

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
log_id	log_id	mediumint(8) unsigned	Y		Y
chat_length	聊天时长(s)	mediumint(8) unsigned	N		N
start_time	开始时间	int(10) unsigned	N		N
end_time	结束时间	int(10) unsigned	N		N
eval_code	评价	varchar(32)	N		N
agent_id	客服	int(11)	N		N
member_id	客户编号	int(10) unsigned	N		N

buyer_nick	买家	varchar(32)	N		N
chat_content	聊天内容	text	N		N
chat_date	聊天日期	int(10) unsigned	N		N
create_time	创建时间	int(10) unsigned	N		N

索引

Key name	Column names	Unique	Comment
primary	log_id	Y	
ind_log_id	log_id	N	
idx_c_agent_id	agent_id	N	
idx_c_member_id	member_id	N	

ecorder_credit_exchange

表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	int(11)	Y		Y
consume_points_cti	消费转互动的消费积分	mediumint(8) unsigned	N		N
interaction_points_cti	消费转互动的互动积分	mediumint(8) unsigned	N		N
interaction_points_itc	互动转消费互动积分	mediumint(8) unsigned	N		N
consume_points_itc	互动转消费的消费积分	mediumint(8) unsigned	N		N
op_user_id	操作人ID	mediumint(8) unsigned	Y	0	N
op_name	操作人	varchar(30)	N		N
create_time	创建时间	int(10) unsigned	N		N

索引

Key name	Column names	Unique	Comment
primary	id	Y	

ecorder_exchange_orders

积分兑换订单

表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
order_id	order_id	int(10) unsigned	Y		Y

member_id	CRM客户ID	int(10) unsigned	N	0	N
order_bn	订单编号	varchar(50)	N		N
uname	买家帐号	varchar(50)	N		N
receiver	收货人	varchar(50)	N		N
tel	电话号码	varchar(20)	N		N
mobile	手机号	bigint(11)	N		N
state	省份	varchar(20)	N		N
city	城市	varchar(20)	N		N
area	区域	varchar(50)	N		N
addr	收货地址	varchar(255)	N		N
goods_bn	商品编码	varchar(50)	N		N
goods_name	商品名称	varchar(255)	N		N
num	数量	int(10) unsigned	Y		N
pay_status	付款状态	tinyint(4)	N		N
ship_status	发货状态	tinyint(4)	N		N
status	订单状态 active:活动订单;finish:已完成;dead:已关闭;	enum('active','finish','dead')	N		N
source	订单来源 ecshop:积分商城;weixin:微信兑换;	enum('ecshop','weixin')	N		N
shop_id	店铺	varchar(32)	N		N
create_time	创建时间	int(10) unsigned	N		N
modified_time	修改时间	int(10) unsigned	N		N
buy_id	积分换购活动id	int(10) unsigned	N		N

● 索引

Key name	Column names	Unique	Comment
primary	order_id	Y	
ind_order_bn	order_bn	N	
ind_mobile	mobile	N	
idx_c_shop_id	shop_id	N	

ecorder_fx_order_items

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoi
------------	---------	------	----------	---------	-------

item_id	item_id	int(10) unsigned	Y		Y
order_id	order_id	int(10) unsigned	Y	0	N
member_id	客户ID	int(10) unsigned	N	0	N
obj_id	obj_id	int(10) unsigned	Y	0	N
shop_goods_id	shop_goods_id	varchar(50)	Y	0	N
product_id	product_id	int(10) unsigned	Y	0	N
goods_id	goods_id	int(10) unsigned	Y	0	N
oid	oid	varchar(50)	Y	0	N
shop_product_id	shop_product_id	varchar(50)	Y	0	N
bn	bn	varchar(40)	N		N
name	name	varchar(200)	N		N
cost	cost	decimal(20,2)	N		N
price	price	decimal(20,2)	Y	0	N
amount	amount	decimal(20,2)	N		N
weight	weight	decimal(20,2)	N		N
nums	nums	mediumint(8) unsigned	Y	1	N
sendnum	sendnum	mediumint(8) unsigned	Y	0	N
addon	addon	longtext	N		N
item_type	item_type product:商品;pkg: 捆绑商品;gift:赠 品;adjunct:配件;	enum('product','pkg','gift','adjunct')	Y	product	N
score	score	mediumint(8) unsigned	N		N
evaluation	评价 good:好 评;bad:差 评;neutral:中 评;unkown:-;	enum('good','bad','neutral','unkown')	N	unkown	N
shop_id	店铺编号	varchar(32)	N		N
create_time	创建时间	int(10) unsigned	N		N
delete	delete	enum('true','false')	N	false	N

- 索引

Key name	Column names	Unique	Comment
primary	item_id	Y	
ind_product_id	product_id	N	
ind_shop_product_id	shop_product_id	N	
ind_create_time	create_time	N	
ind_goods_id	goods_id	N	
ind_member_id	member_id	N	
idx_c_order_id	order_id	N	
idx_c_obj_id	obj_id	N	

idx_c_shop_id	shop_id	N
---------------	---------	---

ecorder_fx_order_objects



- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
obj_id	obj_id	int(10) unsigned	Y		Y
order_id	order_id	int(10) unsigned	Y	0	N
obj_type	obj_type	varchar(50)	Y		N
obj_alias	obj_alias	varchar(255)	N		N
shop_goods_id	shop_goods_id	varchar(50)	Y	0	N
oid	oid	varchar(50)	Y	0	N
goods_id	goods_id	int(10) unsigned	Y	0	N
bn	bn	varchar(40)	N		N
name	name	varchar(200)	N		N
price	price	decimal(20,2)	Y	0	N
amount	amount	decimal(20,2)	Y	0	N
quantity	quantity	mediumint(8) unsigned	Y	1	N
weight	weight	decimal(20,2)	N		N
score	score	mediumint(8) unsigned	N		N

- 索引

Key name	Column names	Unique	Comment
primary	obj_id	Y	
ind_goods_id	goods_id	N	
ind_shop_goods_id	shop_goods_id	N	
idx_c_order_id	order_id	N	

ecorder_fx_orders



- 表结构

ColumnName	Comment	Type	Not null
order_id	order_id	int(10) unsigned	Y
order_bn	订单号	varchar(32)	Y
member_id	客户用户名	int(11)	N

confirm	确认状态	enum('Y','N')	Y
process_status	确认状态 unconfirmed:未确认;confirmed:已确认;splitting:部分拆分;splited:已拆分完;cancel:取消;	enum('unconfirmed','confirmed','splitting','splited','cancel')	Y
status	订单状态 active:活动订单;dead:已作废;finish:已完成;	enum('active','dead','finish')	Y
pay_status	付款状态 0:未支付;1:已支付;2:处理中;3:部分付款;4:部分退款;5:全额退款;	enum('0','1','2','3','4','5')	Y
ship_status	发货状态 0:未发货;1:已发货;2:部分发货;3:部分退货;4:已退货;	enum('0','1','2','3','4')	Y
is_delivery	is_delivery	enum('Y','N')	Y
shipping	配送方式	varchar(100)	N
payment	支付方式	varchar(100)	N
weight	weight	decimal(20,2)	N
tostr	tostr	longtext	N
item_num	商品数量	mediumint(8) unsigned	N
skus	商品SKU数量	mediumint(8) unsigned	N
createtime	下单时间	int(10) unsigned	N
pay_time	支付时间	int(10) unsigned	N
delivery_time	发货时间	int(10) unsigned	N
finish_time	完成时间	int(10) unsigned	N
last_modified	最后更新时间	int(10) unsigned	N
shop_id	来源店铺	varchar(32)	N
shop_type	店铺类型	varchar(50)	N
ip	ip	varchar(15)	N
agent_uname	代理用户名	varchar(50)	N
ship_name	收货人	varchar(50)	N
ship_area	收货地区	varchar(255)	N
ship_addr	收货地址	varchar(100)	N
ship_zip	ship_zip	varchar(20)	N
ship_tel	收货人电话	varchar(30)	N
ship_email	ship_email	varchar(150)	N
ship_time	ship_time	varchar(50)	N
ship_mobile	收货人手机	varchar(50)	N
cost_item	商品金额	decimal(20,2)	Y
is_tax	是否开发票	enum('true','false')	Y

cost_tax	税金	decimal(20,2)	Y
tax_company	tax_company	varchar(255)	N
cost_freight	配送费用	decimal(20,2)	Y
is_protect	is_protect	enum('true','false')	Y
cost_protect	保价费用	decimal(20,2)	Y
is_cod	货到付款	enum('true','false')	Y
cost_payment	cost_payment	decimal(20,2)	N
currency	currency	varchar(8)	N
cur_rate	cur_rate	decimal(10,4)	N
score_u	score_u	decimal(20,2)	Y
score_g	score_g	decimal(20,2)	Y
discount	discount	decimal(20,2)	Y
pmt_goods	pmt_goods	decimal(20,2)	Y
pmt_order	pmt_order	decimal(20,2)	Y
total_amount	订单总额	decimal(20,2)	N
final_amount	final_amount	decimal(20,2)	Y
payed	已付金额	decimal(20,2)	N
custom_mark	买家留言	longtext	N
mark_text	订单备注	longtext	N
disabled	是否失效	enum('true','false')	Y
mark_type	订单备注图标	varchar(2)	Y
tax_no	发票号	varchar(50)	N
dt_begin	分派开始时间	int(10) unsigned	N
is_anti	is_anti	enum('true','false')	Y
group_id	确认组	int(10) unsigned	N
op_id	确认人	int(10) unsigned	N
dispatch_time	分派时间	int(10) unsigned	N
order_limit_time	order_limit_time	int(10) unsigned	N
coupons_name	coupons_name	varchar(255)	N
refer_id	首次来源ID	varchar(50)	N
refer_url	首次来源URL	varchar(200)	N
refer_time	首次来源时间	int(10) unsigned	N
c_refer_id	本次来源ID	varchar(50)	N
c_refer_url	本次来源URL	varchar(200)	N
c_refer_time	本次来源时间	int(10) unsigned	N
abnormal	异常处理状态	enum('true','false')	N
print_finish	print_finish	enum('true','false')	Y

source	source	varchar(50)	N
pause	暂停	enum('true','false')	N
is_modify	已编辑	enum('true','false')	N
old_amount	old_amount	decimal(20,2)	N
order_type	order_type normal:订单;sale:销售单;	enum('normal','sale')	N
product_hash	订单明细数据hash	char(32)	N
f_modified	前端最后修改时间	int(10) unsigned	N
f_ship_time	前端发货时间	int(10) unsigned	N
state_id	省份ID	mediumint(8) unsigned	N
city_id	城市ID	mediumint(8) unsigned	N
district_id	区域ID	mediumint(8) unsigned	N
hour	下单时间(小时)	mediumint(8) unsigned	N
trade_type	订单类型	char(32)	N
step_trade_status	step_trade_status	char(32)	N
step_paid_fee	step_paid_fee	decimal(20,2)	N
errortrade_desc	errortrade_desc	varchar(500)	N
is_errortrade	is_errortrade	char(10)	N
source_order	原始订单	text	N

● 索引

Key name	Column names	Unique	Comment
primary	order_id	Y	
ind_trade_type	trade_type	N	
ind_order_bn_shop	order_bn, shop_id	Y	
ind_order_bn	order_bn	N	
ind_member_id	member_id	N	
ind_ship_status	ship_status	N	
ind_pay_status	pay_status	N	
ind_status	status	N	
ind_process_status	process_status	N	
ind_shop_type	shop_type	N	
ind_is_cod	is_cod	N	
ind_createtime	createtime	N	
idx_c_shop_id	shop_id	N	

ecorder_gift_logs



● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	int(11)	Y		Y
order_bn	订单号	varchar(50)	N		N
buyer_account	客户帐号	varchar(100)	N		N
order_source	订单来源	varchar(50)	N		N
shop_id	店铺	varchar(32)	N		N
paid_amount	付款金额	decimal(20,2)	N	0	N
goods_num	购买商品总数	mediumint(8) unsigned	N	0	N
gift_num	赠品数量	mediumint(8) unsigned	N	0	N
send_num	发货数量	mediumint(8) unsigned	N	0	N
gift_rule_id	赠品活动名称	int(11)	N	0	N
gift_bn	赠品编码	varchar(32)	N		N
gift_name	赠品名称	varchar(100)	N		N
create_time	赠送时间	int(10) unsigned	N		N
update_time	发货时间	int(10) unsigned	N		N
md5_key	唯一识别码，同一秒同一订单号只送出一个货号(order_bn + create_time + gift_bn)	varchar(32)	N		N
status	是否完成 0:未完成;1:已完成;	enum('0','1')	N	0	N

● 索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_order_bn	order_bn	N	
ind_md5_key	md5_key	Y	
idx_c_shop_id	shop_id	N	
idx_c_gift_rule_id	gift_rule_id	N	

ecorder_gift_rule

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	int(11)	Y		Y
title	规则名称	varchar(100)	Y		N

lv_id	客户等级	int(11)	N		N
gift_bn	商家编码	varchar(100)	N		N
gift_ids	赠品ID	varchar(500)	N		N
gift_num	赠品数量	varchar(500)	N		N
shop_id	适用店铺	varchar(32)	N		N
create_time	创建时间	int(10) unsigned	Y		N
modified_time	修改时间	int(10) unsigned	Y		N
time_type	时间类型 sendtime:订单处理时间; createtime:订单创建时间; pay_time:订单付款时间; other:其他;	enum('sendtime','createtime','pay_time','other')	N		N
start_time	开始时间	int(10) unsigned	N		N
end_time	结束时间	int(10) unsigned	N		N
status	规则状态 0:关闭;1:开启;	enum('0','1')	N	1	N
filter_arr	促销条件	text	N		N
priority	优先级	int(10)	N	0	N

● 索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_shop_gift_rule	lv_id, shop_id	N	
idx_c_lv_id	lv_id	N	
idx_c_shop_id	shop_id	N	

ecorder_gift_set_logs

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	int(11)	Y		Y
op_user	操作人	varchar(50)	N		N
set_type	赠品设置 include:叠加;exclude:排他;	enum('include','exclude')	N		N
create_time	操作时间	int(10) unsigned	N		N

● 索引

Key name	Column names	Unique	Comment

primary	id	Y	
ind_op_user	op_user	N	

ecorder_logi_info

订单物流数据

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	int(10) unsigned	Y		Y
rebate_cycle_id	返利周期ID	int(11)	N	0	N
order_id	订单ID	int(10) unsigned	N		N
order_bn	订单编号	varchar(50)	N		N
ship_name	收货人姓名	varchar(30)	N		N
ship_mobile	手机号码	varchar(11)	N		N
logi_company	物流公司	varchar(30)	N		N
logi_no	物流单号	varchar(50)	N		N
member_id	客户ID	int(10) unsigned	N		N
create_time	创建时间	int(10) unsigned	N	0	N
update_time	更新时间	int(10) unsigned	N	0	N
delivery_time	发货时间	int(10) unsigned	N	0	N
transit_step_info	流转信息列表	text	N		N

- 索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_order_bn	order_bn	N	
ind_ship_mobile	ship_mobile	N	
idx_c_order_id	order_id	N	
idx_c_member_id	member_id	N	

ecorder_login_log

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	mediumint(8) unsigned	Y		Y
login_time	操作时间	datetime	Y		N
operate_type	操作类型 login:登	enum('login','delete')	N	login	N

operate_type	陆;delete:删除;	enum('login','delete')	N	login	N
ip	IP地址	varchar(20)	N		N
user_name	用户名	varchar(100)	N		N
status	状态 succ:成功;fail:失败;	enum('succ','fail')	N		N
addon	其他	text	N		N

● 索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_title	user_name	N	

ecorder_member_products

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
mp_id	ID	int(11)	Y		Y
member_id	客户用户名	int(10) unsigned	N		N
product_id	product_id	mediumint(8) unsigned	N	0	N
goods_id	goods_id	mediumint(8) unsigned	N	0	N
name	商品名称	varchar(64)	N		N
last_time	最后购买时间	int(10) unsigned	N		N
buy_times	购买次数	mediumint(8) unsigned	N	0	N
buy_num	购买数量	mediumint(8) unsigned	N	0	N

● 索引

Key name	Column names	Unique	Comment
primary	mp_id	Y	
ind_member_goods	member_id, goods_id	N	

ecorder_order_items

● 表结构

ColumnName	Comment	Type	Not null	Default	Auto i
item_id	item_id	int(10) unsigned	Y		Y
order_id	order_id	int(10) unsigned	Y	0	N
member_id	客户ID	int(10) unsigned	N	0	N
obj_id	obj_id	int(10) unsigned	Y	0	N

shop_goods_id	shop_goods_id	varchar(50)	Y	0	N
product_id	product_id	int(10) unsigned	Y	0	N
goods_id	goods_id	int(10) unsigned	Y	0	N
oid	oid	varchar(50)	Y	0	N
shop_product_id	shop_product_id	varchar(50)	Y	0	N
bn	bn	varchar(40)	N		N
name	name	varchar(200)	N		N
cost	cost	decimal(20,2)	N		N
price	price	decimal(20,2)	Y	0	N
amount	amount	decimal(20,2)	N		N
weight	weight	decimal(20,2)	N		N
nums	nums	mediumint(8) unsigned	Y	1	N
sendnum	sendnum	mediumint(8) unsigned	Y	0	N
addon	addon	longtext	N		N
item_type	item_type product:商品;pkg: 捆绑商品;gift:赠 品;adjunct:配件;	enum('product','pkg','gift','adjunct')	Y	product	N
score	score	mediumint(8) unsigned	N		N
evaluation	评价 good:好 评;bad:差 评;neutral:中 评;unkown:-;	enum('good','bad','neutral','unkown')	N	unkown	N
shop_id	店铺编号	varchar(32)	N		N
create_time	创建时间	int(10) unsigned	N		N
delete	delete	enum('true','false')	N	false	N

- 索引

Key name	Column names	Unique	Comment
primary	item_id	Y	
ind_product_id	product_id	N	
ind_shop_product_id	shop_product_id	N	
ind_create_time	create_time	N	
ind_goods_id	goods_id	N	
ind_member_id	member_id	N	
idx_c_order_id	order_id	N	
idx_c_obj_id	obj_id	N	
idx_c_shop_id	shop_id	N	

ecorder_order_objects

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
obj_id	obj_id	int(10) unsigned	Y		Y
order_id	order_id	int(10) unsigned	Y	0	N
obj_type	obj_type	varchar(50)	Y		N
obj_alias	obj_alias	varchar(255)	N		N
shop_goods_id	shop_goods_id	varchar(50)	Y	0	N
oid	oid	varchar(50)	Y	0	N
goods_id	goods_id	int(10) unsigned	Y	0	N
bn	bn	varchar(40)	N		N
name	name	varchar(200)	N		N
price	price	decimal(20,2)	Y	0	N
amount	amount	decimal(20,2)	Y	0	N
quantity	quantity	mediumint(8) unsigned	Y	1	N
weight	weight	decimal(20,2)	N		N
score	score	mediumint(8) unsigned	N		N

● 索引

Key name	Column names	Unique	Comment
primary	obj_id	Y	
ind_goods_id	goods_id	N	
ind_shop_goods_id	shop_goods_id	N	
idx_c_order_id	order_id	N	

ecorder_order_pmt

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	mediumint(8) unsigned	Y		Y
order_id	order_id	int(10) unsigned	Y		N
pmt_amount	pmt_amount	decimal(20,2)	N		N
pmt_memo	pmt_memo	longtext	N		N
pmt_describe	优惠名称	longtext	N		N
promotion_id	promotion_id	varchar(100)	N		N
pmt_desc	优惠详细描述	varchar(500)	N		N
oid	订单ID	varchar(32)	N		N

coupon_id	优惠券ID	varchar(32)	N		N
-----------	-------	-------------	---	--	---

- 索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_coupon_id	coupon_id	N	
ind_promotion_id	promotion_id	N	
ind_oid	oid	N	
idx_c_order_id	order_id	N	

ecorder_orders

- 表结构

ColumnName	Comment	Type	Not null
order_id	order_id	int(10) unsigned	Y
order_bn	订单号	varchar(32)	Y
member_id	客户帐号	int(10) unsigned	N
is_refund	是否冲红销售 0:否;1:是;	enum('0','1')	N
refund_order_bn	冲红订单号	varchar(32)	N
consumer_terminal	消费终端	varchar(32)	N
op_name	操作人	varchar(32)	N
confirm	确认状态	enum('Y','N')	N
process_status	确认状态 unconfirmed:未确认;confirmed:已确认;splitting:部分拆分;splited:已拆分完;cancel:取消;	enum('unconfirmed','confirmed','splitting','splited','cancel')	N
status	订单状态 active:活动订单;dead:已作废;finish:已完成;	enum('active','dead','finish')	N
pay_status	付款状态 0:未支付;1:已支付;2:处理中;3:部分付款;4:部分退款;5:全额退款;	enum('0','1','2','3','4','5')	Y
ship_status	发货状态 0:未发货;1:已发货;2:部分发货;3:部分退货;4:已退货;	enum('0','1','2','3','4')	Y
is_delivery	is_delivery	enum('Y','N')	Y
shipping	配送方式	varchar(100)	N
payment	支付方式	varchar(100)	N
weight	weight	decimal(20,2)	N

tostr	tostr	longtext	N
item_num	商品数量	mediumint(8) unsigned	N
skus	商品SKU数量	mediumint(8) unsigned	N
createtime	下单时间	int(10) unsigned	N
pay_time	支付时间	int(10) unsigned	N
delivery_time	发货时间	int(10) unsigned	N
finish_time	完成时间	int(10) unsigned	N
last_modified	最后更新时间	int(10) unsigned	N
shop_id	来源店铺	varchar(32)	N
shop_type	店铺类型	varchar(50)	N
ip	ip	varchar(15)	N
ship_name	收货人	varchar(50)	N
ship_area	收货地区	varchar(255)	N
ship_addr	收货地址	varchar(100)	N
ship_zip	ship_zip	varchar(20)	N
ship_tel	收货人电话	varchar(30)	N
ship_email	ship_email	varchar(150)	N
ship_time	ship_time	varchar(50)	N
ship_mobile	收货人手机	varchar(50)	N
cost_item	商品金额	decimal(20,2)	N
is_tax	是否开发票	enum('true', 'false')	N
cost_tax	税金	decimal(20,2)	N
tax_company	tax_company	varchar(255)	N
cost_freight	配送费用	decimal(20,2)	N
is_protect	is_protect	enum('true', 'false')	Y
cost_protect	保价费用	decimal(20,2)	N
is_cod	货到付款	enum('true', 'false')	N
cost_payment	cost_payment	decimal(20,2)	N
currency	currency	varchar(8)	N
cur_rate	cur_rate	decimal(10,4)	N
score_u	score_u	decimal(20,2)	Y
score_g	score_g	decimal(20,2)	Y
discount	discount	decimal(20,2)	Y
pmt_goods	pmt_goods	decimal(20,2)	Y
pmt_order	pmt_order	decimal(20,2)	Y
total_amount	订单总额	decimal(20,2)	N
final_amount	final_amount	decimal(20,2)	Y

payed	已付金额	decimal(20,2)	N
custom_mark	买家留言	longtext	N
mark_text	订单备注	longtext	N
disabled	是否失效	enum('true','false')	Y
mark_type	订单备注图标	varchar(2)	Y
tax_no	发票号	varchar(50)	N
dt_begin	分派开始时间	int(10) unsigned	N
is_anti	is_anti	enum('true','false')	N
group_id	确认组	int(10) unsigned	N
op_id	确认人	int(10) unsigned	N
dispatch_time	分派时间	int(10) unsigned	N
order_limit_time	order_limit_time	int(10) unsigned	N
coupons_name	coupons_name	varchar(255)	N
refer_id	首次来源ID	varchar(50)	N
refer_url	首次来源URL	varchar(200)	N
refer_time	首次来源时间	int(10) unsigned	N
c_refer_id	本次来源ID	varchar(50)	N
c_refer_url	本次来源URL	varchar(200)	N
c_refer_time	本次来源时间	int(10) unsigned	N
abnormal	异常处理状态	enum('true','false')	N
print_finish	print_finish	enum('true','false')	Y
source	source	varchar(50)	N
pause	暂停	enum('true','false')	N
is_modify	已编辑	enum('true','false')	N
old_amount	old_amount	decimal(20,2)	N
order_type	order_type normal:订单;sale: 销售单;	enum('normal','sale')	N
product_hash	订单明细数据hash	char(32)	N
f_modified	前端最后修改时间	int(10) unsigned	N
f_ship_time	前端发货时间	int(10) unsigned	N
state_id	省份ID	mediumint(8) unsigned	N
city_id	城市ID	mediumint(8) unsigned	N
district_id	区域ID	mediumint(8) unsigned	N
hour	下单时间(小时)	mediumint(8) unsigned	N
trade_type	订单类型	char(32)	N
step_trade_status	step_trade_status	char(32)	N
step_paid_fee	step_paid_fee	decimal(20,2)	N
errortrade_desc	errortrade_desc	varchar(500)	N

is_errortrade	is_errortrade	char(10)	N
card_no	会员卡号	varchar(30)	N

● 索引

Key name	Column names	Unique	Comment
primary	order_id	Y	
ind_card_no	card_no	N	
ind_trade_type	trade_type	N	
ind_order_bn_shop	order_bn, shop_id	Y	
ind_order_bn	order_bn	N	
ind_ship_status	ship_status	N	
ind_pay_status	pay_status	N	
ind_status	status	N	
ind_process_status	process_status	N	
ind_shop_type	shop_type	N	
ind_is_cod	is_cod	N	
ind_createtime	createtime	N	
ind_ship_mobile	ship_mobile	N	
idx_c_member_id	member_id	N	
idx_c_shop_id	shop_id	N	

ecorder_orders_manual

手工订单表

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	int(10) unsigned	Y		Y
order_id	订单ID	int(10) unsigned	N		N
order_bn	订单编号	varchar(50)	N		N
uname	客户帐号	varchar(50)	N		N
receiver	收货人	varchar(50)	N		N
mobile	收货人手机	varchar(11)	N		N
shop_id	来源店铺	varchar(32)	N		N
op_name	操作人	varchar(50)	N		N
create_time	下单时间	int(10) unsigned	N		N

● 索引

Key name	Column names	Unique	Comment
primary	id	Y	

ind_order_bn	order_bn	N	
ind_mobile	mobile	N	
idx_c_shop_id	shop_id	N	

ecorder_point_set_logs

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	int(11)	Y		Y
op_user	操作人	varchar(50)	N		N
set_type	积分设置 include: 叠加;exclude:排他;	enum('include','exclude')	N		N
create_time	操作时间	int(10) unsigned	N		N

- 索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_op_user	op_user	N	

ecorder_refunds

支付记录

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
refund_id	refund_id	int(10) unsigned	Y		Y
refund_bn	退款单号	varchar(32)	Y		N
order_id	订单号	int(10) unsigned	N		N
account	退款账号	varchar(50)	N		N
bank	退款银行	varchar(50)	N		N
pay_account	收款账户	varchar(50)	N		N
currency	货币	varchar(10)	N		N
money	支付金额	decimal(20,2)	Y	0	N
paycost	支付网关费用	decimal(20,2)	N		N
cur_money	cur_money	decimal(20,2)	Y	0	N
pay_type	支付类型 online:在线支付;offline:	enum('online','offline','deposit')	Y	online	N

	线下支付;deposit:预存款支付;				
payment	支付方式id	mediumint(8) unsigned	N		N
paymethod	支付方式	varchar(100)	N		N
op_user	操作员	varchar(32)	N		N
t_ready	支付开始时间	int(10) unsigned	N		N
download_time	单据下载时间	int(10) unsigned	N		N
t_sent	发款时间	int(10) unsigned	N		N
t_received	用户确认收款时间	int(10) unsigned	N		N
status	支付状态	varchar(32)	Y		N
memo	memo	longtext	N		N
disabled	是否失效	enum('true','false')	N	false	N
trade_no	trade_no	varchar(30)	N		N
shop_id	来源店铺	varchar(32)	N		N

● 索引

Key name	Column names	Unique	Comment
primary	refund_id	Y	
ind_refund_bn_shop	refund_bn, shop_id	Y	
ind_refund_bn	refund_bn	N	
ind_t_sent	t_sent	N	
idx_c_order_id	order_id	N	
idx_c_shop_id	shop_id	N	

ecorder_relate_products

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
relate_id	ID	int(11)	Y		Y
goods_a	商品A	varchar(32)	Y	0	N
goods_b	商品B	varchar(32)	Y	0	N
times	关联次数	mediumint(8) unsigned	Y	0	N
create_time	关联时间	int(10) unsigned	Y	0	N
update_time	更新时间	int(10) unsigned	Y	0	N

● 索引

Key name	Column names	Unique	Comment
----------	--------------	--------	---------

primary	relate_id	Y	
ind_relate_id	relate_id	N	
ind_goods_a_b	goods_a, goods_b	Y	

ecorder_shop

- 表结构

ColumnName	Comment	Type	Not null	Default	Auto
shop_id	shop_id	varchar(32)	Y		N
shop_bn	店铺编号	varchar(20)	N		N
name	店铺名称	varchar(255)	N		N
shop_type	店铺类型	varchar(32)	N		N
subbiztype	子业务类型	varchar(32)	N		N
config	config	text	N		N
last_download_time	上次下载订单时间(终端)	int(10) unsigned	N		N
last_upload_time	上次上传订单时间(ome)	int(10) unsigned	N		N
last_market_time	最后一次营销时间	int(10) unsigned	N		N
active	激活	enum('true','false')	Y	false	N
disabled	是否失效	enum('true','false')	Y	false	N
last_store_sync_time	上次库存同步时间	int(10) unsigned	N		N
area	area	varchar(255)	N		N
zip	zip	varchar(20)	N		N
addr	addr	varchar(255)	N		N
default_sender	default_sender	varchar(255)	N		N
mobile	mobile	varchar(30)	N		N
tel	tel	varchar(30)	N		N
filter_bn	filter_bn	enum('true','false')	Y	false	N
bn_regular	bn_regular	varchar(255)	N		N
express_remark	express_remark	text	N		N
delivery_template	delivery_template	varchar(255)	N		N
order_bland_template	order_bland_template	varchar(255)	N		N
node_id	node_id	varchar(32)	N		N
node_type	node_type	varchar(32)	N		N
shop_prop	店铺性质 online:电商平台;offline:实体店;wechat:微信;	enum('online','offline','wechat')	N	online	N

channel_id	店铺分类	int(11)	N		N
addon	addon	longtext	N		N
create_time	创建时间	int(10) unsigned	N		N
modified_time	更新时间	int(10) unsigned	N		N
orders	排序	int(11)	N	0	N

索引

Key name	Column names	Unique	Comment
primary	shop_id	Y	
ind_shop_bn	shop_bn	Y	
ind_node_id	node_id	N	
ind_channel_id	channel_id	N	
idx_c_channel_id	channel_id	N	

ecorder_shop_agents

表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
agent_id	agent_id	int(11)	Y		Y
agent_name	客服帐号	varchar(32)	N		N
nickname	昵称	varchar(32)	N		N
chat_num	聊天次数	mediumint(8) unsigned	N	0	N
shop_id	所属店铺	varchar(32)	N		N
create_time	创建时间	int(10) unsigned	N		N

索引

Key name	Column names	Unique	Comment
primary	agent_id	Y	
ind_nickname	nickname	N	
idx_c_shop_id	shop_id	N	

ecorder_shop_analysis

店铺分析表

表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
shop_id	shop_id	varchar(32)	Y		N
refund_orders	退款订单数	mediumint(8) unsigned	N	0	N

refund_members	退款客户数	mediumint(8) unsigned	N	0	N
refund_amount	退款金额	decimal(20,2)	N	0	N
refund_per_amount	退款客单价	decimal(20,2)	N	0	N
finish_amount	交易成功金额	decimal(20,2)	N	0	N
finish_orders	交易成功订单数	mediumint(8) unsigned	N	0	N
finish_members	交易成功客户数	mediumint(8) unsigned	N	0	N
finish_per_amount	成功客单价	decimal(20,2)	N	0	N
unpay_orders	未付款订单数	mediumint(8) unsigned	N	0	N
unpay_amount	未付款金额	decimal(20,2)	N	0	N
unpay_members	未付款客户数	mediumint(8) unsigned	N	0	N
unpay_per_amount	未付款客单价	decimal(20,2)	N	0	N
orders	订单总数	mediumint(8) unsigned	N	0	N
amount	总金额	decimal(20,2)	N	0	N
per_amount	客单价	decimal(20,2)	N	0	N
members	客户数	mediumint(8) unsigned	N	0	N
single_members	单次购买客户数	mediumint(8) unsigned	N	0	N
products	宝贝数	mediumint(8) unsigned	N	0	N
create_time	创建时间	int(10) unsigned	N		N
update_time	更新时间	int(10) unsigned	N		N

● 索引

Key name	Column names	Unique	Comment
primary	shop_id	Y	
ind_products	products	N	

ecorder_shop_channel

渠道分析

● 表结构

ColumnName	Comment	Type	Not null	Default	Auto increment
channel_id	channel_id	int(11)	Y		Y
channel_bn	分类编号	varchar(32)	N		N
channel_name	分类名称	varchar(32)	N		N

orders	订单总数	mediumint(8) unsigned	N	0	N
amount	总金额	decimal(20,2)	N	0	N
members	客户数	mediumint(8) unsigned	N	0	N
per_amount	客单价	decimal(20,2)	N	0	N
finish_amount	成功金额	decimal(20,2)	N	0	N
finish_orders	成功交易数	mediumint(8) unsigned	N	0	N
finish_members	成功客户数	mediumint(8) unsigned	N	0	N
finish_per_amount	成功客单价	decimal(20,2)	N	0	N
unpay_orders	未付款订单数	mediumint(8) unsigned	N	0	N
unpay_amount	未付款金额	decimal(20,2)	N	0	N
unpay_members	未支付客户数	mediumint(8) unsigned	N	0	N
unpay_per_amount	未付款客单价	decimal(20,2)	Y	0	N
refund_orders	退款订单数	mediumint(8) unsigned	N	0	N
refund_amount	退款总金额	decimal(20,2)	N	0	N
refund_per_amount	退款客单价	decimal(20,2)	N	0	N
refund_members	退款客户数	mediumint(8) unsigned	N	0	N
create_time	创建时间	int(10) unsigned	N		N
update_time	更新时间	int(10) unsigned	N		N
is_fixed	固定分类	enum('0','1')	N	0	N
is_active	状态	enum('0','1')	N	1	N

● 索引

Key name	Column names	Unique	Comment
primary	channel_id	Y	
ind_channel_bn	channel_bn	N	

ecorder_shop_credit

● 表结构

ColumnName	Comment	Type
rule_id	rule_id	int(11)
name	规则名称	varchar(32)

is_active	状态	enum('0','1')
order_type	消费类型 all:累计付款;single:单笔付款;	enum('all','single')
amount_symbol	消费金额符号 unlimited:无限制;gthan:大于;sthan:小于;equal:等于;gethan:大于等于;sethan:小于等于;between:介于;	enum('unlimited','gthan','sthan','equal','gethan','sethan','between')
min_amount	最低消费	mediumint(8) unsigned
max_amount	最高消费	mediumint(8) unsigned
cost_amount	每积分需要消费	mediumint(8) unsigned
shop_id	适用店铺	varchar(32)
create_time	创建时间	int(10) unsigned
start_time	开始时间	int(10) unsigned
end_time	结束时间	int(10) unsigned
count_type	消费金额类型 total_amount:订单金额;payed:实付金额;	enum('total_amount','payed')
time_from	活动开始时间	date
time_to	活动结束时间	date
birthday_type	生日送积分时间 类型 1:当天;2:当月;	enum('1','2')
special_point_rule	特殊积分规则	varchar(15)
activity_point_times	活动送积分的倍数 1:1.5;2:2;3:3;4:5;	enum('1','2','3','4')
birthday_point_times	生日送积分的倍数 1:1.5;2:2;3:3;4:5;	enum('1','2','3','4')

● 索引

Key name	Column names	Unique	Comment
primary	rule_id	Y	
ind_shop_id	shop_id	N	
idx_c_shop_id	shop_id	N	

ecorder_shop_gift

● 表结构

			Not		
--	--	--	-----	--	--

			null		
id	id	int(11)	Y		Y
gift_bn	商家编码	varchar(100)	N		N
gift_name	商品名称	varchar(100)	N		N
gift_num	赠品库存	mediumint(8) unsigned	N	0	N
gift_price	成本价	decimal(20,2)	N	0	N
send_num	已赠送数量	mediumint(8) unsigned	N	0	N
is_del	是否启用 0:启用;1:禁用;	enum('0','1')	N	0	N
create_time	创建时间	int(10) unsigned	N		N
update_time	更新日期	int(10) unsigned	N		N
shop_id	来源店铺	varchar(32)	N		N

索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_gift_bn	gift_bn	N	
idx_c_shop_id	shop_id	N	

ecorder_shop_lv

店铺客户等级规则

表结构

ColumnName	Comment	Type	No nu
lv_id	lv_id	int(11)	Y
name	等级名称	varchar(32)	N
amount_symbol	消费金额条件 unlimited: 无限制; gthan: 大于; sthan: 小于; equal: 等于; gethan: 大于等于; sethan: 小于等于; between: 介于;	enum('unlimited','gthan','sthan','equal','gethan','sethan','between')	N
min_amount	最低消费额	mediumint(8) unsigned	N
max_amount	最高消费额	mediumint(8) unsigned	N
	消费次数条件 unlimited: 无限		

buy_times_symbol	制;gthan:大于;sthan:小于;equal:等于;gethan:大于等于;sethan:小于等于;between:介于;	enum('unlimited','gthan','sthan','equal','gethan','sethan','between')	N
min_buy_times	最低消费次数	mediumint(8) unsigned	N
max_buy_times	最高消费次数	mediumint(8) unsigned	N
shop_id	适用店铺	varchar(32)	N
is_active	状态	enum('0','1')	N
is_default	是否默认等级	enum('0','1')	N
create_time	创建时间	int(10) unsigned	N

索引

Key name	Column names	Unique	Comment
primary	lv_id	Y	
ind_shop_id	shop_id	N	
idx_c_shop_id	shop_id	N	

ecorder_shop_vcard

表结构

ColumnName	Comment	Type	Not null	Default	Auto increme
shop_id	shop_id	varchar(32)	Y		N
shop_bn	店铺编号	varchar(20)	N		N
name	店铺名称	varchar(255)	N		N
shop_type	店铺类型	varchar(32)	N		N
subbiztype	子业务类型	varchar(32)	N		N
config	config	text	N		N
last_download_time	上次下载订单时间(终端)	int(10) unsigned	N		N
last_upload_time	上次上传订单时间(ome)	int(10) unsigned	N		N
active	激活	enum('true','false')	Y	false	N
disabled	是否失效	enum('true','false')	N	false	N
last_store_sync_time	上次库存同步时间	int(10) unsigned	N		N
area	area	varchar(255)	N		N

zip	zip	varchar(20)	N		N
addr	addr	varchar(255)	N		N
default_sender	default_sender	varchar(255)	N		N
nick	nick	varchar(30)	N		N
title	title	varchar(30)	N		N
fax	fax	varchar(30)	N		N
email	email	varchar(50)	N		N
company	company	varchar(100)	N		N
shop_url	shop_url	varchar(100)	N		N
address	address	varchar(30)	N		N
mobile	mobile	varchar(30)	N		N
tel	tel	varchar(30)	N		N
filter_bn	filter_bn	enum('true','false')	N	false	N
bn_regular	bn_regular	varchar(255)	N		N
express_remark	express_remark	text	N		N
delivery_template	delivery_template	varchar(255)	N		N
order_bland_template	order_bland_template	varchar(255)	N		N
node_id	node_id	varchar(32)	N		N
node_type	node_type	varchar(32)	N		N
addon	addon	longtext	N		N
vcard_id	淘名片ID	mediumint(8) unsigned	N	0	N
vcard_url	名片短地址	varchar(50)	N		N
passcode	验证码	mediumint(8) unsigned	N		N

● 索引

Key name	Column names	Unique	Comment
primary	shop_id	Y	
ind_shop_bn	shop_bn	Y	

ecorder_sms_sign

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
sign_id	sign_id	int(10) unsigned	Y		Y
sms_sign	短信签名	varchar(30)	N		N
extend_no	签名编号	varchar(32)	N		N
review	是否审核	varchar(32)	N		N

is_code_sign	是否验证码签名	enum('true','false')	N	false	N
shop_ids	店铺ID	varchar(1000)	N		N
create_time	创建时间	int(10) unsigned	N		N
modified_time	更新时间	int(10) unsigned	N		N

● 索引

Key name	Column names	Unique	Comment
primary	sign_id	Y	
ind_sms_sign	sms_sign	N	
ind_extend_no	extend_no	N	

ecorder_tb_refunds

■ 淘宝退款

● 表结构

ColumnName	Comment	
id	id	int(10) unsigned
tid	订单号	bigint(20) unsigned
refund_id	退款单号	bigint(20) unsigned
status	状态 WAIT_SELLER_AGREE:等待卖家同意;WAIT_BUYER_RETURN_GOODS:同意退款，等待买家退货;WAIT_SELLER_CONFIRM_GOODS:已退货，等待确认收货;SELLER_REFUSE_BUYER:卖家拒绝退款;CLOSED:退款关闭;SUCCESS:退款成功;UNKOWN:未知状态;	enum('WAIT_SELLER_AGREE','WAIT_BUYER_F
buyer_nick	客户帐号	varchar(50)
mobile	收货人手机	varchar(11)
title	商品	varchar(100)
num	数量	int(11)
refund_fee	退款金额	decimal(20,2)
payment	付款金额	decimal(20,2)
reason	退款原因	varchar(50)
sid	物流单号	varchar(20)
company_name	物流公司	varchar(50)
shop_id	来源店铺	varchar(32)
oid	子订单号	bigint(20) unsigned
total_fee	订单金额	decimal(20,2)
seller_nick	卖家帐号	varchar(50)
created	创建时间	int(10) unsigned

modified	更新时间	int(10) unsigned
down_time	下载时间	datetime
order_status	订单状态 TRADE_NO_CREATE_PAY:非支付宝交易;WAIT_BUYER_PAY:等待付款;WAIT_SELLER_SEND_GOODS:等待卖家发货;WAIT_BUYER_CONFIRM_GOODS:等待确认收货;TRADE_BUYER_SIGNED:买家已签收;TRADE_FINISHED:交易成功;TRADE_CLOSED:交易关闭;TRADE_CLOSED_BY_TAOBAO:被淘宝关闭;	enum('TRADE_NO_CREATE_PAY','WAIT_BUYE
good_status	商品状态 BUYER_NOT_RECEIVED:买家未收到货;BUYER_RECEIVED:买家已收到货;BUYER_RETURNED_GOODS:买家已退货;	enum('BUYER_NOT_RECEIVED','BUYER_RECE
has_good_return	是否退货	varchar(20)
desc	退款说明	varchar(500)
member_id	客户ID	int(10) unsigned

● 索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_refund_id	refund_id	N	
ind_buyer_nick	buyer_nick	N	
ind_mobile	mobile	N	
ind_created	created	N	
ind_tid	tid	N	
idx_c_shop_id	shop_id	N	
idx_c_member_id	member_id	N	

ecorder_trade_rates

交易评价信息

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
rate_id	rate_id	mediumint(8) unsigned	Y		Y
order_id	订单ID	int(10) unsigned	N		N
order_bn	订单号	varchar(32)	Y	0	N
oid	oid	varchar(50)	Y	0	N
role	评价者角色 seller:卖家;buyer:买家;	enum('seller','buyer')	N	buyer	N
nick	昵称	varchar(32)	N		N

member_id	客户编号	int(10) unsigned	N		N
result	评价 good:好评;neutral:中评;bad:差评;	enum('good','neutral','bad')	N		N
create_time	创建时间	int(10) unsigned	N		N
created	评价时间	int(10) unsigned	N		N
content	评价内容	varchar(1000)	N		N
reply	评价解释	varchar(10000)	N		N
shop_id	来源店铺	varchar(32)	N		N
channel_id	来源渠道	int(11)	N		N

● 索引

Key name	Column names	Unique	Comment
primary	rate_id	Y	
ind_shop_id	shop_id	N	
ind_member_id	member_id	N	
ind_order_id	order_id	N	
ind_nick	nick	N	
ind_oid	oid	N	
idx_c_member_id	member_id	N	
idx_c_shop_id	shop_id	N	
idx_c_channel_id	channel_id	N	

app:ectools tables

ectools_analysis

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	mediumint(8) unsigned	Y		Y
service	service	varchar(100)	Y		N
interval	interval hour:hour;day:day;	enum('hour','day')	Y		N
modify	modify	int(10) unsigned	Y	0	N

● 索引

Key name	Column names	Unique	Comment
primary	id	Y	

ectools_analysis_logs

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	mediumint(8) unsigned	Y		Y
analysis_id	analysis_id	mediumint(8) unsigned	Y		N
type	类型	mediumint(8) unsigned	Y	0	N
target	指标	mediumint(8) unsigned	Y	0	N
flag	标识	mediumint(8) unsigned	Y	0	N
value	数据	float	Y	0	N
time	时间	int(10) unsigned	Y		N

- 索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_analysis_id	analysis_id	N	
ind_type	type	N	
ind_target	target	N	
ind_time	time	N	

ectools_currency

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
cur_id	货币ID	int(8)	Y		Y
cur_name	货币名称	varchar(20)	Y		N
cur_sign	货币符号	varchar(5)	N		N
cur_code	货币代码	varchar(8)	Y		N
cur_rate	汇率	decimal(10,4)	Y	1.0000	N
cur_default	默认货币	enum('true','false')	Y	false	N

- 索引

Key name	Column names	Unique	Comment
primary	cur_id	Y	
uni_ident_type	cur_code	N	

ectools_order_bills

● 表结构

ColumnName	Comment	Type	Not null	Default
rel_id	rel_id	bigint(20) unsigned	Y	0
bill_type	单据类型 payments:付款单;refunds:退款单;	enum('payments','refunds')	Y	payments
pay_object	支付类型 order:订单支付;recharge:预存款充值;joinfee:加盟费;prepaid_recharge:消费卡;	enum('order','recharge','joinfee','prepaid_recharge')	Y	order
bill_id	关联单号	varchar(20)	Y	
money	money	decimal(20,2)	N	

● 索引

Key name	Column names	Unique	Comment
primary	rel_id, bill_id	Y	

ectools_payments

支付记录

● 表结构

ColumnName	Comment	Type	Not null
payment_id	支付单号	varchar(20)	Y
money	支付金额	decimal(20,2)	Y
cur_money	支付货币金额	decimal(20,2)	Y
member_id	客户用户名	varchar(100)	N
status	支付状态 succ:支付成功;failed:支付失败;cancel:未支付;error:处理异常;invalid:非法参数;progress:已付款至担保方;timeout:超时;ready:准备中;	enum('succ','failed','cancel','error','invalid','progress','timeout','ready')	Y
pay_name	pay_name	varchar(100)	N
pay_type	支付类型 online:在线支付;offline:线下支	enum('online','offline','deposit')	Y

	付;deposit: 预存款支付;		
t_payed	支付完成时间	int(10) unsigned	N
op_id	操作员	mediumint(8) unsigned	N
payment_bn	支付单唯一编号	varchar(32)	N
account	收款账号	varchar(50)	N
bank	收款银行	varchar(50)	N
pay_account	支付账户	varchar(50)	N
currency	货币	varchar(10)	N
paycost	支付网关费用	decimal(20,2)	N
pay_app_id	支付方式名称	varchar(100)	Y
pay_ver	支付版本号	varchar(50)	N
ip	支付IP	varchar(20)	N
t_begin	支付开始时间	int(10) unsigned	N
t_confirm	支付确认时间	int(10) unsigned	N
memo	支付注释	longtext	N
return_url	支付返回地址	varchar(100)	N
disabled	是否失效	enum('true','false')	N
trade_no	支付单交易编号	varchar(30)	N

● 索引

Key name	Column names	Unique	Comment
primary	payment_id	Y	
ind_disabled	disabled	N	

ectools_refunds

支付记录

● 表结构

ColumnName	Comment	Type	N
refund_id	退款单号	varchar(20)	Y
money	money	decimal(20,2)	Y
cur_money	支付金额	decimal(20,2)	Y
member_id	客户用户名	varchar(100)	N

account	收款账号	varchar(50)	N
bank	收款银行	varchar(50)	N
pay_account	支付账户	varchar(50)	N
currency	货币	varchar(10)	N
paycost	支付网关费用	decimal(20,2)	N
pay_type	支付类型 online:在线支付; offline:线下支付; deposit:预存款支付;	enum('online','offline','deposit')	Y
status	支付状态 succ:支付成功; failed:支付失败; cancel:未支付; error:处理异常; invalid:非法参数; progress:处理中; timeout:超时; ready:准备中;	enum('succ','failed','cancel','error','invalid','progress','timeout','ready')	Y
pay_name	pay_name	varchar(100)	N
pay_ver	支付版本号	varchar(50)	N
op_id	操作员	mediumint(8) unsigned	N
refund_bn	退款唯一单号	varchar(32)	N
pay_app_id	支付方式	varchar(100)	Y
t_begin	支付开始时间	int(10) unsigned	N
t_payed	支付完成时间	int(10) unsigned	N
t_confirm	支付确认时间	int(10) unsigned	N
memo	memo	longtext	N
disabled	是否失效	enum('true','false')	N
trade_no	trade_no	varchar(30)	N

● 索引

Key name	Column names	Unique	Comment
primary	refund_id	Y	
ind_disabled	disabled	N	

ectools_regions

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
region_id	region_id	int(10) unsigned	Y		Y
local_name	当地名称	varchar(50)	Y		N
package	数据包	varchar(20)	Y		N
p_region_id	p_region_id	int(10) unsigned	N		N
region_path	region_path	varchar(255)	N		N
region_grade	region_grade	mediumint(8) unsigned	N		N
p_1	p_1	varchar(50)	N		N
p_2	p_2	varchar(50)	N		N
ordernum	ordernum	mediumint(8) unsigned	N		N
group_name	所属区域	varchar(32)	N		N
disabled	是否失效	enum('true','false')	N	false	N

● 索引

Key name	Column names	Unique	Comment
primary	region_id	Y	
ind_p_regions_id	p_region_id, region_grade, local_name	Y	
ind_local_name	local_name	N	

app:image tables

image_image

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
image_id	图片Id	char(32)	Y		N
storage	存储引擎	varchar(50)	Y	filesystem	N
image_name	图片名称	varchar(50)	N		N
ident	ident	varchar(200)	Y		N
url	网址	varchar(200)	Y		N
l_ident	l_ident	varchar(200)	N		N
l_url	l_url	varchar(200)	N		N
m_ident	m_ident	varchar(200)	N		N
m_url	m_url	varchar(200)	N		N
s_ident	s_ident	varchar(200)	N		N
s_url	s_url	varchar(200)	N		N

width	宽度	mediumint(8) unsigned	N		N
height	高度	mediumint(8) unsigned	N		N
watermark	有水印	enum('true','false')	N	false	N
last_modified	更新时间	int(10) unsigned	Y	0	N

- 索引

Key name	Column names	Unique	Comment
primary	image_id	Y	

image_image_attach

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
attach_id	attach_id	mediumint(8) unsigned	Y		Y
target_id	target_id	mediumint(8) unsigned	Y	0	N
target_type	target_type	varchar(20)	Y	0	N
image_id	image_id	char(32)	Y	0	N
last_modified	更新时间	int(10) unsigned	Y	0	N

- 索引

Key name	Column names	Unique	Comment
primary	attach_id	Y	
index_1	target_id, target_type	N	
idx_c_image_id	image_id	N	

app:market tables

market_active

- 表结构

ColumnName	Comment	
active_id	active_id	int(10) unsigned
active_name	活动名称	varchar(255)
filter_mem	客户条件	text
filter_sql	筛选语句	text
report_filter	报表条件	text
member_list	客户id	text

shop_id	所属店铺	varchar(32)
type	活动类型	text
total_num	总客户数	mediumint(8) unsigned
valid_num	有效人数	mediumint(8) unsigned
active_num	响应人数	mediumint(8) unsigned
create_source	创建来源 normal:常规;tags:标签;members:店铺客户;	enum('normal','tags','me
is_active	活动是否执行 sel_coupon:选择优惠券;sel_member:等待选择客户;sel_template:等待选择模板;wait_exec:等待执行;finish:执行完成;dead:已作废;execute:正在执行;	enum('sel_coupon','sel_
templete_title	模板标题	varchar(500)
template	模板内容	text
template_id	短信模板	mediumint(8) unsigned
template_edm_id	邮件模板	mediumint(8) unsigned
coupon_id	优惠券id	int(10) unsigned
sent_time	计划发送时间	int(10) unsigned
create_time	创建时间	int(10) unsigned
start_time	开始时间	int(10) unsigned
end_time	结束时间	int(10) unsigned
exec_time	执行时间	int(10) unsigned
remark	备注	varchar(1000)
cost	成本	decimal(20,2)
tags	活动描述	varchar(500)
control_group	是否开启对照组 yes:是;no:否;	enum('yes','no')
unsubscribe	是否开启退订消息	tinyint(4)
is_send_salemember	是否发送已营销客户	tinyint(4)
pay_type	活动来源 free:自主创建;pay:按效果付费;market:营销超市;	enum('free','pay','marke
templete_title_b	模板标题B	varchar(500)
template_b	模板内容B	text
template_id_b	短信模板B	mediumint(8) unsigned
active_remark	shopName,entId,entPwd,license,taskId="activity"+activityId	text
cache_id	缓存ID	int(10) unsigned
cache_id_create_time	cache_id创建时间	int(10) unsigned
is_timing	是否定时发送	tinyint(4)
plan_send_time	定时发送时间	int(10) unsigned
op_user	操作人	varchar(30)
ip	IP地址	varchar(64)

- 索引

Key name	Column names	Unique	Comment

primary	active_id	Y	
ind_shop_id	shop_id	N	
ind_exec_time	exec_time	N	
ind_create_time	create_time	N	
idx_c_shop_id	shop_id	N	
idx_c_template_edm_id	template_edm_id	N	
idx_c_coupon_id	coupon_id	N	

market_active_abc

营销活动效果评估abc拆分数据

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	int(10) unsigned	Y		Y
active_id	营销活动	int(10) unsigned	N		N
total_members	总客户数	int(10) unsigned	N		N
order_members	下单客户数	int(10) unsigned	N		N
paid_members	付款客户数	int(10) unsigned	N		N
finish_members	成功订单客户数	int(10) unsigned	N		N
paid_amount	付款订单金额	decimal(20,2)	N		N
total_amount	订单总金额	decimal(20,2)	N		N
identify	标识符	varchar(3)	N		N
create_time	创建时间	int(10) unsigned	N		N
modified_time	更新时间	int(10) unsigned	N		N
end_time	结束时间	int(10) unsigned	N		N

- 索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_active_id	active_id	N	
idx_c_active_id	active_id	N	

market_active_assess

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	int(10) unsigned	Y		Y

active_id	活动名称	int(10) unsigned	N		N
shop_id	所属店铺	varchar(32)	N		N
msgid	msgid	varchar(100)	N		N
create_time	创建时间	int(10) unsigned	N		N
start_time	开始时间	int(10) unsigned	N		N
end_time	结束时间	int(10) unsigned	N		N
exec_time	执行时间	int(10) unsigned	N		N
active_members_res	活动客户B 评估结果	text	N		N
active_members_res_b	活动客户B 评估结果	text	N		N
control_members_res	对照客户评 估结果	text	N		N
state	状态 finish: 已完 成;unfinish: 未完成;	enum('finish','unfinish')	N	unfinish	N
is_control	是否对照	tinyint(3) unsigned	N	0	N
total_members	参加活动人 数	int(11)	N		N
order_members	下单人数	int(11)	N		N
paid_members	付款人数	int(11)	N		N
paid_amount	付款金额	decimal(20,2)	N		N
total_amount	下单总金额	decimal(20,2)	N		N
data_update_time	数据更新时 间	int(10) unsigned	N	0	N

● 索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_active_id	active_id	N	
idx_c_active_id	active_id	N	
idx_c_shop_id	shop_id	N	

market_active_cycle

● 表结构

ColumnName	Comment	Type	Not null	Default
active_id	active_id	int(10) unsigned	Y	
active_name	活动名称	varchar(255)	N	
goods_id	购买过的商品	text	N	

exclude_filter	排除条件	text	N	
cycle_type	周期设置 auto: 自动周期;fixed: 固定周期;	enum('auto','fixed')	N	
auto_cycle_type	自动周期开始时间 order_finish: 订单完成时间;order_paid: 订单付款时间;order_create: 订单创建时间;	enum('order_finish','order_paid','order_create')	N	
auto_cycle_days	自动周期天数	int(10)	N	0
fixed_cycle_days	固定周期天数	int(10)	N	
auto_run_hour	执行时间小时	int(10)	N	
auto_run_min	执行时间分钟	int(10)	N	
shop_id	适用店铺	varchar(500)	N	
type	活动类型	varchar(20)	N	sms
total_num	总客户数	mediumint(8) unsigned	N	0
valid_num	有效人数	mediumint(8) unsigned	N	0
active_num	响应人数	mediumint(8) unsigned	N	0
group_id	分组id	mediumint(8) unsigned	N	0
tag_id	标签id	mediumint(8) unsigned	N	0
source	数据来源	varchar(15)	Y	
templete_title	模板标题	varchar(500)	N	
templete	模板内容	text	N	
template_id	短信模板	mediumint(8) unsigned	N	0
template_edm_id	邮件模板	mediumint(8) unsigned	N	0
coupon_id	优惠券id	int(10) unsigned	N	0
sent_time	计划发送时间	int(10) unsigned	N	0
create_time	创建时间	int(10) unsigned	N	
start_time	开始时间	int(10) unsigned	N	
end_time	结束时间	int(10) unsigned	N	
exec_time	执行时间	int(10) unsigned	N	
remark	备注	varchar(100)	N	
is_timing	是否定时发送	tinyint(4)	N	
run_times	已执行次数	int(11)	N	0
total_send_num	累计发送人数	int(11)	N	0
status	是否开启 0:关 闭;1:开启;	enum('0','1')	N	1
run_status	执行状态 wait:等 待执行;running: 执行中;finish:完 成;closed:已关 闭;	enum('wait','running','finish','closed')	N	wait

plan_send_time	定时发送时间	int(10) unsigned	N	0
op_user	操作人	varchar(30)	N	
sms_sign	短信签名	varchar(30)	N	
extend_no	短信签名no	char(7)	N	
ip	IP地址	varchar(64)	N	
wait_days	等待天数	varchar(50)	N	

索引

Key name	Column names	Unique	Comment
primary	active_id	Y	
ind_create_time	create_time	N	
idx_c_template_edm_id	template_edm_id	N	
idx_c_coupon_id	coupon_id	N	

market_active_cycle_log

表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
log_id	log_id	int(10) unsigned	Y		Y
active_id	活动名称	int(10) unsigned	N		N
send_num	客户总数	int(10)	N	0	N
succ_num	成功数量	int(10)	N	0	N
status	结果 fail:失败;succ:成功;retry:重试;close:中断;	enum('fail','succ','retry','close')	N		N
create_time	发送时间	int(10) unsigned	N		N
remark	备注说明	varchar(500)	N		N

索引

Key name	Column names	Unique	Comment
primary	log_id	Y	
ind_active_id	active_id	N	
idx_c_active_id	active_id	N	

market_active_member

表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
member_id	member_id	int(10) unsigned	Y		N
active_id	active_id	int(10) unsigned	Y		N
status	0=>未加入,1=>活动组,2=>对照组,3=>短信对照组	tinyint(3) unsigned	N	0	N
issend	0=>未发送,1=>发送	tinyint(3) unsigned	N	0	N
sendtime	发送时间	int(10) unsigned	N		N
shop_id	所属店铺	varchar(32)	N		N
send_type	1=>短信,2=>邮件	tinyint(3) unsigned	N	1	N
active_type	活动类型 1:常规活动;2:周期活动;3:活动计划;	enum('1','2','3')	N	1	N
mobile	手机	bigint(11)	N	0	N

● 索引

Key name	Column names	Unique	Comment
primary	member_id, active_id, active_type	Y	
ind_active_id	active_id	N	
ind_member_id	member_id	N	
idx_c_shop_id	shop_id	N	

market_active_member_cycle

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	int(10) unsigned	Y		Y
member_id	member_id	int(10) unsigned	N		N
active_id	active_id	int(10) unsigned	N		N
status	0=>未加入,1=>活动组,2=>对照组,3=>短信对照组	tinyint(3) unsigned	N	0	N
issend	0=>未发送,1=>发送	tinyint(3) unsigned	N	0	N
sendtime	发送时间	int(10) unsigned	N		N
shop_id	所属店铺	varchar(32)	N		N

send_type	1=>短信,2=>邮件	tinyint(3) unsigned	N	1	N
active_type	活动类型 1:常规活动;2:周 期活动;3:活动计划;	enum('1','2','3')	N	1	N
mobile	手机	bigint(11)	N	0	N

● 索引

Key name	Column names	Unique	Comment
primary	id, member_id, active_id, active_type	Y	
ind_active	active_id, member_id	N	
ind_member_id	member_id	N	
idx_c_shop_id	shop_id	N	

market_active_member_plan

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	int(10) unsigned	Y		Y
member_id	member_id	int(10) unsigned	N		N
active_id	active_id	int(10) unsigned	N		N
status	0=>未加入,1=>活动 组,2=>对照组,3=>短信对 照组	tinyint(3) unsigned	N	0	N
issend	0=>未发送,1=>发送	tinyint(3) unsigned	N	0	N
sendtime	发送时间	int(10) unsigned	N		N
shop_id	所属店铺	varchar(32)	N		N
send_type	1=>短信,2=>邮件	tinyint(3) unsigned	N	1	N
active_type	活动类型 1:常规活动;2:周 期活动;3:活动计划;	enum('1','2','3')	N	1	N
mobile	手机	bigint(11)	N	0	N

● 索引

Key name	Column names	Unique	Comment
primary	id, member_id, active_id, active_type	Y	
ind_active	active_id, member_id	N	
ind_member_id	member_id	N	
idx_c_shop_id	shop_id	N	

market_active_plan

• 表结构

ColumnName	Comment	Type	Not null	Default	Auto increment
active_id	active_id	int(10) unsigned	Y		Y
parent_id	父节点ID	int(10) unsigned	N	0	N
active_name	活动名称	varchar(255)	N		N
filter_mem	筛选条件	text	N		N
exclude_filter	排除条件	text	N		N
cycle_type	周期设置 auto:自动周期;fixed:固定周期;	enum('auto','fixed')	N		N
auto_cycle_days	自动周期天数	int(10)	N		N
fixed_cycle_days	固定周期天数	int(10)	N		N
wait_days	等待天数	varchar(50)	N		N
plan_send_time	计划发送	int(10) unsigned	N		N
exec_time	执行时间	int(10) unsigned	N		N
auto_run_hour	执行时间小时	int(10)	N		N
auto_run_min	执行时间分钟	int(10)	N		N
shop_ids	店铺	text	N		N
type	活动类型	varchar(20)	N	sms	N
total_num	总客户数	mediumint(8) unsigned	N	0	N
valid_num	有效人数	mediumint(8) unsigned	N	0	N
active_num	响应人数	mediumint(8) unsigned	N	0	N
templete	短信内容	text	N		N
templete_b	短信内容B	text	N		N
templete_id	短信模板	mediumint(8) unsigned	N	0	N
templete_id_b	短信模板B	mediumint(8) unsigned	N	0	N
create_time	创建时间	int(10) unsigned	N		N
start_time	开始时间	int(10) unsigned	N		N
end_time	结束时间	int(10) unsigned	N		N
remark	备注	varchar(100)	N		N
is_timing	是否定时发送	tinyint(4)	N		N

run_times	已执行次数	int(11)	N	0	N
total_send_num	累计发送人数	int(10)	N	0	N
status	是否开启 0: 关闭;1:开启;	enum('0','1')	N	1	N
run_status	执行状态 wait:等待执行;running: 执行中;finish:完成;closed: 已关闭;	enum('wait','running','finish','closed')	N	wait	N
op_user	操作人	varchar(30)	N		N
sms_sign	短信签名	varchar(30)	N		N
extend_no	短信签名no	char(7)	N		N
sms_sign_b	短信签名B	varchar(30)	N		N
extend_no_b	短信签名Bno	char(7)	N		N
ip	IP地址	varchar(64)	N		N
half_compare	是否活动对照	int(10)	N	0	N
ab_compare	是否AB短信对照	int(10)	N	0	N

● 索引

Key name	Column names	Unique	Comment
primary	active_id	Y	
ind_ab_compare	ab_compare	N	

market_active_review

营销活动监控

● 表结构

ColumnName	Comment	Type	Not null	Defa
id	id	int(10) unsigned	Y	
active_id	营销活动ID	int(10) unsigned	N	
title	营销名称	varchar(100)	N	
active_type	任务类型 active: 营销活 动;active_ontime: 定时营 销;active_cycle: 周期营销;plugins: 营销插件;	enum('active','active_ontime','active_cycle','plugins')	N	active
begin_time	活动开始时间	int(10) unsigned	N	
end_time	活动结束时间	int(10) unsigned	N	

last_run_time	最后执行时间	int(10) unsigned	N	
status	执行状态 wait:等待执行;running:执行中;finish:完成;dead:关闭;pause:暂停;	enum('wait','running','finish','dead','pause')	N	wait
exec_times	执行次数	int(10) unsigned	N	0
send_members	累计发送人数	int(10) unsigned	N	0
update_time	更新时间	int(10) unsigned	N	

索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_active_key	active_id, active_type	Y	
ind_last_run_time	last_run_time	N	
ind_title	title	N	

market_activity_edm_queue

表结构

ColumnName	Comment	Type	Not null	Default	Auto increment
queue_id	queue_id	int(10) unsigned	Y		Y
active_id	active_id	int(10) unsigned	Y		N
template_id	短信模板id	mediumint(8) unsigned	N		N
member_id	member_id	int(10) unsigned	Y		N
uname	用户名(旺旺帐号)	char(32)	Y		N
truename	真实姓名	char(32)	Y		N
email	电子邮件	varchar(200)	N		N
is_send	是否发送短信	tinyint(3) unsigned	N	1	N
is_send_coupon	是否发送优惠券	tinyint(3) unsigned	N	1	N
is_send_email	是否发送邮箱	tinyint(3) unsigned	N	1	N
is_send_finish	是否发送短信完成	tinyint(3) unsigned	N	0	N
is_send_coupon_finish	是否发送优惠券完成	tinyint(3) unsigned	N	0	N
is_send_email_finish	是否发送邮箱	tinyint(3) unsigned	N	0	N
sent_time	发送短信时间	int(10) unsigned	N	0	N

sent_coupon_time	发送优惠券时间	int(10) unsigned	N	0	N
sent_email_time	发送邮箱时间	int(10) unsigned	N	0	N

● 索引

Key name	Column names	Unique	Comment
primary	queue_id	Y	
ind_active_id	active_id	N	
ind_email	email	N	
ind_sent_time	sent_time	N	

market_activity_m_queue

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
queue_id	queue_id	int(10) unsigned	Y		Y
active_id	active_id	int(10) unsigned	Y		N
template_id	短信模板id	mediumint(8) unsigned	N		N
member_id	member_id	int(10) unsigned	Y		N
uname	用户名(旺旺帐号)	char(32)	Y		N
truename	真实姓名	char(32)	Y		N
mobile	手机号码	char(15)	Y		N
is_send	是否发送短信(0:不发送 1:发送 2 不发送,对照的)	tinyint(3) unsigned	N	1	N
is_send_coupon	是否发送优惠券	tinyint(3) unsigned	N	1	N
is_send_finish	是否发送短信完成	tinyint(3) unsigned	N	0	N
is_send_coupon_finish	是否发送优惠券完成	tinyint(3) unsigned	N	0	N
sent_time	发送短信时间	int(10) unsigned	N	0	N
sent_coupon_time	发送优惠券时间	int(10) unsigned	N	0	N

● 索引

Key name	Column names	Unique	Comment
primary	queue_id	Y	

ind_active_id	active_id	N	
ind_mobile	mobile	N	
ind_sent_time	sent_time	N	
ind_member_id	member_id	N	
ind_is_send	is_send	N	
ind_is_send_finish	is_send_finish	N	

market_activity_m_queue_finished

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
queue_id	queue_id	int(10) unsigned	Y		Y
active_id	active_id	int(10) unsigned	Y		N
template_id	短信模板id	mediumint(8) unsigned	N		N
member_id	member_id	int(10) unsigned	Y		N
uname	用户名(旺旺帐号)	char(32)	Y		N
true_name	真实姓名	char(32)	Y		N
mobile	手机号码	char(15)	Y		N
is_send	是否发送短信(0:不发送 1:发送 2 不发送,对照的)	tinyint(3) unsigned	N	1	N
is_send_coupon	是否发送优惠券	tinyint(3) unsigned	N	1	N
is_send_finish	是否发送短信完成	tinyint(3) unsigned	N	0	N
is_send_coupon_finish	是否发送优惠券完成	tinyint(3) unsigned	N	0	N
sent_time	发送短信时间	int(10) unsigned	N	0	N
sent_coupon_time	发送优惠券时间	int(10) unsigned	N	0	N

- 索引

Key name	Column names	Unique	Comment
primary	queue_id	Y	
ind_active_id	active_id	N	
ind_mobile	mobile	N	
ind_sent_time	sent_time	N	

ind_member_id	member_id	N	
ind_is_send	is_send	N	
ind_is_send_finish	is_send_finish	N	

market_api_log

api日志

- 表结构

ColumnName	Comment	Type	Not null	Default	
log_id	日志编号	varchar(32)	Y		↑
task_name	任务名称	varchar(255)	N		↑
status	状态 running:运行中;success:成功;fail:失败;sending:发起中;	enum('running','success','fail','sending')	Y	sending	↑
worker	api方法名	varchar(200)	Y		↑
params	任务参数	longtext	N		↑
msg	msg	text	N		↑
api_type	同步类型 response:响应;request:请求;	enum('response','request')	Y	request	↑
error_lv	错误级别 normal:正常;system:系统级;application:应用级;warning:警告;	enum('normal','system','application','warning')	Y	normal	↑
marking_value	marking_value	varchar(80)	N		↑
marking_type	marking_type	varchar(32)	N		↑
memo	memo	text	N		↑
msg_id	msg_id	varchar(60)	N		↑
retry	重试次数	mediumint(8) unsigned	Y	0	↑
createtime	发起同步时间	int(10) unsigned	N		↑
last_modified	最后重试时间	int(10) unsigned	N		↑

- 索引

Key name	Column names	Unique	Comment
primary	log_id	Y	
ind_status	status	N	
ind_api_type	api_type	N	

ind_error_lv	error_lv	N	
ind_marking	marking_value, marking_type	Y	

market_callplan

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
callplan_id	callplan_id	int(10) unsigned	Y		Y
callplan_name	呼叫计划名称	varchar(100)	N		N
assign_users	分配客服	varchar(500)	N		N
start_time	开始时间	int(10) unsigned	N		N
end_time	结束时间	int(10) unsigned	N		N
total_num	全部客户数	mediumint(8) unsigned	N	0	N
assign_num	已分配数	mediumint(8) unsigned	N	0	N
called_num	已拨打数	mediumint(8) unsigned	N	0	N
finish_num	完成数	mediumint(8) unsigned	N	0	N
desc	备注说明	text	N		N
create_time	创建时间	int(10) unsigned	N		N
update_time	更新时间	int(10) unsigned	N		N
create_user	创建人	varchar(50)	N		N
status	状态 0:关闭;1:开启;	enum('0','1')	N	1	N
assign_user_id	分配客服ID	varchar(500)	N		N
survey_id	问卷调查	int(11)	N	0	N
source	创建来源	varchar(50)	N	0	N
source_id	来源ID	int(11)	N	0	N
err_msg	错误描述	varchar(500)	N		N

● 索引

Key name	Column names	Unique	Comment
primary	callplan_id	Y	
ind_callplan_name	callplan_name	N	

market_callplan_members

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	int(10) unsigned	Y		Y
callplan_id	呼叫计划	int(10) unsigned	N	0	N
customer	客户昵称	varchar(50)	N		N
member_id	客户ID	int(10) unsigned	N	0	N
truename	姓名	varchar(50)	N		N
mobile	手机号码	varchar(50)	N		N
create_time	创建时间	int(10) unsigned	N		N
update_time	跟进时间	int(10) unsigned	N		N
alarm_time	提醒时间	int(10) unsigned	N		N
call_result	呼叫结果	int(11)	N		N
remark	呼叫备注	text	N		N
call_times	呼叫次数	mediumint(8) unsigned	N	0	N
caselog_id	接待详情ID	int(11)	N		N
assign_user_id	坐席ID	int(11)	N	0	N
assign_user	坐席	varchar(50)	N		N
esc_user	升级对象	varchar(50)	N		N
is_finish	是否完成	tinyint(4)	N	0	N

● 索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_callplan_id	callplan_id	N	
idx_c_callplan_id	callplan_id	N	
idx_c_member_id	member_id	N	
idx_c_call_result	call_result	N	
idx_c_caselog_id	caselog_id	N	

market_coupon_ecstore

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
coupon_id	coupon_id	int(10) unsigned	Y		Y
ecstore_coupon_id	优惠券ID	varchar(32)	N		N
coupon_name	优惠券名称	varchar(255)	N		N

coupon_bn	优惠券编码	varchar(32)	N		N
coupon_type	优惠券类型	varchar(8)	N		N
shop_id	所属店铺	varchar(32)	Y		N
created	创建时间	int(10) unsigned	N		N
sync_last_time	最后同步时间	int(10) unsigned	N		N
start_time	开始时间	int(10) unsigned	N		N
end_time	结束时间	int(10) unsigned	N		N
description	规则描述	text	N		N
user_lv_id	会员级别ID	text	N		N
coupon_status	有效状态 y:是;n:否;	enum('y','n')	N		N
is_del	是否删除 y:是;n:否;	enum('y','n')	N		N

● 索引

Key name	Column names	Unique	Comment
primary	coupon_id	Y	
idx_c_shop_id	shop_id	N	

market_coupon_ecstore_sendlog

● 表结构

ColumnName	Comment	Type	Not null	Default	Auto i
log_id	log_id	int(11)	Y		Y
coupon_id	coupon_id	int(10) unsigned	Y		N
shop_id	shop_id	varchar(32)	N		N
is_send	优惠券是否发送 succ:发送成功;fail:发送失败;unsend:未发送;sending:发送中;	enum('succ','fail','unsend','sending')	N	unsend	N
coupon_total_num	优惠券发送总数	mediumint(8) unsigned	N		N
coupon_valid_num	优惠券发送有效数	mediumint(8) unsigned	N		N
conpon_success_num	优惠券发送成功数	mediumint(8) unsigned	N		N

created	创建时间	int(10) unsigned	N		N
finish_time	完成时间	int(10) unsigned	N		N

- 索引

Key name	Column names	Unique	Comment
primary	log_id	Y	

market_coupon_ecstore_sendlog_item

优惠券发送记录明细

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
log_item_id	log_item_id	int(10) unsigned	Y		Y
log_id	log_id	int(11)	Y		N
shop_id	所属店铺	varchar(32)	N		N
member_id	客户名	int(10) unsigned	N		N
is_sms	0=>否,1=>是	tinyint(3) unsigned	N	0	N
is_coupon	0=>否,1=>是	tinyint(3) unsigned	N	0	N
reason	失败信息	text	N		N
sendtime	发送时间	int(10) unsigned	N		N

- 索引

Key name	Column names	Unique	Comment
primary	log_item_id	Y	
idx_c_shop_id	shop_id	N	
idx_c_member_id	member_id	N	

market_coupon_ecstore_used

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	int(10) unsigned	Y		Y
log_id	log_id	int(11)	Y		N
coupon_id	coupon_id	int(10) unsigned	Y		N
member_id	客户名	int(10) unsigned	N		N
coupon_name	优惠券名称	varchar(255)	N		N
coupon_number	优惠券编号	varchar(32)	N		N
tid	订单号	varchar(32)	N		N
amount	订单金额	varchar(32)	N		N

--	--	--	--	--	--

- 索引

Key name	Column names	Unique	Comment
primary	id	Y	
idx_c_member_id	member_id	N	

market_coupon_sent

优惠券发送记录

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
sent_id	sent_id	int(10) unsigned	Y		Y
coupon_id	优惠券名称	int(10) unsigned	Y		N
coupon_number	发送的优惠券编号	varchar(32)	N		N
buyer_nick	用户名	text	Y		N
shop_id	所属店铺	varchar(32)	N		N
sent_status	发送状态 succ:成功;fail:失败;	enum('succ','fail')	Y	succ	N
reason	失败信息	text	N		N
send_time	发送时间	int(10) unsigned	N		N

- 索引

Key name	Column names	Unique	Comment
primary	sent_id	Y	
idx_c_coupon_id	coupon_id	N	
idx_c_shop_id	shop_id	N	

market_coupon_used

--

- 表结构

ColumnName	Comment	Type
id	id	int(10) unsigned
coupon_id	优惠券名称	int(10) unsigned
coupon_number	发送的优惠券编号	varchar(32)
state	优惠券状态 Unused:未使用;using:使用中;used:已使用;	enum('Unused','using','used')
	发放渠道 rewardforgifts:满就	

channel	送;marketingMessage:营销消息;activityofget:活动领取;createActivity:创建活动;ISV:ISV;other:其他;	enum('rewardforgifts','marketingMessage','activityofget','createActi
buyer_nick	买家昵称	varchar(50)

索引

Key name	Column names	Unique	Comment
primary	id	Y	
idx_c_coupon_id	coupon_id	N	

market_coupons

表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
coupon_id	coupon_id	int(10) unsigned	Y		Y
coupon_name	优惠券名称	varchar(255)	N		N
active_id	活动ID	int(10) unsigned	N		N
outer_activity_id	外部活动ID	varchar(32)	N	0	N
outer_coupon_id	优惠券编号	varchar(32)	N	0	N
outer_activity_url	外部活动url	text	N		N
shop_id	所属店铺	varchar(32)	Y		N
status	优惠券方案状态	enum('0','1')	Y	1	N
created	创建时间	int(10) unsigned	N		N
updated	更新时间	int(10) unsigned	N		N
start_time	开始时间	int(10) unsigned	N		N
end_time	结束时间	int(10) unsigned	N		N
denominations	面额	mediumint(8) unsigned	N		N
conditions	订单满x元	mediumint(8) unsigned	N		N
coupon_count	总数	mediumint(8) unsigned	N		N
person_limit_count	每人限领	mediumint(8) unsigned	N		N
applied_count	已领取数	mediumint(8) unsigned	N	0	N
used_num	已使用数	mediumint(8) unsigned	N	0	N
f_sync_coupon_msg	前台优惠券同	text	N		N

f_sync_coupon_msg	步信息	text	N		N
f_sync_activity_msg	前台活动同步信息	text	N		N
f_sync_coupon	前台优惠券是否同步 y:是;n:否;	enum('y','n')	N	n	N
f_sync_activity	前台活动是否同步 y:是;n:否;	enum('y','n')	N	n	N
remark	备注	text	N		N
source	1:本地 2:淘宝 local:本地;taobao:淘宝;	enum('local','taobao')	N		N
is_exchange	可否兑换	tinyint(4)	N	0	N

索引

Key name	Column names	Unique	Comment
primary	coupon_id	Y	
ind_end_time	end_time	N	
idx_c_shop_id	shop_id	N	

market_edm

表结构

ColumnName	Comment	Type	Not null	Default
id	id	int(11)	Y	
type	发送方式 single:single;batch:batch;	enum('single','batch')	Y	
theme_id	邮件模板	mediumint(8) unsigned	N	
shop_id	店铺ID	varchar(32)	Y	
active_id	活动ID	int(10) unsigned	Y	
active_name	活动名称	varchar(255)	N	
title	邮件主题	varchar(100)	N	
content	邮件内容	text	N	
end_time	结束时间	int(10) unsigned	N	
plan_send_time	计划发送时间	int(10) unsigned	Y	
total_num	总数	mediumint(8) unsigned	N	
success_num	成功数	mediumint(8) unsigned	N	
is_send	邮件是否发送 succ:发送成功;fail:发送失败;unsend:未发送;sending:发送中;	enum('succ','fail','unsend','sending')	N	unsend
create_time	创建时间	int(10) unsigned	Y	

- 索引

Key name	Column names	Unique	Comment
primary	id	Y	
idx_c_theme_id	theme_id	N	
idx_c_shop_id	shop_id	N	
idx_c_active_id	active_id	N	

market_edm_blacklist

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	mediumint(8) unsigned	Y		Y
member_id	客户编号	int(10) unsigned	N		N
contact_id	联系人	mediumint(8) unsigned	N		N
create_time	添加时间	int(10) unsigned	N		N

- 索引

Key name	Column names	Unique	Comment
primary	id	Y	
idx_c_member_id	member_id	N	
idx_c_contact_id	contact_id	N	

market_edm_log

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincren
id	id	int(11)	Y		Y
member_id	member_id	text	N		N
edm_id	edm_id	int(11)	N		N
active_id	活动编号	int(10) unsigned	N		N
type	发送方式 single:single;batch:batch;	enum('single','batch')	Y		N
shop_id	店铺ID	varchar(32)	Y		N
batch_no	批次编号	varchar(150)	N		N
edm_batch_no	发送批次	varchar(50)	N		N
email	email账号	text	N		N
title	邮件主题	varchar(100)	N		N

content	邮件内容	text	N		N
status	status failed:发送失败;success:发送成功;	enum('failed','success')	N	failed	N
reason	失败原因	text	N		N
send_num	发送人数	mediumint(8) unsigned	N		N
plan_send_time	计划发送时间	int(10) unsigned	N	0	N
create_time	执行时间	int(10) unsigned	Y		N

● 索引

Key name	Column names	Unique	Comment
primary	id	Y	
idx_c_edm_id	edm_id	N	
idx_c_active_id	active_id	N	
idx_c_shop_id	shop_id	N	

market_edm_tclass

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
type_id	type_id	mediumint(8) unsigned	Y		Y
title	分类名称	varchar(100)	Y		N
remark	分类备注	varchar(100)	Y		N
create_time	添加时间	int(10) unsigned	N		N
is_fixed	是否固定	tinyint(4)	N	0	N
mbt_type_id	模板堂分类ID	mediumint(8) unsigned	N	0	N

● 索引

Key name	Column names	Unique	Comment
primary	type_id	Y	

market_edm_template_type

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
type_id	type_id	mediumint(8) unsigned	Y		Y
title	分类名称	varchar(100)	Y		N
remark	分类备注	varchar(100)	Y		N
create_time	创建时间	int(10) unsigned	N		N

- 索引

Key name	Column names	Unique	Comment
primary	type_id	Y	

market_edm_templates

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
theme_id	theme_id	mediumint(8) unsigned	Y		Y
theme_title	模板名称	varchar(100)	N		N
theme_content	内容	text	Y		N
type_id	所属分类	mediumint(8) unsigned	N		N
create_time	创建时间	int(10) unsigned	N		N
status	模板状态	tinyint(4)	N	1	N
mbt_theme_id	模板堂模板ID	mediumint(8) unsigned	N	0	N

- 索引

Key name	Column names	Unique	Comment
primary	theme_id	Y	
idx_c_type_id	type_id	N	

market_exchange_items

可兑换物品

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
item_id	item_id	int(10) unsigned	Y		Y
title	兑换名称	varchar(100)	N		N
num	可兑换数量	int(10) unsigned	N		N
price	兑换价格	int(10) unsigned	N		N
max_buy_num	限兑数量	mediumint(8) unsigned	N	0	N
shop_id	适用店铺	varchar(32)	N		N
item_type	兑换类型 coupon:优惠券;gift:礼品;	enum('coupon','gift')	N	coupon	N
relate_id	关联ID	mediumint(8) unsigned	N	0	N
item_desc	兑换说明	text	N		N
is_active	是否可用	tinyint(4)	N	0	N

op_user	操作人	varchar(32)	N		N
user_ip	操作IP	varchar(64)	N		N
end_time	兑换截止时间	int(10) unsigned	N		N
create_time	创建时间	int(10) unsigned	N		N

● 索引

Key name	Column names	Unique	Comment
primary	item_id	Y	
idx_c_shop_id	shop_id	N	

market_exchange_order

优惠券兑换日志

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
order_id	order_id	int(10) unsigned	Y		Y
item_id	兑换名称	int(10) unsigned	N		N
member_id	客户名	int(10) unsigned	N		N
payment	消费积分	int(11)	N	0	N
num	兑换数量	mediumint(8) unsigned	N	0	N
item_relate_id	优惠券原始ID	mediumint(8) unsigned	N	0	N
item_type	兑换类型 coupon:优惠券;gift:礼品;	enum('coupon','gift')	N	coupon	N
shop_id	来源店铺	varchar(32)	N		N
create_time	创建时间	int(10) unsigned	N		N
is_active	状态	enum('0','1')	N	1	N
op_user	操作人	varchar(32)	N		N
status	兑换状态	varchar(50)	N		N
remark	备注	varchar(200)	N		N
user_ip	IP地址	varchar(100)	N		N

● 索引

Key name	Column names	Unique	Comment
primary	order_id	Y	
ind_order_id	order_id	N	
idx_c_item_id	item_id	N	
idx_c_member_id	member_id	N	
idx_c_shop_id	shop_id	N	

market_fx_activity

- 表结构

ColumnName	Comment	
activity_id	activity_id	int(10) unsigned
activity_name	活动名称	varchar(255)
filter_mem	客户条件	text
filter_sql	筛选语句	text
report_filter	报表条件	text
member_list	客户id	text
shop_id	所属店铺	varchar(32)
type	活动类型	text
total_num	总客户数	mediumint(8) unsigned
valid_num	有效人数	mediumint(8) unsigned
unvalid_num	无效人数	mediumint(8) unsigned
is_active	活动是否执行 sel_member:等待选择客户;sel_template:等待选择模板;wait_exec:等待执行;finish:执行完成;dead:已作废;execute:正在执行;	enum('sel_member','sel
templete_title	模板标题	varchar(500)
templete	模板内容	text
template_id	短信模板	mediumint(8) unsigned
template_edm_id	邮件模板	mediumint(8) unsigned
coupon_id	优惠券id	int(10) unsigned
sent_time	计划发送时间	int(10) unsigned
create_time	创建时间	int(10) unsigned
start_time	开始时间	int(10) unsigned
end_time	结束时间	int(10) unsigned
exec_time	执行时间	int(10) unsigned
remark	备注	varchar(1000)
cost	成本	decimal(20,2)
tags	活动描述	varchar(500)
control_group	是否开启对照组 yes:是;no:否;	enum('yes','no')
unsubscribe	是否开启退订消息	tinyint(4)
is_send_salemember	是否发送已营销客户	tinyint(4)
pay_type	活动来源 free:自主创建;pay:按效果付费;market:营销超市;	enum('free','pay','marke
templete_title_b	模板标题B	varchar(500)

templete_b	模板内容B	text
template_id_b	短信模板B	mediumint(8) unsigned
active_remark	shopName,entId,entPwd,license,taskId="activity"+activityId	text
cache_id	缓存ID	int(10) unsigned
cache_id_create_time	cache_id创建时间	int(10) unsigned
op_user	操作人	varchar(30)
ip	IP地址	varchar(64)

● 索引

Key name	Column names	Unique	Comment
primary	activity_id	Y	
ind_shop_id	shop_id	N	
idx_c_shop_id	shop_id	N	
idx_c_template_edm_id	template_edm_id	N	
idx_c_coupon_id	coupon_id	N	

market_fx_sms

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
sms_id	sms_id	int(11)	Y		Y
shop_id	所属店铺	varchar(32)	N		N
activity_id	活动名称	int(10) unsigned	Y		N
total_num	发送总数	int(11)	N	0	N
succ_num	成功总数	int(11)	N	0	N
fail_num	失败总数	int(11)	N	0	N
last_send_time	最后发送时间	int(10) unsigned	N	0	N
send_status	短信是否发送 succ:发送成功;fail:发送失败;unsend:未发送;sending:发送中;	enum('succ','fail','unsend','sending')	N	unsend	N

● 索引

Key name	Column names	Unique	Comment
primary	sms_id	Y	
idx_c_shop_id	shop_id	N	
idx_c_activity_id	activity_id	N	

market_fx_sms_log

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
sms_log_id	sms_log_id	int(11)	Y		Y
sms_id	sms_id	int(11)	Y		N
page	page	int(11)	Y		N
is_send	是否发送(0:未发送 1:发送成功 2:发送失败)	tinyint(3) unsigned	N	0	N
reason	失败原因	text	N		N
send_time	发送时间	int(10) unsigned	N	0	N

- 索引

Key name	Column names	Unique	Comment
primary	sms_log_id	Y	
ind_sms_id	sms_id	N	
ind_is_send	is_send	N	
ind_sms_page	sms_id, page	Y	

market_sms

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
sms_id	sms_id	int(10) unsigned	Y		Y
template_id	短信模板A	mediumint(8) unsigned	N	0	N
template_id_b	短信模板B	mediumint(8) unsigned	N	0	N
active_id	活动编号	int(10) unsigned	N		N
shop_id	所属店铺	varchar(32)	N		N
active_name	活动名称	varchar(255)	N		N
sms_type	短信类型 active:创建活动;coupon:发优惠券;order:订单;	enum('active','coupon','order')	N	active	N
create_time	发送时间	int(10) unsigned	N		N

end_time	结束时间	int(10) unsigned	N		N
plan_send_time	计划发送时间	int(10) unsigned	N		N
total_num	总数	mediumint(8) unsigned	N		N
success_num	成功数	mediumint(8) unsigned	N		N
is_send	短信是否发送 succ:发送成功;fail:发送失败;unsend:未发送;sending:发送中;	enum('succ','fail','unsend','sending')	N	unsend	N

● 索引

Key name	Column names	Unique	Comment
primary	sms_id	Y	
ind_active_id	active_id	N	
idx_c_template_id	template_id	N	
idx_c_template_id_b	template_id_b	N	
idx_c_active_id	active_id	N	
idx_c_shop_id	shop_id	N	

market_sms_blacklist

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	mediumint(8) unsigned	Y		Y
member_id	客户编号	int(10) unsigned	N		N
contact_id	联系人	mediumint(8) unsigned	N		N
create_time	添加时间	int(10) unsigned	N		N

● 索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_member_id	member_id	N	
idx_c_member_id	member_id	N	
idx_c_contact_id	contact_id	N	

market_sms_deduction_record

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	mediumint(8) unsigned	Y		Y
active_id	活动id	int(10) unsigned	N		N
actual_pay	实际支付	decimal(20,2)	N	0	N
plan_pay	计划支付	decimal(20,2)	N	0	N
create_time	创建时间	int(10) unsigned	N		N
update_time	更新时间	int(10) unsigned	N		N
status	支付状态 unpay:未支付;paysucc:支付成功;paypart:部分支付;	enum('unpay','paysucc','paypart')	N	unpay	N

● 索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_create_time	create_time	N	
ind_status	status	N	
idx_c_active_id	active_id	N	

market_sms_deduction_record_item

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	mediumint(8) unsigned	Y		Y
record_id	支付记录id	mediumint(8) unsigned	N		N
pay_nums	支付短信数	decimal(20,2)	N	0	N
create_time	操作时间	int(10) unsigned	N		N

● 索引

Key name	Column names	Unique	Comment
primary	id	Y	

market_sms_log

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
log_id	log_id	int(11)	Y		Y

member_id	member_id	text	N		N
sms_id	sms_id	int(10) unsigned	N		N
active_id	营销活动	int(10) unsigned	N		N
type	发送方式 1:queue;2:cron;	enum('1','2')	N		N
shop_id	shop_id	varchar(32)	N		N
batch_no	批次编号	varchar(150)	N		N
sms_batch_no	短信发送批次	varchar(50)	N		N
mobile	手机号码	text	N		N
content	短信内容	varchar(280)	N		N
status	status wait:等待;failed:发送失败;success:发送成功;	enum('wait','failed','success')	N	failed	N
reason	失败原因	text	N		N
plan_send_time	计划发送时间	int(10) unsigned	N	0	N
create_time	创建时间	int(10) unsigned	N		N

● 索引

Key name	Column names	Unique	Comment
primary	log_id	Y	
ind_sms_id	sms_id	N	
idx_c_sms_id	sms_id	N	
idx_c_active_id	active_id	N	

market_sms_op_record

● 表结构

ColumnName	Comment	Type	Not null	Default
id	id	mediumint(8) unsigned	Y	
action	操作类型 freeze:冻结;unfreeze:解冻;deduct:扣除;	enum('freeze','unfreeze','deduct')	N	
msgid	客户ID	varchar(100)	N	
nums	短信条数	mediumint(8) unsigned	N	
create_time	操作时间	int(10) unsigned	N	
status	操作状态 deductsucc:扣除成功;deductfail:扣除失	enum('deductsucc','deductfail','freezesucc','freezefail')	N	

	败;freezesucc: 冻结成功;freezefail: 冻结失败;			
remark	备注信息	varchar(50)	N	
reason	失败原因	text	N	

索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_create_time	create_time	N	
ind_remark	remark	N	
ind_action	action	N	

market_sms_order_log

表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
order_id	订单号	int(10) unsigned	N		N
sms_type	短信类型 urge:催付;remind:通知;	enum('urge','remind')	Y		N
sms_id	短信编号	int(10) unsigned	Y		N
send_time	发送时间	int(10) unsigned	N		N

索引

Key name	Column names	Unique	Comment
ind_sms_id	sms_id	N	
idx_c_order_id	order_id	N	
idx_c_sms_id	sms_id	N	

market_sms_template_type

表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
type_id	type_id	mediumint(8) unsigned	Y		Y
title	分类名称	varchar(100)	Y		N
remark	分类备注	varchar(100)	Y		N
create_time	添加时间	int(10) unsigned	N		N
is_fixed	是否固定	tinyint(4)	N	0	N

- 索引

Key name	Column names	Unique	Comment
primary	type_id	Y	

market_sms_templates

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
template_id	template_id	mediumint(8) unsigned	Y		Y
title	模板名称	varchar(100)	N		N
content	内容	text	Y		N
type_id	所属分类	mediumint(8) unsigned	N		N
create_time	添加时间	int(10) unsigned	N		N
is_fixed	是否固定	tinyint(4)	N	0	N
status	模板状态	tinyint(4)	N	1	N
cloud_id	云模板ID	int(11)	N	0	N

- 索引

Key name	Column names	Unique	Comment
primary	template_id	Y	
ind_title	title	N	
idx_c_type_id	type_id	N	

market_wx_bind_member_log

手机号绑定会员日志

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	int(10) unsigned	Y		Y
FromUserName	客户微信账号	varchar(100)	N		N
mobile	手机号	varchar(30)	N		N
passcode	验证码	varchar(10)	N		N
create_time	创建时间	int(10) unsigned	N		N
bind_status	绑定是否成功	enum('true','false')	N	false	N

- 索引

Key name	Column names	Unique	Comment
primary	id	Y	

market_wx_chat

微信聊天记录表

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
chat_id	chat_id	int(10) unsigned	Y		Y
wx_member_id	wx_member_id	int(10) unsigned	Y		N
FromUserName	发送方账号	varchar(100)	N		N
ToUserName	开发者账号	varchar(100)	N		N
chat_content	聊天内容	text	N		N
chat_type	回复内容 receive:接收的;send:发送的;	enum('receive','send')	N	receive	N
chat_pid	首短信id	int(10) unsigned	N	0	N
response_type	是否回复 0:未回复;1:已回复;	enum('0','1')	N	0	N
is_response	是否响应	tinyint(3) unsigned	N	1	N
created	创建时间	datetime	N		N

- 索引

Key name	Column names	Unique	Comment
primary	chat_id	Y	
ToUserName	ToUserName	N	

market_wx_due

微信预约

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
due_id	due_id	int(10) unsigned	Y		Y
title	活动名称	varchar(100)	N		N
keywords	关键词	varchar(100)	N		N
desc	简介	varchar(255)	N		N
start_date	开始时间	int(10) unsigned	N		N
end_date	结束时间	int(10) unsigned	N		N
is_active	活动状态 0:不启用;1:启用;	enum('0','1')	N		N
end_words	结束语	varchar(500)	N		N

due_items	预约内容(json格式)	text	N		N
num	库存数量	int(11)	N		N
created	创建时间	datetime	N		N
modified	更新时间	datetime	N		N
picurl	图片地址	varchar(100)	N		N
req_fields	必填资料	text	N		N
content	活动详细说明	text	N		N

索引

Key name	Column names	Unique	Comment
primary	due_id	Y	
ind_title	title	N	

market_wx_due_orders

微信预约订单

表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
order_id	order_id	int(10) unsigned	Y		Y
due_id	活动编号	int(10) unsigned	N		N
order_content	预约内容	varchar(500)	N		N
wx_id	微信用户识别码	varchar(100)	N		N
created	创建时间	datetime	N		N
truename	姓名	varchar(50)	N		N
size	颜色	varchar(50)	N		N
color	尺码	varchar(50)	N		N
mobile	手机号码	varchar(50)	N		N
addr	详细地址	varchar(100)	N		N
num	数量	int(11)	N		N
log	请求字符串	text	N		N

索引

Key name	Column names	Unique	Comment
primary	order_id	Y	
ind_wx_id	wx_id	N	
idx_c_due_id	due_id	N	

market_wx_event

微信客户事件表

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
wx_event_id	wx_event_id	int(10) unsigned	Y		Y
ToUserName	开发者微信号	varchar(100)	N		N
FromUserName	发送方账号	varchar(100)	N		N
event_type	事件类型	varchar(50)	N		N
create_time	创建时间	int(10) unsigned	N		N

● 索引

Key name	Column names	Unique	Comment
primary	wx_event_id	Y	
ind_ToUserName	ToUserName	N	

market_wx_integral_lottery

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
lottery_id	lottery_id	int(10) unsigned	Y		Y
ToUserName	开发者微信号	varchar(100)	N		N
lottery_name	活动名称	varchar(100)	Y		N
lottery_status	活动状态 create:未开始; start:进行中; end:已结束; close:已关闭;	enum('create','start','end','close')	Y	create	N
start_time	开始时间	int(10) unsigned	Y		N
end_time	结束时间	int(10) unsigned	Y		N
create_time	创建时间	int(10) unsigned	Y		N
close_time	关闭时间	int(10) unsigned	N		N
participants	参加人数	int(11)	N	0	N
win_msg	中将提示语	varchar(255)	N		N
lose_msg	未中奖提示语	varchar(255)	N		N
start_msg	活动未开始提示语	varchar(255)	N		N
end_msg	活动结束提示语	varchar(255)	N		N
minus_score	每次扣减积分	int(11)	N	0	N
update_time	修改时间	int(10) unsigned	N		N

• 索引

Key name	Column names	Unique	Comment
primary	lottery_id	Y	

market_wx_integral_lotteryinfo

• 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
info_id	info_id	int(10) unsigned	Y		Y
lottery_id	lottery_id	int(10) unsigned	Y		N
awards_name	奖项名称	varchar(100)	N		N
awards_info	奖项内容	varchar(100)	N		N
win_rate	中奖几率	int(11)	N		N
awards_stock	库存	int(11)	N	0	N
send_num	已送出	int(11)	N	0	N
create_time	创建时间	int(10) unsigned	N		N
update_time	修改时间	int(10) unsigned	N		N

• 索引

Key name	Column names	Unique	Comment
primary	info_id	Y	

market_wx_integral_lotterylog

• 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
log_id	log_id	int(10) unsigned	Y		Y
lottery_id	lottery_id	int(10) unsigned	Y		N
people_name	参与人	varchar(100)	N		N
people_adr	参与人地址	varchar(255)	N		N
lottery_name	活动名称	varchar(100)	N		N
FromUserName	发送方账号	varchar(100)	N		N
phone	手机号	char(11)	N		N
minus_score	扣减积分	int(11)	N		N
lottery_info_id	中奖编号	int(11)	N	0	N
lottery_info_name	中奖结果	varchar(255)	N		N

create_time	创建时间	int(10) unsigned	N		N
update_time	修改时间	int(10) unsigned	N		N

- 索引

Key name	Column names	Unique	Comment
primary	log_id	Y	

market_wx_join_log

微信用户参与日志表

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
log_id	log_id	int(10) unsigned	Y		Y
wx_member_id	wx_member_id	int(10) unsigned	Y		N
FromUserName	开发者账号	varchar(100)	N		N
ToUserName	发送者账号	varchar(100)	N		N
is_regist	是否签到	tinyint(3) unsigned	N	0	N
is_chat	是否聊天	tinyint(3) unsigned	N	0	N
is_keyword	是否关键字	tinyint(3) unsigned	N	0	N
is_survey	是否问卷	tinyint(3) unsigned	N	0	N
is_vote	是否投票	tinyint(3) unsigned	N	0	N
is_due	是否预约	tinyint(3) unsigned	N	0	N
created	创建时间	int(10) unsigned	N		N

- 索引

Key name	Column names	Unique	Comment
primary	log_id	Y	
ind_ToUserName	ToUserName	N	
ind_created	created	N	

market_wx_keywords

微信用户关键字总表

- 表结构

ColumnName	Comment	Type
id	自增id	int(11)
keyword	关键字	varchar(255)
	关键字来源 products:商品推	

source	荐;reply:关键词回复;system:系统;plugin:插件;survey:问答活动;regist:签到;vote:投票;due:预约;unknow:未知;	enum('products','reply','system','plugin','survey','regist','vote','due','unknow')
--------	---	--

- 索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_keyword	keyword	N	

market_wx_keywords_autoreply

微信用户关键字回复规则表

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	自增id	int(11)	Y		Y
rulename	规则名	varchar(255)	N		N
replycontent	微信回复内容	text	N		N
keyword	回复关键词	text	N		N
reply_type	回复方式 msg:一般消息;news:图文素材;	enum('msg','news')	N	msg	N
wx_news_id	wx_news_id	int(10) unsigned	N		N

- 索引

Key name	Column names	Unique	Comment
primary	id	Y	

market_wx_member

微信客户关联表

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoinc
wx_member_id	wx_member_id	int(10) unsigned	Y		Y
member_id	关联帐号	int(10) unsigned	N		N
ToUserName	公众号	varchar(100)	N		N
FromUserName	客户微信账号	varchar(100)	N		N

user_id	用户唯一标示	varchar(100)	N		N
weixin_token	微信账号标示	varchar(100)	N		N
wx_nick	微信昵称	varchar(100)	N		N
sex	性别 female: 女;male: 男;unkown:-;	enum('female','male','unkown')	N	unkown	N
city	地区	varchar(100)	N		N
province	省市	varchar(100)	N		N
country	国家	varchar(100)	N		N
tb_nick	淘宝昵称	varchar(100)	N		N
mobile	手机	varchar(30)	N		N
points	积分	int(10)	N	0	N
continue_regist_count	连续签到次数	int(10)	N	0	N
create_time	创建时间	int(10) unsigned	N		N
update_time	更新时间	int(10) unsigned	N		N
status	绑定状态	enum('true','false')	N	false	N

- 索引

Key name	Column names	Unique	Comment
primary	wx_member_id	Y	
ind_FromUserName	FromUserName	N	
idx_c_member_id	member_id	N	

market_wx_msg_send_all

微信群发消息

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	自增id	int(10) unsigned	Y		Y
send_type	类型 msg:文 本;news:图文;	enum('msg','news')	N	msg	N
name	群发推广名称	varchar(25)	N		N
create_man	创建人	varchar(25)	Y		N
create_time	创建时间	int(10) unsigned	Y	0	N
upload_man	上传人	varchar(25)	Y		N
upload_time	上传时间	int(10) unsigned	Y	0	N
msg_content	图文信息及详情	longtext	N		N
news_id	图文素材id	int(10) unsigned	N	0	N
media_id	微信素材标识	varchar(255)	N		N

created_at_wx	微信保存素材时间	int(10) unsigned	N	0	N
past_time_at_wx	微信素材过期时间	int(10) unsigned	N	0	N
del_flag	状态 0:正常;1:删除;	enum('0','1')	N	0	N
update_time	修改时间	int(10) unsigned	Y	0	N

- 索引

Key name	Column names	Unique	Comment
primary	id	Y	

market_wx_msg_send_all_log

微信群发素材发送log

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	自增id	int(11)	Y		Y
send_openid	发送所用公共账号	varchar(50)	N		N
responses_user_name	公众号群发助手的微信号 公众号群发助手的微信号	varchar(50)	N		N
create_time_for_wx	微信创建时间	int(10) unsigned	Y	0	N
msg_type	消息类型	varchar(20)	Y		N
event	事件信息	varchar(25)	Y		N
send_status	发送状态	varchar(20)	N		N
total_count	发送粉丝数	int(11)	N	0	N
filter_count	过滤后人数	int(11)	N	0	N
send_count	发送成功人数	int(11)	N	0	N
error_count	发送失败粉丝数	int(11)	N	0	N
error_code	错误码	int(11)	N	0	N
error_msg	错误信息	varchar(100)	N		N
msg_id	微信返回消息ID	int(11)	N	0	N
create_time	创建时间	int(10) unsigned	Y	0	N
send_msg_id	群发消息id	int(10) unsigned	N	0	N
update_time	修改时间	int(10) unsigned	N	0	N
send_list	接受者id列表	mediumtext	N		N
send_time	发送时间	int(10) unsigned	Y	0	N
send_man	发送人	varchar(25)	Y		N

- 索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_send_msg_id	send_msg_id	N	

market_wx_news

图文素材

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
wx_news_id	wx_news_id	int(10) unsigned	Y		Y
news_info	图文信息	longtext	N		N
title	标题	varchar(100)	N		N
picurl	封面	varchar(100)	N		N
digest	摘要	varchar(500)	N		N
created	创建时间	datetime	N		N
modified	更新时间	datetime	N		N
type	图文类型 1:单图文;2:多图文;	enum('1','2')	N		N

- 索引

Key name	Column names	Unique	Comment
primary	wx_news_id	Y	

market_wx_news_img

图文图片

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
wx_news_img_id	wx_news_img_id	int(10) unsigned	Y		Y
picurl	封面	varchar(100)	N		N
created	创建时间	datetime	N		N

- 索引

Key name	Column names	Unique	Comment
primary	wx_news_img_id	Y	

market_wx_plugins

微信用户互动插件规则表

表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	自增id	int(11)	Y		Y
plugin_name	插件名称	varchar(255)	N		N
img	图标	varchar(255)	N		N
desc	插件说明	text	N		N
keyword	关键词	varchar(255)	N		N
status	插件状态	tinyint(3) unsigned	N	0	N

索引

Key name	Column names	Unique	Comment
primary	id	Y	

market_wx_point_log

积分日志表

表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
log_id	log_id	int(10) unsigned	Y		Y
wx_member_id	微信客户ID	int(10) unsigned	N		N
ToUserName	微信公众号	varchar(100)	N		N
FromUserName	客户微信号	varchar(100)	N		N
points	积分	int(11)	N	0	N
point_mode	积分方式	varchar(1)	N		N
op_before_point	调整前	int(11)	N	0	N
op_after_point	调整后	int(11)	N	0	N
create_time	创建时间	int(10) unsigned	N		N
point_desc	积分备注	varchar(100)	N		N
op_user	操作人	varchar(50)	N		N

索引

Key name	Column names	Unique	Comment
primary	log_id	Y	
ind_wx_member_id	wx_member_id	N	

market_wx_points_buy

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
buy_id	buy_id	int(10) unsigned	Y		Y
ToUserName	开发者微信号	varchar(100)	N		N
buy_name	活动名称	varchar(100)	Y		N
buy_status	活动状态 create:未开始; start:进行中; end:已结束; close:已关闭;	enum('create','start','end','close')	Y		N
minus_score	每次扣减积分	bigint(20)	N		N
msg	活动说明	varchar(255)	N		N
goods_name	商品名称	varchar(255)	Y		N
goods_code	商品编码	varchar(50)	Y		N
goods_img	商品图片	varchar(255)	N		N
goods_msg	商品描述	varchar(300)	N		N
goods_all_stock	可兑换总量	int(11)	Y	0	N
goods_stock	剩余总量	int(11)	N	0	N
join_num	兑换数量	int(11)	N	0	N
limit_times	限制次数 Unlimited:不限; 1:1次; 2:2次; 3:3次; 4:4次; 5:5次;	enum('Unlimited','1','2','3','4','5')	N	Unlimited	N
start_time	开始时间	int(10) unsigned	Y		N
end_time	结束时间	int(10) unsigned	Y		N
create_time	创建时间	int(10) unsigned	N		N
update_time	修改时间	int(10) unsigned	N		N
shop_gift_id	erp赠品id	int(10) unsigned	N		N

● 索引

Key name	Column names	Unique	Comment
primary	buy_id	Y	
ind_code	goods_code	N	

market_wx_points_buylog

● 表结构

ColumnName	Comment	Type		Default	Autoincrement
------------	---------	------	--	---------	---------------

ColumnName	Comment	Type		Default	Autoincrement
log_id	log_id	int(10) unsigned	Y		Y
buy_id	buy_id	int(10) unsigned	Y		N
FromUserName	发送方账号	varchar(100)	N		N
create_time	创建时间	int(10) unsigned	N		N
receiver	参与人	varchar(100)	N		N
mobile	手机号	char(11)	N		N
addr	参与人地址	varchar(255)	N		N
minus_score	扣减积分	int(10) unsigned	N		N
goods_code	商品编码	varchar(50)	N		N
goods_name	商品名称	varchar(255)	N		N
buy_num	buy_num	int(10) unsigned	Y		N
update_time	修改时间	int(10) unsigned	N		N

- 索引

Key name	Column names	Unique	Comment
primary	log_id	Y	

market_wx_sign_in_log

微信客户签到日志表

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	int(10) unsigned	Y		Y
FromUserName	客户微信账号	varchar(100)	N		N
member_id	关联帐号	int(10) unsigned	N		N
sign_in_times	连续签到次数	int(10)	N	0	N
create_time	创建时间	int(10) unsigned	N		N

- 索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_wx_id	id	N	
idx_c_member_id	member_id	N	

market_wx_store_subbranch

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
------------	---------	------	----------	---------	---------------

store_id	store_id	int(10) unsigned	Y		Y
store_name	活动名称	varchar(100)	N		N
phone	联系电话	char(13)	N		N
store_area	店铺地区	varchar(255)	N		N
province_id	省	int(10)	N		N
city_id	市	int(10)	N		N
area_id	区域	int(10)	N		N
picurl	店铺logo	varchar(255)	N		N
address	地址	varchar(255)	N		N
map_x	坐标X	varchar(30)	N		N
map_y	坐标Y	varchar(30)	N		N
open_time	营业时间	varchar(250)	N		N
business	营业范围	varchar(250)	N		N
create_time	创建时间	int(10) unsigned	N		N

● 索引

Key name	Column names	Unique	Comment
primary	store_id	Y	
ind_store_area	store_area	N	

market_wx_survey

问卷调查表

● 表结构

ColumnName	Comment	Type	Not null	Default	Auto increment
survey_id	survey_id	int(10) unsigned	Y		Y
title	活动名称	varchar(100)	N		N
keywords	关键词	varchar(100)	N		N
start_date	开始时间	int(10) unsigned	N		N
end_date	结束时间	int(10) unsigned	N		N
is_active	活动状态 0:不启用;1:启用;	enum('0','1')	N		N
end_words	结束语	varchar(500)	N		N
item_ids	题目编号	text	N		N
created	创建时间	datetime	N		N
modified	更新时间	datetime	N		N

- 索引

Key name	Column names	Unique	Comment
primary	survey_id	Y	
ind_title	title	N	

market_wx_survey_items

问卷调查题目

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
item_id	item_id	int(10) unsigned	Y		Y
title	问题描述	varchar(100)	N		N
is_active	状态 1:启用;0:不启用;	enum('1','0')	N		N
item_type	问题类型 1:选择题;2:文字题;	enum('1','2')	N		N
options	问题选项	text	N		N
option_tags	问题标志	text	N		N
remark	备注	text	N		N
created	创建时间	datetime	N		N
modified	更新时间	datetime	N		N

- 索引

Key name	Column names	Unique	Comment
primary	item_id	Y	
ind_title	title	N	

market_wx_survey_log

问卷调查快照

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
survey_log_id	survey_log_id	int(10) unsigned	Y		Y
survey_id	活动编号	int(10) unsigned	N		N
start_date	开始时间	int(10) unsigned	N		N
end_date	结束时间	int(10) unsigned	N		N
result	全部回答内容	text	N		N
survey_items	题目快照	text	N		N

wx_id	微信用户识别码	varchar(100)	N		N
status	问答状态 survey:问答中; sysclose:系统关闭; userclose:用户关闭; finish:完成;	enum('survey','sysclose','userclose','finish')	N	survey	N
end_words	结束语	varchar(500)	N		N
created	创建时间	int(10) unsigned	N		N

索引

Key name	Column names	Unique	Comment
primary	survey_log_id	Y	
ind_wx_id	wx_id	N	
idx_c_survey_id	survey_id	N	

market_wx_survey_result

问卷调查结果

表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
result_id	result_id	int(10) unsigned	Y		Y
survey_id	活动编号	int(10) unsigned	N		N
item_id	题目编号	int(10) unsigned	N		N
survey_log_id	调查快照ID	int(10) unsigned	N		N
result_no	答案编号	varchar(32)	N		N
result	回答内容	varchar(500)	N		N
wx_id	微信用户识别码	varchar(100)	N		N
created	创建时间	int(10) unsigned	N		N

索引

Key name	Column names	Unique	Comment
primary	result_id	Y	
ind_wx_id	wx_id	N	
idx_c_survey_id	survey_id	N	
idx_c_item_id	item_id	N	
idx_c_survey_log_id	survey_log_id	N	

market_wx_unbind_member_log

手机号解绑会员日志

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	int(10) unsigned	Y		Y
FromUserName	客户微信账号	varchar(100)	N		N
mobile	手机号	varchar(30)	N		N
passcode	验证码	varchar(10)	N		N
create_time	创建时间	int(10) unsigned	N		N

● 索引

Key name	Column names	Unique	Comment
primary	id	Y	

market_wx_vote

微信投票

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
vote_id	vote_id	int(10) unsigned	Y		Y
title	活动名称	varchar(100)	N		N
keywords	关键词	varchar(100)	N		N
desc	活动描述	varchar(500)	N		N
template_id	模板编号	int(11)	N		N
start_date	开始时间	int(10) unsigned	N		N
end_date	结束时间	int(10) unsigned	N		N
is_active	活动状态 0:不启用;1:启用;	enum('0','1')	N		N
end_words	结束语	varchar(500)	N		N
vote_items	投票选项(json格式)	text	N		N
content	活动详细说明	text	N		N
req_fields	必填资料	varchar(50)	N		N
created	创建时间	datetime	N		N
modified	更新时间	datetime	N		N
picurl	图片地址	varchar(100)	N		N
points	积分	int(10)	N	0	N

● 索引

Key name	Column names	Unique	Comment

primary	vote_id	Y	
ind_title	title	N	
ind_keywords	keywords	N	

market_wx_vote_result

微信投票结果

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
result_id	result_id	int(10) unsigned	Y		Y
vote_id	活动编号	int(10) unsigned	N		N
result_no	答案编号	varchar(32)	N		N
result	回答内容	varchar(500)	N		N
wx_id	微信用户识别码	varchar(100)	N		N
created	创建时间	datetime	N		N
truename	姓名	varchar(50)	N		N
mobile	手机号码	varchar(50)	N		N
log	请求字符串	text	N		N

- 索引

Key name	Column names	Unique	Comment
primary	result_id	Y	
ind_wx_id	wx_id	N	
idx_c_vote_id	vote_id	N	

market_wxautoreply

微信用户规则表

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	自增id	int(11)	Y		Y
rulename	规则名	varchar(255)	N		N
replycontent	微信回复内容	text	N		N

- 索引

Key name	Column names	Unique	Comment
primary	id	Y	

app:marketcenter tables

marketcenter_cards

卡券信息

- 表结构

ColumnName	Comment	
card_no	卡券编号	int(8)
card_id	卡券id	varchar(50)
node_id	节点id	varchar(50)
card_type	卡券类型 DISCOUNT:折扣卷;CASH:代金卷;GIFT:礼品卷;GROUPON:团购卷;GENERAL_COUPON :优惠券;	enum('DISCOUNT','CASH','GIFT','GROUPON')
logo_url	商户logo	varchar(128)
code_type	Code展示类型 CODE_TYPE_TEXT:文本;CODE_TYPE_BARCODE:一维码;CODE_TYPE_QRCODE:二维码;CODE_TYPE_ONLY_QRCODE:二维码无code显示;CODE_TYPE_ONLY_BARCODE :一维码无code显示;	enum('CODE_TYPE_TEXT','CODE_TYPE_BAI')
brand_name	商户名字	varchar(36)
title	卡券名	varchar(27)
sub_title	券名	varchar(54)
color	券颜色	varchar(50)
notice	卡券使用提醒	varchar(48)
description	卡券使用说明	varchar(3072)
quantity	卡券库存的数量	int(10)
type	使用时间的类型 DATE_TYPE_FIX_TIME_RANGE : 固定日期区间;DATE_TYPE_FIX_TERM:固定时长;	enum('DATE_TYPE_FIX_TIME_RANGE ','DATE')
begin_timestamp	起用时间	int(10) unsigned
end_timestamp	结束时间	int(10) unsigned
fixed_term	领取后多少天有效	int(8)
fixed_begin_term	领取后多少天生效	int(8)
use_custom_code	是否自定义Code码	enum('true','false')
bind_openid	是否指定用户领取	enum('true','false')
service_phone	客服电话	varchar(24)
location_id_list	门店位置ID	longtext
source	第三方来源名	varchar(36)
custom_url_name	自定义跳转外链的入口名字	varchar(15)
custom_url	自定义跳转的URL	varchar(128)
custom_url_sub_title	显示在入口右侧的提示语	varchar(18)

promotion_url_name	营销场景的自定义入口名称	varchar(15)
promotion_url	入口跳转外链的地址链接	varchar(128)
promotion_url_sub_title	显示在营销入口右侧的提示语	varchar(128)
get_limit	每人可领券的数量限制	int(8)
can_share	分享	enum('true','false')
can_give_friend	转赠	enum('true','false')
default_detail	优惠券专用，填写优惠详情	varchar(3072)
gift	礼品券专用，填写礼品的名称	varchar(3072)
discount	折扣券专用，表示打折额度	int(8)
least_cost	代金券专用，表示起用金额	int(8)
reduce_cost	代金券专用，表示减免金额	int(8)
deal_detail	团购券专用，团购详情	varchar(24)
status	卡券状态 update :已同步;unupdate:未同步;dead:未启用;	enum('update ','unupdate','dead')
create_time	创建时间	int(10) unsigned
update_time	更新时间	int(10) unsigned
creator	创建人	varchar(50)
card_deliver	已发送	int(8)
card_use	已使用	int(8)

- 索引

Key name	Column names	Unique	Comment
primary	card_no	Y	

marketcenter_consume_cards

卡券核销

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	序号	int(8)	Y		Y
CardId	卡券id	varchar(50)	N		N
UserCardCode	code序列号	varchar(36)	N		N

- 索引

Key name	Column names	Unique	Comment
primary	id	Y	

marketcenter_get_cards

卡券领取

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	序号	int(8)	Y		Y
CardId	卡券id	varchar(50)	N		N
ToUserName	开发者微信号	varchar(36)	N		N
FromUserName	领券方帐号	varchar(36)	N		N
FriendUserName	赠送方账号	varchar(36)	N		N
CreateTime	消息创建时间	int(10) unsigned	N		N
IsGiveByFriend	是否为转赠	enum('true','false')	N	false	N
UserCardCode	code序列号	varchar(36)	N		N
OldUserCardCode	转赠前的code序列号	varchar(36)	N		N
OuterId	领取场景值	varchar(36)	N		N

● 索引

Key name	Column names	Unique	Comment
primary	id	Y	

app:openapi tables

openapi_api_log

api日志

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
log_id	主键ID	bigint(20) unsigned	Y		Y
api_name	api方法名	varchar(255)	N		N
api_flag	访问来源标示	varchar(60)	N		N
status	状态 succ:成功;fail:失败;timeout:请求超时;	enum('succ','fail','timeout')	Y	succ	N
params	params	text	N		N
msg	返回信息	text	N		N
api_type	同步类型 response:响应; request:请求;	enum('response','request')	Y	response	N
createtime	发起同步时间	int(10) unsigned	N		N

● 索引

--	--	--	--

Key name	Column names	Unique	Comment
primary	log_id	Y	
ind_status_type	status	N	
ind_api_type	api_type	N	

openapi_setting

开放数据接口配置表

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
s_id	ID	int(10) unsigned	Y		Y
name	访问来源名称	varchar(200)	Y		N
code	标识	varchar(200)	Y		N
interfacekey	私钥	varchar(100)	Y		N
config	config	longtext	N		N
status	接口状态	tinyint(1)	N	0	N

- 索引

Key name	Column names	Unique	Comment
primary	s_id	Y	
uni_code	code	N	
ind_name	name	N	

app:pam tables

pam_account

--

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
account_id	account_id	mediumint(8) unsigned	N		Y
account_type	account_type	varchar(30)	N		N
login_name	login_name	varchar(100)	Y		N
login_password	login_password	varchar(32)	Y		N
disabled	是否失效	enum('true','false')	N	false	N
createtime	createtime	int(10) unsigned	N		N

- 索引

Key name	Column names	Unique	Comment

primary	account_id	Y	
account	account_type, login_name	N	

pam_auth

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
auth_id	auth_id	mediumint(8) unsigned	N		Y
account_id	account_id	mediumint(8) unsigned	N		N
module_uid	module_uid	varchar(50)	N		N
module	module	varchar(50)	N		N
data	data	text	N		N

- 索引

Key name	Column names	Unique	Comment
primary	auth_id	Y	
account_id	module, account_id	N	
module_uid	module, module_uid	N	
idx_c_account_id	account_id	N	

pam_log

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
event_id	event_id	mediumint(8) unsigned	N		Y
event_time	event_time	varchar(50)	N		N
event_data	event_data	varchar(500)	N		N
event_type	event_type	text	N		N

- 索引

Key name	Column names	Unique	Comment
primary	event_id	Y	

app:plugins tables

plugins_hits

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	int(11)	Y		Y
market_id	营销ID	int(11)	N		N
market_name	营销名称	char(100)	N		N
type	类型	char(10)	N		N
shop_id	店铺ID	char(100)	N		N
shop_name	店铺名称	char(100)	N		N
created	创建时间	int(10) unsigned	N	0	N

● 索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_created	created	N	
ind_market_id	market_id	N	
ind_shop_id	shop_id	N	
ind_type	type	N	

plugins_log

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
log_id	log_id	int(11)	Y		Y
plugin_id	插件编号	int(11)	Y		N
plugin_name	插件名称	varchar(100)	N		N
worker	执行方法	varchar(100)	N		N
run_key	防止重复运行	varchar(32)	N		N
start_time	开始时间	int(10) unsigned	N	0	N
end_time	结束时间	int(10) unsigned	N	0	N
sms_count	发送短信数	int(11)	N	0	N
desc	备注	text	N		N
status	运行结果	varchar(32)	N	未知	N

● 索引

Key name	Column names	Unique	Comment
primary	log_id	Y	
ind_start_time	start_time	N	
ind_end_time	end_time	N	

ind_run_key	run_key	N
-------------	---------	---

plugins_orders

• 表结构

ColumnName	Comment	Type	Not null	Default	Auto increment
order_id	order_id	int(11)	Y		Y
plugin_id	插件编号	int(11)	Y		N
plugin_name	插件名称	varchar(100)	N		N
worker	执行方法	varchar(100)	N		N
amount	付款金额	int(10) unsigned	N		N
month	服务时限	int(11)	N		N
buy_time	购买时间	int(10) unsigned	N	0	N
end_time	截止时间	int(10) unsigned	N	0	N
desc	备注	tinytext	N		N
status	插件状态 wait:等待; running:运行中; success:成功; failed:失败;	enum('wait','running','success','failed')	N	wait	N
op_user	操作人	varchar(32)	N		N

• 索引

Key name	Column names	Unique	Comment
primary	order_id	Y	
ind_buy_time	buy_time	N	
ind_end_time	end_time	N	

plugins_plugins

• 表结构

ColumnName	Comment	Type	Not null	Default	Auto increment
plugin_id	plugin_id	int(11)	Y		Y
plugin_name	插件名称	varchar(100)	N		N
worker	执行方法	varchar(100)	N		N
price	单价	int(10) unsigned	N		N
amount	付款金额	int(10) unsigned	N		N

month	服务时限	int(11)	N		N
last_run_time	最后运行时间	int(10) unsigned	N	0	N
buy_time	启用时间	int(10) unsigned	N	0	N
end_time	过期时间	int(10) unsigned	N	0	N
params	配置参数	text	N		N
status	插件状态 wait:等待; running:运行中; success:成功; failed:失败;	enum('wait','running','success','failed')	N	wait	N

● 索引

Key name	Column names	Unique	Comment
primary	plugin_id	Y	
ind_buy_time	buy_time	N	
ind_end_time	end_time	N	

plugins_sms_logs

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	bigint(20)	Y		Y
tid	订单号	bigint(20)	N		N
shop_id	店铺ID	varchar(50)	N		N
plugin_name	插件名称	varchar(50)	N		N
shop_name	店铺名称	varchar(50)	N		N
worker	执行方法	varchar(100)	N		N
create_time	创建时间	int(10) unsigned	N	0	N
create_date	创建时间	datetime	N	0	N
sms_content	短信内容	varchar(500)	N	0	N
mobile	手机号码	varchar(11)	N	0	N
status	运行结果	varchar(32)	N	未知	N

● 索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_create_time	create_time	N	
ind_worker	worker	N	
ind_tid	tid	N	

ind_mobile	mobile	N	
------------	--------	---	--

plugins_trades

● 表结构

ColumnName	Comment	Type	Not null	Default	Auto increment
id	id	int(11)	Y		Y
tid	订单编号	varchar(50)	N		N
ship_mobile	手机号码	varchar(50)	N		N
buyer_nick	买家帐号	varchar(50)	N		N
ship_name	收货人姓名	varchar(50)	N		N
logi_company	物流公司	varchar(50)	N		N
logi_no	物流单号	varchar(50)	N		N
shop_name	店铺名称	varchar(50)	N		N
shop_id	店铺ID	varchar(50)	N		N
member_id	客户ID	int(11)	N		N
order_status	订单状态	varchar(50)	N		N
ship_status	物流状态	varchar(50)	N		N
sms_status	短信发送状态(0或1)	int(11)	N	0	N
create_time	创建时间	int(10) unsigned	N	0	N
update_time	更新时间	int(10) unsigned	N	0	N
sms_time	短信发送时间	int(10) unsigned	N	0	N
delivery_time	发货时间	int(10) unsigned	N	0	N
logi_status	物流信息是否完整 0:未送达;1:到达收货城市;2:已签收;9:获取数据失败;	enum('0','1','2','9')	N	0	N
province	省份	varchar(50)	N	0	N
city	城市	varchar(50)	N	0	N
plugin_id	插件ID	varchar(50)	N	0	N
seller_nick	卖家昵称	varchar(50)	N	0	N
transit_step_info	流转信息列表	text	N		N
sign_time	签收时间	int(10) unsigned	N	0	N

● 索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_tid	tid	N	

ind_plugin_id	plugin_id	N	
ind_mobile	ship_mobile	N	
ind_delivery_time	delivery_time	N	
ind_logi_status	logi_status	N	

app:taocrm tables

taocrm_all_points_log



• 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	int(10) unsigned	Y		Y
member_id	客户帐号	int(10) unsigned	N		N
shop_id	来源店铺	varchar(32)	N		N
op_time	操作时间	int(10) unsigned	N		N
op_before_point	调整前的积分	mediumint(8) unsigned	N	0	N
op_after_point	调整后的积分	mediumint(8) unsigned	N	0	N
points	积分	int(11)	N	0	N
freeze_time	冻结时间	int(10) unsigned	N	0	N
unfreeze_time	解冻时间	int(10) unsigned	N	0	N
is_expired	是否过期 0:未过期;1:已过期;	enum('0','1')	N	0	N
expired_time	过期时间	int(10) unsigned	N	0	N
point_desc	积分说明	text	N		N
order_id	订单ID	int(10) unsigned	N		N
order_bn	订单号	varchar(50)	N		N
refund_id	退款单编号	int(10) unsigned	N		N
is_active	状态	enum('0','1')	N	1	N
op_user	操作人	varchar(32)	N		N
pid	撤销积分日志ID	mediumint(8) unsigned	N		N
user_ip	IP地址	varchar(100)	N		N

• 索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_member_id	member_id	N	

idx_c_member_id	member_id	N	
idx_c_order_id	order_id	N	
idx_c_refund_id	refund_id	N	

taocrm_app

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	int(11)	Y		Y
app_type	应用类型 wwgenius: 旺旺精灵;	enum('wwgenius')	Y		N
app_name	应用名称	varchar(50)	Y		N
app_desc	应用描述	text	N		N
status	绑定状态	tinyint(4)	N	0	N
seller_nick	卖家昵称	varchar(100)	N		N
shop_id	绑定店铺	varchar(32)	N		N

- 索引

Key name	Column names	Unique	Comment
primary	id	Y	
idx_c_shop_id	shop_id	N	

taocrm_app_members

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	int(11)	Y		Y
app_type	应用类型 wwgenius: 旺旺精灵;	enum('wwgenius')	Y		N
shop_id	来源店铺	varchar(32)	N		N
uname	客户名	varchar(50)	Y		N
member_id	客户ID	int(11)	N	0	N

- 索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_uname_shop_apptype	uname, shop_id, app_type	N	
idx_c_shop_id	shop_id	N	

taocrm_cache_area

报表缓存(地域分析)

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	int(10) unsigned	Y		Y
area_id	区域ID	int(10) unsigned	N		N
area_name	区域名称	char(32)	N		N
total_orders	总订单数	int(10) unsigned	N	0	N
total_amount	订单总金额	decimal(20,2)	N	0	N
total_per_amount	平均单价	decimal(20,2)	N	0	N
total_members	客户总数	int(10) unsigned	N	0	N
paid_orders	付款订单数	int(10) unsigned	N	0	N
paid_amount	付款金额	decimal(20,2)	N	0	N
paid_per_amount	平均付款单价	decimal(20,2)	N	0	N
paid_members	付款客户数	int(10) unsigned	N	0	N
finish_members	完成客户数	int(10) unsigned	N	0	N
finish_orders	完成订单数	int(10) unsigned	N	0	N
finish_amount	完成金额	decimal(20,2)	N	0	N
finish_per_amount	平均完成单价	decimal(20,2)	N	0	N
cdate	日期	int(10) unsigned	N	0	N
shop_id	店铺ID	char(32)	N	0	N
create_date	创建时间	datetime	N	0	N

- 索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_area_id	area_id	N	
ind_cdate	cdate	N	
ind_shop_id	shop_id	N	

taocrm_cache_dashboard

首页缓存

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	int(10)	Y		Y

id	id	unsigned	Y		Y
day	天, 格式 YYYYMMDD	int(10) unsigned	N	0	N
bind_shop_cnt	绑定店铺数	int(10) unsigned	N	0	N
unbind_shop_cnt	未绑定店铺 数	int(10) unsigned	N	0	N
weixin_member_cnt	微信关注数	int(10) unsigned	N	0	N
once_buy_member_cnt	一次购买用 户数	int(10) unsigned	N	0	N
more_buy_member_cnt	多次购买用 户数	int(10) unsigned	N	0	N
total_member_cnt	总客户数	int(10) unsigned	N	0	N
total_amount	总成交金额	decimal(10,2)	N	0	N
avg_member_amount	平均客单价	decimal(10,2)	N	0	N
avg_order_amount	平均订单价	decimal(10,2)	N	0	N
total_order_cnt	总成交订单 数	int(10) unsigned	N	0	N
total_marketing_member_cnt	营销客户数	int(10) unsigned	N	0	N
total_marketing_buy_member_cnt	营销参与客 户数	int(10) unsigned	N	0	N
total_marketing_buy_order_amount	营销下单金 额	decimal(10,2)	N	0	N
weixin_buy_member_cnt	微信参与客 户数	int(10) unsigned	N	0	N
active_member_cnt	活跃客户数	int(10) unsigned	N	0	N
inactive_member_cnt	沉睡客户数	int(10) unsigned	N	0	N
total_tag_member_cnt	客户标签数	int(10) unsigned	N	0	N
unorder_member_cnt	未下单客户	int(10) unsigned	N	0	N
avg_member_goods_cnt	人均成交件 数	decimal(10,2)	N	0	N
avg_member_order_cnt	人均成交笔 数	decimal(10,2)	N	0	N
avg_buy_times_cnt	平均购买次 数	decimal(10,2)	N	0	N
avg_buy_days	平均回购周 期	int(10) unsigned	N	0	N
create_time	插入时间	int(10) unsigned	N	0	N

- 索引

--	--	--	--

Key name	Column names	Unique	Comment
primary	id	Y	
ind_day	day	N	

taocrm_cache_hour

报表缓存(购买时段)

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	int(10) unsigned	Y		Y
hour	小时	int(10) unsigned	N		N
total_orders	总订单数	int(10) unsigned	N	0	N
total_amount	订单总金额	decimal(20,2)	N	0	N
total_per_amount	平均单价	decimal(20,2)	N	0	N
total_members	客户总数	int(10) unsigned	N	0	N
paid_orders	付款订单数	int(10) unsigned	N	0	N
paid_amount	付款金额	decimal(20,2)	N	0	N
paid_per_amount	平均付款单价	decimal(20,2)	N	0	N
paid_members	付款客户数	int(10) unsigned	N	0	N
finish_members	完成客户数	int(10) unsigned	N	0	N
finish_orders	完成订单数	int(10) unsigned	N	0	N
finish_amount	完成金额	decimal(20,2)	N	0	N
finish_per_amount	平均完成单价	decimal(20,2)	N	0	N
cdate	日期	int(10) unsigned	N	0	N
shop_id	店铺ID	char(32)	N	0	N
create_date	创建时间	datetime	N	0	N

- 索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_hour	hour	N	
ind_cdate	cdate	N	
ind_shop_id	shop_id	N	

taocrm_cache_members

报表缓存(客户相关报表)

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
------------	---------	------	----------	---------	---------------

id	id	int(10) unsigned	Y		Y
itype	报表类型	char(100)	N		N
report_data	报表结果	text	N		N
date_from	日期	int(10) unsigned	N	0	N
date_to	日期	int(10) unsigned	N	0	N
cdate	日期	int(10) unsigned	N	0	N
shop_id	店铺ID	char(32)	N	0	N
create_date	创建时间	datetime	N	0	N

● 索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_cdate	cdate	N	
ind_shop_id	shop_id	N	

taocrm_cache_rfm

报表缓存(购买时段)

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	int(10) unsigned	Y		Y
param_r	小时	char(32)	N		N
param_f	总订单数	char(32)	N	0	N
date_from	订单总金额	int(10) unsigned	N	0	N
date_to	平均单价	int(10) unsigned	N	0	N
analysis_data	客户总数	text	N		N
total_data	付款订单数	text	N		N
total_r_data	付款金额	text	N		N
total_f_data	平均付款单价	text	N		N
cdate	日期	int(10) unsigned	N	0	N
shop_id	店铺ID	char(32)	N	0	N
create_date	创建时间	datetime	N	0	N

● 索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_cdate	cdate	N	
ind_shop_id	shop_id	N	

taocrm_cache_tree

报表缓存(购买时段)

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	int(10) unsigned	Y		Y
total_items	小时	int(10) unsigned	N		N
total_orders	总订单数	int(10) unsigned	N	0	N
total_amount	订单总金额	decimal(20,2)	N	0	N
total_per_amount	平均单价	decimal(20,2)	N	0	N
total_members	客户总数	int(10) unsigned	N	0	N
paid_orders	付款订单数	int(10) unsigned	N	0	N
paid_amount	付款金额	decimal(20,2)	N	0	N
paid_per_amount	平均付款单价	decimal(20,2)	N	0	N
paid_per_user_amount	平均付款单价	decimal(20,2)	N	0	N
unpaid_amount	平均付款单价	decimal(20,2)	N	0	N
paid_members	付款客户数	int(10) unsigned	N	0	N
finish_members	完成客户数	int(10) unsigned	N	0	N
finish_orders	完成订单数	int(10) unsigned	N	0	N
finish_amount	完成金额	decimal(20,2)	N	0	N
finish_per_amount	平均完成单价	decimal(20,2)	N	0	N
cdate	日期	int(10) unsigned	N	0	N
shop_id	店铺ID	char(32)	N	0	N
create_date	创建时间	datetime	N	0	N
new_members	完成订单数	int(10) unsigned	N	0	N
new_orders	完成订单数	int(10) unsigned	N	0	N
new_amount	完成订单数	decimal(20,2)	N	0	N
new_per_amount	完成订单数	decimal(20,2)	N	0	N
new_per_items	完成订单数	decimal(20,2)	N	0	N
new_per_price	完成订单数	decimal(20,2)	N	0	N
old_members	完成订单数	int(10) unsigned	N	0	N
old_amount	完成订单数	decimal(20,2)	N	0	N
old_orders	完成订单数	int(10) unsigned	N	0	N
old_items	完成订单数	int(10) unsigned	N	0	N
old_per_amount	完成订单数	decimal(20,2)	N	0	N
old_per_items	完成订单数	decimal(20,2)	N	0	N
old_per_price	完成订单数	decimal(20,2)	N	0	N
date_from	完成订单数	int(10) unsigned	N	0	N

date_to	完成订单数	int(10) unsigned	N	0	N
---------	-------	------------------	---	---	---

- 索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_cdate	cdate	N	
ind_shop_id	shop_id	N	

taocrm_fx_member_group

客户分组表

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
group_id	group_id	mediumint(8) unsigned	Y		Y
group_name	分组名称	varchar(100)	N		N
members	客户数	mediumint(8) unsigned	N	0	N
group_content	分组描述	varchar(500)	N		N
shop_id	所属店铺	varchar(32)	N		N
create_time	添加时间	int(10) unsigned	N		N
update_time	更新时间	int(10) unsigned	N		N
filter	查询条件	text	N		N
parent_id	上级分组	mediumint(8) unsigned	N	0	N
childs	子分组数量	mediumint(8) unsigned	N	0	N
op_user	操作人	varchar(32)	N		N

- 索引

Key name	Column names	Unique	Comment
primary	group_id	Y	
ind_shop_id	shop_id	N	
idx_c_shop_id	shop_id	N	

taocrm_fx_members

分销客户表

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
member_id	member_id	int(10) unsigned	Y		Y
mobile	手机	varchar(30)	N		N
last_send_time	最后发送时间	int(10) unsigned	N	0	N

is_mobile_valid	手机是否有效	tinyint(3) unsigned	N	0	N
update_time	更新时间	int(10) unsigned	N	0	N
create_time	创建时间	int(10) unsigned	N	0	N

- 索引

Key name	Column names	Unique	Comment
primary	member_id	Y	
ind_unique_mobile	mobile	Y	
ind_is_mobile_valid	is_mobile_valid	N	

taocrm_java_info

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
java_id	java_id	int(11)	Y		Y
java_class	java类名	varchar(10)	Y		N
java_version	java版本	varchar(10)	N		N
last_modify_time	更新时间	int(10) unsigned	N	0	N

- 索引

Key name	Column names	Unique	Comment
primary	java_id	Y	

taocrm_member_all_analysis

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	int(10) unsigned	Y		Y
member_id	客户	int(10) unsigned	N		N
total_orders	订单总数	mediumint(8) unsigned	N	0	N
total_amount	订单总金额	decimal(20,2)	N	0	N
total_per_amount	平均订单价	decimal(20,2)	N	0	N
buy_freq	购买频次(天)	mediumint(8) unsigned	N	0	N
avg_buy_interval	平均购买间隔(天)	decimal(20,2)	N	0	N
buy_month	购买月数	mediumint(8) unsigned	N	0	N

buy_skus	下单商品种数	mediumint(8) unsigned	N	0	N
buy_products	下单商品总数	mediumint(8) unsigned	N	0	N
avg_buy_skus	平均下单商品 种数	decimal(20,2)	N	0	N
avg_buy_products	平均下单商品 件数	decimal(20,2)	N	0	N
finish_orders	成功的订单数	mediumint(8) unsigned	N	0	N
finish_total_amount	成功的订单金 额	decimal(20,2)	N	0	N
finish_per_amount	成功的平均订 单价	decimal(20,2)	N	0	N
unpay_orders	未付款订单数	mediumint(8) unsigned	N	0	N
unpay_amount	未付款订单金 额	decimal(20,2)	N	0	N
unpay_per_amount	未支付平均订 单价	decimal(20,2)	N	0	N
refund_orders	退款订单数	mediumint(8) unsigned	N	0	N
refund_amount	退款总金额	decimal(20,2)	N	0	N
lv_id	客户等级	int(11)	N		N
first_buy_time	第一次下单时 间	int(10) unsigned	N		N
last_buy_time	最后下单时间	int(10) unsigned	N		N
update_time	更新时间	int(10) unsigned	N		N
month3_finish_amount	近3个月成功金 额	decimal(20,2)	N	0	N
month3_finish_orders	近3个月成功订 单数	mediumint(8) unsigned	N	0	N
active_times	参加营销次数	mediumint(8) unsigned	N	0	N
active_buy_times	营销成功购买 次数	mediumint(8) unsigned	N	0	N

● 索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_member_id	member_id	N	
idx_c_member_id	member_id	N	
idx_c_lv_id	lv_id	N	

taocrm_member_analysis

- 表结构

ColumnName	Comment	
id	id	int(10) unsigned
member_id	客户名	int(10) unsigned
shop_id	来源店铺	varchar(32)
district	地区	varchar(32)
channel_id	来源渠道	int(11)
total_orders	订单总数	mediumint(8) unsigned
total_amount	订单总金额	decimal(20,2)
total_per_amount	平均订单价	decimal(20,2)
buy_freq	购买频次(天)	mediumint(8) unsigned
avg_buy_interval	平均购买间隔(天)	decimal(20,2)
buy_month	购买月数	mediumint(8) unsigned
buy_skus	下单商品种数	mediumint(8) unsigned
buy_products	下单商品总数	mediumint(8) unsigned
avg_buy_skus	平均下单商品种数	decimal(20,2)
avg_buy_products	平均下单商品件数	decimal(20,2)
finish_orders	成功订单数	mediumint(8) unsigned
finish_total_amount	成功订单金额	decimal(20,2)
finish_per_amount	成功的平均订单价	decimal(20,2)
unpay_orders	未付款订单数	mediumint(8) unsigned
unpay_amount	未付款订单金额	decimal(20,2)
unpay_per_amount	未支付平均订单价	decimal(20,2)
refund_orders	退款订单数	mediumint(8) unsigned
refund_amount	退款总金额	decimal(20,2)
points	客户积分	bigint(20)
lv_id	客户等级	int(11)
is_vip	贵宾客户	enum('true', 'false')
shop_evaluation	店铺评价 good:好评;bad:差评;neutral:中评;unkown:-;	enum('good', 'bad', 'neutral')
shop_grade	店铺客户等级 0:店铺客户;1:普通客户;2:高级客户;3:VIP客户;4:至尊VIP客户;-1:非客户;	enum('0', '1', '2', '3', '4', '-1')
first_buy_time	第一次下单时间	int(10) unsigned
last_buy_time	最后下单时间	int(10) unsigned
update_time	更新时间	int(10) unsigned
f_vip_info	淘宝客户等级 c:普通客户;asso_vip:荣誉客户;vip1:vip1;vip2:vip2;vip3:vip3;vip4:vip4;vip5:vip5;vip6:vip6;	enum('c', 'asso_vip', 'vip1', 'vip2', 'vip3', 'vip4', 'vip5', 'vip6')
f_level	信用等级	mediumint(8) unsigned
f_score	信用总分	bigint(20)

f_last_visit	店铺最后访问时间	int(10) unsigned
f_created	店铺客户注册时间	int(10) unsigned
f_status	店铺客户状态 unkown :-; normal :正常; inactive :未激活; delete :删除; reeze :冻结; supervise :监管;	enum('unkown','norma
property	客户属性	text
month3_finish_amount	近3个月成功金额	decimal(20,2)
month3_finish_orders	近3个月成功订单数	mediumint(8) unsigned
active_times	参加营销次数	mediumint(8) unsigned
active_buy_times	营销成功购买次数	mediumint(8) unsigned

● 索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_member_shop	member_id, shop_id	N	
ind_first_buy_time	first_buy_time	N	
ind_last_buy_time	last_buy_time	N	
ind_channel_id	channel_id	N	
ind_lv_id	lv_id	N	
is_vip	is_vip	N	
ind_month3_finish_amount	month3_finish_amount	N	
idx_c_member_id	member_id	N	
idx_c_shop_id	shop_id	N	
idx_c_lv_id	lv_id	N	

taocrm_member_analysis_day

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	int(10) unsigned	Y		Y
shop_id	来源店铺	varchar(64)	N		N
channel_id	来源渠道	mediumint(8) unsigned	N	0	N
total_orders	订单总数	mediumint(8) unsigned	N	0	N
total_members	客户总数	mediumint(8) unsigned	N	0	N
total_amount	订单总金额	decimal(20,2)	N	0	N
total_per_amount	订单客单价	decimal(20,2)	N	0	N
		mediumint(8)			

		unsigned			
buy_products	购买商品总数	mediumint(8) unsigned	N	0	N
avg_buy_skus	平均购买商品 种数	decimal(20,2)	N	0	N
avg_buy_products	平均购买商品 件数	decimal(20,2)	N	0	N
finish_orders	完成的单数	mediumint(8) unsigned	N	0	N
finish_members	完成的客户总 数	mediumint(8) unsigned	N	0	N
finish_total_amount	成功的金额	decimal(20,2)	N	0	N
finish_per_amount	成功的客单价	decimal(20,2)	N	0	N
unpay_orders	未付款单数	mediumint(8) unsigned	N	0	N
unpay_amount	未付款金额	decimal(20,2)	N	0	N
unpay_per_amount	未支付客单价	decimal(20,2)	N	0	N
refund_orders	退款订单数	mediumint(8) unsigned	N	0	N
refund_amount	退款总金额	decimal(20,2)	N	0	N
failed_orders	失败订单数	mediumint(8) unsigned	N	0	N
failed_members	失败客户数	mediumint(8) unsigned	N	0	N
failed_amount	失败总金额	decimal(20,2)	N	0	N
paid_orders	付款订单数	mediumint(8) unsigned	N	0	N
paid_members	付款客户数	mediumint(8) unsigned	N	0	N
paid_amount	付款总金额	decimal(20,2)	N	0	N
update_time	更新时间	int(10) unsigned	N		N
c_time	统计时间	int(10) unsigned	N		N
c_date	统计日期	varchar(10)	N		N
c_week	统计周	varchar(10)	N		N
c_month	统计月	varchar(10)	N		N
c_year	统计年	mediumint(8) unsigned	N	0	N

- 索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_shop_date	shop_id, c_date	N	
ind_shop_id	shop_id	N	
ind_c_time	c_time	N	

taocrm_member_attr

会员自定义属性

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
attr_id	attr_id	int(10) unsigned	Y		Y
member_id	会员ID	int(10) unsigned	Y		N
shop_id	店铺ID	char(32)	N	all	N
attr1	自定义属性1	varchar(50)	N		N
attr2	自定义属性2	varchar(50)	N		N
attr3	自定义属性3	varchar(50)	N		N
attr4	自定义属性4	varchar(50)	N		N
attr5	自定义属性5	varchar(50)	N		N
attr6	自定义属性6	varchar(50)	N		N
attr7	自定义属性7	varchar(50)	N		N
attr8	自定义属性8	varchar(50)	N		N
attr9	自定义属性9	varchar(50)	N		N
attr10	自定义属性10	varchar(50)	N		N
create_time	创建时间	int(10) unsigned	N		N
update_time	修改时间	int(10) unsigned	N		N

- 索引

Key name	Column names	Unique	Comment
primary	attr_id	Y	
ind_member_id	member_id	N	
ind_shop_member	member_id, shop_id	Y	

taocrm_member_benefits

客户标签表

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	mediumint(8) unsigned	Y		Y
member_id	客户ID	int(11)	N		N
benefits_type	权益类型 0:金额;1:计次;2:折扣;3:其它;	enum('0','1','2','3')	N		N
benefits_code	权益项代码	varchar(100)	N		N
benefits_name	权益项名称	varchar(100)	N		N

nums	值	varchar(100)	Y		N
is_enable	状态 0:不可用;1:可用;	enum('0','1')	N		N
effectie_time	生效时间	int(10) unsigned	N		N
failure_time	失效时间	int(10) unsigned	N		N
update_time	更新时间	int(10) unsigned	N		N
create_time	创建时间	int(10) unsigned	N		N

- 索引

Key name	Column names	Unique	Comment
primary	id	Y	

taocrm_member_benefits_item

客户标签表

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	mediumint(8) unsigned	Y		Y
benefits_code	权益项代码	varchar(100)	N		N
benefits_name	权益项名称	varchar(100)	N		N
source	来源业务	varchar(100)	N		N
is_enable	是否启用 0:未启用;1:启用;	enum('0','1')	N	1	N
create_op_name	创建人	varchar(100)	N		N
create_op_time	创建人时间	int(10) unsigned	N	0	N
update_time	更新时间	int(10) unsigned	N	0	N
create_time	创建时间	int(10) unsigned	N	0	N

- 索引

Key name	Column names	Unique	Comment
primary	id	Y	

taocrm_member_benefits_log

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	int(10) unsigned	Y		Y
member_benefits_id	member_benefits_id	mediumint(8) unsigned	Y		N

member_id	客户ID	int(11)	N		N
benefits_type	权益类型 0:金额;1:计次;2:折扣;3:其它;	enum('0','1','2','3')	N		N
get_benefits_mode	获取权益方式 0:收费;1:赠送;2:其它;	enum('0','1','2')	N		N
op_mode	操作方式 0:新增;1:扣减(使用);	enum('0','1')	N		N
get_benefits_desc	获取权益说明	varchar(255)	N		N
benefits_code	权益项代码	varchar(100)	N		N
benefits_name	权益项名称	varchar(100)	N		N
nums	值	varchar(100)	Y		N
op_before_nums	调整前的值	varchar(100)	N		N
op_after_nums	调整后的值	varchar(100)	N		N
effectie_time	生效时间	int(10) unsigned	N		N
failure_time	失效时间	int(10) unsigned	N		N
is_enable	状态 0:不可用;1:可用;	enum('0','1')	N		N
source_order_bn	来源关联单号	varchar(100)	N		N
source_business_code	来源业务Code	varchar(100)	N		N
source_business_name	来源业务名称	varchar(100)	N		N
source_store_name	来源门店代码	varchar(100)	N		N
source_terminal_code	来源终端代码	varchar(100)	N		N
memo	说明备注	text	N		N
create_time	系统创建时间	int(10) unsigned	N		N
create_op_time	创建人时间	int(10) unsigned	N		N
create_op_name	创建人	varchar(100)	N		N

● 索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_member_id	member_id	N	

taocrm_member_bind_queue

客户去重任务

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincr
queue_id	queue_id	int(10) unsigned	Y		Y
bind_dimensions	合并维度	varchar(50)	Y		N
finish_time	处理时间	int(10) unsigned	N	0	N

create_time	创建时间	int(10) unsigned	N	0	N
is_send	处理状态 succ:处理成功;fail:处理失败;unsend:未处理;sending:处理中;	enum('succ','fail','unsend','sending')	N	unsend	N

索引

Key name	Column names	Unique	Comment
primary	queue_id	Y	

taocrm_member_card

会员卡

表结构

ColumnName	Comment	Type	Not null
id	id	bigint(20) unsigned	Y
member_card_type_id	member_card_type_id	bigint(20) unsigned	Y
member_card_template_id	member_card_template_id	bigint(20) unsigned	Y
member_card_make_log_id	member_card_make_log_id	bigint(20) unsigned	Y
member_id	member_id	int(10) unsigned	N
card_no	会员卡号	varchar(20)	N
card_pwd	会员卡卡密	varchar(20)	N
create_time	创建时间	int(10) unsigned	N
send_card_channel	发卡渠道	varchar(20)	N
bind_card_channel	激活渠道	varchar(20)	N
update_time	修改时间	int(10) unsigned	N
bind_time	激活时间	int(10) unsigned	N
card_status	会员卡状态 unactive:未激活;active:激活;loss:挂失;logout:注销;	enum('unactive','active','loss','logout')	Y

索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_card_no	card_no	Y	

taocrm_member_card_make_log

会员卡生成记录

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	bigint(20) unsigned	Y		Y
member_card_type_id	member_card_type_id	bigint(20) unsigned	Y		N
member_card_template_id	member_card_template_id	bigint(20) unsigned	Y		N
is_type_code	是否启用会员卡类型编码	varchar(20)	N		N
card_len	会员卡长度	tinyint(3) unsigned	N	6	N
card_pwd_len	会员卡卡密长度	tinyint(3) unsigned	N	4	N
card_pwd_rule	会员卡卡密规则 0:纯字母;1:纯数字;2:字母数字混合;	enum('0','1','2')	N	0	N
make_count	发卡数	int(5) unsigned	N	0	N
bind_count	激活数量	int(5) unsigned	N	0	N
op_name	操作者	varchar(20)	N		N
type_code	会员卡类型编码	varchar(20)	N		N
batch_no	批次号	varchar(20)	N		N
create_time	创建时间	int(10) unsigned	N		N
send_card_channel	发卡渠道	varchar(20)	N		N

● 索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_batch_no	batch_no	Y	

taocrm_member_card_template

会员卡模板

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	bigint(20) unsigned	Y		Y
member_card_type_id	member_card_type_id	bigint(20) unsigned	Y		N
card_name	会员卡名称	varchar(20)	N		N
is_type_code	是否启用会员卡类型编码 0:否;1:是;	enum('0','1')	N	0	N
card_len	会员卡长度	tinyint(3)	N	6	N

		unsigned			
card_pwd_len	会员卡卡密长度	tinyint(3) unsigned	N	4	N
card_pwd_rule	会员卡卡密规则 0:纯字母;1:纯数字;2:字母数字混合;	enum('0','1','2')	N	0	N
card_type	会员卡生成类型 0:手动生成;1:微信自动生成;	enum('0','1')	N	0	N
create_time	创建时间	int(10) unsigned	N		N
update_time	修改时间	int(10) unsigned	N		N
card_img	会员卡图片	varchar(255)	N		N

● 索引

Key name	Column names	Unique	Comment
primary	id	Y	

taocrm_member_card_type

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	bigint(20) unsigned	Y		Y
type_name	类型名称	varchar(20)	N		N
type_code	会员卡类型编码	varchar(20)	N		N
create_time	创建时间	int(10) unsigned	N		N
update_time	修改时间	int(10) unsigned	N		N
current_card_no	current_card_no	int(10) unsigned	Y	0	N

● 索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_type_code	type_code	Y	

taocrm_member_caselog

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	int(11)	Y		Y
member_id	客户	int(10) unsigned	N		N
shop_id	店铺	varchar(32)	N		N

customer	客户	varchar(50)	N		N
mobile	手机号码	char(11)	N		N
create_time	创建时间	int(10) unsigned	N		N
modified_time	修改时间	int(10) unsigned	N		N
title	标题	varchar(100)	N		N
order_bn	订单号	int(10) unsigned	N		N
content	服务内容	text	N		N
buyer_nick	买家	varchar(50)	N		N
seller_nick	卖家	varchar(50)	N		N
service_nick	子帐号	varchar(50)	N		N
category	分类	int(11)	N		N
media	媒体	int(11)	N		N
alarm_time	提醒时间	int(10) unsigned	N		N
agent	客服	varchar(50)	N		N
begin_time	开始时间	int(10) unsigned	N		N
end_time	结束时间	int(10) unsigned	N		N
alarm_user_id	提醒对象	int(10)	N		N
status	状态	int(11)	N		N
source	来源	int(11)	N		N
is_finish	是否结束	tinyint(4)	N		N

- 索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_order_bn	order_bn	N	
ind_mobile	mobile	N	
ind_alarm_time	alarm_time	N	
idx_c_member_id	member_id	N	
idx_c_shop_id	shop_id	N	
idx_c_order_bn	order_bn	N	
idx_c_category	category	N	
idx_c_media	media	N	
idx_c_status	status	N	
idx_c_source	source	N	

taocrm_member_caselog_category

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
category_id	category_id	int(11)	Y		Y
category_name	名称	varchar(50)	N		N
desc	描述	varchar(100)	N		N
type	分类 1:媒体;2:类型;3:来源;4:状态;5:其它;	enum('1','2','3','4','5')	N		N
create_time	创建时间	int(10) unsigned	N		N
status	状态	tinyint(2)	N		N

● 索引

Key name	Column names	Unique	Comment
primary	category_id	Y	
ind_category_name	category_name	N	

taocrm_member_contacts

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
contact_id	联系人ID	mediumint(8) unsigned	Y		Y
member_id	用户ID	int(10) unsigned	N		N
name	姓名	varchar(50)	N		N
area	冗余地区	varchar(32)	N		N
state	省份	varchar(32)	N		N
city	城市	varchar(32)	N		N
district	地区	varchar(32)	N		N
addr	地址	varchar(255)	N		N
mobile	手机	varchar(30)	N		N
tel	固定电话	varchar(30)	N		N
email	电子邮件	varchar(200)	N		N
wangwang	旺旺	varchar(200)	N		N
qq	QQ	varchar(200)	N		N
msn	MSN	varchar(200)	N		N
weibo	微博	varchar(200)	N		N
zip	邮编	varchar(20)	N		N
sex	性别 unkown:- ;female:	enum('unkown','female','male')	Y	unkown	N

	女;male:男;				
remark	备注	varchar(500)	N		N
channel_id	来源渠道	int(11)	N		N
shop_id	来源店铺	varchar(32)	N		N
md5	唯一识别码	varchar(32)	N		N
disabled	是否失效	enum('true','false')	N		N
create_time	创建时间	int(10) unsigned	N		N

● 索引

Key name	Column names	Unique	Comment
primary	contact_id	Y	
ind_name	name	N	
ind_md5	md5	N	
ind_member_id	member_id	N	
idx_c_channel_id	channel_id	N	
idx_c_shop_id	shop_id	N	

taocrm_member_export

● 表结构

ColumnName	Comment	Type	Not null	Default	Auto increment
export_id	export_id	mediumint(8) unsigned	Y		Y
total_num	总数	int(11)	N	0	N
export_param	导出条件	text	N		N
export_status	导出状态 succ:导出成功;fail:导出失败;unexport:准备导出;exporting:导出中;	enum('succ','fail','unexport','exporting')	N	unexport	N
create_time	创建时间	int(10) unsigned	N		N
finish_time	完成时间	int(10) unsigned	N		N
export_content	导出内容	LongBlob	N		N

● 索引

Key name	Column names	Unique	Comment
primary	export_id	Y	

taocrm_member_export_log

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
export_log_id	export_log_id	int(11)	Y		Y
export_id	export_id	mediumint(8) unsigned	Y		N
mobile	手机	varchar(32)	N		N
create_time	创建时间	int(10) unsigned	N		N

● 索引

Key name	Column names	Unique	Comment
primary	export_log_id	Y	

taocrm_member_ext

会员扩展属性

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
ext_id	ext_id	int(10) unsigned	Y		Y
member_id	会员ID	int(10) unsigned	Y		N
b_year	生日(年)	smallint(5) unsigned	N	0	N
b_month	生日(月)	tinyint(3) unsigned	N	0	N
b_day	生日(天)	tinyint(3) unsigned	N	0	N
create_time	创建时间	int(10) unsigned	N		N
update_time	修改时间	int(10) unsigned	N		N

● 索引

Key name	Column names	Unique	Comment
primary	ext_id	Y	
ind_member_id	member_id	N	
ind_b_year	b_year	N	
ind_b_month	b_month	N	
ind_b_day	b_day	N	

taocrm_member_fav

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	mediumint(8) unsigned	Y		Y
analysis_id	analysis_id	mediumint(8) unsigned	Y		N

type	类型	mediumint(8) unsigned	Y	0	N
target	指标	mediumint(8) unsigned	Y	0	N
flag	标识	mediumint(8) unsigned	Y	0	N
value	数据	float	Y	0	N
time	时间	int(10) unsigned	Y		N

● 索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_analysis_id	analysis_id	N	
ind_type	type	N	
ind_target	target	N	
ind_time	time	N	

taocrm_member_group

客户分组表

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
group_id	group_id	mediumint(8) unsigned	Y		Y
group_name	分组名称	varchar(100)	N		N
members	客户数	mediumint(8) unsigned	N	0	N
group_content	分组描述	varchar(500)	N		N
shop_id	所属店铺	varchar(32)	N		N
create_time	添加时间	int(10) unsigned	N		N
update_time	更新时间	int(10) unsigned	N		N
filter	查询条件	text	N		N
parent_id	上级分组	mediumint(8) unsigned	N	0	N
childs	子分组数量	mediumint(8) unsigned	N	0	N
op_user	操作人	varchar(32)	N		N
create_type	创建类别 system:系统;user:用户;	enum('system','user')	N	user	N

● 索引

Key name	Column names	Unique	Comment
primary	group_id	Y	
ind_shop_id	shop_id	N	

idx_c_shop_id	shop_id	N
---------------	---------	---

taocrm_member_import

导入客户表

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
member_id	member_id	int(10) unsigned	Y		Y
group_id	group_id	int(10) unsigned	Y	0	N
batch_id	batch_id	int(10) unsigned	Y	0	N
succ_member_id	succ_member_id	int(10) unsigned	Y	0	N
uname	客户名	varchar(50)	N		N
mobile	手机	varchar(30)	N		N
email	电子邮件	varchar(200)	N		N
is_mobile_valid	手机是否有效	tinyint(3) unsigned	N	0	N
is_email_valid	邮箱是否有效	tinyint(3) unsigned	N	0	N
send_count	发送次数	int(11)	N	0	N
last_send_time	最后发送时间	int(10) unsigned	N	0	N
update_time	更新时间	int(10) unsigned	N	0	N
create_time	创建时间	int(10) unsigned	N	0	N
unique_md5	唯一串	varchar(32)	N		N

- 索引

Key name	Column names	Unique	Comment
primary	member_id	Y	
ind_group_id	group_id	N	
ind_batch_id	batch_id	N	
ind_mobile	mobile	N	
ind_is_mobile_valid	is_mobile_valid	N	
ind_is_email_valid	is_email_valid	N	
ind_unique_md5	unique_md5	Y	

taocrm_member_import_batch

导入客户分组批次表

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincr

batch_id	batch_id	int(10) unsigned	Y		Y
group_id	group_id	int(10) unsigned	Y		N
send_nums	发送次数	int(11)	N	0	N
last_send_status	短信是否发送 succ:发送成功;fail:发送失败;unsend:未发送;sending:发送中;	enum('succ','fail','unsend','sending')	N	unsend	N
total_nums	批次总人数	int(11)	N	0	N
mobile_valid_nums	手机有效人数	int(11)	N	0	N
email_valid_nums	邮箱有效人数	int(11)	N	0	N
last_send_time	最后发送时间	int(10) unsigned	N	0	N
create_time	创建时间	int(10) unsigned	N	0	N

• 索引

Key name	Column names	Unique	Comment
primary	batch_id	Y	

taocrm_member_import_group

导入客户分组表

• 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
group_id	group_id	int(10) unsigned	Y		Y
group_name	分组名称	varchar(50)	N		N
total_nums	分组人数	int(11)	N	0	N
mobile_valid_nums	手机有效人数	int(11)	N	0	N
email_valid_nums	邮箱有效人数	int(11)	N	0	N
last_import_time	最后导入时间	int(10) unsigned	N	0	N
create_time	创建时间	int(10) unsigned	N	0	N

• 索引

Key name	Column names	Unique	Comment
primary	group_id	Y	

taocrm_member_import_sms

外部客户短信发送记录

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
sms_id	sms_id	int(11)	Y		Y
group_id	分组名称	int(10) unsigned	Y		N
batch_id	batch_id	int(10) unsigned	Y		N
total_num	发送总数	int(11)	N	0	N
succ_num	成功总数	int(11)	N	0	N
fail_num	失败总数	int(11)	N	0	N
last_send_time	最后发送时间	int(10) unsigned	N	0	N
template	模板内容	text	N		N
send_status	短信是否发送 succ:发送成功;fail:发送失败;unsend:未发送;sending:发送中;	enum('succ','fail','unsend','sending')	N	unsend	N

● 索引

Key name	Column names	Unique	Comment
primary	sms_id	Y	

taocrm_member_import_sms_log

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
sms_log_id	sms_log_id	int(11)	Y		Y
batch_id	batch_id	int(10) unsigned	N		N
mobile	手机号码	varchar(11)	Y		N
sms_id	sms_id	int(11)	N		N
page	page	int(11)	N		N
is_send	是否发送(0:未发送 1:发送成功 2:发送失败)	tinyint(3) unsigned	N	0	N
reason	失败原因	text	N		N
send_time	发送时间	int(10) unsigned	N	0	N

● 索引

Key name	Column names	Unique	Comment

primary	sms_log_id	Y	
ind_sms_id	sms_id	N	
ind_is_send	is_send	N	

taocrm_member_level

全局客户等级

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
level_id	level_id	bigint(20) unsigned	Y		Y
level_name	等级名称	varchar(20)	N		N
create_time	创建时间	int(10) unsigned	N		N
update_time	修改时间	int(10) unsigned	N		N
rule_type	规则类型 pay:根据消费金额设定; point:根据会员积分设定;	enum('pay','point')	N	pay	N
count_member	当前累计客户	int(11)	N	0	N
total_amount	累计成交金额	decimal(20,2)	N	0	N
average_amount	平均客单价	decimal(20,2)	N	0	N
statistics_time	统计日期	int(10) unsigned	N		N
rule_point_month	积分统计时效月份	int(11)	N	0	N
rule_point_condition	积分条件 between:介于; nolimit:不限制;	enum('between','nolimit')	N		N
rule_point_min	最小限制积分	int(11)	N	0	N
rule_point_max	最大限制积分	int(11)	N	0	N
rule_amount_month	成功交易金额月	int(11)	N	0	N
rule_amount_condition	成功交易金额条件 between:介于; nolimit:不限制;	enum('between','nolimit')	N		N
rule_amount_min	最小限制金额	int(11)	N	0	N
rule_amount_max	最大限制金额	int(11)	N	0	N
rule_count_month	成功交易次数月	int(11)	N	0	N

rule_count_condition	成功交易次数条件 between:介于;nolimit:不限制;	enum('between','nolimit')	N		N
rule_count_min	最小限制次数	int(11)	N	0	N
rule_count_max	最大限制次数	int(11)	N	0	N
rule_select	规则条件选项 and:同时满足所有条件;or:满足以上任一条件;	enum('and','or')	N	or	N
rule_msg	规则描述	varchar(255)	N		N

● 索引

Key name	Column names	Unique	Comment
primary	level_id	Y	

taocrm_member_orders_day

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	bigint(20) unsigned	Y		Y
member_id	member_id	int(10) unsigned	N		N
pay_amount	pay_amount	decimal(20,2)	N		N
finish_amount	finish_amount	decimal(20,2)	N		N
day	day	date	N		N
update_time	update_time	date	N		N

● 索引

Key name	Column names	Unique	Comment
primary	id	Y	
uk_day_memberid	day, member_id	Y	

taocrm_member_overall_property

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	int(10) unsigned	Y		Y

member_id	member_id	int(10) unsigned	Y		N
uname	客户名	varchar(50)	Y		N
property	客户属性名	varchar(50)	Y		N
value	客户属性值	varchar(50)	Y		N

索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_mmember_id	member_id	N	

taocrm_member_point_log

表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	int(10) unsigned	Y		Y
member_id	客户ID	int(11)	N		N
shop_id	来源店铺	varchar(32)	N		N
point_type	积分类型	varchar(32)	N		N
point_mode	积分方式	varchar(1)	N		N
op_time	操作时间	int(10) unsigned	N		N
op_before_point	调整前的积分	mediumint(8) unsigned	N	0	N
op_after_point	调整后的积分	mediumint(8) unsigned	N	0	N
point	积分	mediumint(8) unsigned	N	0	N
freeze_time	冻结时间	int(10) unsigned	N	0	N
unfreeze_time	解冻时间	int(10) unsigned	N	0	N
is_expired	是否过期 0:未过期;1:已过期;	enum('0','1')	N	0	N
expired_time	过期时间	int(10) unsigned	N	0	N
point_desc	积分说明	text	N		N

索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_member_id	member_id	N	

taocrm_member_point_type

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	int(10) unsigned	Y		Y
name	类型名称	varchar(100)	N		N
code	类型代码	varchar(50)	N		N
create_time	创建时间	int(10) unsigned	N		N

● 索引

Key name	Column names	Unique	Comment
primary	id	Y	

taocrm_member_points

● 表结构

ColumnName	Comment	Type	Not null	Default	Auto
id	id	int(10) unsigned	Y		Y
member_id	客户	int(10) unsigned	N		N
shop_id	店铺	varchar(32)	N		N
points	积分	int(16)	N		N
points_type	积分类型 trade:交易积分; wechat:微信积分; manual:手动积分; active:活动积分; other:其它积分;	enum('trade','wechat','manual','active','other')	N	other	N
create_time	创建时间	int(10) unsigned	N		N
modified_time	更新时间	int(10) unsigned	N		N
invalid_time	过期时间	int(10) unsigned	N		N

● 索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_modified_time	modified_time	N	
ind_invalid_time	invalid_time	N	
idx_c_member_id	member_id	N	
idx_c_shop_id	shop_id	N	

taocrm_member_property

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	int(10) unsigned	Y		Y
shop_id	来源店铺	varchar(32)	Y		N
uname	客户名	varchar(50)	Y		N
property	客户属性名	varchar(50)	Y		N
value	客户属性值	varchar(50)	Y		N

- 索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_member_property	shop_id, uname	N	

taocrm_member_receivers

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
receiver_id	收货人ID	mediumint(8) unsigned	Y		Y
member_id	客户帐号	int(10) unsigned	N		N
name	姓名	varchar(50)	N		N
area	冗余地区	varchar(255)	N		N
state	省份	varchar(32)	N		N
city	城市	varchar(32)	N		N
district	地区	varchar(32)	N		N
addr	地址	varchar(255)	N		N
mobile	手机	varchar(30)	N		N
tel	固定电话	varchar(30)	N		N
email	电子邮件	varchar(200)	N		N
zip	邮编	varchar(20)	N		N
order_num	订单数	mediumint(8) unsigned	N	0	N
sex	性别 unkown:- ;female: 女;male:男;	enum('unkown','female','male')	N	unkown	N
remark	备注	varchar(500)	N		N
create_time	创建时间	int(10) unsigned	N		N

default_addr	是否是默认地址	enum('true','false')	N	false	N
selected	是否选中为收货地址	enum('true','false')	N	false	N
md5	联系人唯一识别码	varchar(32)	N		N

● 索引

Key name	Column names	Unique	Comment
primary	receiver_id	Y	
ind_md5	md5	N	
ind_mobile	mobile	N	
ind_name	name	N	
ind_member_id	member_id	N	
idx_c_member_id	member_id	N	

taocrm_member_tag

客户标签表

● 表结构

ColumnName	Comment	Type	Nullable
tag_id	tag_id	mediumint(8) unsigned	Y
tag_name	标签名称	varchar(100)	N
members	客户数	mediumint(8) unsigned	N
mobile_valid_nums	手机有效人数	int(11)	N
last_send_time	最后发送时间	int(10) unsigned	N
update_time	更新时间	int(10) unsigned	N
create_time	创建时间	int(10) unsigned	N
get_tag	规则开关 true:规则开启;false:规则关闭;	enum('true','false')	N
tag_select	规则类型	tinyint(4)	N
activity_num	活动次数	int(11)	N
one_min	单笔最小金额	int(11)	N
one_max	单笔最大金额	int(11)	N
all_min	总计最小金额	int(11)	N
all_max	总计最大金额	int(11)	N
	标签类型 system_a:系统标签; system_b:系统标		

tag_type	签;system_c:系统标签;system_d:系统标签;store:商家自动打标;hand:手动打标;	enum('system_a','system_b','system_c','system_d','store','hand')	↑
----------	---	--	---

- 索引

Key name	Column names	Unique	Comment
primary	tag_id	Y	

taocrm_member_to_tag

客户标签关联表

- 表结构

ColumnName	Comment	Type	Not null	Default
tag_id	tag_id	mediumint(8) unsigned	Y	
member_id	客户ID	int(11)	N	
mobile	手机	varchar(30)	N	0
tag_type	标签类型 system_on:系统打标;system_off:系统删除;hand_on:手动打标;hand_off:手动删除;	enum('system_on','system_off','hand_on','hand_off')	N	hand_o

- 索引

Key name	Column names	Unique	Comment
ind_member_shop	tag_id, member_id	N	
ind_member_id	member_id	N	

taocrm_members

客户表

- 表结构

ColumnName	Comment	Type	Not null	Default	Auto inc
member_id	member_id	int(10) unsigned	Y		Y
ext_uid	外部用户ID	varchar(50)	N		N
stand_node_id	独立店节点ID	varchar(32)	N		N
uname	客户名	varchar(50)	N		N
unique_code	客户唯一码	int(10) unsigned	Y	0	N

name	姓名	varchar(50)	N		N
source_terminal	来源终端	varchar(50)	N		N
channel_type	渠道类型	varchar(32)	N	taobao	N
parent_member_id	parent_member_id	int(10) unsigned	Y	0	N
is_merger	是否合并	tinyint(3) unsigned	N	0	N
member_card	会员卡号	varchar(64)	N		N
qq	QQ	varchar(64)	N		N
wangwang	旺旺账号	varchar(64)	N		N
weixin	微信	varchar(64)	N		N
weibo	微博	varchar(64)	N		N
other_contact	其他联系方式	text	N		N
points	积分	bigint(20)	N	0	N
area	区域	varchar(255)	N		N
state	省份	varchar(32)	N		N
city	城市	varchar(32)	N		N
district	地区	varchar(32)	N		N
addr	地址	varchar(255)	N		N
mobile	手机	varchar(30)	N		N
tel	固定电话	varchar(30)	N		N
email	电子邮件	varchar(200)	N		N
zip	邮编	varchar(20)	N		N
alipay_account	支付宝账号	varchar(255)	N		N
alipay_no	支付宝ID	varchar(200)	N		N
order_total_num	订单数	mediumint(8) unsigned	N	0	N
order_total_amount	订单总额	decimal(20,2)	N	0	N
order_succ_num	成功订单数	mediumint(8) unsigned	N	0	N
order_succ_amount	成功订单金额	decimal(20,2)	N	0	N
order_first_time	首次购买时间	int(10) unsigned	N		N
order_last_time	最后购买时间	int(10) unsigned	N		N
birthday	生日	int(10) unsigned	N	0	N
sex	性别 female: 女;male: 男;unkown:-;	enum('female','male','unkown')	N	unkown	N
create_time	创建时间	int(10) unsigned	N	0	N
update_time	更新时间	int(10) unsigned	N	0	N
point_update_time	积分更新时间	int(10) unsigned	N	0	N
remark	备注	varchar(500)	N		N
disabled	是否失效	enum('true','false')	N	false	N

is_vip	贵宾客户	enum('true','false')	N	false	N
sms_blacklist	短信黑名单	enum('true','false')	N	false	N
edm_blacklist	邮件黑名单	enum('true','false')	N	false	N
last_caselog	最后一次服务(不含服务内容)	varchar(500)	N		N
last_contact_time	最后服务时间	int(10) unsigned	N		N
contact_times	服务次数	int(10)	N	0	N
props	自定义属性	text	N		N
level_id	全局会员等级	bigint(20) unsigned	N	0	N
shop_id	店铺ID	varchar(32)	N		N
stored_value	储值金额	decimal(20,2)	N	0	N

● 索引

Key name	Column names	Unique	Comment
primary	member_id	Y	
ind_unique_code	unique_code	N	
ind_name	name	N	
ind_uname	uname	N	
ind_mobile	mobile	N	
ind_order_first_time	order_first_time	N	
ind_order_last_time	order_last_time	N	
ind_tel	tel	N	
ind_is_merger	is_merger	N	
ind_parent_member_id	parent_member_id	N	
ind_create_time	create_time	N	
idx_c_level_id	level_id	N	

taocrm_members_recommend

推荐表

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
member_id	member_id	int(10) unsigned	Y		N
uname	推荐人名称(客户名)	varchar(50)	N		N
name	真实姓名	varchar(50)	N		N
mobile	手机号	varchar(30)	N		N
create_time	创建时间	int(10) unsigned	N	0	N
is_parent	是否有被推荐人	enum('true','false')	N	false	N

self_code	推荐唯一码	int(11)	N	0	N
parent_code	推荐人CODE	int(11)	N	0	N
update_time	更新时间	int(10) unsigned	N	0	N
mRTwoStatus	二级推荐人数返利是否已经统计过了。0未统计1统计过了	int(11)	N	0	N
mRThreeStatus	三级推荐人是否返利0未统计，1统计过了	int(11)	N	0	N

● 索引

Key name	Column names	Unique	Comment
primary	member_id	Y	
ind_comm	parent_code	N	
ind_code	self_code	N	
ind_name	name	N	
ind_uname	uname	N	

taocrm_members_recommend_no

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	int(10) unsigned	Y		Y

● 索引

Key name	Column names	Unique	Comment
primary	id	Y	

taocrm_members_rule_log

会员等级规则设置日志

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
log_id	log_id	int(10) unsigned	Y		Y
type	积分类型 pay:根据消费金额设定;point:根据会员积分设定;	enum('pay','point')	N	pay	N
create_time	创建时间	int(10) unsigned	N		N

● 索引

Key name	Column names	Unique	Comment
primary	log_id	Y	

create_time	create_time	N
-------------	-------------	---

taocrm_points_log

积分日志表

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
log_id	log_id	int(10) unsigned	Y		Y
member_id	客户名	int(10) unsigned	N		N
points	积分	int(11)	N	0	N
points_type	积分类型 trade:交易积分; wechat:微信积分; active:活动积分; other:其它积分;	enum('trade','wechat','active','other')	N	other	N
order_id	订单ID	int(10) unsigned	N		N
order_bn	订单号	varchar(50)	N		N
refund_id	退款单编号	int(10) unsigned	N		N
shop_id	来源店铺	varchar(32)	N		N
create_time	创建时间	int(10) unsigned	N		N
is_active	状态	enum('0','1')	N	1	N
remark	备注	varchar(200)	N		N
op_user	操作人	varchar(32)	N		N
pid	撤销积分日志ID	mediumint(8) unsigned	N		N
user_ip	IP地址	varchar(100)	N		N

- 索引

Key name	Column names	Unique	Comment
primary	log_id	Y	
ind_order_id	order_id	N	
ind_order_bn	order_bn	N	
ind_refund_id	refund_id	N	
ind_shop_id	shop_id	N	
ind_member_id	member_id	N	
idx_c_member_id	member_id	N	
idx_c_order_id	order_id	N	
idx_c_refund_id	refund_id	N	

idx_c_shop_id	shop_id	N
---------------	---------	---

taocrm_rebate

返利发放记录表

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	int(10) unsigned	Y		Y
rebate_cycle_id	返利周期ID	int(11)	N	0	N
order_id	订单编号	int(11)	N		N
member_id	消费者id	int(11)	N	0	N
uname	客户名称	varchar(50)	N		N
mobile	手机号	varchar(20)	N		N
rebate_amount	返利值	decimal(20,2)	N	0	N
rebate_type	返利类型 0:-;1:金额;2:积分;	enum('0','1','2')	N	0	N
is_send	是否发放 false:否;true:是;	enum('false','true')	N	false	N
send_time	发送时间	int(10) unsigned	N		N
create_time	创建时间	int(10) unsigned	N		N
origin_modified	推荐人关系生成时间	int(10) unsigned	N		N

- 索引

Key name	Column names	Unique	Comment
primary	id	Y	

taocrm_rebate_cycle

返利周期表

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	int(10) unsigned	Y		Y
rebate_start_time	周期开始时间	int(10) unsigned	Y		N
rebate_end_time	周期结束时间	int(10) unsigned	Y		N
rebate_number	本周期返利次数	mediumint(8) unsigned	N	0	N
rebate_price	本周期返利值	decimal(20,2)	Y		N
is_send	是否发放 false:否;true:是;	enum('false','true')	N	false	N
send_time	发送时间	int(10) unsigned	N		N

create_time	创建时间	int(10) unsigned	N		N
-------------	------	------------------	---	--	---

- 索引

Key name	Column names	Unique	Comment
primary	id	Y	

taocrm_rebate_rule

返点规则设置

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	int(10) unsigned	Y		Y
conf	配置信息	varchar(500)	N		N
op_user	操作人	varchar(32)	N		N
create_time	创建时间	datetime	N	0	N
is_del	是否删除	tinyint(4)	N	0	N

- 索引

Key name	Column names	Unique	Comment
primary	id	Y	

taocrm_sms_log

- 表结构

ColumnName	Comment	
log_id	log_id	bigint(20) unsigned
member_id	member_id	int(11)
source_id	来源ID	int(11)
source	短信类型 active_plan:营销计划;active_cycle:周期营销;market_active:营销活动;plugins_plugins:自动插件;taocrm_member_import_batch:导入客户;taocrm_member_caselog:服务记录;market_callplan:呼叫计划;taocrm_member_group:自定义分组;market_fx_activity:分销活动;sale_model:营销模型;weixin:微信服务;report:运营报表;other:其他;	enum('active_plan','active_cycle','market_active','plugin
shop_id	店铺ID	varchar(32)
shop_name	店铺	varchar(32)
batch_no	批次编号	varchar(64)

mobile	手机号码	varchar(11)
content	短信内容	varchar(350)
status	状态 wait:待发送;fail:失败;succ:成功;	enum('wait','fail','succ')
remark	备注	text
plan_send_time	计划发送时间	int(10) unsigned
send_time	发送时间	int(10) unsigned
create_time	创建时间	int(10) unsigned
sms_size	短信长度	int(11)
cyear	年	int(11)
cmonth	月	int(11)
cday	天	int(11)
op_user	操作人	varchar(50)
ip	操作IP	varchar(64)

● 索引

Key name	Column names	Unique	Comment
primary	log_id	Y	
ind_mobile	mobile	N	
ind_op_user	op_user	N	
ind_send_time	send_time	N	

taocrm_stored_value

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	id	bigint(20) unsigned	Y		Y
member_id	客户ID	int(11)	N	0	N
shop_id	店铺ID	varchar(32)	N		N
stored_value	储值	decimal(20,2)	N	0	N
stored_value_type	储值类型 0:手动调整;1:推广返利;	enum('0','1')	N	0	N
create_time	创建时间	int(10) unsigned	N	0	N
last_modification_time	最后修改时间	int(10) unsigned	N	0	N

● 索引

Key name	Column names	Unique	Comment

primary	id	Y	
ind_member	member_id	N	

taocrm_stored_value_log

- 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
log_id	log_id	bigint(20) unsigned	Y		Y
member_id	客户ID	int(11)	N	0	N
shop_id	店铺ID	varchar(32)	N		N
uname	客户名称	varchar(32)	N		N
mobile	手机号码	varchar(20)	N		N
value_time	储值更改时间	int(10) unsigned	N	0	N
change_amount	变动金额	decimal(20,2)	N		N
before_change_amount	期初值(变动前金额)	decimal(20,2)	N		N
after_change_amount	期末值(变动后金额)	decimal(20,2)	N		N
trade_no	订单号	varchar(50)	N		N
payment_no	支付单号	varchar(50)	N		N
sn	序列号	varchar(50)	N		N
op_user	操作人	varchar(50)	N		N
remark	备注	varchar(200)	N		N

- 索引

Key name	Column names	Unique	Comment
primary	log_id	Y	
ind_member	member_id	N	
ind_mobile	mobile	N	
ind_op_user	op_user	N	
ind_sn	sn	N	
ind_value_time	value_time	N	

taocrm_wangwang_shop

- 表结构

ColumnName	Comment	Type	Not	Default	Autoincrement
------------	---------	------	-----	---------	---------------

			null		
id	序号	int(10) unsigned	Y		Y
shop_id	店铺ID	varchar(32)	Y		N
seller_nick	主账号昵称	varchar(65)	N		N
nick	子帐户用户名	varchar(65)	N		N
seller_id	子账号所属的主账号的唯一标识	int(11)	N		N
status	子旺旺状态 1:正常;-1:删除;2:冻结;	enum('1','-1','2')	N		N
sub_id	子帐号ID	int(11)	N		N
is_online	是否参与分流 1:不参与 ;2:参与;	enum('1','2')	N		N

● 索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_shop_id	shop_id	N	

taocrm_wangwang_shop_chat_log

● 表结构

ColumnName	Comment	Type	Not null	Default	Autoincrement
id	序号	int(10) unsigned	Y		Y
shop_id	来源店铺	varchar(32)	Y		N
member_id	客户ID	int(11)	N	0	N
uname	客户名	varchar(50)	Y		N
seller_nick	客服旺旺号	varchar(65)	N		N
chat_date	咨询日期	int(10) unsigned	N		N

● 索引

Key name	Column names	Unique	Comment
primary	id	Y	
ind_shop_id	shop_id	N	
ind_uname	uname	N	
ind_chat_date	chat_date	N	
idx_c_shop_id	shop_id	N	