
ACM TEMPLATE

UESTC_Lasagne

Last build at October 16, 2012

Contents

1	To Do List	4
2	注意事项	5
3	字符串处理	6
3.1	*AC自动机	6
3.1.1	指针	6
3.1.2	非指针	7
3.2	后缀数组	8
3.2.1	DC3	8
3.2.2	DA	10
3.3	后缀三兄弟	10
3.3.1	例题	14
3.4	KMP	20
3.5	e-KMP	20
3.6	*Manacher	21
3.7	*字符串最小表示法	22
3.8	带*通配符的匹配	22
4	数学	25
4.1	扩展GCD	25
4.2	模线性方程组	25
4.3	矩阵	26
4.4	康拓展开	26
4.5	FFT	27
4.6	爬山法计算器	30
4.7	线性筛	32
4.8	线性规划	33
4.9	分解质因数	36
4.9.1	米勒拉宾+分解因数	36
4.9.2	暴力版本	39
4.10	baby step giant step	39
4.11	原根	40
4.12	逆元	40
4.13	卢卡斯	41
4.14	欧拉函数	41
4.14.1	分解质因数	41
4.14.2	一次预处理	41
4.15	费马降阶法	42
4.16	自适应simp	43
4.17	组合数求模	43
4.18	其它公式	45
4.18.1	拉格朗日插值法	45
4.18.2	正多面体顶点着色	45
4.18.3	求和公式	45
4.18.4	几何公式	46
4.18.5	小公式	46

5	数据结构	47
5.1	*Splay	47
5.2	动态树	55
5.2.1	维护点权	55
5.2.2	维护边权	59
5.3	可持久化线段树	63
5.4	treap正式版	66
5.5	树链剖分	69
5.5.1	点权	69
5.5.2	边权	75
5.6	划分树	79
5.7	树状数组	80
6	图论	82
6.1	优先队列优化的dijkstra	82
6.2	SAP四版	83
6.3	费用流三版	85
6.4	匈牙利	87
6.4.1	新版,隐式图可解	87
6.4.2	邻接矩阵	88
6.4.3	邻接表	88
6.5	一般图匹配带花树	89
6.6	KM	92
6.6.1	最大加权匹配	92
6.6.2	自认为正确的Kuhn_Munkras	93
6.7	*二维平面图的最大流	95
6.8	强联通	99
6.9	最大团以及相关知识	100
6.10	双连通分量	101
6.11	割点与桥	103
6.12	LCA	105
6.13	最优比例生成树	107
6.14	全局最小割	108
6.15	欧拉路	109
6.15.1	有向图	109
6.15.2	无向图	110
6.15.3	混合图	110
6.16	K短路	111
6.17	稳定婚姻	113
6.18	最小树形图	115
7	计算几何	118
7.1	基本函数	118
7.1.1	Point定义	118
7.1.2	Line定义	118
7.1.3	距离: 两点距离	119
7.1.4	距离: 点到直线距离	119
7.1.5	距离: 点到线段距离	119
7.1.6	面积: 多边形	120
7.1.7	判断: 线段相交	120
7.2	圆	120
7.2.1	面积: 两圆相交	120

7.2.2	三角形外接圆	121
7.2.3	三角形内切圆	121
7.2.4	点对圆的两个切点	121
7.2.5	两圆公切点	122
7.3	矩阵	122
7.3.1	基本矩阵	122
7.3.2	刘汝佳的几何教室	123
7.4	重心	126
7.5	KD树	127
7.5.1	例题	128
7.6	半平面交	130
7.7	凸包	131
7.8	直线与凸包求交点	132
7.9	三维凸包	133
7.10	旋转卡壳	138
7.10.1	单个凸包	138
7.10.2	两个凸包	138
7.10.3	外接矩形	139
7.11	三角形内点个数	140
7.11.1	无三点共线	140
7.11.2	有三点共线且点有类别之分	141
7.12	最近点对	143
7.12.1	类快排算法	143
7.12.2	随机增量法	144
7.13	多圆面积并	146
7.13.1	去重	146
7.13.2	圆并	146
7.14	一个圆与多边形面积交	149
7.15	精度问题	150
7.15.1	浮点数为啥会有精度问题	150
8	搜索	151
8.1	Dancing Links	151
9	杂物	154
9.1	高精度数	154
9.2	整数外挂	155
9.3	Java	155
9.3.1	IO	155
9.3.2	优先队列	155
9.3.3	Map	156
9.3.4	sort	156
9.4	hashmap	156
9.5	C++&STL常用函数	157
9.5.1	lower_bound/upper_bound	157
9.5.2	rotate	158
9.5.3	nth_element	158
9.5.4	bitset	158
9.5.5	multimap	159
9.6	其它	161
9.6.1	对跑脚本	161
9.6.2	枚举长为 n 含 k 个1的01串	161

1 To Do List

所有带*的内容。。。

可以从原来的模板里面继承一些好东西过来。

set,map,multiset等的搞基用法，以及注意事项。

生成树计数

2 注意事项

10^6 数量级慎用后缀数组

TLE的时候要冷静哟。。

思考的时候结合具体步骤来的话 会体会到一些不同的东西

C++与G++是很不一样的。。。

map套字符串是很慢的。。。

栈会被记录内存。。。

浮点数最短路要注意取 \leq 来判断更新。。。

注意 long long

不要相信.size()

重复利用数组时 小心数组范围

先构思代码框架 每当实际拍马框架变化时 停手 重新思考

有时候四边形不等式也是帮得上忙的 dp 优化是可以水的

结构体里面带数组会非常慢,有时候 BFS 把数组压成数字会快很多。

```
1 | void fun(int a[])
2 | {
3 |     printf("%d\n", sizeof(a));
4 | }
```

结果是 sizeof(a[0]),如果传数组指针然后要清空的话不要用 sizeof。

sqrt 某些时候会出现 sqrt(-0.00)的问题。

将code::blocks的默认终端改成gnome-terminal

```
1 | gnome-terminal -t $TITLE -x
```

最小割割集找法 在残量网络中从源点出发能到的点集记为S原图中S到S'的边即是最小割集

double全局变量初始值可能不是0

3 字符串处理

3.1 *AC自动机

3.1.1 指针

```
1  const int CHAR=26;
2  const int TOTLEN=500000;
3  const int MAXLEN=1000000;
4  struct Vertex
5  {
6      Vertex *fail,*next[CHAR];
7      Vertex(){}
8      Vertex(bool flag)//为什么要这样写?
9      {
10         fail=0;
11         memset(next,0,sizeof(next));
12     }
13 };
14 int size;
15 Vertex vertex[TOTLEN+1];
16 void init()
17 {
18     vertex[0]=Vertex(0);
19     size=1;
20 }
21 void add(Vertex *pos,int cha)
22 {
23     vertex[size]=Vertex(0);
24     pos->next[cha]=&vertex[size++];
25 }
26 void add(vector<int> s)
27 {
28     int l=s.size();
29     Vertex *pos=&vertex[0];
30     for (int i=0; i<l; i++)
31     {
32         if (pos->next[s[i]]==NULL)
33             add(pos,s[i]);
34         pos=pos->next[s[i]];
35     }
36 }
37 void bfs()
38 {
39     queue<Vertex *> que;
40     Vertex *u=&vertex[0];
41     for (int i=0; i<CHAR; i++)
42         if (u->next[i]!=NULL)
43         {
44             que.push(u->next[i]);
45             u->next[i]->fail=u;
46         }
```



```

47         else
48             u->next[i]=u;
49     u->fail=NULL;
50     while (!que.empty())
51     {
52         u=que.front();
53         que.pop();
54         for (int i=0; i<CHAR; i++)
55             if (u->next[i]!=NULL)
56             {
57                 que.push(u->next[i]);
58                 u->next[i]->fail=u->fail->next[i];
59             }
60         else
61             u->next[i]=u->fail->next[i];
62     }
63 }

```

3.1.2 非指针

```

1 struct Trie
2 {
3     int next[50][10],fail[50];
4     bool end[50];
5     int L,root;
6
7     int newNode()
8     {
9         for (int i = 0;i < 10;i++)
10             next[L][i] = -1;
11         end[L] = false;
12         return L++;
13     }
14
15     void Init()
16     {
17         L = 0;
18         root = newNode();
19     }
20
21     void Insert(char s[])
22     {
23         int now = root;
24         for (int i = 0;s[i] != 0;i++)
25         {
26             if (next[now][s[i]-'0'] == -1)
27                 next[now][s[i]-'0'] = newNode();
28             now = next[now][s[i]-'0'];
29         }
30         end[now] = true;
31     }
32
33     void Build()

```

```

34     {
35         queue<int> Q;
36         for (int i = 0; i < 10; i++)
37             if (next[root][i] == -1)
38                 next[root][i] = root;
39             else
40             {
41                 fail[next[root][i]] = root;
42                 Q.push(next[root][i]);
43             }
44         while (!Q.empty())
45         {
46             int now = Q.front();
47             Q.pop();
48             end[now] |= end[fail[now]];
49             for (int i = 0; i < 10; i++)
50                 if (next[now][i] == -1)
51                     next[now][i] = next[fail[now]][i];
52                 else
53                 {
54                     fail[next[now][i]] = next[fail[now]][i];
55                     Q.push(next[now][i]);
56                 }
57         }
58     }
59 };

```

3.2 后缀数组

3.2.1 DC3

所有下标都是0 n-1, height[0]无意义。

```

1 //所有相关数组都要开三倍
2 const int maxn = 300010;
3 # define F(x) ((x)/3+((x)%3==1?0:tb))
4 # define G(x) ((x)<tb?(x)*3+1:((x)-tb)*3+2)
5 int wa[maxn * 3], wb[maxn * 3], wv[maxn * 3], ws[maxn * 3];
6 int c0(int *r, int a, int b)
7 {
8     return r[a] == r[b] && r[a + 1] == r[b + 1] && r[a + 2] == r[
9         b + 2];
10 }
11 int c12(int k, int *r, int a, int b)
12 {
13     if (k == 2) return r[a] < r[b] || r[a] == r[b] && c12(1, r, a
14         + 1, b + 1);
15     else return r[a] < r[b] || r[a] == r[b] && wv[a + 1] < wv[b +
16         1];
17 }
18 void sort(int *r, int *a, int *b, int n, int m)
19 {
20     int i;
21     for (i = 0; i < n; i++) wv[i] = r[a[i]];

```

```

19     for (i = 0; i < m; i++) ws[i] = 0;
20     for (i = 0; i < n; i++) ws[wv[i]]++;
21     for (i = 1; i < m; i++) ws[i] += ws[i - 1];
22     for (i = n - 1; i >= 0; i--) b[--ws[wv[i]]] = a[i];
23     return;
24 }
25 void dc3(int *r, int *sa, int n, int m)
26 {
27     int i, j, *rn = r + n, *san = sa + n, ta = 0, tb = (n + 1) /
        3, tbc = 0, p;
28     r[n] = r[n + 1] = 0;
29     for (i = 0; i < n; i++) if (i % 3 != 0) wa[tbc++] = i;
30     sort(r + 2, wa, wb, tbc, m);
31     sort(r + 1, wb, wa, tbc, m);
32     sort(r, wa, wb, tbc, m);
33     for (p = 1, rn[F(wb[0])] = 0, i = 1; i < tbc; i++)
34         rn[F(wb[i])] = c0(r, wb[i - 1], wb[i]) ? p - 1 : p++;
35     if (p < tbc) dc3(rn, san, tbc, p);
36     else for (i = 0; i < tbc; i++) san[rn[i]] = i;
37     for (i = 0; i < tbc; i++) if (san[i] < tb) wb[ta++] = san[i]
        * 3;
38     if (n % 3 == 1) wb[ta++] = n - 1;
39     sort(r, wb, wa, ta, m);
40     for (i = 0; i < tbc; i++) wv[wb[i] = G(san[i])] = i;
41     for (i = 0, j = 0, p = 0; i < ta && j < tbc; p++)
42         sa[p] = c12(wb[j] % 3, r, wa[i], wb[j]) ? wa[i++] : wb[j]
            ++;
43     for (; i < ta; p++) sa[p] = wa[i++];
44     for (; j < tbc; p++) sa[p] = wb[j++];
45 }
46 //str和sa也要三倍
47 void da(int str[], int sa[], int rank[], int height[], int n, int
    m)
48 {
49     for (int i = n; i < n * 3; i++)
50         str[i] = 0;
51     dc3 (str , sa , n + 1 , m);
52     int i, j, k;
53     for (i = 0; i < n; i++)
54     {
55         sa[i] = sa[i + 1];
56         rank[sa[i]] = i;
57     }
58     for (i = 0, j = 0, k = 0; i < n; height[rank[i ++]] = k)
59         if (rank[i] > 0)
60             for (k ? k-- : 0 , j = sa[rank[i] - 1]; i + k < n &&
                j + k < n &&
61                 str[i + k] == str[j + k]; k ++);
62 }

```

3.2.2 DA

这份似乎就没啥要注意的了。

```
1  const int maxn = 200010;
2  int wx[maxn],wy[maxn],*x,*y,wss[maxn],wv[maxn];
3
4  bool cmp(int *r,int n,int a,int b,int l)
5  {
6      return a+l<n && b+l<n && r[a]==r[b]&&r[a+l]==r[b+l];
7  }
8  void da(int str[],int sa[],int rank[],int height[],int n,int m)
9  {
10     int *s = str;
11     int *x=wx,*y=wy,*t,p;
12     int i,j;
13     for(i=0; i<m; i++)wss[i]=0;
14     for(i=0; i<n; i++)wss[x[i]=s[i]]++;
15     for(i=1; i<m; i++)wss[i]+=wss[i-1];
16     for(i=n-1; i>=0; i--)sa[--wss[x[i]]]=i;
17     for(j=1,p=1; p<n && j<n; j*=2,m=p)
18     {
19         for(i=n-j,p=0; i<n; i++)y[p++]=i;
20         for(i=0; i<n; i++)if(sa[i]-j>=0)y[p++]=sa[i]-j;
21         for(i=0; i<n; i++)wv[i]=x[y[i]];
22         for(i=0; i<m; i++)wss[i]=0;
23         for(i=0; i<n; i++)wss[wv[i]]++;
24         for(i=1; i<m; i++)wss[i]+=wss[i-1];
25         for(i=n-1; i>=0; i--)sa[--wss[wv[i]]]=y[i];
26         for(t=x,x=y,y=t,p=1,i=1,x[sa[0]]=0; i<n; i++)
27             x[sa[i]]=cmp(y,n,sa[i-1],sa[i],j)?p-1:p++;
28     }
29     for(int i=0; i<n; i++) rank[sa[i]]=i;
30     for(int i=0,j=0,k=0; i<n; height[rank[i++]]=k)
31         if(rank[i]>0)
32             for(k?k--:0,j=sa[rank[i]-1]; i+k < n && j+k < n &&
33                 str[i+k]==str[j+k]; k++);
34 }
```

3.3 后缀三兄弟

```
1  #include <cstdio>
2  #include <cstring>
3  #include <algorithm>
4  using namespace std;
5  const int CHAR = 26;
6  const int MAXN = 100000;
7  struct SAM_Node
8  {
9      SAM_Node *fa,*next[CHAR];
10     int len;
11     int id,pos;
12     SAM_Node() {}
13 }
```

```

13     SAM_Node(int _len)
14     {
15         fa = 0;
16         len = _len;
17         memset(next,0,sizeof(next));
18     }
19 };
20 SAM_Node SAM_node[MAXN * 2], *SAM_root, *SAM_last;
21 int SAM_size;
22 SAM_Node *newSAM_Node(int len)
23 {
24     SAM_node[SAM_size] = SAM_Node(len);
25     SAM_node[SAM_size].id=SAM_size;
26     return &SAM_node[SAM_size++];
27 }
28 SAM_Node *newSAM_Node(SAM_Node *p)
29 {
30     SAM_node[SAM_size] = *p;
31     SAM_node[SAM_size].id=SAM_size;
32     return &SAM_node[SAM_size++];
33 }
34 void SAM_init()
35 {
36     SAM_size = 0;
37     SAM_root = SAM_last = newSAM_Node(0);
38     SAM_node[0].pos=0;
39 }
40 void SAM_add(int x,int len)
41 {
42     SAM_Node *p = SAM_last, *np = newSAM_Node(p->len + 1);
43     np->pos=len;
44     SAM_last = np;
45     for (; p && !p->next[x]; p = p->fa)
46         p->next[x] = np;
47     if (!p)
48     {
49         np->fa = SAM_root;
50         return ;
51     }
52     SAM_Node *q = p->next[x];
53     if (q->len == p->len + 1)
54     {
55         np->fa = q;
56         return ;
57     }
58     SAM_Node *nq = newSAM_Node(q);
59     nq->len = p->len + 1;
60     q->fa = nq;
61     np->fa = nq;
62     for (; p && p->next[x] == q; p = p->fa)
63         p->next[x] = nq;
64 }

```

```

65 void SAM_build(char *s)
66 {
67     SAM_init();
68     int l = strlen(s);
69     for (int i = 0; i < l; i++)
70         SAM_add(s[i] - 'a', i+1);
71 }
72
73 SAM_Node * SAM_add(SAM_Node *p, int x, int len)
74 {
75     SAM_Node *np = newSAM_Node(p->len + 1);
76     np->pos = len;
77     SAM_last = np;
78     for (; p && !p->next[x]; p = p->fa)
79         p->next[x] = np;
80     if (!p)
81     {
82         np->fa = SAM_root;
83         return np;
84     }
85     SAM_Node *q = p->next[x];
86     if (q->len == p->len + 1)
87     {
88         np->fa = q;
89         return np;
90     }
91     SAM_Node *nq = newSAM_Node(q);
92     nq->len = p->len + 1;
93     q->fa = nq;
94     np->fa = nq;
95     for (; p && p->next[x] == q; p = p->fa)
96         p->next[x] = nq;
97     return np;
98 }
99 void SAM_build(char *s) //多串建立 注意SAM_init()的调用
100 {
101     int l = strlen(s);
102     SAM_Node *p = SAM_root;
103     for (int i = 0; i < l; i++)
104     {
105         if (!p->next[s[i] - 'a'] || !(p->next[s[i] - 'a']->len ==
106             i + 1))
107             p = SAM_add(p, s[i] - 'a', i + 1);
108         else
109             p = p->next[s[i] - 'a'];
110     }
111 }
112 struct ST_Node
113 {
114     ST_Node *next[CHAR], *fa;
115     int len, pos;

```

```

116 }ST_node[MAXN*2],*ST_root;
117 int Sufpos[MAXN];
118 void ST_add(int u,int v,int chr,int len)
119 {
120     ST_node[u].next[chr]=&ST_node[v];
121     ST_node[v].len=len;
122 }
123 void init(int n)
124 {
125     for (int i=0;i<n;i++)
126     {
127         ST_node[i].pos=-1;
128         ST_node[i].fa=0;
129         memset(ST_node[i].next,0,sizeof(ST_node[i].next));
130     }
131     ST_node[0].pos=0;
132     ST_root=&ST_node[0];
133 }
134 void ST_build(char *s)
135 {
136     int n=strlen(s);
137     reverse(s,s+n);
138     SAM_build(s);
139     init(SAM_size);
140     for (int i=1;i<SAM_size;i++)
141     {
142         ST_add(SAM_node[i].fa->id,SAM_node[i].id,s[SAM_node[i].
            pos-SAM_node[i].fa->len-1]-'a',SAM_node[i].len-
            SAM_node[i].fa->len);
143         if (SAM_node[i].pos==SAM_node[i].len)
144         {
145             Sufpos[n-SAM_node[i].pos+1]=i;
146             ST_node[i].pos=n-SAM_node[i].pos+1;
147         }
148     }
149 }
150
151 int rank[MAXN],sa[MAXN+1];
152 int height[MAXN];
153 int L;
154 void ST_dfs(ST_Node *p)
155 {
156     if (p->pos!=-1)
157         sa[L++]=p->pos;
158     for (int i=0;i<CHAR;i++)
159         if (p->next[i])
160             ST_dfs(p->next[i]);
161 }
162 char s[MAXN+1];
163 int main()
164 {
165     gets(s);

```

```

166     ST_build(s);
167     L=0;
168     ST_dfs(ST_root);
169     int n=strlen(s);
170     for (int i=0; i<n; i++)
171         sa[i]=sa[i+1]-1;
172     for (int i=0; i<n; i++)
173         rank[sa[i]]=i;
174     reverse(s,s+n);
175     for (int i=0,j=0,k=0; i<n; height[rank[i++]]=k)
176         if (rank[i])
177             for (k?k--:0,j=sa[rank[i]-1]; s[i+k]==s[j+k]; k++);
178 }

```

3.3.1 例题

```

1  #include <iostream>
2  #include <algorithm>
3  #include <cstdio>
4  #include <cstring>
5  using namespace std;
6
7  const int CHAR = 26;
8  const int MAXN = 100000;
9
10 struct SAM_Node
11 {
12     SAM_Node *fa,*next[CHAR];
13     int len;
14     int id;
15     int mat[9];
16     SAM_Node() {}
17     SAM_Node(int _len)
18     {
19         fa = 0;
20         len = _len;
21         memset(mat,0,sizeof(mat));
22         memset(next,0,sizeof(next));
23     }
24 };
25 SAM_Node SAM_node[MAXN*2],*SAM_root,*SAM_last;
26 int SAM_size;
27 SAM_Node *newSAM_Node(int len)
28 {
29     SAM_node[SAM_size] = SAM_Node(len);
30     SAM_node[SAM_size].id = SAM_size;
31     return &SAM_node[SAM_size++];
32 }
33 SAM_Node *newSAM_Node(SAM_Node *p)
34 {
35     SAM_node[SAM_size] = *p;
36     SAM_node[SAM_size].id = SAM_size;
37     return &SAM_node[SAM_size++];

```



```

38 }
39 void SAM_init()
40 {
41     SAM_size = 0;
42     SAM_root = SAM_last = newSAM_Node(0);
43 }
44 void SAM_add(int x,int len)
45 {
46     SAM_Node *p = SAM_last,*np = newSAM_Node(p->len+1);
47     SAM_last = np;
48     for (; p&&!p->next[x]; p=p->fa)
49         p->next[x] = np;
50     if (!p)
51     {
52         np->fa = SAM_root;
53         return;
54     }
55     SAM_Node *q = p->next[x];
56     if (q->len == p->len+1)
57     {
58         np->fa = q;
59         return;
60     }
61     SAM_Node *nq = newSAM_Node(q);
62     nq->len = p->len+1;
63     q->fa = nq;
64     np->fa = nq;
65     for (; p&&p->next[x] == q; p = p->fa)
66         p->next[x] = nq;
67 }
68 int getid(char ch)
69 {
70     return ch-'a';
71 }
72 void SAM_build(char *s)
73 {
74     SAM_init();
75     int l = strlen(s);
76     for (int i = 0; i < l; i++)
77         SAM_add(getid(s[i]),i+1);
78 }
79 char s[10][MAXN+1];
80 int ans;
81 int head[MAXN*2];
82 struct Edge
83 {
84     int to,next;
85 } edge[MAXN*2];
86 int M;
87 int n;
88 void add_edge(int u,int v)
89 {

```

```

90     edge[M].to=v;
91     edge[M].next=head[u];
92     head[u]=M++;
93 }
94 void dfs(int u)
95 {
96     for (int i=head[u]; i!=-1; i=edge[i].next)
97     {
98         int v=edge[i].to;
99         dfs(v);
100         for (int j=0; j<n-1; j++)
101             SAM_node[u].mat[j]=max(SAM_node[v].mat[j], SAM_node[u]
                                     ].mat[j]);
102     }
103     int tmp=SAM_node[u].len;
104     for (int i=0; i<n-1; i++)
105         tmp=min(tmp, SAM_node[u].mat[i]);
106     ans=max(ans, tmp);
107 }
108 int main()
109 {
110
111     while (scanf("%s", s[n]) != EOF)
112         n++;
113     int L=strlen(s[0]);
114     ans=M=0;
115     SAM_build(s[0]);
116     for (int j=1; j<n; j++)
117     {
118         int l=strlen(s[j]), len=0;
119         SAM_Node *p=SAM_root;
120         for (int i=0; i<l; i++)
121         {
122             if (p->next[getid(s[j][i])])
123             {
124                 p=p->next[getid(s[j][i])];
125                 p->mat[j-1]=max(p->mat[j-1], ++len);
126             }
127             else
128             {
129                 while (p && !p->next[getid(s[j][i])])
130                     p=p->fa;
131                 if (!p)
132                 {
133                     p=SAM_root;
134                     len=0;
135                 }
136                 else
137                 {
138                     len=p->len+1;
139                     p=p->next[getid(s[j][i])];
140                 }

```

```

141         p->mat[j-1]=max(p->mat[j-1],len);
142     }
143 }
144 }
145 memset(head,-1,4*SAM_size);
146 for (int i=1; i<SAM_size; i++)
147     add_edge(SAM_node[i].fa->id,i);
148 dfs(0);
149 printf("%d\n",ans);
150 return 0;
151 }

```

LCS2

```

1  #include <iostream>
2  #include <algorithm>
3  #include <cstdio>
4  #include <cstring>
5  using namespace std;
6
7  const int CHAR = 26;
8  const int MAXN = 100000;
9
10 struct SAM_Node
11 {
12     SAM_Node *fa,*next[CHAR];
13     int len;
14     int id;
15     int mat[9];
16     SAM_Node() {}
17     SAM_Node(int _len)
18     {
19         fa = 0;
20         len = _len;
21         memset(mat,0,sizeof(mat));
22         memset(next,0,sizeof(next));
23     }
24 };
25 SAM_Node SAM_node[MAXN*2],*SAM_root,*SAM_last;
26 int SAM_size;
27 SAM_Node *newSAM_Node(int len)
28 {
29     SAM_node[SAM_size] = SAM_Node(len);
30     SAM_node[SAM_size].id = SAM_size;
31     return &SAM_node[SAM_size++];
32 }
33 SAM_Node *newSAM_Node(SAM_Node *p)
34 {
35     SAM_node[SAM_size] = *p;
36     SAM_node[SAM_size].id = SAM_size;
37     return &SAM_node[SAM_size++];
38 }
39 void SAM_init()

```

```

40 {
41     SAM_size = 0;
42     SAM_root = SAM_last = newSAM_Node(0);
43 }
44 void SAM_add(int x,int len)
45 {
46     SAM_Node *p = SAM_last,*np = newSAM_Node(p->len+1);
47     SAM_last = np;
48     for (; p&&!p->next[x]; p=p->fa)
49         p->next[x] = np;
50     if (!p)
51     {
52         np->fa = SAM_root;
53         return;
54     }
55     SAM_Node *q = p->next[x];
56     if (q->len == p->len+1)
57     {
58         np->fa = q;
59         return;
60     }
61     SAM_Node *nq = newSAM_Node(q);
62     nq->len = p->len+1;
63     q->fa = nq;
64     np->fa = nq;
65     for (; p&&p->next[x] == q; p = p->fa)
66         p->next[x] = nq;
67 }
68 int getid(char ch)
69 {
70     return ch-'a';
71 }
72 void SAM_build(char *s)
73 {
74     SAM_init();
75     int l = strlen(s);
76     for (int i = 0; i < l; i++)
77         SAM_add(getid(s[i]),i+1);
78 }
79 char s[MAXN+1];
80 int ans;
81 int head[MAXN*2];
82 struct Edge
83 {
84     int to,next;
85 } edge[MAXN*2];
86 int M;
87 int n;
88 void add_edge(int u,int v)
89 {
90     edge[M].to=v;
91     edge[M].next=head[u];

```

```

92     head[u]=M++;
93 }
94 void dfs(int u)
95 {
96     for (int i=head[u]; i!=-1; i=edge[i].next)
97     {
98         int v=edge[i].to;
99         /*for (int j=0; j<n; j++)
100             SAM_node[v].mat[j]=max(SAM_node[v].mat[j], SAM_node[u]
101                                     ].mat[j]);*/
102         dfs(v);
103         for (int j=0; j<n; j++)
104             SAM_node[u].mat[j]=max(SAM_node[v].mat[j], SAM_node[u]
105                                     ].mat[j]);
106     }
107     int tmp=SAM_node[u].len;
108     for (int i=0; i<n; i++)
109         tmp=min(tmp, SAM_node[u].mat[i]);
110     ans=max(ans, tmp);
111 }
112 int main()
113 {
114     //freopen("in.txt", "r", stdin);
115     //freopen("out.txt", "w", stdout);
116     n=0;
117     gets(s);
118     SAM_build(s);
119     while (gets(s))
120     {
121         int l=strlen(s), len=0;
122         SAM_Node *p=SAM_root;
123         for (int i=0; i<l; i++)
124         {
125             if (p->next[getid(s[i])])
126             {
127                 p=p->next[getid(s[i])];
128                 p->mat[n]=max(p->mat[n], ++len);
129             }
130             else
131             {
132                 while (p && !p->next[getid(s[i])])
133                     p=p->fa;
134                 if (!p)
135                 {
136                     p=SAM_root;
137                     len=0;
138                 }
139                 else
140                 {
141                     len=p->len+1;
142                     p=p->next[getid(s[i])];
143                 }
144             }
145         }
146     }

```

```

142         p->mat[n]=max(p->mat[n],len);
143     }
144     //printf("%d %d %d\n",i,len,p->id);
145 }
146     n++;
147 }
148     memset(head,-1,4*SAM_size);
149     for (int i=1; i<SAM_size; i++)
150         add_edge(SAM_node[i].fa->id,i);
151     dfs(0);
152     printf("%d\n",ans);
153     return 0;
154 }

```

3.4 KMP

求A[0..i]的一个后缀最多能匹配B的前缀多长。先对B进行自匹配然后与A匹配。KMP[i]就是对应答案，p[i+1]是B[0..i]的一个后缀最多能匹配B的前缀多长。

```

1 //自匹配过程
2 int j;
3 p[0] = j = -1;
4 for ( int i = 1; i < lb; i++)
5 {
6     while (j >= 0 && b[j + 1] != b[i]) j = p[j];
7     if (b[j + 1] == b[i]) j ++;
8     p[i] = j;
9 }
10 //下面是匹配过程
11 j = -1;
12 for ( int i = 0; i < la; i++)
13 {
14     while (j >= 0 && b[j + 1] != a[i]) j = p[j];
15     if (b[j + 1] == a[i]) j ++;
16     KMP[i] = j + 1;
17 }

```

3.5 e-KMP

求A[i..len-1]和B的最长公共前缀有多长。先对B进行自匹配然后与A匹配。eKMP[i]就是对应答案。p[i]是B[i..len-1]和B的最长公共前缀有多长。

```

1 //自匹配过程
2 int j = 0;
3 while (j < lb && b[j] == b[j + 1])
4     j++;
5 p[0] = lb, p[1] = j;
6 int k = 1;
7 for (int i = 2; i < lb; i++)
8 {
9     int Len = k + p[k] - 1, L = p[i - k];
10    if (L < Len - i + 1)
11        p[i] = L;
12    else

```

```

13     {
14         j = max(0, Len - i + 1);
15         while (i + j < lb && b[i + j] == b[j])
16             j++;
17         p[i] = j, k = i;
18     }
19 }
20 //下面是匹配过程
21 j = 0;
22 while (j < la && j < lb && a[j] == b[j])
23     j++;
24 eKMP[0] = j;
25 k = 0;
26 for (int i = 1; i < la; i++)
27 {
28     int Len = k + eKMP[k] - 1, L = p[i - k];
29     if (L < Len - i + 1)
30         eKMP[i] = L;
31     else
32     {
33         j = max(0, Len - i + 1);
34         while (i + j < la && j < lb && a[i + j] == b[j])
35             j++;
36         eKMP[i] = j, k = i;
37     }
38 }

```

3.6 *Manacher

待整理

```

1 char s[1000], a[3000];
2 int p[3000], len, l, pnow, pid, res, resid;
3
4 int main()
5 {
6     while (scanf("%s", s) != EOF)
7     {
8         len = strlen(s);
9         l = 0;
10        a[l++] = '.';
11        a[l++] = ',';
12        for (int i = 0; i < len; i++)
13        {
14            a[l++] = s[i];
15            a[l++] = ',';
16        }
17        pnow = 0;
18        res = 0;
19        for (int i = 1; i < l; i++)
20        {
21            if (pnow > i)
22                p[i] = min(p[2*pid-i], pnow-i);

```

```

23         else
24             p[i] = 1;
25         for (;a[i-p[i]] == a[i+p[i]];p[i]++);
26         if (i+p[i] > pnow)
27         {
28             pnow = i+p[i];
29             pid = i;
30         }
31         if (p[i] > res)
32         {
33             res = p[i];
34             resid = i;
35         }
36     }
37     for (int i = resid-res+2;i < resid+res-1;i += 2)
38         printf("%c",a[i]);
39     printf("\n");
40 }
41 return 0;
42 }

```

3.7 *字符串最小表示法

```

1 int Gao(char a[],int len)
2 {
3     int i = 0,j = 1,k = 0;
4     while (i < len && j < len && k < len)
5     {
6         int cmp = a[(j+k)%len]-a[(i+k)%len];
7         if (cmp == 0)
8             k++;
9         else
10        {
11            if (cmp > 0)
12                j += k+1;
13            else
14                i += k+1;
15            if (i == j) j++;
16            k = 0;
17        }
18    }
19    return min(i,j);
20 }

```

3.8 带*通配符的匹配

```

1 #include <iostream>
2 #include <algorithm>
3 #include <cstdio>
4 #include <cstring>
5 using namespace std;
6

```



```

7 char a[110],b[110],sp[110][110],tot,place[110];
8 int n,la,lb,ll;
9
10 bool check(int id,int pos)
11 {
12     for (int i = 0;sp[id][i] != 0;i++)
13         if (b[pos+i] != sp[id][i])
14             return false;
15     return true;
16 }
17
18 bool check()
19 {
20     lb = strlen(b);
21     int pre = 0;
22     for (int i = 0;i < tot;i++)
23     {
24         bool find = false;
25         for (int j = pre;j < lb;j++)
26             if (check(i,j) == true)
27             {
28                 place[i] = j;
29                 pre = place[i]+1;
30                 find = true;
31                 break;
32             }
33         if (find == false) return false;
34     }
35     if (a[0] != '*')
36         if (place[0] != 0)
37             return false;
38     if (a[la-1] != '*')
39         if (check(tot-1,lb-ll) == false)
40             return false;
41     return true;
42 }
43
44 int main()
45 {
46     while (scanf("%s",a) != EOF)
47     {
48         tot = 0;
49         for (int i = 0;a[i] != 0;i++)
50             if (a[i] != '*')
51             {
52                 int j;
53                 for (j = i;a[j] != 0 && a[j] != '*';j++)
54                     sp[tot][j-i] = a[j];
55                 sp[tot++][j-i] = 0;
56                 i = j;
57             }
58         la = strlen(a);

```

```

59         ll = strlen(sp[tot-1]);
60         scanf("%d",&n);
61         for (int i = 0;i < n;i++)
62         {
63             scanf("%s",b);
64             if (check() == true)
65                 puts(b);
66         }
67     }
68     return 0;
69 }
70 /*
71 Sample Input 1
72 *. *
73 4
74 main.c
75 a.out
76 readme
77 yacc
78
79 Sample Input 2
80 *a*a*a
81 4
82 aaa
83 aaaaaa
84 aaaaaa x
85 ababab a
86
87 Sample Output 1
88 main.c
89 a.out
90
91 Sample Output 2
92 aaa
93 aaaaaa
94 ababab a
95 */

```

4 数学

4.1 扩展GCD

求 $ax+by=\gcd(a,b)$ 的一组解

```
1 long long ex_gcd(long long a,long long b,long long &x,long long &
  y)
2 {
3     if (b)
4     {
5         long long ret = ex_gcd(b,a%b,x,y),tmp = x;
6         x = y;
7         y = tmp-(a/b)*y;
8         return ret;
9     }
10    else
11    {
12        x = 1;
13        y = 0;
14        return a;
15    }
16 }
```

4.2 模线性方程组

```
1 //有更新
2 int m[10],a[10]; //模数m 余数a
3 bool solve(int &m0,int &a0,int m,int a) //模线性方程组
4 {
5     int y,x;
6     int g=ex_gcd(m0,m,x,y);
7     if (abs(a-a0)%g) return 0;
8     x*=(a-a0)/g;
9     x%=m/g;
10    a0=(x*m0+a0);
11    m0*=m/g;
12    a0%=m0;
13    if (a0<0) a0+=m0;
14    return 1;
15 }
16 int MLES()
17 {
18     bool flag=1;
19     int m0=1,a0=0;
20     for (int i=0; i<n; i++)
21         if (!solve(m0,a0,m[i],a[i]))
22         {
23             flag=0;
24             break;
25         }
26     if (flag)
```

```

27         return a0;
28     else
29         return -1;
30 }

```

4.3 矩阵

乘法的时候将 B 数组转置一下然后 $C[i][j] = \sum A[i][k] \times B[j][k]$ 会有奇效。

```

1 struct Matrix
2 {
3     int a[52][52];
4     Matrix operator * (const Matrix &b) const
5     {
6         Matrix res;
7         for (int i = 0; i < 52; i++)
8             for (int j = 0; j < 52; j++)
9             {
10                 res.a[i][j] = 0;
11                 for (int k = 0; k < 52; k++)
12                     res.a[i][j] += a[i][k] * b.a[k][j];
13             }
14         return res;
15     }
16     Matrix operator ^ (int y) const
17     {
18         Matrix res, x;
19         for (int i = 0; i < 52; i++)
20         {
21             for (int j = 0; j < 52; j++)
22                 res.a[i][j] = 0, x.a[i][j] = a[i][j];
23             res.a[i][i] = 1;
24         }
25         for (; y; y >>= 1, x = x * x)
26             if (y & 1)
27                 res = res * x;
28         return res;
29     }
30 };

```

4.4 康拓展开

```

1 const int PermSize = 12;
2 int factory[PermSize] = {1, 1, 2, 6, 24, 120, 720, 5040, 40320,
3     362880, 3628800, 39916800};
4 int Cantor(int a[])
5 {
6     int i, j, counted;
7     int result = 0;
8     for (i = 0; i < PermSize; ++i)
9     {
10         counted = 0;
11         for (j = i + 1; j < PermSize; ++j)

```

```

11         if (a[i] > a[j])
12             ++counted;
13         result = result + counted * factory[PermSize - i - 1];
14     }
15     return result;
16 }
17
18 bool h[13];
19
20 void UnCantor(int x, int res[])
21 {
22     int i,j,l,t;
23     for (i = 1;i <= 12;i++)
24         h[i] = false;
25     for (i = 1; i <= 12; i++)
26     {
27         t = x / factory[12 - i];
28         x -= t * factory[12 - i];
29         for (j = 1, l = 0; l <= t; j++)
30             if (!h[j])l++;
31         j--;
32         h[j] = true;
33         res[i - 1] = j;
34     }
35 }

```

4.5 FFT

```

1  const double PI= acos(-1.0);
2  struct vir
3  {
4      double re,im; //实部和虚部
5      vir(double a=0,double b=0)
6      {
7          re=a;
8          im=b;
9      }
10     vir operator +(const vir &b)
11     {return vir(re+b.re,im+b.im);}
12     vir operator -(const vir &b)
13     {return vir(re-b.re, im-b.im);}
14     vir operator *(const vir &b)
15     {return vir(re*b.re-im*b.im , re*b.im+im*b.re);}
16 };
17 vir x1[200005],x2[200005];
18 void change(vir *x,int len,int loglen)
19 {
20     int i,j,k,t;
21     for(i=0;i<len;i++)
22     {
23         t=i;
24         for(j=k=0; j<loglen; j++,t>>=1)
25             k= (k<<1)|(t&1);

```

```

26     if(k<i)
27     {
28         //    printf("%d %d\n",k,i);
29         vir wt=x[k];
30         x[k]=x[i];
31         x[i]=wt;
32     }
33 }
34 }
35 void fft(vir *x,int len,int loglen)
36 {
37     int i,j,t,s,e;
38     change(x,len,loglen);
39     t=1;
40     for(i=0;i<loglen;i++,t<<=1)
41     {
42         s=0;
43         e=s+t;
44         while(s<len)
45         {
46             vir a,b,wo(cos(PI/t),sin(PI/t)),wn(1,0);
47             for(j=s;j<s+t;j++)
48             {
49                 a=x[j];
50                 b=x[j+t]*wn;
51                 x[j]=a+b;
52                 x[j+t]=a-b;
53                 wn=wn*wo;
54             }
55             s=e+t;
56             e=s+t;
57         }
58     }
59 }
60 void dit_fft(vir *x,int len,int loglen)
61 {
62     int i,j,s,e,t=1<<loglen;
63     for(i=0;i<loglen;i++)
64     {
65         t>>=1;
66         s=0;
67         e=s+t;
68         while(s<len)
69         {
70             vir a,b,wn(1,0),wo(cos(PI/t),-sin(PI/t));
71             for(j=s;j<s+t;j++)
72             {
73                 a=x[j]+x[j+t];
74                 b=(x[j]-x[j+t])*wn;
75                 x[j]=a;
76                 x[j+t]=b;
77                 wn=wn*wo;

```

```

78     }
79     s=e+t;
80     e=s+t;
81 }
82 }
83 change(x,len,loglen);
84 for(i=0;i<len;i++)
85     x[i].re/=len;
86 }
87 int main()
88 {
89     char a[100005],b[100005];
90     int i,len1,len2,len,loglen;
91     int t,over;
92     while(scanf("%s%s",a,b)!=EOF)
93     {
94         len1=strlen(a)<<1;
95         len2=strlen(b)<<1;
96         len=1;loglen=0;
97         while(len<len1)
98         {
99             len<<=1;    loglen++;
100        }
101        while(len<len2)
102        {
103            len<<=1;    loglen++;
104        }
105        for(i=0;a[i];i++)
106        {
107            x1[i].re=a[i]-'0';
108            x1[i].im=0;
109        }
110        for(;i<len;i++)
111            x1[i].re=x1[i].im=0;
112        for(i=0;b[i];i++)
113        {
114            x2[i].re=b[i]-'0';
115            x2[i].im=0;
116        }
117        for(;i<len;i++)
118            x2[i].re=x2[i].im=0;
119        fft(x1,len,loglen);
120        fft(x2,len,loglen);
121        for(i=0;i<len;i++)
122            x1[i] = x1[i]*x2[i];
123        dit_fft(x1,len,loglen);
124        for(i=(len1+len2)/2-2,over=len=0;i>=0;i--)
125        {
126            t=(int)(x1[i].re+over+0.5);
127            a[len++]= t%10;
128            over = t/10;
129        }

```

```

130     while(over)
131     {
132         a[len++]=over%10;
133         over/=10;
134     }
135     for(len--;len>=0&&!a[len];len--);
136     if(len<0)
137         putchar('0');
138     else
139         for(;len>=0;len--)
140             putchar(a[len]+'0');
141     putchar('\n');
142 }
143 return 0;
144 }

```

4.6 爬山法计算器

注意灵活运用。

双目运算符在calc()中，左结合单目运算符在P()中，右结合单目运算符在calc_exp中。（但是还没遇到过。。）

```

1  #include <iostream>
2  #include <cstdio>
3  #include <cstring>
4  #include <algorithm>
5  #include <string>
6  using namespace std;
7
8  char s[100000];
9  int n,cur;
10 const string OP = "+-*";
11
12 char next_char()
13 {
14     if (cur >= n) return EOF;
15     return s[cur];
16 }
17
18 int get_priority(char ch)
19 {
20     if (ch == '*') return 2;
21     return 1;
22 }
23
24 int P();
25
26 int calc(int a,char op,int b)
27 {
28     if (op == '+')
29         return a+b;
30     if (op == '-')
31         return a-b;

```



```

32     if (op == '*')
33         return a*b;
34 }
35
36 int calc_exp(int p)
37 {
38     int a = P();
39     while ((OP.find(next_char()) != OP.npos) && (get_priority(
40         next_char()) >= p))
41     {
42         char op = next_char();
43         cur++;
44         a = calc(a,op,calc_exp(get_priority(op)+1));
45     }
46     return a;
47 }
48
49 int totvar,m,var[26],varid[26];
50
51 int P()
52 {
53     if (next_char() == '-')
54     {
55         cur++;
56         return -P();
57     }
58     else if (next_char() == '+')
59     {
60         cur++;
61         return P();
62     }
63     else if (next_char() == '(')
64     {
65         cur++;
66         int res = calc_exp(0);
67         cur++;
68         return res;
69     }
70     else
71     {
72         cur++;
73         //cout << "getvar at " << cur << ' ' << var[varid[s[cur
74             ]-'a']] << endl;
75         return var[varid[s[cur-1]-'a']];
76     }
77 }
78
79 int id[26],minid;
80
81 int main()
82 {
83     while (true)

```

```

82     {
83         scanf("%d%d",&totvar,&var[0]);
84         if (totvar == 0 && var[0] == 0) break;
85         for (int i = 1;i < totvar;i++)
86             scanf("%d",&var[i]);
87         scanf("%d",&m);
88         scanf("%s",s);
89         for (int i = 0;i < 26;i++)
90             id[i] = -1;
91         minid = 0;
92         n = strlen(s);
93         for (int i = 0;i < n;i++)
94             if (s[i] >= 'a' && s[i] <= 'z')
95             {
96                 if (id[s[i]-'a'] == -1)
97                 {
98                     id[s[i]-'a'] = minid;
99                     minid++;
100                 }
101                 s[i] = 'a'+id[s[i]-'a'];
102             }
103         for (int i = 0;i < totvar;i++)
104             varid[i] = i;
105         int res = 0;
106         do
107         {
108             cur = 0;
109             int tmp = calc_exp(0);
110             if (tmp == m)
111             {
112                 res++;
113                 break;
114             }
115         }
116         while (next_permutation(varid,varid+totvar));
117         //puts(s);
118         if (res > 0)
119             puts("YES");
120         else
121             puts("NO");
122     }
123     return 0;
124 }

```

4.7 线性筛

```

1  int N;
2  bool isPrime[10001];
3  int prime[10000];
4  void getPrime(int n)
5  {
6      memset(isPrime,1,++n);

```

```

7      N=0;
8      isPrime[0]=isPrime[1]=0;
9      for (int i=2;i<n;i++)
10     {
11         if (isPrime[i])
12             prime[N++]=i;
13         for (int j=0;j<N && prime[j]*i<n;j++)
14         {
15             isPrime[i*prime[j]]=0;
16             if (i%prime[j]==0)
17                 break;
18         }
19     }
20 }

```

4.8 线性规划

```

1  #define MAXM 20  //max num of basic variables
2  #define INF 1E200
3
4  double A[MAXM+5][MAXN+MAXM+5];
5  double b[MAXM+5],c[MAXN+MAXM+5];
6  int N[MAXN+5],B[MAXM+5];
7  double X[MAXN+MAXM+5],V;
8  int n,m,R,C,nCnt,bCnt;
9  int v1[MAXN],v2[MAXN];
10
11 int fcmp(double a,double b)
12 {
13     if(fabs(a-b)<1E-7) return 0;
14     if(a>b) return 1;
15     return -1;
16 }
17
18 void Pivot(int l,int e)
19 {
20     double t=A[l][e],p=c[e];
21     b[l]=b[l]/t;
22     for(int i=1;i<=C;i++)
23         A[l][i]/=t;
24     V=V-c[e]*b[l];
25     for(int i=1;i<=R;i++)
26     {
27         if(i==l||fcmp(A[i][e],0.0)==0)
28             continue;
29         t=A[i][e];
30         b[i]=b[i]-t*b[l];
31         for(int j=1;j<=C;j++)
32             A[i][j]=A[i][j]-t*A[l][j];
33     }
34     for(int i=1;i<=C;i++)
35         c[i]=c[i]-p*A[l][i];
36     for(int i=1;i<=nCnt;i++)

```

```

37     {
38         if(N[i]==e)
39         {
40             N[i]=B[l];
41             break;
42         }
43     }
44     B[l]=e;
45 }
46
47 bool Process(double P[])
48 {
49     while(true)
50     {
51         int e=-1;
52         double mV=-INF;
53         for(int i=1;i<=nCnt;i++)
54             if(fcmp(P[N[i]],mV)==1)
55                 mV=P[N[i]],e=N[i];
56
57         if(fcmp(mV,0.0)<=0) break;
58         int l=-1;
59         mV=INF;
60         for(int i=1;i<=bCnt;i++)
61         {
62             if(fcmp(A[i][e],0.0)==1)
63             {
64                 double t=b[i]/A[i][e];
65                 if(fcmp(mV,t)==1||(fcmp(mV,t)==0&&(l==-1||B[l]>B[i])))
66                     mV=t,l=i;
67             }
68         }
69         if(l==-1) return false;
70         Pivot(l,e);
71     }
72     return true;
73 }
74
75 bool initSimplex()
76 {
77     nCnt=bCnt=0;
78     for(int i=1;i<=n;i++)
79         N[++nCnt]=i;
80     for(int i=1;i<=m;i++)
81         B[++bCnt]=i+n,A[i][n+i]=1.0;
82     R=bCnt,C=bCnt+nCnt;
83     double minV=INF;
84     int p=-1;
85     for(int i=1;i<=m;i++)
86         if(fcmp(minV,b[i])==1)
87             minV=b[i],p=i;
88     if(fcmp(minV,0.0)>=0)

```

```

89     return true;
90     N[++nCnt]=n+m+1;R++,C++;
91     for(int i=0;i<=C;i++)
92         A[R][i]=0.0;
93     for(int i=1;i<=R;i++)
94         A[i][n+m+1]=-1.0;
95     Pivot(p,n+m+1);
96     if(!Process(A[R])) return false;
97     if(fcmp(b[R],0.0)!=0)
98         return false;
99     p=-1;
100    for(int i=1;i<=bCnt&&p==-1;i++)
101        if(B[i]==n+m+1) p=i;
102    if(p!=-1)
103    {
104        for(int i=1;i<=nCnt;i++)
105        {
106            if(fcmp(A[p][N[i]],0.0)!=0)
107            {
108                Pivot(p,N[i]);
109                break;
110            }
111        }
112    }
113    bool f=false;
114    for(int i=1;i<=nCnt;i++)
115    {
116        if(N[i]==n+m+1) f=true;
117        if(f&& i+1<=nCnt)
118            N[i]=N[i+1];
119    }
120    nCnt--;
121    R--,C--;
122    return true;
123 }
124
125 // -1: no solution 1: no bound 0: has a solution -V
126 int Simplex()
127 {
128     if(!initSimplex())
129         return -1;
130     if(!Process(c))
131         return 1;
132     for(int i=1;i<=nCnt;i++)
133         X[N[i]]=0.0;
134     for(int i=1;i<=bCnt;i++)
135         X[B[i]]=b[i];
136     return 0;
137 }
138
139 int main()
140 {

```

```

141 //n = 1;m=1;
142 //V= 0.0;
143 //c[1] = 1.0;
144 //A[1][1] = 1.0;
145 //b[1] = 5.0;
146 //Simplex();
147 //printf("V = %.3f\n",V);
148
149 while(scanf("%d",&v1[1]) == 1)
150 {
151     for(int i = 2; i<=6;i++)
152         scanf("%d",&v1[i]);
153     n = 4; m = 6;
154     for(int i = 0 ; i<=m+1;i++)
155         for(int j=0;j<=n+m+2;j++)
156             A[i][j] = c[j] = 0;
157     memset(b,0,sizeof(b));
158     V = 0.0;
159     /*
160     n 为未知数个数
161     m 为约束个数
162     目标: siama(c[i]*xi)
163     约束: sigma(A[i][j]*xj) <=b[i]; j = 1 ... n
164     解存在X里面
165     */
166     b[1] = v1[1] ; A[1][1] = 1;A[1][4] = 1;
167     b[2] = v1[2] ; A[2][1] = 1;A[2][3] = 1;
168     b[3] = v1[3] ; A[3][3] = 1;A[3][4] = 1;
169     b[4] = v1[4] ; A[4][2] = 1;A[4][3] = 1;
170     b[5] = v1[5] ; A[5][2] = 1;A[5][4] = 1;
171     b[6] = v1[6] ; A[6][1] = 1;A[6][2] = 1;
172     c[1] = 1;c[2] = 1;c[3] = 1;c[4] = 1;
173     Simplex();
174     //printf("V = %.3f\n",V);
175     printf("%.3f□%.3f□%.3f□%.3f\n",X[1],X[2],X[3],X[4]);
176
177 }
178 return 0;
179 }

```

4.9 分解质因数

4.9.1 米勒拉宾+分解因数

```

1 #include<ctime>
2 #include<iostream>
3 #define bint long long
4 using namespace std;
5 const int TIME = 8;//测试次数, 够了8~10
6 int factor[100],fac_top = -1;
7
8 //计算两个数的gcd
9 bint gcd(bint small,bint big)

```

```

10 {
11     while(small)
12     {
13         swap(small,big);
14         small%=big;
15     }
16     return abs(big);
17 }
18
19 //ret = (a*b)%n (n<2^62)
20 bint muti_mod(bint a,bint b,bint n)
21 {
22     bint exp = a%n, res = 0;
23     while(b)
24     {
25         if(b&1)
26         {
27             res += exp;
28             if(res>n) res -= n;
29         }
30         exp <<= 1;
31         if (exp>n) exp -= n;
32         b>>=1;
33     }
34     return res;
35 }
36
37 // ret = (a^b)%n
38 bint mod_exp(bint a,bint p,bint m)
39 {
40     bint exp=a%m, res=1; //
41     while(p>1)
42     {
43         if(p&1)
44             res=muti_mod(res,exp,m);
45         exp = muti_mod(exp,exp,m);
46         p>>=1;
47     }
48     return muti_mod(res,exp,m);
49 }
50
51 //miller-法测试素数rabin, time 测试次数
52 bool miller_rabin(bint n, int times)
53 {
54     if(n==2)return 1;
55     if(n<2||!(n&1))return 0;
56     bint a, u=n-1, x, y;
57     int t=0;
58     while(u%2==0)
59     {
60         t++;
61         u/=2;

```

```

62     }
63     srand(time(0));
64     for(int i=0; i<times; i++)
65     {
66         a = rand() % (n-1) + 1;
67         x = mod_exp(a, u, n);
68         for(int j=0; j<t; j++)
69         {
70             y = muti_mod(x, x, n);
71             if ( y == 1 && x != 1 && x != n-1 )
72                 return false; //must not
73             x = y;
74         }
75         if( y!=1) return false;
76     }
77     return true;
78 }
79
80 bint pollard_rho(bint n,int c)//找出一个因子
81 {
82     bint x,y,d,i = 1,k = 2;
83     srand(time(0));
84     x = rand()%(n-1)+1;
85     y = x;
86     while(true)
87     {
88         i++;
89         x = (muti_mod(x,x,n) + c) % n;
90         d = gcd(y-x, n);
91         if (1 < d && d < n) return d;
92         if( y == x) return n;
93         if(i == k)
94         {
95             y = x;
96             k <<= 1;
97         }
98     }
99 }
100
101 void findFactor(bint n,int k)//二分找出所有质因子，存入factor
102 {
103     if(n==1)return;
104     if(miller_rabin(n, TIME))
105     {
106         factor[++fac_top] = n;
107         return;
108     }
109     bint p = n;
110     while(p >= n)
111         p = pollard_rho(p,k--);//值变化，防止死循环k
112     findFactor(p,k);
113     findFactor(n/p,k);

```



```

114 }
115
116 int main()
117 {
118     bint cs,n,min;
119     cin>>cs;
120     while (cs--)
121     {
122         cin>>n;
123         fac_top = min = -1;
124         if(miller_rabin(n,TIME)) cout<<"Prime"<<endl;
125         else
126         {
127             findFactor(n,107);
128             for(int i=0; i<=fac_top; i++)
129             {
130                 if(min<0||factor[i]<min)
131                     min = factor[i];
132             }
133             cout<<min<<endl;
134         }
135     }
136     return 0;
137 }

```

4.9.2 暴力版本

```

1 int N;
2 int num[30],fac[30];
3 void getFactor(int x)
4 {
5     N=0;
6     memset(num,0,sizeof(num));
7     for (int i=0; prime[i]*prime[i]<=x && i<L; i++)
8     {
9         if (x%prime[i]==0)
10        {
11            while (x%prime[i]==0)
12            {
13                x/=prime[i];
14                num[N]++;
15            }
16            fac[N++]=prime[i];
17        }
18    }
19    if (x>1)
20    {
21        num[N]=1;
22        fac[N++]=x;
23    }
24 }

```

4.10 baby step giant step

```

1 | #define MOD 76543
2 | int hs[MOD], head[MOD], next[MOD], id[MOD], top;
3 | void insert(int x, int y)
4 | {
5 |     int k = x%MOD;
6 |     hs[top] = x, id[top] = y, next[top] = head[k], head[k] = top
7 |     ++;
8 | }
9 | int find(int x)
10 | {
11 |     int k = x%MOD;
12 |     for (int i = head[k]; i; i = next[i]) if (hs[i] == x) return
13 |         id[i];
14 |     return -1;
15 | }
16 | int BSGS(int a, int b, int n)
17 | {
18 |     memset(head, 0, sizeof(head));
19 |     top = 1;
20 |     if (b==1) return 0;
21 |     int m = sqrt(n+.0), j;
22 |     long long x = 1, p = 1;
23 |     for (int i = 0; i < m; ++i, p = p*a%n) insert(p*b%n, i);
24 |     for (long long i = m; ; i += m)
25 |     {
26 |         if ((j = find(x=x*p%n)) != -1) return i-j;
27 |         if (i > n) break;
28 |     }
29 |     return -1;
30 | }

```

4.11 原根

```

1 | int getPriRoot(int p)
2 | {
3 |     if (p==2) return 1;
4 |     int phi = p - 1;
5 |     getFactor(phi);
6 |     for (int g = 2; g < p; ++g)
7 |     {
8 |         bool flag=1;
9 |         for (int i = 0; flag && i < N; ++i)
10 |             if (power(g, phi/fac[i], p) == 1)
11 |                 flag=0;
12 |         if (flag)
13 |             return g;
14 |     }
15 | }

```

4.12 逆元

```

1 | void getInv2(int x)
2 | {

```

```

3     inv[1]=1;
4     for (int i=2; i<=x; i++)
5         inv[i]=(mod-(mod/i)*inv[mod%i]%mod)%mod;
6 }
7 int getInv(int x)//为素数mod
8 {
9     return power(x,mod-2);
10 }

```

4.13 卢卡斯

卢卡斯, $num[i]$ 阶乘也

```

1 int comLucus(int n,int m,int p)
2 {
3     int ans=1;
4     for (; n && m && ans; n/=p,m/=p)
5     {
6         if (n%p>=m%p)
7             ans = ans*num[n%p]%p*getInv(num[m%p]%p)%p*getInv(num[
                n%p-m%p])%p;
8         else
9             ans=0;
10    }
11    return ans;
12 }

```

4.14 欧拉函数

4.14.1 分解质因数

```

1 int getEuler(int x)
2 {
3     getFactor(x);
4     int ret=x;
5     for (int i=0; i<N; i++)
6         ret = ret/fac[i]*(fac[i]-1);
7     return ret;
8 }

```

4.14.2 一次预处理

```

1 void getEuler2()
2 {
3     memset(euler,0,sizeof(euler));
4     euler[1] = 1;
5     for (int i = 2; i <= 3000000; i++)
6     {
7         if (!euler[i])
8         {
9             for (int j = i; j <= 3000000; j += i)
10            {
11                if (!euler[j])
12                    euler[j] = j;

```

```

13         euler[j] = euler[j]/i*(i-1);
14     }
15 }
16 }
17 }

```

4.15 费马降阶法

分解素数 p 为 $x^2 + y^2$ 的费马降阶法，失败返回-1，主程序调用calcu(p,x,y)

```

1  #include <stdio.h>
2  #include <string.h>
3  #include <stdlib.h>
4  int p,expp,A,B,aa,ans,tt;
5  long long M;
6  long long exp(int a,int b,long long mod)
7  {
8      long long ans=1,num=a;
9      while (b!=0)
10     {
11         if (b&1)
12         {
13             ans=((ans%mod)*(num%mod))%mod;
14         }
15         num=((num%mod)*(num%mod))%mod;
16         b>>=1;
17     }
18     return ans;
19 }
20 int calcu(int p,int &x,int &y)
21 {
22     if (p%4!=1) return -1;
23     else
24     {
25         exp=(p-1)/4;
26         A,B;
27         while (1)
28         {
29             aa=rand()%p;
30             if (aa==0) continue;
31             A=exp(aa,exp,p);
32             ans=((long long)A%p)*((long long)A%p)%p;
33             if (ans==p-1) break;
34         }
35         B=1;
36         M=((long long)A*(long long)A+(long long)B*(long
37             long)B)/p;
38         if (M!=1) B=p;
39         while (M!=1)
40         {
41             if (B>A)
42             {tt=A; A=B; B=tt;}
43             tt=A;
44             A=B;

```

```

44         B=tt%B;
45         M=((long long)A*(long long)A+(long long)B*(
            long long)B)/p;
46     }
47     if (B<=A)
48     {
49         x=B;
50         y=A;
51     }
52     else
53     {
54         x=A;
55         y=B;
56     }
57 }
58 }
59 int main()
60 {
61     while (scanf("%d",&p)!=EOF)
62     {
63         int x,y;
64         if (calcu(p,x,y)!=-1)
65         }
66         return 0;
67 }

```

4.16 自适应simp

过了哈尔滨积分题，精度要求不高的时候可以考虑使用。
暂时我只能用这个做做类似于凸函数或者凹函数的函数。

```

1 double Simp(double l,double r)
2 {
3     double h = (r-l)/2.0;
4     return h*(calc(l)+4*calc((l+r)/2.0)+calc(r))/3.0;
5 }
6
7 double rSimp(double l,double r)
8 {
9     double mid = (l+r)/2.0;
10    if (abs((Simp(l,r)-Simp(l,mid)-Simp(mid,r)))/15 < eps)
11        return Simp(l,r);
12    else
13        return rSimp(l,mid)+rSimp(mid,r);
14 }

```

4.17 组合数求模

模是质数

```

1 #include<cstdio>
2 #include<cstring>
3 #include<iostream>

```

```

4 using namespace std;
5 int mod;
6 long long num[100000];
7 int ni[100],mi[100];
8 int len;
9 void init(int p)
10 {
11     mod=p;
12     num[0]=1;
13     for (int i=1; i<p; i++)
14         num[i]=i*num[i-1]%p;
15 }
16 void get(int n,int ni[],int p)
17 {
18     for (int i = 0; i < 100; i++)
19         ni[i] = 0;
20     int tlen = 0;
21     while (n != 0)
22     {
23         ni[tlen++] = n%p;
24         n /= p;
25     }
26     len = tlen;
27 }
28 long long power(long long x,long long y)
29 {
30     long long ret=1;
31     for (long long a=x%mod; y; y>>=1,a=a*a%mod)
32         if (y&1)
33             ret=ret*a%mod;
34     return ret;
35 }
36 long long getInv(long long x)//mod为素数
37 {
38     return power(x,mod-2);
39 }
40 long long calc(int n,int m,int p)// $C(n,m)\%p$ 
41 {
42     init(p);
43     long long ans=1;
44     for (; n && m && ans; n/=p,m/=p)
45     {
46         if (n%p>=m%p)
47             ans = ans*num[n%p]%p*getInv(num[m%p]%p)%p*getInv(num[
48                 n%p-m%p])%p;
49         else
50             ans=0;
51     }
52     return ans;
53 }
54 int main()
55 {

```

```

55     int t;
56     scanf("%d",&t);
57     while (t--)
58     {
59         int n,m,p;
60         scanf("%d%d%d",&n,&m,&p);
61         printf("%I64d\n",calc(n+m,m,p));
62     }
63     return 0;
64 }

```

4.18 其它公式

4.18.1 拉格朗日插值法

已知 $y = a_0 + a_1x + a_2x^2 + \cdots + a_{n-1}x^{n-1}$ 曲线上的 n 个点 $(x_1, y_1), (x_2, y_2), (x_3, y_3) \cdots (x_n, y_n)$ 用拉格朗日插值法可以不求系数可知任意 x 对应的 y 值。

$$\begin{aligned}
 y = & y_1 \frac{(x-x_2)(x-x_3) \cdots (x-x_n)}{(x_1-x_2)(x_1-x_3) \cdots (x_1-x_n)} \\
 & + y_2 \frac{(x-x_1)(x-x_3) \cdots (x-x_n)}{(x_2-x_1)(x_2-x_3) \cdots (x_2-x_n)} \\
 & + \cdots \\
 & + y_n \frac{(x-x_1)(x-x_2) \cdots (x-x_{n-1})}{(x_n-x_1)(x_n-x_2) \cdots (x_n-x_{n-1})}
 \end{aligned}$$

特别的，如果 $x_1 \sim x_n$ 为连续自然数，那么对于下一个自然数对应的 y 值为：

$$y_{n+1} = (-1)^{n-1}C_n^0y_1 + (-1)^{n-2}C_n^1y_2 + \cdots + (-1)^0C_n^{n-1}y_n$$

这个组合系数可以通过高斯消元求出来，前提是要猜到它满足递推关系。

4.18.2 正多面体顶点着色

正四面体： $N = \frac{(n^4+11 \times n^2)}{12}$

正六面体： $N = \frac{(n^8+17 \times n^4+6 \times n^2)}{24}$

正八面体： $N = \frac{(n^6+3 \times n^4+12 \times n^3+8 \times n^2)}{24}$

正十二面体： $N = \frac{(n^{20}+15 \times n^{10}+20 \times n^8+24 \times n^4)}{60}$

正二十面体： $N = \frac{(n^{12}+15 \times n^6+44 \times n^4)}{60}$

4.18.3 求和公式

$$\sum k = \frac{n \times (n+1)}{2}$$

$$\sum 2k - 1 = n^2$$

$$\sum k^2 = \frac{n \times (n+1) \times (2n+1)}{6}$$

$$\sum (2k-1)^2 = \frac{n \times (4n^2-1)}{3}$$

$$\sum k^3 = \left(\frac{n \times (n+1)}{2}\right)^2$$

$$\sum (2k-1)^3 = n^2 \times (2n^2-1)$$

$$\sum k^4 = \frac{n \times (n+1) \times (2n+1) \times (3n^2+3n-1)}{30}$$

$$\sum k^5 = \frac{n^2 \times (n+1)^2 \times (2n^2+2n-1)}{12}$$

$$\begin{aligned}\sum k \times (k+1) &= \frac{n \times (n+1) \times (n+2)}{3} \\ \sum k \times (k+1) \times (k+2) &= \frac{n \times (n+1) \times (n+2) \times (n+3)}{4} \\ \sum k \times (k+1) \times (k+2) \times (k+3) &= \frac{n \times (n+1) \times (n+2) \times (n+3) \times (n+4)}{5}\end{aligned}$$

4.18.4 几何公式

球扇形:

全面积: $T = \pi r(2h + r_0)$, h 为球冠高, r_0 为球冠底面半径

体积: $V = \frac{2\pi r^2 h}{3}$

4.18.5 小公式

Pick 公式: $A = E \times 0.5 + I - 1$ (A 是多边形面积, E 是边界上的整点, I 是多边形内部的整点)

海伦公式: $S = \sqrt{p(p-a)(p-b)(p-c)}$, 其中 $p = \frac{(a+b+c)}{2}$, abc 为三角形的三条边长

求 $\binom{n}{k}$ 中素因子 P 的个数:

1. 把 n 转化为 P 进制, 并记它每个位上的和为 $S1$

2. 把 $n - k$, k 做同样的处理, 得到 $S2$, $S3$

则 $\binom{n}{k}$ 中素因子 P 的个数: $\frac{S2+S3-S1}{P-1}$

部分错排公式:

$n + m$ 个数中 m 个数必须错排 求排列数

```
1 | dp[i] = n*dp[i-1] + (i-1)*(dp[i-1] + dp[i-2]);
2 | dp[0] = n!;
3 | dp[1] = n*n!;
```

$dp[m]$ 为所求解

5 数据结构

5.1 *Splay

持续学习中。

注意节点的size值不一定是真实的值！如果有需要需要特别维护！

1. 旋转和Splay操作
2. rank操作
3. insert操作（。。很多题目都有）
4. del操作（郁闷的出纳员）
5. 由数组建立Splay
6. 前驱后继（营业额统计）
7. Pushdown Pushup的位置
8. *。。。暂时想不起了

节点定义。。

```
1 | const int MaxN = 50003;
2 |
3 | struct Node
4 | {
5 |     int size, key;
6 |
7 |     Node *c[2];
8 |     Node *p;
9 | } mem[MaxN], *cur, *nil;
```

无内存池的几个初始化函数。

```
1 | Node *newNode(int v, Node *p)
2 | {
3 |     cur->c[0] = cur->c[1] = nil, cur->p = p;
4 |     cur->size = 1;
5 |     cur->key = v;
6 |     return cur++;
7 | }
8 |
9 | void Init()
10 | {
11 |     cur = mem;
12 |     nil = newNode(0, cur);
13 |     nil->size = 0;
14 | }
```

带内存池的几个函数。

```

1 int emp[MaxN], totemp;
2
3 Node *newNode(int v, Node *p)
4 {
5     cur = mem + emp[--totemp];
6     cur->c[0] = cur->c[1] = nil, cur->p = p;
7     cur->size = 1;
8     cur->key = v;
9     return cur;
10 }
11
12 void Init()
13 {
14     for (int i = 0; i < MaxN; ++i)
15         emp[i] = i;
16     totemp = MaxN;
17     cur = mem + emp[--totemp];
18     nil = newNode(0, cur);
19     nil->size = 0;
20 }
21
22 void Recycle(Node *p)
23 {
24     if (p == nil) return;
25     Recycle(p->c[0]), Recycle(p->c[1]);
26     emp[totemp++] = p - mem;
27 }

```

基本的Splay框架。维护序列用。
一切下标从0开始。

```

1 struct SplayTree
2 {
3     Node *root;
4     void Init()
5     {
6         root = nil;
7     }
8     void Pushup(Node *x)
9     {
10         if (x == nil) return;
11         Pushdown(x); Pushdown(x->c[0]); Pushdown(x->c[1]);
12         x->size = x->c[0]->size + x->c[1]->size + 1;
13     }
14     void Pushdown(Node *x)
15     {
16         if (x == nil) return;
17         //do something
18     }
19     void Rotate(Node *x, int f)
20     {
21         if (x == nil) return;

```

```

22     Node *y = x->p;
23     y->c[f ^ 1] = x->c[f], x->p = y->p;
24     if (x->c[f] != nil)
25         x->c[f]->p = y;
26     if (y->p != nil)
27         y->p->c[y->p->c[1] == y] = x;
28     x->c[f] = y, y->p = x;
29     Pushup(y);
30 }
31 void Splay(Node *x, Node *f)
32 {
33     while (x->p != f)
34     {
35         Node *y = x->p;
36         if (y->p == f)
37             Rotate(x, x == y->c[0]);
38         else
39         {
40             int fd = y->p->c[0] == y;
41             if (y->c[fd] == x)
42                 Rotate(x, fd ^ 1), Rotate(x, fd);
43             else
44                 Rotate(y, fd), Rotate(x, fd);
45         }
46     }
47     Pushup(x);
48     if (f == nil)
49         root = x;
50 }
51 void Select(int k, Node *f)
52 {
53     Node *x = root;
54     Pushdown(x);
55     int tmp;
56     while ((tmp = x->c[0]->size) != k)
57     {
58         if (k < tmp)    x = x->c[0];
59         else
60             x = x->c[1], k -= tmp + 1;
61         Pushdown(x);
62     }
63     Splay(x, f);
64 }
65 void Select(int l, int r)
66 {
67     Select(l, nil), Select(r + 2, root);
68 }
69 Node *Make_tree(int a[], int l, int r, Node *p)
70 {
71     if (l > r)    return nil;
72     int mid = l + r >> 1;
73     Node *x = newNode(a[mid], p);

```

```

74         x->c[0] = Make_tree(a, l, mid - 1, x);
75         x->c[1] = Make_tree(a, mid + 1, r, x);
76         Pushup(x);
77         return x;
78     }
79     void Insert(int pos, int a[], int n)
80     {
81         Select(pos, nil), Select(pos + 1, root);
82         root->c[1]->c[0] = Make_tree(a, 0, n - 1, root->c[1]);
83         Splay(root->c[1]->c[0], nil);
84     }
85     void Insert(int v)
86     {
87         Node *x = root, *y = nil;
88         while (x != nil)
89         {
90             y = x;
91             y->size++;
92             x = x->c[v >= x->key];
93         }
94         y->c[v >= y->key] = x = newNode(v, y);
95         Splay(x, nil);
96     }
97     void Remove(int l, int r)
98     {
99         Select(l, r);
100         //Recycle(root->c[1]->c[0]);
101         root->c[1]->c[0] = nil;
102         Splay(root->c[1], nil);
103     }
104 };

```

例题：旋转区间赋值求和求最大子序列。

注意打上懒标记后立即Pushup。Pushup(root-c[1]-c[0]),Pushup(root-c[1]),Pushup(root);

```

1  void Pushup(Node *x)
2  {
3      if (x == nil) return;
4      Pushdown(x); Pushdown(x->c[0]); Pushdown(x->c[1]);
5      x->size = x->c[0]->size+x->c[1]->size+1;
6
7      x->sum = x->c[0]->sum+x->c[1]->sum+x->key;
8      x->lsum = max(x->c[0]->lsum, x->c[0]->sum+x->key+max(0, x->c[1]->lsum));
9      x->rsum = max(x->c[1]->rsum, x->c[1]->sum+x->key+max(0, x->c[0]->rsum));
10     x->maxsum = max(max(x->c[0]->maxsum, x->c[1]->maxsum), x->key+max(0, x->c[0]->rsum)+max(0, x->c[1]->lsum));
11 }
12 void Pushdown(Node *x)
13 {
14     if (x == nil) return;

```

```

15     if (x->rev)
16     {
17         x->rev = 0;
18         x->c[0]->rev ^= 1;
19         x->c[1]->rev ^= 1;
20         swap(x->c[0],x->c[1]);
21
22         swap(x->lsum,x->rsum);
23     }
24     if (x->same)
25     {
26         x->same = false;
27         x->key = x->lazy;
28         x->sum = x->key*x->size;
29         x->lsum = x->rsum = x->maxsum = max(x->key,x->sum);
30         x->c[0]->same = true, x->c[0]->lazy = x->key;
31         x->c[1]->same = true, x->c[1]->lazy = x->key;
32     }
33 }
34
35 int main()
36 {
37     int totcas;
38     scanf("%d",&totcas);
39     for (int cas = 1;cas <= totcas;cas++)
40     {
41         Init();
42         sp.Init();
43         nil->lsum = nil->rsum = nil->maxsum = -Inf;
44         sp.Insert(0);
45         sp.Insert(0);
46
47         int n,m;
48         scanf("%d%d",&n,&m);
49         for (int i = 0;i < n;i++)
50             scanf("%d",&a[i]);
51         sp.Insert(0,a,n);
52
53         for (int i = 0;i < m;i++)
54         {
55             int pos,tot,c;
56             scanf("%s",buf);
57             if (strcmp(buf,"MAKE-SAME") == 0)
58             {
59                 scanf("%d%d%d",&pos,&tot,&c);
60                 sp.Select(pos-1,pos+tot-2);
61                 sp.root->c[1]->c[0]->same = true;
62                 sp.root->c[1]->c[0]->lazy = c;
63                 sp.Pushup(sp.root->c[1]), sp.Pushup(sp.root);
64             }
65             else if (strcmp(buf,"INSERT") == 0)
66             {

```

```

67         scanf("%d%d",&pos,&tot);
68         for (int i = 0;i < tot;i++)
69             scanf("%d",&a[i]);
70         sp.Insert(pos,a,tot);
71     }
72     else if (strcmp(buf,"DELETE") == 0)
73     {
74         scanf("%d%d",&pos,&tot);
75         sp.Remove(pos-1,pos+tot-2);
76     }
77     else if (strcmp(buf,"REVERSE") == 0)
78     {
79         scanf("%d%d",&pos,&tot);
80         sp.Select(pos-1,pos+tot-2);
81         sp.root->c[1]->c[0]->rev ^= 1;
82         sp.Pushup(sp.root->c[1]), sp.Pushup(sp.root);
83     }
84     else if (strcmp(buf,"GET-SUM") == 0)
85     {
86         scanf("%d%d",&pos,&tot);
87         sp.Select(pos-1,pos+tot-2);
88         printf("%d\n",sp.root->c[1]->c[0]->sum);
89     }
90     else if (strcmp(buf,"MAX-SUM") == 0)
91     {
92         sp.Select(0,sp.root->size-3);
93         printf("%d\n",sp.root->c[1]->c[0]->maxsum);
94     }
95 }
96 }
97 return 0;
98 }

```

维护多个序列的时候，不需要建立很多Splay。只需要记录某个点在内存池中的绝对位置就可以了。

需要操作它所在的序列时直接Splay到nil。此时Splay的root所在的Splay就是这个序列了。新建序列的时候需要多加入两个额外节点。如果某个Splay只有两个节点了需要及时回收。

例题：Box（维护括号序列）

```

1  \\下面都是专用函数
2  \\判断x在不在f里面
3  bool Ancestor(Node *x,Node *f)
4  {
5      if (x == f) return true;
6      while (x->p != nil)
7      {
8          if (x->p == f) return true;
9          x = x->p;
10     }
11     return false;
12 }
13 \\把Splay v插入到pos后面，pos=nil时新开一个序列

```

```

14 void Insert(Node *pos, Node *v)
15 {
16     int pl;
17     if (pos == nil)
18     {
19         Init();
20         Insert(0), Insert(0);
21         pl = 0;
22     }
23     else
24     {
25         Splay(pos, nil);
26         pl = root->c[0]->size;
27     }
28     Select(pl, nil), Select(pl + 1, root);
29     root->c[1]->c[0] = v;
30     v->p = root->c[1];
31     Splay(v, nil);
32 }
33 \\把[l,r]转出来 (这里记录的是绝对位置)
34 void Select(Node *l, Node *r)
35 {
36     Splay(l, nil);
37     int pl = root->c[0]->size - 1;
38     Splay(r, nil);
39     int pr = root->c[0]->size - 1;
40     Select(pl, pr);
41 }
42 \\分离[l,r]
43 Node *Split(Node *l, Node *r)
44 {
45     Select(l, r);
46     Node *res = root->c[1]->c[0];
47     root->c[1]->c[0] = res->p = nil;
48     Splay(root->c[1], nil);
49     if (root->size == 2)
50     {
51         Recycle(root);
52         Init();
53     }
54     return res;
55 }
56
57 int main(int argc, char const *argv[])
58 {
59     freopen("P.in", "r", stdin);
60     bool first = true;
61     while (scanf("%d", &n) != EOF)
62     {
63         if (!first) puts("");
64         first = false;
65         Init();

```

```

66     for (int i = 0; i < n; i++)
67     {
68         \\建立独立的N个区间，记录绝对位置
69         sp.Init();
70         sp.Insert(0), sp.Insert(0);
71         sp.Insert(0,i+1),sp.Insert(1,i+1);
72         sp.Select(0, 0), l[i] = sp.root->c[1]->c[0];
73         sp.Select(1, 1), r[i] = sp.root->c[1]->c[0];
74     }
75     for (int i = 0; i < n; i++)
76     {
77         int f;
78         scanf("%d", &f);
79         if (f != 0)
80         {
81             \\把[l[i],r[i]]插入到l[f-1]后面
82             Node *pos = sp.Split(l[i], r[i]);
83             sp.Insert(l[f - 1], pos);
84         }
85     }
86     scanf("%d", &n);
87     for (int i = 0; i < n; i++)
88     {
89         scanf("%s", com);
90         if (com[0] == 'Q')
91         {
92             int pos;
93             scanf("%d", &pos);
94             \\求[l[pos-1],r[pos-1]]在哪个序列里面
95             sp.Splay(l[pos - 1], nil);
96             sp.Select(1, nil);
97             printf("%d\n", sp.root->key);
98         }
99         else
100         {
101             int u, v;
102             scanf("%d%d", &u, &v);
103             if (v == 0)
104                 sp.Insert(nil, sp.Split(l[u-1], r[u-1]));
105             else
106             {
107                 sp.Select(l[u-1], r[u-1]);
108                 if (sp.Ancestor(l[v-1], sp.root->c[1]->c[0])
109                     == false)
110                     sp.Insert(l[v - 1], sp.Split(l[u-1], r[u
111                         -1]));
112             }
113         }
114     }
115     return 0;
}

```


5.2 动态树

懒标记是否及时Pushdown了?
修改之后有没有及时Pushup?

5.2.1 维护点权

查询链上的最长字段和
GetRoute是用换根写的

```
1  const int MaxN = 110000;
2
3  struct Node
4  {
5      int size, key;
6      bool rev;
7
8      //    bool same;
9      //    int lsum, rsum, sum, maxsum, sa;
10
11     Node *c[2];
12     Node *p;
13 } mem[MaxN], *cur, *nil, *pos[MaxN];
14
15 Node *newNode(int v, Node *p)
16 {
17     cur->c[0] = cur->c[1] = nil, cur->p = p;
18     cur->size = 1;
19     cur->key = v;
20     cur->rev = false;
21
22     //    cur->same = false;
23     //    cur->sa = 0;
24     //    cur->lsum = cur->rsum = cur->maxsum = 0;
25     //    cur->sum = v;
26
27     return cur++;
28 }
29
30 void Init()
31 {
32     cur = mem;
33     nil = newNode(0, cur);
34     nil->size = 0;
35 }
36
37 struct SplayTree
38 {
39     void Pushup(Node *x)
40     {
41         if (x == nil)    return;
42         Pushdown(x); Pushdown(x->c[0]); Pushdown(x->c[1]);
```

```

43         x->size = x->c[0]->size + x->c[1]->size + 1;
44
45         //         x->sum = x->c[0]->sum + x->c[1]->sum + x->key;
46         //         x->lsum = max(x->c[0]->lsum, x->c[0]->sum + x->key +
max(0, x->c[1]->lsum));
47         //         x->rsum = max(x->c[1]->rsum, x->c[1]->sum + x->key +
max(0, x->c[0]->rsum));
48         //         x->maxsum = max(max(x->c[0]->maxsum, x->c[1]->maxsum),
49         //         x->key + max(0, x->c[0]->rsum) + max(0, x->c[1]->
lsum));
50
51     }
52     void Pushdown(Node *x)
53     {
54         if (x == nil)    return;
55         if (x->rev)
56         {
57             x->rev = 0;
58             x->c[0]->rev ^= 1;
59             x->c[1]->rev ^= 1;
60             swap(x->c[0], x->c[1]);
61         //注意修改与位置有关的量
62         //         swap(x->lsum, x->rsum);
63     }
64
65     //         if (x->same)
66     //         {
67     //             x->same = false;
68     //             x->key = x->sa;
69     //             x->sum = x->sa * x->size;
70     //             x->lsum = x->rsum = x->maxsum = max(0, x->sum);
71     //             if (x->c[0] != nil)
72     //                 x->c[0]->same = true, x->c[0]->sa = x->sa;
73     //             if (x->c[1] != nil)
74     //                 x->c[1]->same = true, x->c[1]->sa = x->sa;
75     //         }
76     }
77     bool isRoot(Node *x)
78     {
79         return (x == nil) || (x->p->c[0] != x && x->p->c[1] != x)
;
80     }
81     void Rotate(Node *x, int f)
82     {
83         if (isRoot(x))    return;
84         Node *y = x->p;
85         y->c[f ^ 1] = x->c[f], x->p = y->p;
86         if (x->c[f] != nil)
87             x->c[f]->p = y;
88         if (y != nil)
89         {
90             if (y == y->p->c[1])

```

```

91         y->p->c[1] = x;
92     else if (y == y->p->c[0])
93         y->p->c[0] = x;
94     }
95     x->c[f] = y, y->p = x;
96     Pushup(y);
97 }
98 void Splay(Node *x)
99 {
100     static Node *stack[MaxN];
101     int top = 0;
102     stack[top++] = x;
103     for (Node *y = x; !isRoot(y); y = y->p)
104         stack[top++] = y->p;
105     while (top)
106         Pushdown(stack[--top]);
107
108     while (!isRoot(x))
109     {
110         Node *y = x->p;
111         if (isRoot(y))
112             Rotate(x, x == y->c[0]);
113         else
114         {
115             int fd = y->p->c[0] == y;
116             if (y->c[fd] == x)
117                 Rotate(x, fd ^ 1), Rotate(x, fd);
118             else
119                 Rotate(y, fd), Rotate(x, fd);
120         }
121     }
122     Pushup(x);
123 }
124 Node *Access(Node *u)
125 {
126     Node *v = nil;
127     while (u != nil)
128     {
129         Splay(u);
130         v->p = u;
131         u->c[1] = v;
132         Pushup(u);
133         u = (v = u)->p;
134         if (u == nil)
135             return v;
136     }
137 }
138 Node *LCA(Node *u, Node *v)
139 {
140     Access(u);
141     return Access(v);
142 }

```

```

143     Node *Link(Node *u, Node *v)
144     {
145         Access(u);
146         Splay(u);
147         u->rev = true;
148         u->p = v;
149     }
150     void ChangeRoot(Node *u)
151     {
152         Access(u)->rev ^= 1;
153     }
154     Node *GetRoute(Node *u, Node *v)
155     {
156         ChangeRoot(u);
157         return Access(v);
158     }
159 };
160
161 int n, m;
162 SplayTree sp;
163
164 int main(int argc, char const *argv[])
165 {
166     while (scanf("%d", &n) != EOF)
167     {
168         Init();
169         for (int i = 0; i < n; i++)
170         {
171             int v;
172             scanf("%d", &v);
173             pos[i] = newNode(v, nil);
174         }
175         for (int i = 0; i < n - 1; i++)
176         {
177             int u, v;
178             scanf("%d%d", &u, &v);
179             u--, v--;
180             sp.Link(pos[u], pos[v]);
181         }
182
183         //         scanf("%d", &m);
184         //         for (int i = 0; i < m; i++)
185         //         {
186         //             int typ, u, v, c;
187         //             scanf("%d%d%d", &typ, &u, &v);
188         //             u--, v--;
189         //             if (typ == 1)
190         //                 printf("%d\n", sp.GetRoute(pos[u], pos[v])->
maxsum);
191         //             else
192         //                 {
193         //                     scanf("%d", &c);

```

```

194 //          Node *p = sp.GetRoute(pos[u], pos[v]);
195 //          p->same = true;
196 //          p->sa = c;
197 //      }
198 //  }
199 }
200 return 0;
201 }

```

5.2.2 维护边权

刘汝佳的Happy Painting!
 查询链上边的不同颜色数量
 不能换根，但是可以Link和Cut

```

1  const int MaxN = 60000;
2
3  struct Node
4  {
5      int size, key;
6
7      int msk, lazy;
8
9      Node *c[2];
10     Node *p;
11 } mem[MaxN], *cur, *nil, *pos[MaxN];
12
13 Node *newNode(int v, Node *p)
14 {
15     cur->c[0] = cur->c[1] = nil, cur->p = p;
16     cur->size = 1;
17     cur->key = v;
18
19     cur->msk = 0;
20     cur->lazy = -1;
21
22     return cur++;
23 }
24
25 void Init()
26 {
27     cur = mem;
28     nil = newNode(0, cur);
29     nil->size = 0;
30 }
31
32 struct SplayTree
33 {
34     void Pushup(Node *x)
35     {
36         if (x == nil) return;
37         Pushdown(x);

```

```

38     Pushdown(x->c[0]);
39     Pushdown(x->c[1]);
40     x->size = x->c[0]->size + x->c[1]->size + 1;
41
42     x->msk = x->c[0]->msk | x->c[1]->msk | (1<<x->key);
43 }
44 void Pushdown(Node *x)
45 {
46     if (x == nil) return;
47
48     if (x->lazy != -1)
49     {
50         x->key = x->lazy;
51         x->msk = (1<<x->key);
52         x->c[0]->lazy = x->c[1]->lazy = x->lazy;
53         x->lazy = -1;
54     }
55 }
56 bool isRoot(Node *x)
57 {
58     return (x == nil) || (x->p->c[0] != x && x->p->c[1] != x)
59     ;
60 }
61 void Rotate(Node *x, int f)
62 {
63     if (isRoot(x)) return;
64     Node *y = x->p;
65     y->c[f ^ 1] = x->c[f], x->p = y->p;
66     if (x->c[f] != nil)
67         x->c[f]->p = y;
68     if (y != nil)
69     {
70         if (y == y->p->c[1])
71             y->p->c[1] = x;
72         else if (y == y->p->c[0])
73             y->p->c[0] = x;
74     }
75     x->c[f] = y, y->p = x;
76     Pushup(y);
77 }
78 void Splay(Node *x)
79 {
80     static Node *stack[MaxN];
81     int top = 0;
82     stack[top++] = x;
83     for (Node *y = x; !isRoot(y); y = y->p)
84         stack[top++] = y->p;
85     while (top)
86         Pushdown(stack[--top]);
87
88     while (!isRoot(x))
89     {

```

```

89         Node *y = x->p;
90         if (isRoot(y))
91             Rotate(x, x == y->c[0]);
92         else
93         {
94             int fd = y->p->c[0] == y;
95             if (y->c[fd] == x)
96                 Rotate(x, fd ^ 1), Rotate(x, fd);
97             else
98                 Rotate(y, fd), Rotate(x, fd);
99         }
100     }
101     Pushup(x);
102 }
103 Node *Access(Node *u)
104 {
105     Node *v = nil;
106     while (u != nil)
107     {
108         Splay(u);
109         v->p = u;
110         u->c[1] = v;
111         Pushup(u);
112         u = (v = u)->p;
113         if (u == nil) return v;
114     }
115 }
116 Node *Root(Node *u)
117 {
118     Access(u);
119     Splay(u);
120     for (Pushdown(u); u->c[0] != nil; u = u->c[0])
121         Pushdown(u);
122     Splay(u);
123     return u;
124 }
125 Node *LCA(Node *u, Node *v)
126 {
127     if (Root(u) != Root(v))
128         return nil;
129     Access(u);
130     return Access(v);
131 }
132 void Cut(Node *u)
133 {
134     Access(u);
135     Splay(u);
136     u->c[0] = u->c[0]->p = nil;
137     Pushup(u);
138 }
139 void Link(Node *u, Node *v, int val)
140 {

```

```

141     Access(u);
142     Splay(u);
143     u->p = v;
144     u->key = val;
145     Pushup(u);
146 }
147 };
148
149 int cntbit(int x)
150 {
151     x = (x & 0x55555555) + ((x >> 1) & 0x55555555);
152     x = (x & 0x33333333) + ((x >> 2) & 0x33333333);
153     x = (x & 0x0F0F0F0F) + ((x >> 4) & 0x0F0F0F0F);
154     x = (x & 0x00FF00FF) + ((x >> 8) & 0x00FF00FF);
155     x = (x & 0x0000FFFF) + ((x >> 16) & 0x0000FFFF);
156     return x;
157 }
158
159 SplayTree sp;
160 int n,Q,f[MaxN];
161
162 int main(int argc, char const *argv[])
163 {
164     while (scanf("%d%d",&n,&Q) != EOF)
165     {
166         Init();
167         for (int i = 0; i < n; i++)
168         {
169             scanf("%d",&f[i]);
170             pos[i] = newNode(0, nil);
171         }
172         for (int i = 0; i < n; i++)
173         {
174             int col;
175             scanf("%d",&col);
176             if (f[i] > 0)
177                 sp.Link(pos[i],pos[f[i]-1],col-1);
178         }
179         for (int q = 0; q < Q; q++)
180         {
181             int typ,x,y,c;
182             scanf("%d%d%d",&typ,&x,&y);
183             x--,y--;
184             if (typ == 3)
185             {
186                 Node *lca = sp.LCA(pos[x],pos[y]);
187                 if (lca == nil || x == y)
188                 {
189                     printf("0_0\n");
190                     continue;
191                 }
192                 int totedge = lca->c[1]->size;

```



```

193         int msk = lca->c[1]->msk;
194
195         if (pos[x] != lca)
196         {
197             sp.Splay(pos[x]);
198             totedge += pos[x]->size;
199             msk |= pos[x]->msk;
200         }
201
202         printf("%d□%d\n", totedge, cntbit(msk));
203     }
204     else
205     {
206         scanf("%d",&c);
207         c--;
208         if (typ == 1)
209         {
210             if (x == y) continue;
211
212             Node *lca = sp.LCA(pos[x], pos[y]);
213             if (pos[x] == lca) continue;
214
215             sp.Cut(pos[x]);
216             sp.Link(pos[x], pos[y], c);
217
218         }
219         else
220         {
221             Node *lca = sp.LCA(pos[x], pos[y]);
222
223             if (lca == nil || x == y)
224                 continue;
225
226             lca->c[1]->lazy = c;
227             sp.Pushup(lca->c[1]);
228             sp.Pushup(lca);
229             if (pos[x] != lca)
230             {
231                 sp.Splay(pos[x]);
232                 pos[x]->lazy = c;
233                 sp.Pushup(pos[x]);
234             }
235         }
236     }
237 }
238 }
239 return 0;
240 }

```

5.3 可持久化线段树

区间第 k 小数，内存压缩版，POJ2014。

```

1  #include <cstdio>
2  #include <algorithm>
3  using namespace std;
4
5  const int MAXN=100000,MAXM=100000;
6
7  struct node
8  {
9      node *l,*r;
10     int sum;
11 }tree[MAXN*4+MAXM*20];
12
13 int N;
14 node *newnode()
15 {
16     tree[N].l=tree[N].r=NULL;
17     tree[N].sum=0;
18     return &tree[N++];
19 }
20 node *newnode(node *x)
21 {
22     tree[N].l=x->l;
23     tree[N].r=x->r;
24     tree[N].sum=x->sum;
25     return &tree[N++];
26 }
27 node *build(int l,int r)
28 {
29     node *x=newnode();
30     if (l<r)
31     {
32         int mid=l+r>>1;
33         x->l=build(l,mid);
34         x->r=build(mid+1,r);
35         x->sum=x->l->sum+x->r->sum;
36     }
37     else
38         x->sum=0;
39     return x;
40 }
41 node *update(node *x,int l,int r,int p,int v)
42 {
43     if (l<r)
44     {
45         int mid=l+r>>1;
46         node *nx=newnode(x);
47         if (p<=mid)
48         {
49             node *ret=update(x->l,l,mid,p,v);
50             nx->l=ret;
51         }
52         else

```

```

53     {
54         node *ret=update(x->r,mid+1,r,p,v);
55         nx->r=ret;
56     }
57     nx->sum=nx->l->sum+nx->r->sum;
58     return nx;
59 }
60 else
61 {
62     node *nx=newnode(x);
63     nx->sum+=v;
64     return nx;
65 }
66 }
67 int query(node *x1,node *x2,int l,int r,int k)
68 {
69     if (l<r)
70     {
71         int mid=l+r>>1;
72         int lsum=x2->l->sum-x1->l->sum;
73         if (lsum>=k)
74             return query(x1->l,x2->l,l,mid,k);
75         else
76             return query(x1->r,x2->r,mid+1,r,k-lsum);
77     }
78     else
79         return l;
80 }
81 char s[10];
82 node *root[MAXM+1];
83 int a[MAXN],b[MAXN];
84 int init(int n)
85 {
86     for (int i=0;i<n;i++)
87         b[i]=a[i];
88     sort(b,b+n);
89     int tn=unique(b,b+n)-b;
90     for (int i=0;i<n;i++)
91     {
92         int l=0,r=tn-1;
93         while (l<r)
94         {
95             int mid=l+r>>1;
96             if (b[mid]>=a[i])
97                 r=mid;
98             else
99                 l=mid+1;
100         }
101         a[i]=l;
102     }
103     return tn;
104 }

```

```

105 int main()
106 {
107     int cas=1,n;
108     while (scanf("%d",&n)!=EOF)
109     {
110         printf("Case_□%d:\n",cas++);
111         for (int i=0;i<n;i++)
112             scanf("%d",&a[i]);
113         int tn=init(n);
114         N=0;
115         root[0]=build(0,tn-1);
116         for (int i=1;i<=n;i++)
117             root[i]=update(root[i-1],0,tn-1,a[i-1],1);
118         int m;
119         scanf("%d",&m);
120         for (int i=0;i<m;i++)
121         {
122             int s,t;
123             scanf("%d%d",&s,&t);
124             printf("%d\n",b[query(root[s-1],root[t],0,tn-1,t-s
125                 +2>>1)]);
126         }
127     }
128     return 0;
129 }

```

5.4 treap正式版

支持翻转。

```

1 #include <cstdio>
2 #include <cstdlib>
3 #include <algorithm>
4 using namespace std;
5
6 const int MAXN = 100000;
7 const int MAXM = 100000;
8 const int inf = 0x7fffffff;
9 int a[MAXN];
10 struct Treap
11 {
12     int N;
13     Treap()
14     {
15         N = 0;
16         root = NULL;
17     }
18     void init()
19     {
20         N = 0;
21         root = NULL;
22     }
23     struct Treap_Node

```

```

24 {
25     Treap_Node *son[2]; //left & right
26     int value, fix;
27     bool lazy;
28     int size;
29     Treap_Node() {}
30     Treap_Node(int _value)
31     {
32         son[0] = son[1] = NULL;
33         value = _value;
34         fix = rand() * rand();
35         lazy = 0;
36         size = 1;
37     }
38     int sonSize(bool flag)
39     {
40         if (son[flag] == NULL)
41             return 0;
42         else
43             return son[flag]->size;
44     }
45 } node[MAXN], *root, *pos[MAXN];
46 void up(Treap_Node *p)
47 {
48     p->size = p->sonSize(0) + p->sonSize(1) + 1;
49 }
50 void down(Treap_Node *p)
51 {
52     if (!p->lazy)
53         return ;
54     for (int i = 0; i < 2; i++)
55         if (p->son[i])
56             p->son[i]->lazy = !p->son[i]->lazy;
57     swap(p->son[0], p->son[1]);
58     p->lazy = 0;
59 }
60 Treap_Node *merge(Treap_Node *p, Treap_Node *q)
61 {
62     if (p == NULL)
63         return q;
64     else if (q == NULL)
65         return p;
66     if (p->fix <= q->fix)
67     {
68         down(p);
69         p->son[1] = merge(p->son[1], q);
70         up(p);
71         return p;
72     }
73     else
74     {
75         down(q);

```

```

76         q->son[0] = merge(p, q->son[0]);
77         up(q);
78         return q;
79     }
80 }
81 pair<Treap_Node *, Treap_Node *> split(Treap_Node *p, int n)
82 {
83     if (p == NULL)
84         return make_pair((Treap_Node *)NULL, (Treap_Node *)
85             NULL);
86     if (!n)
87         return make_pair((Treap_Node *)NULL, p);
88     if (n == p->size)
89         return make_pair(p, (Treap_Node *)NULL);
90     down(p);
91     if (p->sonSize(0) >= n)
92     {
93         pair<Treap_Node *, Treap_Node *> ret = split(p->son
94             [0], n);
95         p->son[0] = ret.second;
96         up(p);
97         return make_pair(ret.first, p);
98     }
99     else
100     {
101         pair<Treap_Node *, Treap_Node *> ret = split(p->son
102             [1], n - p->sonSize(0) - 1);
103         p->son[1] = ret.first;
104         up(p);
105         return make_pair(p, ret.second);
106     }
107 }
108 int smalls(Treap_Node *p, int value)
109 {
110     if (p==NULL)
111         return 0;
112     if (p->value<=value)
113         return 1+p->sonSize(0)+smalls(p->son[1], value);
114     else
115         return smalls(p->son[0], value);
116 }
117 void insert(int value)
118 {
119     Treap_Node *p = &node[N++];
120     *p = Treap_Node(value);
121     pair<Treap_Node *, Treap_Node *> ret = split(root, smalls
122         (root, value));
123     root = merge(merge(ret.first, p), ret.second);
124 }
125 void remove(int value)
126 {

```

```

123     pair<Treap_Node *, Treap_Node *> ret = split(root, smalls
        (root, value) - 1);
124     root = merge(ret.first, split(ret.second, 1).second);
125 }
126 Treap_Node *build(int s, int t)
127 {
128     int idx = t + s >> 1;
129     Treap_Node *p = &node[N++];
130     *p = Treap_Node(a[idx]);
131     pos[a[idx]] = p;
132     if (idx > s)
133         p = merge(build(s, idx - 1), p);
134     if (idx < t)
135         p = merge(p, build(idx + 1, t));
136     up(p);
137     return p;
138 }
139 void build(int n)
140 {
141     root = build(0, n - 1);
142 }
143 void *reverse(int s, int t)
144 {
145     pair<Treap_Node *, Treap_Node *> tmp1, tmp2;
146     tmp1 = split(root, s - 1);
147     tmp2 = split(tmp1.second, t - s + 1);
148     tmp2.first->lazy = !tmp2.first->lazy;
149     root = merge(tmp1.first, merge(tmp2.first, tmp2.second));
150 }
151 };
152 Treap treap;
153 int main()
154 {
155     treap.init();
156     int n;
157     scanf("%d", &n);
158     for (int i = 0; i < n; i++)
159         scanf("%d", &a[i]);
160     treap.build(n);
161 }

```

5.5 树链剖分

5.5.1 点权

```

1 #include <cstdio>
2 #include <cstring>
3 #include <cstdlib>
4 #include <algorithm>
5 using namespace std;
6 const int MAX = 12000;
7 const int LOG = 15;

```

```

8  const int oo = 0x3f3f3f3f;
9  struct Edge
10 {
11     int to, w, id;
12     Edge* next;
13 } memo[MAX << 1], *cur, *g[MAX], *pree[MAX], *solid[MAX], *valid[
    MAX];
14 int dp[MAX][LOG], pos[MAX], lst[MAX], dep[MAX], cnt[MAX], h[MAX],
    K, n;
15 void init()
16 {
17     for (int i = 1; i <= n; i++)
18     {
19         g[i] = NULL;
20         valid[i] = NULL;
21         solid[i] = NULL;
22         pree[i] = NULL;
23     }
24     for (int i = 0; i < LOG; i++)
25     {
26         dp[1][i] = 1;
27     }
28     cur = memo;
29     K = 0;
30 }
31 void add(int u, int v, int w, int id)
32 {
33     cur->to = v;
34     cur->w = w;
35     cur->id = id;
36     cur->next = g[u];
37     g[u] = cur++;
38 }
39 void dfsLCA(int d, int u, int f)
40 {
41     dep[u] = d;
42     dp[u][0] = f;
43     cnt[u] = 1;
44     for (int i = 1; i < LOG; i++)
45     {
46         dp[u][i] = dp[dp[u][i - 1]][i - 1];
47     }
48     for (Edge* it = g[u]; it; it = it->next)
49     {
50         int v = it->to;
51         if (v != f)
52         {
53             pree[v] = it;
54             valid[it->id] = it;
55             dfsLCA(d + 1, v, u); //RE
56             cnt[u] += cnt[v];
57             if (solid[u] == NULL || cnt[solid[u]->to] < cnt[v])

```



```

58         {
59             solid[u] = it;
60         }
61     }
62 }
63 }
64 void dfsChain(int u, int head)
65 {
66     h[u] = head;
67     if (solid[u])
68     {
69         lst[pos[u] = K++] = u;
70         dfsChain(solid[u]->to, head);
71     }
72     else
73     for (Edge* it = g[u]; it; it = it->next)
74     {
75         int v = it->to;
76         if (it != solid[u] && v != dp[u][0])
77         {
78             dfsChain(v, v);
79         }
80     }
81 }
82 int getLCA(int u, int v)
83 {
84     if (dep[u] < dep[v])
85         swap(u, v);
86     for (int st = 1 << (LOG - 1), i = LOG - 1; i >= 0; i--, st
87         >>= 1)
88     {
89         if (st <= dep[u] - dep[v])
90         {
91             u = dp[u][i];
92         }
93     }
94     if (u == v)
95         return u;
96     for (int i = LOG - 1; i >= 0; i--)
97     {
98         if (dp[u][i] != dp[v][i])
99         {
100             u = dp[u][i];
101             v = dp[v][i];
102         }
103     }
104     return dp[u][0];
105 }
106 struct Node
107 {
108     int l, r, ma, mi;
109     bool rev;

```

```

109 } seg[MAX << 2];
110 void reverse(int k)
111 {
112     seg[k].mi *= -1;
113     seg[k].ma *= -1;
114     seg[k].rev ^= 1;
115     swap(seg[k].mi, seg[k].ma);
116 }
117 void pushdown(int k)
118 {
119     if (seg[k].rev)
120     {
121         reverse(k << 1);
122         reverse(k << 1 | 1);
123         seg[k].rev = false;
124     }
125 }
126 void update(int k)
127 {
128     seg[k].mi = min(seg[k << 1].mi, seg[k << 1 | 1].mi);
129     seg[k].ma = max(seg[k << 1].ma, seg[k << 1 | 1].ma);
130 }
131 void init(int k, int l, int r)
132 {
133     seg[k].l = l;
134     seg[k].r = r;
135     seg[k].rev = false;
136     if (l == r)
137     {
138         seg[k].mi = seg[k].ma = solid[lst[l]]->w; //solid WA
139         return;
140     }
141     int mid = l + r >> 1;
142     init(k << 1, l, mid);
143     init(k << 1 | 1, mid + 1, r);
144     update(k);
145 }
146 void update(int k, int id, int v)
147 {
148     if (seg[k].l == seg[k].r)
149     {
150         seg[k].mi = seg[k].ma = solid[lst[id]]->w = v;
151         return;
152     }
153     pushdown(k);
154     int mid = seg[k].l + seg[k].r >> 1;
155     if (id <= mid)
156         update(k << 1, id, v);
157     else
158         update(k << 1 | 1, id, v);
159     update(k);
160 }

```

```

161 void reverse(int k, int l, int r)
162 {
163     if (seg[k].l > r || seg[k].r < l)
164         return;
165     if (seg[k].l >= l && seg[k].r <= r)
166     {
167         reverse(k);
168         return;
169     }
170     pushdown(k);
171     reverse(k << 1, l, r);
172     reverse(k << 1 | 1, l, r);
173     update(k);
174 }
175 int read(int k, int l, int r)
176 {
177     if (seg[k].l > r || seg[k].r < l)
178         return -oo;
179     if (seg[k].l >= l && seg[k].r <= r)
180         return seg[k].ma;
181     pushdown(k);
182     return max(read(k << 1, l, r), read(k << 1 | 1, l, r));
183 }
184 void setEdge(int id, int v)
185 {
186     Edge* it = valid[id];
187     if (h[it->to] != it->to)
188     {
189         update(1, pos[dp[it->to][0]], v);
190     }
191     else
192     {
193         it->w = v;
194     }
195 }
196 void negateLCA(int t, int u)
197 {
198     while (t != u)
199     {
200         int tmp = h[u];
201         if (dep[tmp] < dep[t])
202             tmp = t;
203         if (h[u] == u)
204         {
205             pree[u]->w *= -1;
206             u = dp[u][0];
207         }
208         else
209         {
210             reverse(1, pos[tmp], pos[dp[u][0]]);
211             u = tmp;
212         }

```

```

213     }
214 }
215 void negate(int u, int v)
216 {
217     int t = getLCA(u, v);
218     negateLCA(t, u);
219     negateLCA(t, v);
220 }
221 int maxLCA(int t, int u)
222 {
223     int ret = -oo;
224     while (t != u)
225     {
226         int tmp = h[u];
227         if (dep[tmp] < dep[t])
228             tmp = t;
229         if (h[u] == u)
230         {
231             ret = max(ret, pree[u]->w);
232             u = dp[u][0];
233         }
234         else
235         {
236             ret = max(ret, read(1, pos[tmp], pos[dp[u][0]]));
237             u = tmp;
238         }
239     }
240     return ret;
241 }
242 int query(int u, int v)
243 {
244     int t = getLCA(u, v);
245     return max(maxLCA(t, u), maxLCA(t, v));
246 }
247 int main()
248 {
249     int T;
250     int u, v, w;
251     char op[15];
252     scanf("%d", &T);
253     while (T--)
254     {
255         scanf("%d", &n);
256         init();
257         for (int i = 1; i < n; i++)
258         {
259             scanf("%d%d%d", &u, &v, &w);
260             add(u, v, w, i);
261             add(v, u, w, i);
262         }
263         dfsLCA(0, 1, 1);
264         dfsChain(1, 1);

```

```

265         init(1, 0, K - 1);
266         while (scanf("%s", op), op[0] != 'D')
267         {
268             scanf("%d%d", &u, &v);
269             if (op[0] == 'C')
270             {
271                 setEdge(u, v);
272             }
273             else if (op[0] == 'N')
274             {
275                 negate(u, v);
276             }
277             else
278             {
279                 printf("%d\n", query(u, v));
280             }
281         }
282     }
283     return 0;
284 }

```

5.5.2 边权

```

1  #include <cstdio>
2  #include <iostream>
3  #include <cstdlib>
4  #include <algorithm>
5  #include <cmath>
6  #include <cstring>
7  using namespace std;
8  int n,m,sum,pos;
9  int head[50005],e;
10 int s[50005],from[50005];
11 int fa[50005][20],deep[50005],num[50005];
12 int solid[50005],p[50005],fp[50005];
13 struct N
14 {
15     int l,r,mid;
16     int add,w;
17 }nod[50005*4];
18 struct M
19 {
20     int v,next;
21 }edge[100005];
22 void addedge(int u,int v)
23 {
24     edge[e].v=v;
25     edge[e].next=head[u];
26     head[u]=e++;
27
28     edge[e].v=u;
29     edge[e].next=head[v];
30     head[v]=e++;

```

```

31 }
32 void LCA(int st,int f,int d)
33 {
34     deep[st]=d;
35     fa[st][0]=f;
36     num[st]=1;
37     int i,v;
38     for(i=1;i<20;i++)
39         fa[st][i]=fa[fa[st][i-1]][i-1];
40     for(i=head[st];i!=-1;i=edge[i].next)
41     {
42         v=edge[i].v;
43         if(v!=f)
44         {
45             LCA(v,st,d+1);
46             num[st]+=num[v];
47             if(solid[st]==-1||num[v]>num[solid[st]])
48                 solid[st]=v;
49         }
50     }
51 }
52 void getpos(int st,int sp)
53 {
54     from[st]=sp;
55     if(solid[st]!=-1)
56     {
57         p[st]=pos++;
58         fp[p[st]]=st;
59         getpos(solid[st],sp);
60     }
61     else
62     {
63         p[st]=pos++;
64         fp[p[st]]=st;
65         return;
66     }
67     int i,v;
68     for(i=head[st];i!=-1;i=edge[i].next)
69     {
70         v=edge[i].v;
71         if(v!=solid[st]&&v!=fa[st][0])
72             getpos(v,v);
73     }
74 }
75 int getLCA(int u,int v)
76 {
77     if(deep[u]<deep[v])
78         swap(u,v);
79     int d=1<<19,i;
80     for(i=19;i>=0;i--)
81     {
82         if(d<=deep[u]-deep[v])

```

```

83     u=fa[u][i];
84     d>>=1;
85 }
86 if(u==v)
87     return u;
88 for(i=19;i>=0;i--)
89     if(fa[u][i]!=fa[v][i])
90     {
91         u=fa[u][i];
92         v=fa[v][i];
93     }
94     return fa[u][0];
95 }
96 void init(int p,int l,int r)
97 {
98     nod[p].l=l;
99     nod[p].r=r;
100    nod[p].mid=(l+r)>>1;
101    nod[p].add=0;
102    if(l==r)
103        nod[p].w=s[fp[l]];
104    else
105    {
106        init(p<<1,l,nod[p].mid);
107        init(p<<1|1,nod[p].mid+1,r);
108    }
109 }
110 void lazy(int p)
111 {
112     if(nod[p].add!=0)
113     {
114         nod[p<<1].add+=nod[p].add;
115         nod[p<<1|1].add+=nod[p].add;
116         nod[p].add=0;
117     }
118 }
119 void update(int p,int l,int r,int v)
120 {
121     if(nod[p].l==l&&nod[p].r==r)
122     {
123         nod[p].add+=v;
124         return;
125     }
126     lazy(p);
127     if(nod[p].mid<l)
128         update(p<<1|1,l,r,v);
129     else if(nod[p].mid>=r)
130         update(p<<1,l,r,v);
131     else
132     {
133         update(p<<1,l,nod[p].mid,v);
134         update(p<<1|1,nod[p].mid+1,r,v);

```

```

135     }
136 }
137 int read(int p,int l,int r)
138 {
139     if(nod[p].l==l&&nod[p].r==r)
140         return nod[p].w+nod[p].add;
141     lazy(p);
142     if(nod[p].mid<l)
143         return read(p<<1|1,l,r);
144     else if(nod[p].mid>=r)
145         return read(p<<1,l,r);
146 }
147 void jump(int st,int ed,int val)
148 {
149     while(deep[st]>=deep[ed])
150     {
151         int tmp=from[st];
152         if(deep[tmp]<deep[ed])
153             tmp=ed;
154         update(1,p[tmp],p[st],val);
155         st=fa[tmp][0];
156     }
157 }
158 void change(int st,int ed,int val)
159 {
160     int lca=getLCA(st,ed);
161     jump(st,lca,val);
162     jump(ed,lca,val);
163     jump(lca,lca,-val);
164 }
165 int main()
166 {
167     while(scanf("%d%d%d",&n,&m,&sum)==3)
168     {
169         int i;
170         s[0]=0;pos=0;deep[0]=-1;
171         memset(fa,0,sizeof(fa));
172         for(i=1;i<=n;i++)
173         {
174             solid[i]=-1;
175             scanf("%d",&s[i]);
176         }
177         memset(head,-1,sizeof(head));
178         e=0;
179         for(i=0;i<m;i++)
180         {
181             int a,b;
182             scanf("%d%d",&a,&b);
183             addedge(a,b);
184         }
185         LCA(1,0,0);
186         getpos(1,1);

```



```

187     init(1,0,pos-1);
188     for(i=0;i<sum;i++)
189     {
190         char que[5];
191         scanf("%s",que);
192         if(que[0]!='Q')
193         {
194             int a,b,c;
195             scanf("%d%d%d",&a,&b,&c);
196             if(que[0]=='D')
197                 c=-c;
198             change(a,b,c);
199         }
200         else
201         {
202             int a;
203             scanf("%d",&a);
204             printf("%d\n",read(1,p[a],p[a]));
205         }
206     }
207 }
208 return 0;
209 }

```

5.6 划分树

```

1  int n,m;
2  struct elem
3  {
4      int v,index;
5  }a[120000];
6  int d[30][120000];
7  int s[30][120000];
8
9  bool cmp(elem a,elem b)
10 {
11     if (a.v == b.v)
12         return a.index <= b.index;
13     return a.v < b.v;
14 }
15
16 void build(int depth,int l,int r)
17 {
18     if (l == r)
19         return;
20     int mid = (l+r)/2;
21     int tl,tr;
22     tl = tr = 0;
23     for (int i = l;i <= r;i++)
24     {
25         if (cmp(a[d[depth][i]],a[mid]))
26         {
27             d[depth+1][l+tl] = d[depth][i];

```

```

28         tl++;
29     }
30     else
31     {
32         d[depth+1][mid+1+tr] = d[depth][i];
33         tr++;
34     }
35     s[depth][i] = tl;
36 }
37 build(depth+1,l,mid);
38 build(depth+1,mid+1,r);
39 }
40
41 int find(int depth,int dl,int dr,int fl,int fr,int k)
42 {
43     if (fl == fr)
44         return a[d[depth][fl]].v;
45     int ls,rs;
46     int mid = (dl+dr)/2;
47     ls = (fl == dl)? 0 : s[depth][fl-1];
48     rs = s[depth][fr];
49     return (rs-ls < k)? find(depth+1,mid+1,dr,mid+fl-dl-ls+1,mid+
        fr-dl-rs+1,k-(rs-ls)) : find(depth+1,dl,mid,dl+ls,dl+rs-1,
        k);
50 }
51
52 int main()
53 {
54     while (scanf("%d%d",&n,&m) != EOF)
55     {
56         for (int i = 1;i <= n;i++)
57         {
58             scanf("%d",&a[i].v);
59             a[i].index = i;
60         }
61         sort(a+1,a+n+1,cmp);
62         for (int i = 1;i <= n;i++)
63             d[0][a[i].index] = i;
64         build(0,1,n);
65         int l,r,k;
66         for (int i = 1;i <= m;i++)
67         {
68             scanf("%d%d%d",&l,&r,&k);
69             printf("%d\n",find(0,1,n,l,r,k));
70         }
71     }
72     return 0;
73 }

```

5.7 树状数组

```

1 int read(int k)
2 {

```

```

3      int sum = 0;
4      for (; k; k^=k&-k)
5          sum+=tree[k];
6      return sum;
7  }
8  void update(int k, int v)
9  {
10     for (; k<=MaxN; k+=k&-k)
11         tree[k]+=v;
12 }
13 int find_Kth(int k)
14 {
15     int idx = 0;
16     for(int i=20; i>=0; i--)
17     {
18         idx |= 1 << i;
19         if(idx <= MaxN && tree[idx] < k)
20             k -= tree[idx];
21         else    idx ^= 1 << i;
22     }
23     return idx + 1;
24 }

```

6 图论

6.1 优先队列优化的dijkstra

```
1  #include<cstdio>
2  #include<cstring>
3  #include<iostream>
4  #include<algorithm>
5  #include<queue>
6  #include<vector>
7  using namespace std;
8  const int MAXN=100;
9  const int MAXM=1000;
10 int N,L;
11 int head[MAXN];
12 struct edges
13 {
14     int to,next,cost;
15 } edge[MAXM];
16 int dist[MAXN];
17 class states
18 {
19 public:
20     int cost,id;
21 };
22 class cmp
23 {
24 public:
25     bool operator()(const states &i,const states &j)
26     {
27         return i.cost>j.cost;
28     }
29 };
30 void init(int n)
31 {
32     N=n;
33     L=0;
34     for (int i=0; i<n; i++)
35         head[i]=-1;
36 }
37 void add_edge(int x,int y,int cost)
38 {
39     edge[L].to=y;
40     edge[L].cost=cost;
41     edge[L].next=head[x];
42     head[x]=L++;
43 }
44 int dijkstra(int s,int t)
45 {
46     memset(dist,63,sizeof(dist));
47     states u;
48     u.id=s;
```

```

49     u.cost=0;
50     dist[s]=0;
51     priority_queue<states,vector<states>,cmp> q;
52     q.push(u);
53     while (!q.empty())
54     {
55         u=q.top();
56         q.pop();
57         if (u.id==t) return dist[t];
58         if (u.cost!=dist[u.id]) continue;
59         for (int i=head[u.id]; i!=-1; i=edge[i].next)
60         {
61             states v=u;
62             v.id=edge[i].to;
63             if (dist[v.id]>dist[u.id]+edge[i].cost)
64             {
65                 v.cost=dist[v.id]=dist[u.id]+edge[i].cost;
66                 q.push(v);
67             }
68         }
69     }
70     return -1;
71 }
72 int main()
73 {
74     int n,m;
75     scanf("%d%d",&n,&m);
76     init(n);
77     for (int i=0; i<m; i++)
78     {
79         int x,y,z;
80         scanf("%d%d%d",&x,&y,&z);
81         add_edge(x,y,z);
82         add_edge(y,x,z);
83     }
84     int s,t;
85     scanf("%d%d",&s,&t);
86     printf("%d\n",dijkstra(s,t));
87     return 0;
88 }

```

6.2 SAP四版

```

1  const int MAXEDGE=20400;
2  const int MAXN=400;
3  const int inf=0x3fffffff;
4  struct edges
5  {
6      int cap,to,next,flow;
7  } edge[MAXEDGE+100];
8  struct nodes
9  {
10     int head,label,pre,cur;

```

```

11 } node[MAXN+100];
12 int L,N;
13 int gap[MAXN+100];
14 void init(int n)
15 {
16     L=0;
17     N=n;
18     for (int i=0; i<N; i++)
19         node[i].head=-1;
20 }
21 void add_edge(int x,int y,int z,int w)
22 {
23     edge[L].cap=z;
24     edge[L].flow=0;
25     edge[L].to=y;
26     edge[L].next=node[x].head;
27     node[x].head=L++;
28     edge[L].cap=w;
29     edge[L].flow=0;
30     edge[L].to=x;
31     edge[L].next=node[y].head;
32     node[y].head=L++;
33 }
34 int maxflow(int s,int t)
35 {
36     memset(gap,0,sizeof(gap));
37     gap[0]=N;
38     int u,ans=0;
39     for (int i=0; i<N; i++)
40     {
41         node[i].cur=node[i].head;
42         node[i].label=0;
43     }
44     u=s;
45     node[u].pre=-1;
46     while (node[s].label<N)
47     {
48         if (u==t)
49         {
50             int min=inf;
51             for (int i=node[u].pre; i!=-1; i=node[edge[i^1].to].pre)
52                 if (min>edge[i].cap-edge[i].flow)
53                     min=edge[i].cap-edge[i].flow;
54             for (int i=node[u].pre; i!=-1; i=node[edge[i^1].to].pre)
55             {
56                 edge[i].flow+=min;
57                 edge[i^1].flow-=min;
58             }
59             u=s;
60             ans+=min;

```

```

61         continue;
62     }
63     bool flag=false;
64     int v;
65     for (int i=node[u].cur; i!=-1; i=edge[i].next)
66     {
67         v=edge[i].to;
68         if (edge[i].cap-edge[i].flow && node[v].label+1==node
            [u].label)
69         {
70             flag=true;
71             node[u].cur=node[v].pre=i;
72             break;
73         }
74     }
75     if (flag)
76     {
77         u=v;
78         continue;
79     }
80     node[u].cur=node[u].head;
81     int min=N;
82     for (int i=node[u].head; i!=-1; i=edge[i].next)
83         if (edge[i].cap-edge[i].flow && node[edge[i].to].
            label<min)
84             min=node[edge[i].to].label;
85     gap[node[u].label]--;
86     if (!gap[node[u].label]) return ans;
87     node[u].label=min+1;
88     gap[node[u].label]++;
89     if (u!=s) u=edge[node[u].pre^1].to;
90 }
91 return ans;
92 }

```

6.3 费用流三版

T了可以改成栈。

```

1  const int MAXM=60000;
2  const int MAXN=400;
3  const int inf=0x3fffffff;
4  int L,N;
5  int K;
6  struct edges
7  {
8      int to,next,cap,flow,cost;
9  } edge[MAXM];
10 struct nodes
11 {
12     int dis,pre,head;
13     bool visit;
14 } node[MAXN];

```

```

15 void init(int n)
16 {
17     N=n;
18     L=0;
19     for (int i=0; i<N; i++)
20         node[i].head=-1;
21 }
22 void add_edge(int x,int y,int cap,int cost)
23 {
24     edge[L].to=y;
25     edge[L].cap=cap;
26     edge[L].cost=cost;
27     edge[L].flow=0;
28     edge[L].next=node[x].head;
29     node[x].head=L++;
30     edge[L].to=x;
31     edge[L].cap=0;
32     edge[L].cost=-cost;
33     edge[L].flow=0;
34     edge[L].next=node[y].head;
35     node[y].head=L++;
36 }
37 bool spfa(int s,int t)
38 {
39     queue <int> q;
40     for (int i=0; i<N; i++)
41     {
42         node[i].dis=0x3fffffff;
43         node[i].pre=-1;
44         node[i].visit=0;
45     }
46     node[s].dis=0;
47     node[s].visit=1;
48     q.push(s);
49     while (!q.empty())
50     {
51         int u=q.front();
52         node[u].visit=0;
53         for (int i=node[u].head; i!=-1; i=edge[i].next)
54         {
55             int v=edge[i].to;
56             if (edge[i].cap>edge[i].flow &&
57                 node[v].dis>node[u].dis+edge[i].cost)
58             {
59                 node[v].dis=node[u].dis+edge[i].cost;
60                 node[v].pre=i;
61                 if (!node[v].visit)
62                 {
63                     node[v].visit=1;
64                     q.push(v);
65                 }
66             }

```



```

67         }
68         q.pop();
69     }
70     if (node[t].pre==-1)
71         return 0;
72     else
73         return 1;
74 }
75 int mcmf(int s,int t,int &cost)
76 {
77     int flow=0;
78     while (spfa(s,t))
79     {
80         int max=inf;
81         for (int i=node[t].pre; i!=-1; i=node[edge[i^1].to].pre)
82         {
83             if (max>edge[i].cap-edge[i].flow)
84                 max=edge[i].cap-edge[i].flow;
85         }
86         for (int i=node[t].pre; i!=-1; i=node[edge[i^1].to].pre)
87         {
88             edge[i].flow+=max;
89             edge[i^1].flow-=max;
90             cost+=edge[i].cost*max;
91         }
92         flow+=max;
93     }
94     return flow;
95 }

```

6.4 匈牙利

6.4.1 新版,隐式图可解

```

1 bool check(int u)
2 {
3     for (int i=head[u]; i!=-1; i=edge[i].next)
4     {
5         int v=edge[i].to;
6         if (matc[v]==u) continue;
7         if (!use[v])
8         {
9             use[v]=1;
10            if (matc[v]==-1 || check(matc[v]))
11            {
12                matc[v]=u;
13                matc[u]=v;
14                return 1;
15            }
16        }
17    }
18    return 0;

```

```

19 }
20 int match()
21 {
22     int ret=0;
23     memset(matc,-1,sizeof(matc));
24     for (int u=0; u<N; u++)
25     {
26         if (matc[u]!=-1) continue;
27         memset(use,0,sizeof(use));
28         if (check(u))
29             ret++;
30     }
31     return ret;
32 }

```

6.4.2 邻接矩阵

```

1 bool check(int u)
2 {
3     for (int v=0; v<N; v++)
4         if (am[u][v] && !use[v])
5         {
6             use[v]=1;
7             if (pre[v]==-1 || check(pre[v]))
8             {
9                 pre[v]=u;
10                return 1;
11            }
12        }
13    return 0;
14 }
15 int match()
16 {
17     int ret=0;
18     memset(pre,-1,sizeof(pre));
19     for (int u=0; u<N; u++)
20     {
21         memset(use,0,sizeof(use));
22         if (check(u))
23             ret++;
24     }
25     return ret;
26 }

```

6.4.3 邻接表

```

1 bool check(int u)
2 {
3     for (int i=head[u]; i!=-1; i=edge[i].next)
4     {
5         int v=edge[i].to;
6         if (!use[v])
7         {
8             use[v]=1;

```

```

9         if (pre[v]==-1 || check(pre[v]))
10        {
11            pre[v]=u;
12            return 1;
13        }
14    }
15 }
16 return 0;
17 }
18 int match()
19 {
20     int ret=0;
21     memset(pre,-1,sizeof(pre));
22     for (int u=1; u<=N; u++)
23     {
24         memset(use,0,sizeof(use));
25         if (check(u))
26             ret++;
27     }
28     return ret;
29 }

```

6.5 一般图匹配带花树

```

1  const int MaxN = 222;
2  int N;
3  bool Graph[MaxN+1][MaxN+1];
4  int Match[MaxN+1];
5  bool InQueue[MaxN+1], InPath[MaxN+1], InBlossom[MaxN+1];
6  int Head, Tail;
7  int Queue[MaxN+1];
8  int Start, Finish;
9  int NewBase;
10 int Father[MaxN+1], Base[MaxN+1];
11 int Count;
12 void CreateGraph()
13 {
14     int u, v;
15     memset(Graph, false, sizeof(Graph));
16     scanf("%d", &N);
17     while (scanf("%d%d", &u, &v) != EOF)
18         Graph[u][v] = Graph[v][u] = true;
19 }
20 void Push(int u)
21 {
22     Queue[Tail] = u;
23     Tail++;
24     InQueue[u] = true;
25 }
26 int Pop()
27 {
28     int res = Queue[Head];
29     Head++;

```

```

30     return res;
31 }
32 int FindCommonAncestor(int u,int v)
33 {
34     memset(InPath,false,sizeof(InPath));
35     while (true)
36     {
37         u = Base[u];
38         InPath[u] = true;
39         if (u == Start) break;
40         u = Father[Match[u]];
41     }
42     while (true)
43     {
44         v = Base[v];
45         if (InPath[v]) break;
46         v = Father[Match[v]];
47     }
48     return v;
49 }
50 void ResetTrace(int u)
51 {
52     int v;
53     while (Base[u] != NewBase)
54     {
55         v = Match[u];
56         InBlossom[Base[u]] = InBlossom[Base[v]] = true;
57         u = Father[v];
58         if (Base[u] != NewBase) Father[u] = v;
59     }
60 }
61 void BlossomContract(int u,int v)
62 {
63     NewBase = FindCommonAncestor(u,v);
64     memset(InBlossom,false,sizeof(InBlossom));
65     ResetTrace(u);
66     ResetTrace(v);
67     if (Base[u] != NewBase) Father[u] = v;
68     if (Base[v] != NewBase) Father[v] = u;
69     for (int tu = 1; tu <= N; tu++)
70         if (InBlossom[Base[tu]])
71         {
72             Base[tu] = NewBase;
73             if (!InQueue[tu]) Push(tu);
74         }
75 }
76 void FindAugmentingPath()
77 {
78     memset(InQueue,false,sizeof(InQueue));
79     memset(Father,0,sizeof(Father));
80     for (int i = 1; i <= N; i++)
81         Base[i] = i;

```

```

82     Head = Tail = 1;
83     Push(Start);
84     Finish = 0;
85     while (Head < Tail)
86     {
87         int u = Pop();
88         for (int v = 1; v <= N; v++)
89             if (Graph[u][v] && (Base[u] != Base[v]) && (Match[u]
90                 != v))
91             {
92                 if ((v == Start) || ((Match[v] > 0) && (Father[
93                     Match[v]] > 0)))
94                     BlossomContract(u,v);
95                 else if (Father[v] == 0)
96                 {
97                     Father[v] = u;
98                     if (Match[v] > 0)
99                         Push(Match[v]);
100                     else
101                     {
102                         Finish = v;
103                         return;
104                     }
105                 }
106             }
107 void AugmentPath()
108 {
109     int u,v,w;
110     u = Finish;
111     while (u > 0)
112     {
113         v = Father[u];
114         w = Match[v];
115         Match[v] = u;
116         Match[u] = v;
117         u = w;
118     }
119 }
120 void Edmonds()
121 {
122     memset(Match,0,sizeof(Match));
123     for (int u = 1; u <= N; u++)
124         if (Match[u] == 0)
125         {
126             Start = u;
127             FindAugmentingPath();
128             if (Finish > 0) AugmentPath();
129         }
130 }
131 void PrintMatch()

```

```

132 {
133     for (int u = 1; u <= N; u++)
134         if (Match[u] > 0)
135             Count++;
136     printf("%d\n", Count);
137     for (int u = 1; u <= N; u++)
138         if (u < Match[u])
139             printf("%d_ %d\n", u, Match[u]);
140 }
141 int main()
142 {
143     CreateGraph();
144     Edmonds();
145     PrintMatch();
146 }

```

6.6 KM

6.6.1 最大加权匹配

```

1 | bool visx[N],visy[N]; //x,y中的点是否被访问
2 | int lx[N],ly[N]; //x,y中的点的标号
3 | int matchy[N]; //y中各点匹配状态
4 | int map[N][N]; //二分图描述[x][y]
5 | bool find(int x)
6 | {
7 |     visx[x]=true;
8 |     int t;
9 |     for (int y=0;y<ycnt;y++)
10 |     {
11 |         if (!visy[y])
12 |         {
13 |             t=lx[x]+ly[y]-map[x][y];
14 |             if (t==0)
15 |             {
16 |                 visy[y]=true;
17 |                 if (matchy[y]==-1 || find(matchy[y]))
18 |                 {
19 |                     matchy[y]=x;
20 |                     return true;
21 |                 }
22 |             }
23 |             else if (lack>t) lack=t;
24 |         }
25 |     }
26 |     return false;
27 | }
28 | void KM()
29 | {
30 |     memset(lx,0,sizeof(lx));
31 |     memset(ly,0,sizeof(ly));
32 |     memset(matchy,-1,sizeof(matchy));
33 |     for (int i=0;i<xcnt;i++)

```

```

34     for (int j=0;j<ycnt;j++)
35         if (map[i][j]>lx[i])
36             lx[i]=map[i][j];
37     for (int x=0;x<xcnt;x++)
38     {
39         while (true)
40         {
41             memset(visx,false,sizeof(visx));
42             memset(visy,false,sizeof(visy));
43             lack=INFI;
44             if (find(x)) break;
45             for (int i=0;i<xcnt;i++)
46             {
47                 if (visx[i]) lx[i]-=lack;
48                 if (visy[i]) ly[i]+=lack;
49             }
50         }
51     }
52     int cost=0;
53     for (int i=0;i<ycnt;i++)
54         cost+=map[matchy[i]][i];
55 }

```

6.6.2 自认为正确的Kuhn_Munkras

未验证

```

1  #include<cstdio>
2  #include<cstring>
3  #include<algorithm>
4  using namespace std;
5  const int MAXN=100;
6  const int inf=0x3f3f3f3f;
7  bool visitx[MAXN],visity[MAXN];
8  int labx[MAXN],laby[MAXN],matx[MAXN],maty[MAXN],slack[MAXN];
9  int ma[MAXN][MAXN];
10 bool check(int x,int n)
11 {
12     visitx[x]=1;
13     for (int i=0; i<n; i++)
14         if (!visity[i])
15             if (labx[x]+laby[i]==ma[x][i])
16             {
17                 visity[i]=1;
18                 if (maty[i]==-1 || check(maty[i],n))
19                 {
20                     matx[x]=i;
21                     maty[i]=x;
22                     return 1;
23                 }
24             }
25     else
26         slack[i]=min(slack[i],labx[x]+laby[i]-ma[x][i]);
27 }

```

```

28     return 0;
29 }
30 void maintain(int n)
31 {
32     int diff=inf;
33     for (int i=0; i<n; i++)
34         if (!visity[i])
35             diff=min(diff,slack[i]);
36     for (int i=0; i<n; i++)
37     {
38         if (visitx[i])
39             labx[i]-=diff;
40         if (visity[i])
41             laby[i]+=diff;
42         else
43             slack[i]-=diff;
44     }
45 }
46 int Kuhn_Munkras(int n)
47 {
48     for (int i=0; i<n; i++)
49     {
50         labx[i]=-inf;
51         for (int j=0; j<n; j++)
52             labx[i]=max(labx[i],ma[i][j]);
53     }
54     memset(laby,0,4*n);
55     memset(matx,-1,4*n);
56     memset(maty,-1,4*n);
57     for (int i=0; i<n; i++)
58     {
59         memset(visitx,0,n);
60         memset(visity,0,n);
61         memset(slack,63,4*n);
62         while (!check(i,n))
63         {
64             maintain(n);
65             memset(visitx,0,n);
66             memset(visity,0,n);
67         }
68     }
69     int ret=0;
70     for (int i=0;i<n;i++)
71         ret+=labx[i]+laby[i];
72     return ret;
73 }
74 int main()
75 {
76     int n,m;
77     scanf("%d%d",&m,&n);
78     for (int i=m; i<n; i++)
79         for (int j=0; j<n; j++)

```



```

80         ma[i][j]=0;
81     for (int i=0; i<m; i++)
82         for (int j=0; j<n; j++)
83             scanf("%d",&ma[i][j]);
84     printf("%d\n",Kuhn_Munkras(n));
85     printf("%d",matx[0]+1);
86     for (int i=1;i<m;i++)
87         printf("□%d",matx[i]+1);
88     puts("");
89     return 0;
90 }

```

6.7 *二维平面图的最大流

待整理

```

1  #include <iostream>
2  #include <algorithm>
3  #include <cstdio>
4  #include <cstring>
5  #include <vector>
6  #include <cmath>
7  #include <map>
8  #include <queue>
9  using namespace std;
10
11 const int maxn = 100100;
12 const int inf = 0x3f3f3f3f;
13 struct Point
14 {
15     int x,y,id;
16     double theta;
17     Point() {}
18     Point(int _x,int _y)
19     {
20         x = _x;
21         y = _y;
22     }
23     Point(Point _s,Point _e,int _id)
24     {
25         id = _id;
26         x = _s.x-_e.x;
27         y = _s.y-_e.y;
28         theta = atan2(y,x);
29     }
30     bool operator < (const Point &b)const
31     {
32         return theta < b.theta;
33     }
34 };
35
36 map<pair<int,int>,int > idmap;

```

```

37 struct Edge
38 {
39     int from,to,next,cap,near,mark;
40 };
41 Edge edge[maxn*2];
42 int head[maxn],L;
43 int cntd[maxn];
44 void addedge(int u,int v,int cap)
45 {
46     cntd[u]++;
47     cntd[v]++;
48     idmap[make_pair(u,v)] = L;
49     edge[L].from = u;
50     edge[L].to = v;
51     edge[L].cap = cap;
52     edge[L].next = head[u];
53     edge[L].mark = -1;
54     head[u] = L++;
55 }
56
57 int rtp[maxn];
58 Point p[maxn],tp[maxn];
59 int n,m,S,T;
60 int vid;
61
62 struct Edge2
63 {
64     int to,next,dis;
65 } edge2[maxn*2];
66 int head2[maxn],L2;
67
68 void addedge2(int u,int v,int dis)
69 {
70     edge2[L2].to = v;
71     edge2[L2].dis = dis;
72     edge2[L2].next = head2[u];
73     head2[u] = L2++;
74 }
75
76 int dist[maxn];
77 bool inq[maxn];
78 int SPFA(int s,int t)
79 {
80     queue<int> Q;
81     memset(inq,false,sizeof(inq));
82     memset(dist,63,sizeof(dist));
83     Q.push(s);
84     dist[s] = 0;
85     while (!Q.empty())
86     {
87         int now = Q.front();
88         Q.pop();

```

```

89         for (int i = head2[now]; i != -1; i = edge2[i].next)
90             if (dist[edge2[i].to] > dist[now]+edge2[i].dis)
91             {
92                 dist[edge2[i].to] = dist[now]+edge2[i].dis;
93                 if (inq[edge2[i].to] == false)
94                 {
95                     inq[edge2[i].to] = true;
96                     Q.push(edge2[i].to);
97                 }
98             }
99         inq[now] = false;
100     }
101     return dist[t];
102 }
103
104 int main()
105 {
106     int totcas;
107     scanf("%d",&totcas);
108     for (int cas = 1; cas <= totcas; cas++)
109     {
110         idmap.clear();
111         L = 0;
112         scanf("%d%d",&n,&m);
113         S = T = 0;
114         for (int i = 0; i < n; i++)
115         {
116             head[i] = -1;
117             scanf("%d%d",&p[i].x,&p[i].y);
118             if (p[S].x > p[i].x)
119                 S = i;
120             if (p[T].x < p[i].x)
121                 T = i;
122             cntd[i] = 0;
123         }
124         //源汇中间加入一个特殊节点
125         head[n] = -1;
126         n ++;
127         addedge(S,n-1,inf);
128         addedge(n-1,S,inf);
129         addedge(T,n-1,inf);
130         addedge(n-1,T,inf);
131
132         for (int i = 0; i < m; i++)
133         {
134             int u,v,cap;
135             scanf("%d%d%d",&u,&v,&cap);
136             u--;
137             v--;
138             addedge(u,v,cap);
139             addedge(v,u,cap);
140         }

```

```

141
142     for (int i = 0; i < n; i++)
143     {
144         int tot = 0;
145         //源点汇点连到特殊点的方向需要特别考虑一下
146         if (i == S)
147             tp[tot++] = Point(Point(0,0),Point(-1,0),n-1);
148         else if (i == T)
149             tp[tot++] = Point(Point(0,0),Point(1,0),n-1);
150         else if (i == n-1)
151         {
152             tp[tot++] = Point(Point(0,0),Point(1,0),S);
153             tp[tot++] = Point(Point(0,0),Point(-1,0),T);
154         }
155         if (i < n-1)
156         {
157             for (int j = head[i]; j != -1; j = edge[j].next)
158             {
159                 if (i == S && edge[j].to == n-1) continue;
160                 if (i == T && edge[j].to == n-1) continue;
161                 tp[tot++] = Point(p[i],p[edge[j].to],edge[j].
                    to);
162             }
163         }
164         sort(tp,tp+tot);
165         for (int j = 0; j < tot; j++)
166             rtp[tp[j].id] = j;
167         for (int j = head[i]; j != -1; j = edge[j].next)
168             edge[j].near = tp[(rtp[edge[j].to]+1)%tot].id;
169     }
170
171     vid = 0;
172     for (int i = 0;i < L;i++)
173         if (edge[i].mark == -1)
174         {
175             int now = edge[i].from;
176             int eid = i;
177             int to = edge[i].to;
178             while (true)
179             {
180                 edge[eid].mark = vid;
181                 eid ^= 1;
182                 now = to;
183                 to = edge[eid].near;
184                 eid = idmap[make_pair(now,to)];
185
186                 if (now == edge[i].from) break;
187             }
188             vid++;
189         }
190
191     L2 = 0;

```

```

192         for (int i = 0; i < vid; i++)
193             head2[i] = -1;
194         for (int i = 0; i < L; i++)
195             addedge2(edge[i].mark, edge[i^1].mark, edge[i].cap);
196         printf("%d\n", SPFA(edge[0].mark, edge[1].mark));
197     }
198     return 0;
199 }

```

6.8 强联通

```

1  int dfsnum[2000];
2  int low[2000];
3  int stack[2000];
4  int top;
5  int ans;
6  int an;
7  int be[2000];
8  int flag[2000];
9  void dfs(int x)
10 {
11     dfsnum[x] = low[x] = ans++;
12     stack[++top] = x;
13     flag[x] = 1;
14     for (int i = head[x]; i != -1; i = edge[i].next)
15     {
16         int y = edge[i].to;
17         if (dfsnum[y] == -1)
18         {
19             dfs(y);
20             low[x] = min(low[x], low[y]);
21         }
22         else if (flag[y] == 1)
23             low[x] = min(low[x], dfsnum[y]);
24     }
25     if (dfsnum[x] == low[x])
26     {
27         while (stack[top] != x)
28         {
29             flag[stack[top]] = 0;
30             be[stack[top]] = an;
31             top--;
32         }
33         flag[x] = 0;
34         be[x] = an++;
35         top--;
36     }
37 }

```

调用:

```

1 void SC()

```

```

2 {
3     memset(dfsnum, -1, sizeof(dfsnum));
4     memset(flag, 0, sizeof(flag));
5     top = 0;
6     an = 0;
7     ans = 0;
8     for (int i = 0; i < n; i++)
9         if (dfsnum[i] == -1)
10             dfs(i);
11 }

```

6.9 最大团以及相关知识

独立集： 独立集是指图的顶点集的一个子集,该子集的导出子图不含边.如果一个独立集不是任何一个独立集的子集, 那么称这个独立集是一个极大独立集.一个图中包含顶点数目最多的独立集称为最大独立集。最大独立集 一定是极大独立集，但是极大独立集不一定是最大的独立集。

支配集： 与独立集相对应的就是支配集，支配集也是图顶点集的一个子集，设 S 是图 G 的一个支配集，则对于图中的任意一个顶点 u ，要么属于集合 s ，要么与 s 中的顶点相邻。在 s 中除去任何元素后 s 不再是支配集，则支配集 s 是极小支配集。称 G 的所有支配集中顶点个数最少的支配集为最小支配集，最小支配集中的顶点个数成为支配数。

最小点的覆盖： 最小点的覆盖也是图的顶点集的一个子集，如果我们选中一个点，则称这个点将以他为端点的所有边都覆盖了。将图中所有的边都覆盖所用顶点数最少，这个集合就是最小的点的覆盖。

最大团： 图 G 的顶点的子集，设 D 是最大团，则 D 中任意两点相邻。若 u, v 是最大团，则 u, v 有边相连，其补图 u, v 没有边相连，所以图 G 的最大团=其补图的最大独立集。给定无向图 $G = (V, E)$ ，如果 U 属于 V ，并且对于任意 u, v 包含于 U 有 $\langle u, v \rangle$ 包含于 E ，则称 U 是 G 的完全子图， G 的完全子图 U 是 G 的团，当且仅当 U 不包含在 G 的更大的完全子图中， G 的最大团是指 G 中所含顶点数目最多的团。如果 U 属于 V ，并且对于任意 u, v 包含于 U 有 $\langle u, v \rangle$ 不包含于 E ，则称 U 是 G 的空子图， G 的空子图 U 是 G 的独立集，当且仅当 U 不包含在 G 的更大的独立集， G 的最大团是指 G 中所含顶点数目最多的独立集。

一些性质： 最大独立集+最小覆盖集= V ，最大团=补图的最大独立集，最小覆盖集=最大匹配

```

1 #include <cstdio>
2 bool am[100][100];
3 int ans;
4 int c[100];
5 int U[100][100];
6 int n;
7 bool dfs(int rest, int num)
8 {
9     if (!rest)
10     {
11         if (num >= ans)
12             return 1;
13         else
14             return 0;
15     }

```

```

16     int pre=-1;
17     for (int i=0;i<rest && rest-i+num>=ans;i++)
18     {
19         int idx=U[num][i];
20         if (num+c[idx]<ans)
21             return 0;
22         int nrest=0;
23         for (int j=i+1; j<rest; j++)
24             if (am[idx][U[num][j]])
25                 U[num+1][nrest++]=U[num][j];
26         if (dfs(nrest,num+1))
27             return 1;
28     }
29     return 0;
30 }
31 int main()
32 {
33     while (scanf("%d",&n),n)
34     {
35         for (int i=0;i<n;i++)
36             for (int j=0;j<n;j++)
37                 scanf("%d",&am[i][j]);
38         ans=0;
39         for (int i=n-1; i>=0; i--)
40         {
41             int rest=0;
42             for (int j=i+1; j<n; j++)
43                 if (am[i][j])
44                     U[0][rest++]=j;
45             ans+=dfs(rest,0);
46             c[i]=ans;
47         }
48         printf("%d\n",ans);
49     }
50     return 0;
51 }

```

6.10 双连通分量

标号从0起

```

1  #include<cstdio>
2  #include<cstring>
3  #include<stack>
4  #include<queue>
5  #include<algorithm>
6  using namespace std;
7  const int MAXN=100000*2;
8  const int MAXM=200000;
9  struct edges
10 {
11     int to,next;
12     bool cut,visit;

```

```

13 } edge[MAXM<<1];
14 int head[MAXN],low[MAXN],dpt[MAXN],L;
15 bool visit[MAXN],cut[MAXN];
16 void init(int n)
17 {
18     L=0;
19     memset(head,-1,4*n);
20     memset(visit,0,n);
21 }
22 void add_edge(int u,int v)
23 {
24     edge[L].cut=edge[L].visit=0;
25     edge[L].to=v;
26     edge[L].next=head[u];
27     head[u]=L++;
28 }
29 int idx;
30 stack<int> st;
31 int bcc[MAXM];
32 void dfs(int u,int fu,int deg)
33 {
34     cut[u]=0;
35     visit[u]=1;
36     low[u]=dpt[u]=deg;
37     int tot=0;
38     for (int i=head[u]; i!=-1; i=edge[i].next)
39     {
40         int v=edge[i].to;
41         if (edge[i].visit)
42             continue;
43         st.push(i/2);
44         edge[i].visit=edge[i^1].visit=1;
45         if (visit[v])
46         {
47             low[u]=dpt[v]>low[u]?low[u]:dpt[v];
48             continue;
49         }
50         dfs(v,u,deg+1);
51         edge[i].cut=edge[i^1].cut=(low[v]>dpt[u] || edge[i].cut);
52         if (u!=fu) cut[u]=low[v]>=dpt[u]?1:cut[u];
53         if (low[v]>=dpt[u] || u==fu)
54         {
55             while (st.top()!=i/2)
56             {
57                 int x=st.top()*2,y=st.top()*2+1;
58                 bcc[st.top()]=idx;
59                 st.pop();
60             }
61             bcc[i/2]=idx++;
62             st.pop();
63         }
64         low[u]=low[v]>low[u]?low[u]:low[v];

```



```

65         tot++;
66     }
67     if (u==fu && tot>1) cut[u]=1;
68 }
69 int main()
70 {
71     int n,m;
72     while (scanf("%d%d",&n,&m)!=EOF)
73     {
74         init(n);
75         for (int i=0; i<m; i++)
76         {
77             int u,v;
78             scanf("%d%d",&u,&v);
79             add_edge(u,v);
80             add_edge(v,u);
81         }
82         idx=0;
83         for (int i=0; i<n; i++)
84             if (!visit[i])
85                 dfs(i,i,0);
86     }
87     return 0;
88 }

```

6.11 割点与桥

```

1  #include<cstdio>
2  #include<cstring>
3  const int MAXN=10000;
4  struct edges
5  {
6      int to,next;
7      bool cut,visit;
8      int from;
9  } edge[MAXN-1<<1];
10 int head[MAXN],low[MAXN],dfn[MAXN],L;
11 bool visit[MAXN],cut[MAXN];
12 void init(int n)
13 {
14     L=0;
15     memset(head,-1,4*n);
16     memset(cut,0,4*n);
17     memset(visit,0,4*n);
18 }
19 void add_edge(int u,int v)
20 {
21     edge[L].from=u;
22     edge[L].cut=edge[L].visit=0;
23     edge[L].to=v;
24     edge[L].next=head[u];
25     head[u]=L++;

```

```

26 }
27 int idx;
28 void dfs(int u,int fu)
29 {
30     visit[u]=1;
31     low[u]=dfn[u]=idx++;
32     int tot=0;
33     for (int i=head[u]; i!=-1; i=edge[i].next)
34     {
35         int v=edge[i].to;
36         if (edge[i].visit)
37             continue;
38         edge[i].visit=edge[i^1].visit=1;
39         if (visit[v])
40         {
41             low[u]=dfn[v]>low[u]?low[u]:dfn[v];
42             continue;
43         }
44         dfs(v,u);
45         edge[i].cut=edge[i^1].cut=low[v]>dfn[u] || edge[i].cut;
46         if (u!=fu) cut[u]=low[v]>=dfn[u]?1:cut[u];
47         low[u]=low[v]>low[u]?low[u]:low[v];
48         tot++;
49     }
50     if (u==fu && tot>1) cut[u]=1;
51 }
52 int main()
53 {
54     int t;
55     scanf("%d",&t);
56     while (t--)
57     {
58         int n,m;
59         scanf("%d%d",&n,&m);
60         init(n);
61         for (int i=0; i<m; i++)
62         {
63             int u,v;
64             scanf("%d%d",&u,&v);
65             add_edge(--u,--v);
66             add_edge(v,u);
67         }
68         for (int i=0; i<n; i++)
69             if (!visit[i])
70             {
71                 idx=0;
72                 dfs(i,i);
73             }
74     }
75     return 0;
76 }

```

6.12 LCA

在线LCA, bfs

```
1  #include<cstdio>
2  #include<cstring>
3  #include<queue>
4  using namespace std;
5  const int NSIZE = 50000;
6  const int DEG = 20;
7  struct trees
8  {
9
10     int fa[DEG];
11     int head,deg;
12 } tree[NSIZE];
13 struct edges
14 {
15     int to , next;
16 } edge[NSIZE];
17 struct states
18 {
19     int u,fu,deg;
20 };
21 int L;
22 void add_edge(int x, int y)
23 {
24     edge[L].to = y;
25     edge[L].next = tree[x].head;
26     tree[x].head = L++;
27 }
28 int Root;
29 void BFS(int s)
30 {
31     queue<states> que;
32     states st;
33     st.deg=0;
34     st.fu=st.u=s;
35     que.push(st);
36     while(!que.empty())
37     {
38         states st=que.front();
39         que.pop();
40         tree[st.u].deg = st.deg;
41         tree[st.u].fa[0] = st.fu;
42         for (int i=1;i<DEG;i++)
43             tree[st.u].fa[i]=s;
44         for (int tmp=st.fu,num=1;tree[tmp].deg;tmp=tree[st.u].fa[
            num++])
45             tree[st.u].fa[num]=tree[tmp].fa[num-1];
46         for(int i = tree[st.u].head ; i != -1; i = edge[i].next)
47         {
48             int v = edge[i].to;
```

```

49         if (v == st.fu) continue;
50         states nst;
51         nst.u=v;
52         nst.fu=st.u;
53         nst.deg=st.deg+1;
54         que.push(nst);
55     }
56 }
57 }
58 int LCA(int x, int y)
59 {
60     if(tree[x].deg > tree[y].deg) swap(x,y);
61     int hx=tree[x].deg,hy=tree[y].deg;
62     int tx=x,ty=y;
63     for (int det=hy-hx,i=0; det; det>>=1,i++)
64         if (det&1)
65             ty=tree[ty].fa[i];
66     if(tx == ty) return tx;
67     for (int i=DEG-1; i>=0; i--)
68     {
69         if(tree[tx].fa[i] == tree[ty].fa[i])
70             continue;
71         tx = tree[tx].fa[i];
72         ty = tree[ty].fa[i];
73     }
74     return tree[tx].fa[0];
75 }
76 int main()
77 {
78     int t;
79     scanf("%d",&t);
80     while(t--)
81     {
82         int n;
83         scanf("%d",&n);
84         L = 0;
85         for(int i = 0 ; i < n ; i++)
86             tree[i].head = -1;
87         for(int i = 0 ; i < n-1 ; i++)
88         {
89             int a,b;
90             scanf("%d%d",&a ,&b);
91             add_edge(a-1,b-1);
92             add_edge(b-1,a-1);
93         }
94         Root=0;
95         BFS(Root);
96         int a,b;
97         scanf("%d%d",&a,&b);
98         int lca=LCA(a-1,b-1)+1;
99         printf("%d\n",lca);
100     }

```

```

101     return 0;
102 }

```

6.13 最优比例生成树

```

1  #include<stdio.h>
2  #include<string.h>
3  #include<math.h>
4  struct
5  {
6      int x,y;
7      double z;
8  } node[1100];
9  struct
10 {
11     double l,c;
12 } map[1100][1100];
13 int n,l,f[1100],pre[1100];
14 double dis[1100];
15 double mst(double x)
16 {
17     int i,j,tmp;
18     double min,s=0,t=0;
19     memset(f,0,sizeof(f));
20     f[1]=1;
21     for (i=2; i<=n; i++)
22     {
23         dis[i]=map[1][i].c-map[1][i].l*x;
24         pre[i]=1;
25     }
26     for (i=1; i<n; i++)
27     {
28         min=1e10;
29         for (j=1; j<=n; j++)
30             if (!f[j] && min>dis[j])
31             {
32                 min=dis[j];
33                 tmp=j;
34             }
35         f[tmp]=1;
36         t+=map[pre[tmp]][tmp].l;
37         s+=map[pre[tmp]][tmp].c;
38         for (j=1; j<=n; j++)
39             if (!f[j] && map[tmp][j].c-map[tmp][j].l*x<dis[j])
40             {
41                 dis[j]=map[tmp][j].c-map[tmp][j].l*x;
42                 pre[j]=tmp;
43             }
44     }
45     return s/t;
46 }
47 int main()

```

```

48 {
49     int i,j;
50     double a,b;
51     scanf("%d",&n);
52     while (n)
53     {
54         for (i=1; i<=n; i++)
55             scanf("%d%d%lf",&node[i].x,&node[i].y,&node[i].z);
56         for (i=1; i<=n; i++)
57             for (j=i+1; j<=n; j++)
58             {
59                 map[j][i].l=map[i][j].l=sqrt(1.0*(node[i].x-node[
                    j].x)*(node[i].x-node[j].x)+(node[i].y-node[j
                    ].y)*(node[i].y-node[j].y));
60                 map[j][i].c=map[i][j].c=fabs(node[i].z-node[j].z)
                    ;
61             }
62         a=0,b=mst(a);
63         while (fabs(b-a)>1e-8)
64         {
65             a=b;
66             b=mst(a);
67         }
68         printf("%.3f\n",b);
69         scanf("%d",&n);
70     }
71 }

```

6.14 全局最小割

```

1  #include <iostream>
2  using namespace std;
3  const int maxn=510;
4  int map[maxn][maxn];
5  int n;
6  void contract(int x,int y)
7  {
8      int i,j;
9      for (i=0; i<n; i++)
10         if (i!=x) map[x][i]+=map[y][i],map[i][x]+=map[i][y];
11     for (i=y+1; i<n; i++) for (j=0; j<n; j++)
12     {
13         map[i-1][j]=map[i][j];
14         map[j][i-1]=map[j][i];
15     }
16     n--;
17 }
18 int w[maxn],c[maxn];
19 int sx,tx;
20 int mincut()
21 {
22     int i,j,k,t;
23     memset(c,0,sizeof(c));

```

```

24     c[0]=1;
25     for (i=0; i<n; i++) w[i]=map[0][i];
26     for (i=1; i+1<n; i++)
27     {
28         t=k=-1;
29         for (j=0; j<n; j++) if (c[j]==0&&w[j]>k)
30             k=w[t=j];
31         c[sx=t]=1;
32         for (j=0; j<n; j++) w[j]+=map[t][j];
33     }
34     for (i=0; i<n; i++) if (c[i]==0) return w[tx=i];
35 }
36 int main()
37 {
38     int i,j,k,m;
39     while (scanf("%d%d",&n,&m)!=EOF)
40     {
41         memset(map,0,sizeof(map));
42         while (m--)
43         {
44             scanf("%d%d%d",&i,&j,&k);
45             map[i][j]+=k;
46             map[j][i]+=k;
47         }
48         int mint=999999999;
49         while (n>1)
50         {
51             k=mincut();
52             if (k<mint) mint=k;
53             contract(sx,tx);
54         }
55         printf("%d\n",mint);
56     }
57     return 0;
58 }

```

6.15 欧拉路

6.15.1 有向图

```

1 void solve(int x)
2 {
3     int i;
4     if (!match[x])
5     {
6         path[++l]=x;
7         return ;
8     }
9     for (i=1; i<=n; i++)
10         if (b[x][i])
11         {
12             b[x][i]--;
13             match[x]--;

```

```

14         solve(i);
15     }
16     path[++l]=x;
17 }

```

6.15.2 无向图

```

1 void solve(int x)
2 {
3     int i;
4     if (!match[x])
5     {
6         path[++l]=x;
7         return ;
8     }
9     for (i=1; i<=n; i++)
10        if (b[x][i])
11        {
12            b[x][i]--;
13            b[i][x]--;
14            match[x]--;
15            match[i]--;
16            solve(i);
17        }
18    path[++l]=x;
19 }

```

6.15.3 混合图

zju1992

```

1 int in[MAXN+100],out[MAXN+100];
2 int main()
3 {
4     int t;
5     scanf("%d",&t);
6     while (t--)
7     {
8         int n,m;
9         scanf("%d%d",&n,&m);
10        N=n+2;L=-1;
11        for (int i=0;i<N;i++)
12            head[i]=-1;
13        memset(in,0,sizeof(in));
14        memset(out,0,sizeof(out));
15
16        for (int i=0;i<m;i++)
17        {
18            int x,y,z;
19            scanf("%d%d%d",&x,&y,&z);
20            in[y]++;out[x]++;
21            if (!z)
22                add_edge(x,y,1);
23        }
24        int flag=1;

```



```

25         for (int i=1;i<=n;i++)
26         {
27             if (in[i]-out[i]>0)
28                 add_edge(i,n+1,(in[i]-out[i])/2);
29             else
30                 if (out[i]-in[i]>0)
31                     add_edge(0,i,(out[i]-in[i])/2);
32             //printf("%d %d %d\n",i,out[i],in[i]);
33             if ((in[i]+out[i])&1)
34             {
35                 flag=0;
36                 break;
37             }
38         }
39         maxflow(0,n+1);
40         for (int i=head[0];i!=-1;i=edge[i].next)
41             if (edge[i].cap>0 && edge[i].cap>edge[i].flow)
42             {
43                 flag=0;
44                 break;
45             }
46         if (flag)
47             puts("possible");
48         else
49             puts("impossible");
50     }
51     return 0;
52 }

```

6.16 K短路

```

1  #include<cstdio>
2  #include<cstring>
3  #include<queue>
4  using namespace std;
5  int K;
6  class states
7  {
8  public:
9      int cost,id;
10 };
11 int dist[1000];
12 class cmp
13 {
14 public:
15     bool operator()(const states &i,const states &j)
16     {
17         return i.cost>j.cost;
18     }
19 };
20 class cmp2
21 {

```

```

22 public:
23     bool operator()(const states &i, const states &j)
24     {
25         return i.cost+dist[i.id]>j.cost+dist[j.id];
26     }
27 };
28 struct edges
29 {
30     int to,next,cost;
31 } edger[100000],edge[100000];
32 int headr[1000],head[1000],Lr,L;
33 void dijkstra(int s)
34 {
35     states u;
36     u.id=s;
37     u.cost=0;
38     dist[s]=0;
39     priority_queue<states,vector<states>,cmp> q;
40     q.push(u);
41     while (!q.empty())
42     {
43         u=q.top();
44         q.pop();
45         if (u.cost!=dist[u.id]) continue;
46         for (int i=headr[u.id]; i!=-1; i=edger[i].next)
47         {
48             states v=u;
49             v.id=edger[i].to;
50             if (dist[v.id]>dist[u.id]+edger[i].cost)
51             {
52                 v.cost=dist[v.id]=dist[u.id]+edger[i].cost;
53                 q.push(v);
54             }
55         }
56     }
57 }
58 int num[1000];
59 void init(int n)
60 {
61     Lr=L=0;
62     memset(head,-1,4*n);
63     memset(headr,-1,4*n);
64     memset(dist,63,4*n);
65     memset(num,0,4*n);
66 }
67 void add_edge(int u,int v,int x)
68 {
69     edge[L].to=v;
70     edge[L].cost=x;
71     edge[L].next=head[u];
72     head[u]=L++;
73     edger[Lr].to=u;

```

```

74     edger[Lr].cost=x;
75     edger[Lr].next=headr[v];
76     headr[v]=Lr++;
77 }
78 int a_star(int s,int t)
79 {
80     if (dist[s]==0x3f3f3f3f)
81         return -1;
82     priority_queue<states,vector<states>,cmp2> q;
83     states tmp;
84     tmp.id=s;
85     tmp.cost=0;
86     q.push(tmp);
87     while (!q.empty())
88     {
89         states u=q.top();
90         q.pop();
91         num[u.id]++;
92         if (num[t]==K)
93             return u.cost;
94         for (int i=head[u.id]; i!=-1; i=edge[i].next)
95         {
96             int v=edge[i].to;
97             tmp.id=v;
98             tmp.cost=u.cost+edge[i].cost;
99             q.push(tmp);
100         }
101     }
102     return -1;
103 }
104 int main()
105 {
106     int n,m;
107     scanf("%d%d",&n,&m);
108     init(n);
109     for (int i=0; i<m; i++)
110     {
111         int u,v,x;
112         scanf("%d%d%d",&u,&v,&x);
113         add_edge(u-1,v-1,x);
114     }
115     int s,t;
116     scanf("%d%d%d",&s,&t,&K);
117     if (s==t)
118         K++;
119     dijkstra(t-1);
120     printf("%d\n",a_star(s-1,t-1));
121 }

```

6.17 稳定婚姻

假定有 n 个男生和 M 个女生，理想的拍拖状态就是对于每对情侣 (a,b) ，找不到另一对情侣 (c,d) 使得 c 更喜欢 b ， b 也更喜欢 c ，同理，对 a 来说也没有 (e,f) 使得 a 更喜欢 e 而 e 更喜欢 a ，当然

最后会有一些人落单。这样子一个状态可以称为理想拍拖状态，它也有一个专业的名词叫稳定婚姻。

求解这个问题可以用一个专有的算法，延迟认可算法，其核心就是让每个男生按自己喜欢的顺序逐个向女生表白，例如leokan向一个女生求爱，这个过程中，若这个女生没有男朋友，那么这个女生就暂时成为leokan的女朋友，或这个女生喜欢她现有男朋友的程度没有喜欢leokan高，这个女生也暂时成为leokan的女朋友，而她原有的男朋友则再将就找下一个次喜欢的女生来当女朋友。

```
1 #include<string.h>
2 #include<stdio.h>
3 #define N 1050
4 int boy[N][N];
5 int girl[N][N];
6 int ans[N];
7 int cur[N];
8 int n;
9 void getMarry(int g)
10 {
11     for (int i=ans[g]+1;i<n;i++)
12     {
13         int b=girl[g][i]-1;
14         if (cur[b]<0)
15         {
16             ans[g]=i;
17             cur[b]=g;
18             return;
19         }
20         int og=cur[b];
21         if (boy[b][og] > boy[b][g])
22         {
23             cur[b]=g;
24             ans[g]=i;
25             getMarry(og);
26             return;
27         }
28     }
29 };
30 int main()
31 {
32     int t,a;
33     scanf("%d",&t);
34     while(t--)
35     {
36         memset(girl,0,sizeof(girl));
37         memset(boy,0,sizeof(boy));
38         scanf("%d",&n);
39         for (int i=0;i<n;i++)
40             for (int j=0;j<n;j++)
41                 scanf("%d",&girl[i][j]);
42         for (int i=0;i<n;i++)
43             for (int j=0;j<n;j++)
44             {
45                 scanf("%d",&a);
```

```

46         boy[i][a-1]=j;
47     }
48     memset(cur,0xff,sizeof(cur));
49     memset(ans,0xff,sizeof(ans));
50     for (int i=0;i<n;i++)
51         getMarry(i);
52     for (int i=0;i<n;i++)
53         printf("%d\n",girl[i][ans[i]]);
54 }
55 return 0;
56 }

```

6.18 最小树形图

```

1  const int inf = 19921005;
2  int n,m,u,v,cost,dis[1001][1001],L;
3
4  void init(int n)
5  {
6      L = 0;
7      for (int i = 0; i < n; i++)
8          for (int j = 0; j < n; j++)
9              dis[i][j] = inf;
10 }
11
12 struct Edge
13 {
14     int u,v,cost;
15 };
16
17 Edge e[1001*1001];
18
19 int pre[1001],id[1001],visit[1001],in[1001];
20
21 int zhuliu(int root,int n,int m,Edge e[])
22 {
23     int res = 0,u,v;
24     while (true)
25     {
26         for (int i = 0; i < n; i++)
27             in[i] = inf;
28         for (int i = 0; i < m; i++)
29             if (e[i].u != e[i].v && e[i].cost < in[e[i].v])
30             {
31                 pre[e[i].v] = e[i].u;
32                 in[e[i].v] = e[i].cost;
33             }
34         for (int i = 0; i < n; i++)
35             if (i != root)
36                 if (in[i] == inf) return -1;
37         int tn = 0;
38         memset(id,-1,sizeof(id));

```

```

39     memset(visit,-1,sizeof(visit));
40     in[root] = 0;
41     for (int i = 0; i < n; i++)
42     {
43         res += in[i];
44         v = i;
45         while (visit[v] != i && id[v] == -1 && v != root)
46         {
47             visit[v] = i;
48             v = pre[v];
49         }
50         if(v != root && id[v] == -1)
51         {
52             for(int u = pre[v] ; u != v ; u = pre[u])
53                 id[u] = tn;
54             id[v] = tn++;
55         }
56     }
57     if(tn == 0) break;
58     for (int i = 0; i < n; i++)
59         if (id[i] == -1)
60             id[i] = tn++;
61     for (int i = 0; i < m;)
62     {
63         int v = e[i].v;
64         e[i].u = id[e[i].u];
65         e[i].v = id[e[i].v];
66         if (e[i].u != e[i].v)
67             e[i++].cost -= in[v];
68         else
69             swap(e[i],e[--m]);
70     }
71     n = tn;
72     root = id[root];
73 }
74 return res;
75 }
76
77 int main()
78 {
79     freopen("in.txt","r",stdin);
80     while (scanf("%d%d",&n,&m) != EOF)
81     {
82         init(n);
83         for (int i = 0; i < m; i++)
84         {
85             scanf("%d%d%d",&u,&v,&cost);
86             if (u == v) continue;
87             dis[u][v] = min(dis[u][v],cost);
88         }
89         L = 0;
90         for (int i = 0; i < n; i++)

```

```

91         for (int j = 0; j < n; j++)
92             if (dis[i][j] != inf)
93             {
94                 e[L].u = i;
95                 e[L].v = j;
96                 e[L++].cost = dis[i][j];
97             }
98         printf("%d\n",zhuliu(0,n,L,e));
99     }
100     return 0;
101 }

```

7 计算几何

7.1 基本函数

7.1.1 Point定义

```
1 struct Point
2 {
3     double x, y;
4     Point() {}
5     Point(double _x, double _y)
6     {
7         x = _x, y = _y;
8     }
9     Point operator -(const Point &b) const
10    {
11        return Point(x - b.x, y - b.y);
12    }
13    double operator *(const Point &b) const
14    {
15        return x * b.y - y * b.x;
16    }
17    double operator &(const Point &b) const
18    {
19        return x * b.x + y * b.y;
20    }
21    void transXY(double B)
22    {
23        double tx = x, ty = y;
24        x = tx*cos(B) - ty*sin(B);
25        y = tx*sin(B) + ty*cos(B);
26    }
27 };
```

7.1.2 Line定义

```
1 struct Line
2 {
3     Point s, e;
4     double k;
5     Line() {}
6     Line(Point _s, Point _e)
7     {
8         s = _s, e = _e;
9         k = atan2(e.y - s.y, e.x - s.x);
10    }
11    Point operator &(const Line &b) const
12    {
13        Point res = s;
14        //注意: 有些题目可能会有直线相交或者重合情况
15        //可以把返回值改成pair<Point,int>来返回两直线的状态。
16        double t = ((s - b.s) * (b.s - b.e)) / ((s - e) * (b.s -
            b.e));
```



```

17         res.x += (e.x - s.x) * t;
18         res.y += (e.y - s.y) * t;
19         return res;
20     }
21 };

```

7.1.3 距离：两点距离

```

1 double dist2(Point a, Point b)
2 {
3     return (a.x - b.x) * (a.x - b.x) + (a.y - b.y) * (a.y - b.y);
4 }

```

7.1.4 距离：点到直线距离

result:点到直线最近点

```

1 Point NPT(Point P, Line L)
2 {
3     Point result;
4     double a, b, t;
5
6     a = L.p2.x - L.p1.x;
7     b = L.p2.y - L.p1.y;
8     t = ( (P.x - L.p1.x) * a + (P.y - L.p1.y) * b ) / (a * a + b
          * b);
9
10    result.x = L.p1.x + a * t;
11    result.y = L.p1.y + b * t;
12    return dist2(P, result);
13 }

```

7.1.5 距离：点到线段距离

res: 点到线段最近点

```

1 double dist2(Point p1, Point p2, Point p)
2 {
3     Point res;
4     double a, b, t;
5     a = p2.x - p1.x;
6     b = p2.y - p1.y;
7     t = ((p.x - p1.x) * a + (p.y - p1.y) * b) / (a * a + b * b);
8     if (t >= 0 && t <= 1)
9     {
10        res.x = p1.x + a * t;
11        res.y = p1.y + b * t;
12    }
13    else
14    {
15        if (dist2(p, p1) < dist2(p, p2))
16            res = p1;
17        else
18            res = p2;
19    }

```

```

20 |     return dist2(p, res);
21 | }

```

旧版

```

1 | double CalcDis(Point a,Point s,Point e) //点到线段距离
2 | {
3 |     if (pmult(Point(s,e),Point(s,a)) < 0 || pmult(Point(e,s),
        Point(e,a)) < 0)
4 |         return min(CalcDis(a,s),CalcDis(a,e));
5 |     return abs(xmult(Point(a,s),Point(a,e)))/CalcDis(s,e);
6 | }

```

7.1.6 面积: 多边形

点按逆时针排序。

```

1 | double CalcArea(Point p[], int n)
2 | {
3 |     double res = 0;
4 |     for (int i = 0; i < n; i++)
5 |         res += (p[i] * p[(i + 1) % n]) / 2;
6 |     return res;
7 | }

```

7.1.7 判断: 线段相交

```

1 | bool inter(Line l1,Line l2)
2 | {
3 |     return (max(l1.s.x,l1.e.x) >= min(l2.s.x,l2.e.x) &&
4 |             max(l2.s.x,l2.e.x) >= min(l1.s.x,l1.e.x) &&
5 |             max(l1.s.y,l1.e.y) >= min(l2.s.y,l2.e.y) &&
6 |             max(l2.s.y,l2.e.y) >= min(l1.s.y,l1.e.y) &&
7 |             ((l2.s-l1.s)*(l1.e-l1.s))*((l2.e-l1.s)*(l1.e-l1.s))
            <= 0 &&
8 |             ((l1.s-l2.s)*(l2.e-l2.s))*((l1.e-l2.s)*(l2.e-l2.s))
            <= 0);
9 | }

```

7.2 圆

7.2.1 面积: 两圆相交

圆不可包含

```

1 | double dis(int x,int y)
2 | {
3 |     return sqrt((double)(x*x+y*y));
4 | }
5 | double area(int x1,int y1,int x2,int y2,double r1,double r2)
6 | {
7 |     double s=dis(x2-x1,y2-y1);
8 |     if(r1+r2<s) return 0;
9 |     else if(r2-r1>s) return PI*r1*r1;
10 |    else if(r1-r2>s) return PI*r2*r2;

```

```

11     double q1=acos((r1*r1+s*s-r2*r2)/(2*r1*s));
12     double q2=acos((r2*r2+s*s-r1*r1)/(2*r2*s));
13     return (r1*r1*q1+r2*r2*q2-r1*s*sin(q1));
14 }

```

7.2.2 三角形外接圆

```

1 void CircumscribedCircle()
2 {
3     for (int i = 0; i < 3; i++)
4         scanf("%lf%lf",&p[i].x,&p[i].y);
5     tp = Point((p[0].x+p[1].x)/2,(p[0].y+p[1].y)/2);
6     l[0] = Line(tp,Point(tp.x-(p[1].y-p[0].y),tp.y+(p[1].x-p[0].x
7         )),);
8     tp = Point((p[0].x+p[2].x)/2,(p[0].y+p[2].y)/2);
9     l[1] = Line(tp,Point(tp.x-(p[2].y-p[0].y),tp.y+(p[2].x-p[0].x
10        )),);
11     tp = LineToLine(l[0],l[1]);
12     r = Point(tp,p[0]).Length();
13     printf("(%.6f,%.6f,%.6f)\n",tp.x,tp.y,r);
14 }

```

7.2.3 三角形内切圆

```

1 void InscribedCircle()
2 {
3     for (int i = 0; i < 3; i++)
4         scanf("%lf%lf",&p[i].x,&p[i].y);
5     if (xmult(Point(p[0],p[1]),Point(p[0],p[2])) < 0)
6         swap(p[1],p[2]);
7     for (int i = 0; i < 3; i++)
8         len[i] = Point(p[i],p[(i+1)%3]).Length();
9     tr = (len[0]+len[1]+len[2])/2;
10    r = sqrt((tr-len[0])*(tr-len[1])*(tr-len[2])/tr);
11    for (int i = 0; i < 2; i++)
12    {
13        v = Point(p[i],p[i+1]);
14        tv = Point(-v.y,v.x);
15        tr = tv.Length();
16        tv = Point(tv.x*r/tr,tv.y*r/tr);
17        tp = Point(p[i].x+tv.x,p[i].y+tv.y);
18        l[i].s = tp;
19        tp = Point(p[i+1].x+tv.x,p[i+1].y+tv.y);
20        l[i].e = tp;
21    }
22    tp = LineToLine(l[0],l[1]);
23    printf("(%.6f,%.6f,%.6f)\n",tp.x,tp.y,r);
24 }

```

7.2.4 点对圆的两个切点

```

1 void calc_qie(Point poi,Point o,double r,Point &result1,Point &
    result2) {

```

```

2   double line=sqrt((poi.x-o.x)*(poi.x-o.x)+(poi.y-o.y)*(poi.y-o
   .y));
3   double angle=acos(r/line);
4   Point unitvector,lin;
5   lin.x=poi.x-o.x;
6   lin.y=poi.y-o.y;
7   unitvector.x=lin.x/sqrt(lin.x*lin.x+lin.y*lin.y)*r;
8   unitvector.y=lin.y/sqrt(lin.x*lin.x+lin.y*lin.y)*r;
9   result1=Rotate(unitvector,-angle);
10  result2=Rotate(unitvector,angle);
11  result1.x+=o.x;
12  result1.y+=o.y;
13  result2.x+=o.x;
14  result2.y+=o.y;
15  return;
16 }

```

7.2.5 两圆公切点

```

1 void Gao()
2 {
3     tn = 0;
4     Point a,b,vab;
5     double tab,tt,dis,theta;
6     for (int i = 0; i < tc; i++)
7         for (int j = 0; j < tc; j++)
8             if (i != j)
9                 {
10                     a = c[i];
11                     b = c[j];
12                     vab = Point(a,b);
13                     tab = atan2(vab.y,vab.x);
14                     dis = sqrt(vab.x*vab.x+vab.y*vab.y);
15                     if (b.r > a.r)
16                         tt = asin((b.r-a.r)/dis);
17                     else
18                         tt = -asin((a.r-b.r)/dis);
19                     theta = tab+pi/2+tt;
20                     tp[tn++] = Point(a.x+a.r*cos(theta),a.y+a.r*sin(
21                         theta));
21                     tp[tn++] = Point(b.x+b.r*cos(theta),b.y+b.r*sin(
22                         theta));
22                 }
23 }

```

7.3 矩阵

7.3.1 基本矩阵

按向量 $\overrightarrow{(x,y,z)}$ 平移:

$$\begin{pmatrix} 1 & 0 & 0 & x \\ 0 & 1 & 0 & y \\ 0 & 0 & 1 & z \\ 0 & 0 & 0 & 1 \end{pmatrix}$$

按比例 (x, y, z) 缩放:

$$\begin{pmatrix} x & 0 & 0 & 0 \\ 0 & y & 0 & 0 \\ 0 & 0 & z & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix}$$

绕向量 $\overrightarrow{(x, y, z)}$ 旋转 $angle$ 角度:

$$\begin{pmatrix} x^2 \times (1-c) + c & x \times y \times (1-c) - z \times s & x \times z \times (1-c) + y \times s & 0 \\ y \times x \times (1-c) + z \times s & y^2 \times (1-c) + c & y \times z \times (1-c) - x \times s & 0 \\ x \times z \times (1-c) - y \times s & y \times z \times (1-c) + x \times s & z^2 \times (1-c) + c & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix} \begin{cases} s = \sin(angle) \\ c = \cos(angle) \end{cases}$$

7.3.2 刘汝佳的几何教室

```

1 | const double pi = acos(-1.0);
2 |
3 | int n,m,q;
4 | struct Point
5 | {
6 |     double a,b,c,d;
7 | };
8 | Point p[50000],f[50000];
9 |
10 | double a,b,c,theta,mt[4][4],tmp[4][4],tmt[4][4],rmt[4][8];
11 | char com[20];
12 |
13 | void TRANSLATE()
14 | {
15 |     memset(tmt,0,sizeof(tmt));
16 |     tmt[0][0] = tmt[1][1] = tmt[2][2] = tmt[3][3] = 1;
17 |     tmt[3][0] = a;
18 |     tmt[3][1] = b;
19 |     tmt[3][2] = c;
20 |     memset(tmp,0,sizeof(tmp));
21 |     for (int i = 0; i < 4; i++)
22 |         for (int j = 0; j < 4; j++)
23 |             for (int k = 0; k < 4; k++)
24 |                 tmp[i][j] += mt[i][k]*tmt[k][j];
25 |     for (int i = 0; i < 4; i++)
26 |         for (int j = 0; j < 4; j++)
27 |             mt[i][j] = tmp[i][j];
28 | }
29 |
30 | void ROTATE()
31 | {
32 |     theta = -theta*pi/180;
33 |     memset(tmt,0,sizeof(tmt));
34 |     tmt[3][3] = 1;
35 |     tmt[0][0] = cos(theta)+(1-cos(theta))*a*a;
```

```

36     tmt[1][0] = (1-cos(theta))*a*b+c*sin(theta);
37     tmt[2][0] = (1-cos(theta))*a*c-b*sin(theta);
38     tmt[0][1] = (1-cos(theta))*a*b-c*sin(theta);
39     tmt[1][1] = cos(theta)+(1-cos(theta))*b*b;
40     tmt[2][1] = (1-cos(theta))*b*c+a*sin(theta);
41     tmt[0][2] = (1-cos(theta))*a*c+b*sin(theta);
42     tmt[1][2] = (1-cos(theta))*b*c-a*sin(theta);
43     tmt[2][2] = cos(theta)+(1-cos(theta))*c*c;
44     memset(tmp,0,sizeof(tmp));
45     for (int i = 0; i < 4; i++)
46         for (int j = 0; j < 4; j++)
47             for (int k = 0; k < 4; k++)
48                 tmp[i][j] += mt[i][k]*tmt[k][j];
49     for (int i = 0; i < 4; i++)
50         for (int j = 0; j < 4; j++)
51             mt[i][j] = tmp[i][j];
52 }
53
54 void SCALE()
55 {
56     memset(tmt,0,sizeof(tmt));
57     tmt[0][0] = a;
58     tmt[1][1] = b;
59     tmt[2][2] = c;
60     tmt[3][3] = 1;
61     memset(tmp,0,sizeof(tmp));
62     for (int i = 0; i < 4; i++)
63         for (int j = 0; j < 4; j++)
64             for (int k = 0; k < 4; k++)
65                 tmp[i][j] += mt[i][k]*tmt[k][j];
66     for (int i = 0; i < 4; i++)
67         for (int j = 0; j < 4; j++)
68             mt[i][j] = tmp[i][j];
69 }
70
71 void solvep(Point p)
72 {
73     memset(tmt,0,sizeof(tmt));
74     tmt[0][0] = p.a;
75     tmt[0][1] = p.b;
76     tmt[0][2] = p.c;
77     tmt[0][3] = 1;
78     memset(tmp,0,sizeof(tmp));
79     for (int i = 0; i < 1; i++)
80         for (int j = 0; j < 4; j++)
81             for (int k = 0; k < 4; k++)
82                 tmp[i][j] += tmt[i][k]*mt[k][j];
83     printf("%.2f□%.2f□%.2f\n",tmp[0][0],tmp[0][1],tmp[0][2]);
84 }
85
86 void solvef(Point f)
87 {

```

```

88     memset(tmt,0,sizeof(tmt));
89     tmt[0][0] = f.a;
90     tmt[1][0] = f.b;
91     tmt[2][0] = f.c;
92     tmt[3][0] = 0;
93     memset(tmp,0,sizeof(tmp));
94     for (int i = 0;i < 4;i++)
95         for (int j = 0;j < 1;j++)
96             for (int k = 0;k < 4;k++)
97                 tmp[i][j] += mt[i][k]*tmt[k][j];
98     tmp[3][0] += f.d;
99     double kk = tmp[0][0]*tmp[0][0]+tmp[1][0]*tmp[1][0]+tmp
        [2][0]*tmp[2][0];
100    kk = sqrt(1/kk);
101    for (int i = 0;i < 4;i++)
102        printf("%.2f□",tmp[i][0]*kk);
103    printf("\n");
104 }
105
106 void solvermt()
107 {
108     memset(rmt,0,sizeof(rmt));
109     for (int i = 0;i < 4;i++)
110         for (int j = 0;j < 4;j++)
111             rmt[i][j] = mt[i][j];
112     rmt[0][4] = rmt[1][5] = rmt[2][6] = rmt[3][7] = 1;
113     for (int i = 0;i < 4;i++)
114     {
115         for (int j = i;j < 4;j++)
116             if (fabs(rmt[j][i]) > 1e-8)
117             {
118                 for (int k = i;k < 8;k++)
119                     swap(rmt[i][k],rmt[j][k]);
120                 break;
121             }
122         double tt = rmt[i][i];
123         for (int j = i;j < 8;j++)
124             rmt[i][j] /= tt;
125         for (int j = 0;j < 4;j++)
126             if (i != j)
127             {
128                 tt = rmt[j][i];
129                 for (int k = i;k < 8;k++)
130                     rmt[j][k] -= rmt[i][k]*tt;
131             }
132     }
133     for (int i = 0;i < 4;i++)
134         for (int j = 0;j < 4;j++)
135             mt[i][j] = rmt[i][4+j];
136 }
137
138 int main()

```

```

139 {
140     scanf("%d%d%d",&n,&m,&q);
141     for (int i = 0; i < n; i++)
142         scanf("%lf%lf%lf",&p[i].a,&p[i].b,&p[i].c);
143     for (int i = 0; i < m; i++)
144         scanf("%lf%lf%lf%lf",&f[i].a,&f[i].b,&f[i].c,&f[i].d);
145     memset(mt,0,sizeof(mt));
146     mt[0][0] = mt[1][1] = mt[2][2] = mt[3][3] = 1;
147     for (int i = 0; i < q; i++)
148     {
149         scanf("%s",com);
150         if (strcmp(com,"TRANSLATE") == 0)
151         {
152             scanf("%lf%lf%lf",&a,&b,&c);
153             TRANSLATE();
154         }
155         else if (strcmp(com,"ROTATE") == 0)
156         {
157             scanf("%lf%lf%lf%lf",&a,&b,&c,&theta);
158             ROTATE();
159         }
160         else if (strcmp(com,"SCALE") == 0)
161         {
162             scanf("%lf%lf%lf",&a,&b,&c);
163             SCALE();
164         }
165     }
166     //处理点
167     for (int i = 0; i < n; i++)
168         solvep(p[i]);
169     //处理面
170     solvermt();
171     for (int i = 0; i < m; i++)
172         solvef(f[i]);
173     return 0;
174 }

```

7.4 重心

```

1 Point CenterOfPolygon(Point poly[],int n)
2 {
3     Point p, p0, p1, p2, p3;
4     double m, m0;
5     p1 = poly[0];
6     p2 = poly[1];
7     p.x = p.y = m = 0;
8     for (int i = 2; i < n; i++)
9     {
10         p3 = poly[i];
11         p0.x = (p1.x + p2.x + p3.x) / 3.0;
12         p0.y = (p1.y + p2.y + p3.y) / 3.0;
13         m0 = p1.x * p2.y + p2.x * p3.y + p3.x * p1.y - p1.y * p2.x - p2
            .y * p3.x - p3.y * p1.x;

```



```

14     if (cmp(m + m0, 0.0) == 0)
15         m0 += eps;
16     p.x = (m * p.x + m0 * p0.x) / (m + m0);
17     p.y = (m * p.y + m0 * p0.y) / (m + m0);
18     m = m + m0;
19     p2 = p3;
20 }
21     return p;
22 }

```

7.5 KD树

查找某个点距离最近的点，基本思想是每次分治把点分成两部分，建议按照坐标规模决定是垂直划分还是水平划分，查找时先往分到的那一部分查找，然后根据当前最优答案决定是否去另一个区间查找。

```

1  bool Div[MaxN];
2  void BuildKD(int deep, int l, int r, Point p[])\\记得备份一下p
3  {
4      if (l > r) return;
5      int mid = l + r >> 1;
6      int minX, minY, maxX, maxY;
7      minX = min_element(p + l, p + r + 1, cmpX)->x;
8      minY = min_element(p + l, p + r + 1, cmpY)->y;
9      maxX = max_element(p + l, p + r + 1, cmpX)->x;
10     maxY = max_element(p + l, p + r + 1, cmpY)->y;
11     Div[mid] = (maxX - minX >= maxY - minY);
12     nth_element(p + l, p + mid, p + r + 1, Div[mid] ? cmpX : cmpY);
13     BuildKD(l, mid - 1, p);
14     BuildKD(mid + 1, r, p);
15 }
16
17 long long res;
18 void Find(int l, int r, Point a, Point p[])\\查找
19 {
20     if (l > r) return;
21     int mid = l + r >> 1;
22     long long dist = dist2(a, p[mid]);
23     if (dist > 0)\\如果有重点不能这样判断
24         res = min(res, dist);
25     long long d = Div[mid] ? (a.x - p[mid].x) : (a.y - p[mid].y);
26     int l1, l2, r1, r2;
27     l1 = l, l2 = mid + 1;
28     r1 = mid - 1, r2 = r;
29     if (d > 0)
30         swap(l1, l2), swap(r1, r2);
31     Find(l1, r1, a, p);
32     if (d * d < res)
33         Find(l2, r2, a, p);
34 }

```

7.5.1 例题

查询一个点为中心的给定正方形内所有点并删除 (2012金华网赛A)

```
1  #include <iostream>
2  #include <cstdio>
3  #include <cstring>
4  #include <algorithm>
5  #include <cmath>
6  #include <queue>
7  using namespace std;
8
9  const int MaxN = 100000;
10 struct Point
11 {
12     int x,y,r;
13     int id;
14     bool del;
15 };
16
17 int cmpTyp;
18 bool cmp(const Point& a,const Point& b)
19 {
20     if (cmpTyp == 0)
21         return a.x < b.x;
22     else
23         return a.y < b.y;
24 }
25
26 int cnt[MaxN];
27 bool Div[MaxN];
28 int minX[MaxN],minY[MaxN],maxX[MaxN],maxY[MaxN];
29 void BuildKD(int l,int r,Point p[])
30 {
31     if (l > r) return;
32     int mid = l+r>>1;
33     cmpTyp = 0;
34     minX[mid] = min_element(p+l,p+r+1,cmp)->x;
35     maxX[mid] = max_element(p+l,p+r+1,cmp)->x;
36     cmpTyp = 1;
37     minY[mid] = min_element(p+l,p+r+1,cmp)->y;
38     maxY[mid] = max_element(p+l,p+r+1,cmp)->y;
39
40     cnt[mid] = r-l+1;
41     cmpTyp = Div[mid] = (maxX[mid]-minX[mid] < maxY[mid]-minY[mid])
42         ;
43     nth_element(p+l,p+mid,p+r+1,cmp);
44     BuildKD(l,mid-1,p);
45     BuildKD(mid+1,r,p);
46 }
47 queue<int> Q;
```

```

48 int Find(int l,int r,Point a,Point p[])
49 {
50     if (l > r) return 0;
51     int mid = l+r>>1;
52     if (cnt[mid] == 0) return 0;
53
54     if (maxX[mid] < a.x-a.r ||
55         minX[mid] > a.x+a.r ||
56         maxY[mid] < a.y-a.r ||
57         minY[mid] > a.y+a.r)
58         return 0;
59
60     int totdel = 0;
61
62     if (p[mid].del == false)
63         if (abs(p[mid].x-a.x) <= a.r && abs(p[mid].y-a.y) <= a.r)
64         {
65             p[mid].del = true;
66             Q.push(p[mid].id);
67             totdel++;
68         }
69
70     totdel += Find(l,mid-1,a,p);
71     totdel += Find(mid+1,r,a,p);
72
73     cnt[mid] -= totdel;
74
75     return totdel;
76 }
77
78 Point p[MaxN],tp[MaxN];
79 int n;
80
81 int main()
82 {
83     int cas = 1;
84     while (true)
85     {
86         scanf("%d",&n);
87         if (n == 0) break;
88
89         for (int i = 0;i < n;i++)
90         {
91             p[i].id = i;
92             int tx,ty;
93             scanf("%d%d",&tx,&ty,&p[i].r);
94             p[i].x = tx-ty;
95             p[i].y = tx+ty;
96             p[i].del = false;
97             tp[i] = p[i];
98         }
99         BuildKD(0,n-1,tp);

```

```

100
101     printf("Case_#%d:\n",cas++);
102     int q;
103     scanf("%d",&q);
104     for (int i = 0;i < q;i++)
105     {
106         int id;
107         scanf("%d",&id);
108         int res = 0;
109         id--;
110         Q.push(id);
111         while (!Q.empty())
112         {
113             int now = Q.front();
114             Q.pop();
115             if (p[now].del == true) continue;
116             p[now].del = true;
117             res += Find(0,n-1,p[now],tp);
118         }
119         printf("%d\n",res);
120     }
121 }
122 return 0;
123 }

```

7.6 半平面交

直线左边代表有效区域。

```

1 bool HPIcmp(Line a, Line b)
2 {
3     if (fabs(a.k - b.k) > eps)    return a.k < b.k;
4     return ((a.s - b.s) * (b.e-b.s)) < 0;
5 }
6
7 Line Q[100];
8 void HPI(Line line[], int n, Point res[], int &resn)
9 {
10     int tot = n;
11     sort(line, line + n, HPIcmp);
12     tot = 1;
13     for (int i = 1; i < n; i++)
14         if (fabs(line[i].k - line[i - 1].k) > eps)
15             line[tot++] = line[i];
16     int head = 0, tail = 1;
17     Q[0] = line[0];
18     Q[1] = line[1];
19     resn = 0;
20     for (int i = 2; i < tot; i++)
21     {
22         if (fabs((Q[tail].e-Q[tail].s) * (Q[tail - 1].e-Q[tail -

```

```

23         fabs((Q[head].e-Q[head].s) * (Q[head + 1].e-Q[
24             head + 1].s)) < eps)
25         return;
26     while (head < tail && (((Q[tail]&Q[tail - 1]) - line[i].s
27         ) * (line[i].e-line[i].s)) > eps)
28         tail--;
29     while (head < tail && (((Q[head]&Q[head + 1]) - line[i].s
30         ) * (line[i].e-line[i].s)) > eps)
31         head++;
32     Q[++tail] = line[i];
33 }
34 while (head < tail && (((Q[tail]&Q[tail - 1]) - Q[head].s) *
35     (Q[head].e-Q[head].s)) > eps)
36     tail--;
37 while (head < tail && (((Q[head]&Q[head + 1]) - Q[tail].s) *
38     (Q[tail].e-Q[tail].s)) > eps)
39     head++;
40 if (tail <= head + 1) return;
41 for (int i = head; i < tail; i++)
42     res[resn++] = Q[i] & Q[i + 1];
43 if (head < tail + 1)
44     res[resn++] = Q[head] & Q[tail];
45 }

```

7.7 凸包

得到的凸包按照逆时针方向排序。

```

1 bool GScmp(Point a, Point b)
2 {
3     if (fabs(a.x - b.x) < eps)
4         return a.y < b.y - eps;
5     return a.x < b.x - eps;
6 }
7
8 void GS(Point p[], int n, Point res[], int &resn)
9 {
10     resn = 0;
11     int top = 0;
12     sort(p, p + n, GScmp);
13     for (int i = 0; i < n; i++)
14         if (resn < 2 || (res[resn - 1] - res[resn - 2]) * (p[i] -
15             res[resn - 1]) > eps)
16             res[resn++] = p[i++];
17         else
18             --resn;
19     top = resn - 1;
20     for (int i = n - 2; i >= 0; i--)
21         if (resn < top + 2 || (res[resn - 1] - res[resn - 2]) * (
22             p[i] - res[resn - 1]) > eps)
23             res[resn++] = p[i--];
24         else
25             --resn;

```

```

24     resn--;
25     if (resn < 3)     resn = 0;
26 }

```

7.8 直线与凸包求交点

复杂度 $O(\log n)$ 。

需要先预处理几个东西。

```

1 //二分[la,lb]这段区间那条边与line相交
2 int Gao(int la,int lb,Line line)
3 {
4     if (la > lb)
5         lb += n;
6     int l = la,r = lb,mid;
7     while (l < r)
8     {
9         mid = l+r+1>>1;
10        if (cmp((line.e-line.s)*(p[la]-line.s),0)*cmp((line.e-
11            line.s)*(p[mid]-line.s),0) >= 0)
12            l = mid;
13        else
14            r = mid-1;
15    }
16    return l%n;
17 }
18 //求l与凸包的交点
19 //先调用Gettheta预处理出凸包每条边的斜率，然后处理成升序排列
20 double theta[maxn];
21
22 void Gettheta()
23 {
24     for (int i = 0;i < n;i++)
25     {
26         Point v = p[(i+1)%n]-p[i];
27         theta[i] = atan2(v.y,v.x);
28     }
29     for (int i = 1;i < n;i++)
30         if (theta[i-1] > theta[i]+eps)
31             theta[i] += 2*pi;
32 }
33
34 double Calc(Line l)
35 {
36     double tnow;
37     Point v = l.e-l.s;
38     tnow = atan2(v.y,v.x);
39     if (cmp(tnow,theta[0]) < 0)     tnow += 2*pi;
40     int pl = lower_bound(theta,theta+n,tnow)-theta;
41     tnow = atan2(-v.y,-v.x);
42     if (cmp(tnow,theta[0]) < 0)     tnow += 2*pi;

```

```

43     int pr = lower_bound(theta, theta+n, tnow)-theta;
44     //pl和pr是在l方向上距离最远的点对
45     pl = pl%n;
46     pr = pr%n;
47
48     if (cmp(v*(p[pl]-l.s), 0)*cmp(v*(p[pr]-l.s), 0) >= 0)
49         return 0.0;
50
51     int xa = Gao(pl, pr, l);
52     int xb = Gao(pr, pl, l);
53
54     if (xa > xb)        swap(xa, xb);
55     //与[xa, xa+1]和[xb, xb+1]这两条线段相交
56
57     if (cmp(v*(p[xa+1]-p[xa]), 0) == 0)    return 0.0;
58     if (cmp(v*(p[xb+1]-p[xb]), 0) == 0)    return 0.0;
59
60     Point pa, pb;
61     pa = Line(p[xa], p[xa+1])&l;
62     pb = Line(p[xb], p[xb+1])&l;
63     //题目：求直线切凸包得到的两部分的面积
64     double area0 = sum[xb]-sum[xa+1]+(pa*p[xa+1])/2.0+(p[xb]*pb)
65         /2.0+(pb*pa)/2.0;
66     double area1 = sum[xa+n]-sum[xb+1]+(pb*p[xb+1])/2.0+(p[xa]*pa
67         )/2.0+(pa*pb)/2.0;
68     return min(area0, area1);
69 }

```

7.9 三维凸包

暴力写法

```

1  #define eps 1e-7
2  #define MAXV 505
3
4  struct pt
5  {
6      double x, y, z;
7      pt() {}
8      pt(double _x, double _y, double _z): x(_x), y(_y), z(_z) {}
9      pt operator - (const pt p1)
10     {
11         return pt(x - p1.x, y - p1.y, z - p1.z);
12     }
13     pt operator * (pt p)
14     {
15         return pt(y*p.z-z*p.y, z*p.x-x*p.z, x*p.y-y*p.x);
16     }
17     double operator ^ (pt p)
18     {
19         return x*p.x+y*p.y+z*p.z;

```

```

20     }
21 };
22 struct _3DCH
23 {
24     struct fac
25     {
26         int a, b, c;
27         bool ok;
28     };
29     int n;
30     pt P[MAXV];
31     int cnt;
32     fac F[MAXV*8];
33     int to[MAXV][MAXV];
34     double vlen(pt a)
35     {
36         return sqrt(a.x*a.x+a.y*a.y+a.z*a.z);
37     }
38     double area(pt a, pt b, pt c)
39     {
40         return vlen((b-a)*(c-a));
41     }
42     double volume(pt a, pt b, pt c, pt d)
43     {
44         return (b-a)*(c-a)^(d-a);
45     }
46     double ptof(pt &p, fac &f)
47     {
48         pt m = P[f.b]-P[f.a], n = P[f.c]-P[f.a], t = p-P[f.a];
49         return (m * n) ^ t;
50     }
51     void deal(int p, int a, int b)
52     {
53         int f = to[a][b];
54         fac add;
55         if (F[f].ok)
56         {
57             if (ptof(P[p], F[f]) > eps)
58                 dfs(p, f);
59             else
60             {
61                 add.a = b, add.b = a, add.c = p, add.ok = 1;
62                 to[p][b] = to[a][p] = to[b][a] = cnt;
63                 F[cnt++] = add;
64             }
65         }
66     }
67     void dfs(int p, int cur)
68     {
69         F[cur].ok = 0;
70         deal(p, F[cur].b, F[cur].a);
71         deal(p, F[cur].c, F[cur].b);

```



```

72         deal(p, F[cur].a, F[cur].c);
73     }
74     bool same(int s, int t)
75     {
76         pt &a = P[F[s].a], &b = P[F[s].b], &c = P[F[s].c];
77         return fabs(volume(a, b, c, P[F[t].a])) < eps && fabs(
78             volume(a, b, c,
79                 P[F[t].b])) < eps && fabs(volume(a, b, c, P[F[t].
80                 c])) < eps;
81     }
82     void construct()
83     {
84         cnt = 0;
85         if (n < 4)
86             return;
87         bool sb = 1;
88         for (int i = 1; i < n; i++)
89         {
90             if (vlen(P[0] - P[i]) > eps)
91             {
92                 swap(P[1], P[i]);
93                 sb = 0;
94                 break;
95             }
96         }
97         if (sb) return;
98         sb = 1;
99         for (int i = 2; i < n; i++)
100         {
101             if (vlen((P[0] - P[1]) * (P[1] - P[i]))) > eps)
102             {
103                 swap(P[2], P[i]);
104                 sb = 0;
105                 break;
106             }
107         }
108         if (sb) return;
109         sb = 1;
110         for (int i = 3; i < n; i++)
111         {
112             if (fabs((P[0] - P[1]) * (P[1] - P[2]) ^ (P[0] - P[i]
113                 ])) > eps)
114             {
115                 swap(P[3], P[i]);
116                 sb = 0;
117                 break;
118             }
119         }
120         if (sb) return;
121         fac add;
122         for (int i = 0; i < 4; i++)
123         {

```

```

121         add.a = (i+1)%4, add.b = (i+2)%4, add.c = (i+3)%4,
           add.ok = 1;
122         if (ptof(P[i], add) > 0)
123             swap(add.b, add.c);
124         to[add.a][add.b] = to[add.b][add.c] = to[add.c][add.a]
           ] = cnt;
125         F[cnt++] = add;
126     }
127     for (int i = 4; i < n; i++)
128     {
129         for (int j = 0; j < cnt; j++)
130         {
131             if (F[j].ok && ptof(P[i], F[j]) > eps)
132             {
133                 dfs(i, j);
134                 break;
135             }
136         }
137     }
138     int tmp = cnt;
139     cnt = 0;
140     for (int i = 0; i < tmp; i++)
141     {
142         if (F[i].ok)
143         {
144             F[cnt++] = F[i];
145         }
146     }
147 }
148 //表面积
149 double area()
150 {
151     double ret = 0.0;
152     for (int i = 0; i < cnt; i++)
153     {
154         ret += area(P[F[i].a], P[F[i].b], P[F[i].c]);
155     }
156     return ret / 2.0;
157 }
158 //体积
159 double volume()
160 {
161     pt O(0, 0, 0);
162     double ret = 0.0;
163     for (int i = 0; i < cnt; i++)
164     {
165         ret += volume(O, P[F[i].a], P[F[i].b], P[F[i].c]);
166     }
167     return fabs(ret / 6.0);
168 }
169 //表面三角形数
170 int facetCnt_tri()

```

```

171     {
172         return cnt;
173     }
174 //表面多边形数
175     int facetCnt()
176     {
177         int ans = 0;
178         for (int i = 0; i < cnt; i++)
179         {
180             bool nb = 1;
181             for (int j = 0; j < i; j++)
182             {
183                 if (same(i, j))
184                 {
185                     nb = 0;
186                     break;
187                 }
188             }
189             ans += nb;
190         }
191         return ans;
192     }
193
194     pt Fc[MAXV*8];
195     double V[MAXV*8];
196     pt Center()//重心
197     {
198         pt O(0,0,0);
199         for (int i = 0; i < cnt; i++)
200         {
201             Fc[i].x = (O.x+P[F[i].a].x+P[F[i].b].x+P[F[i].c].x)
202                     /4.0;
203             Fc[i].y = (O.y+P[F[i].a].y+P[F[i].b].y+P[F[i].c].y)
204                     /4.0;
205             Fc[i].z = (O.z+P[F[i].a].z+P[F[i].b].z+P[F[i].c].z)
206                     /4.0;
207             V[i] = volume(O,P[F[i].a],P[F[i].b],P[F[i].c]);
208         }
209         pt res = Fc[0],tmp;
210         double m = V[0];
211         for (int i = 1; i < cnt; i++)
212         {
213             if (fabs(m+V[i]) < eps)
214                 V[i] += eps;
215             tmp.x = (m*res.x+V[i]*Fc[i].x)/(m+V[i]);
216             tmp.y = (m*res.y+V[i]*Fc[i].y)/(m+V[i]);
217             tmp.z = (m*res.z+V[i]*Fc[i].z)/(m+V[i]);
218             m += V[i];
219             res = tmp;
220         }
221         return res;
222     }
223 }

```

```

220 };
221
222 _3DCH hull;
223
224 int main()
225 {
226     while (scanf("%d",&hull.n) != EOF)
227     {
228         for (int i = 0; i < hull.n; i++)
229             scanf("%lf%lf%lf",&hull.P[i].x,&hull.P[i].y,&hull.P[i]
                ].z);
230         hull.construct();
231     }
232     return 0;
233 }

```

7.10 旋转卡壳

“对踵”

7.10.1 单个凸包

```

1 void solve(Point p[],int n)
2 {
3     Point v;
4     int cur = 1;
5     for (int i = 0;i < n;i++)
6     {
7         v = p[i]-p[(i+1)%n];
8         while (v*(p[(cur+1)%n]-p[cur]) < 0)
9             cur = (cur+1)%n;
10        //p[cur] -> p[i]
11        //p[cur] -> p[i+1]
12        //p[cur] -> (p[i],p[i+1])
13    }
14 }

```

7.10.2 两个凸包

注意初始点的选取，代码只是个示例。

有时候答案需要取solve(p0,n,p1,m)和solve(p1,m,p0,n)的最优值。

何老鱼说我是错的。。

```

1 void solve(Point p0[],int n,Point p1[],int m)
2 {
3     Point v;
4     int cur = 0;
5     for (int i = 0;i < n;i++)
6     {
7         v = p0[i]-p0[(i+1)%n];
8         while (v*(p1[(cur+1)%m]-p1[cur]) < 0)
9             cur = (cur+1)%m;

```

```

10      //p1[cur] -> p0[i]
11      //p1[cur] -> p0[i+1]
12      //p1[cur] -> (p0[i],p0[i+1])
13  }
14 }

```

7.10.3 外接矩形

```

1 void solve()
2 {
3     resa = resb = 1e100;
4     double dis1,dis2;
5     Point xp[4];
6     Line l[4];
7     int a,b,c,d;
8     int sa,sb,sc,sd;
9     a = b = c = d = 0;
10    sa = sb = sc = sd = 0;
11    Point va,vb,vc,vd;
12    for (a = 0; a < n; a++)
13    {
14        va = Point(p[a],p[(a+1)%n]);
15        vc = Point(-va.x,-va.y);
16        vb = Point(-va.y,va.x);
17        vd = Point(-vb.x,-vb.y);
18        if (sb < sa)
19        {
20            b = a;
21            sb = sa;
22        }
23        while (xmult(vb,Point(p[b],p[(b+1)%n])) < 0)
24        {
25            b = (b+1)%n;
26            sb++;
27        }
28        if (sc < sb)
29        {
30            c = b;
31            sc = sb;
32        }
33        while (xmult(vc,Point(p[c],p[(c+1)%n])) < 0)
34        {
35            c = (c+1)%n;
36            sc++;
37        }
38        if (sd < sc)
39        {
40            d = c;
41            sd = sc;
42        }
43        while (xmult(vd,Point(p[d],p[(d+1)%n])) < 0)
44        {

```

```

45         d = (d+1)%n;
46         sd++;
47     }
48
49     //卡在p[a],p[b],p[c],p[d]上
50     sa++;
51 }
52 }

```

7.11 三角形内点个数

7.11.1 无三点共线

```

1 Point p[1000], tp[2000], base;
2
3 bool cmp(const Point &a, const Point &b)
4 {
5     return a.theta < b.theta;
6 }
7
8 int cnt[1000][1000];
9 int cntleft[1000][1000];
10 int n, m;
11
12 int calc(int a, int b, int c)
13 {
14     Point p1 = p[b] - p[a], p2 = p[c] - p[a];
15     if (atan2(p1.y, p1.x) > atan2(p2.y, p2.x))
16         swap(b, c);
17     if ((p[b] - p[a]) * (p[c] - p[a]) > 0)
18         return cnt[a][c] - cnt[a][b] - 1;
19     else
20         return n - 3 - (cnt[a][c] - cnt[a][b] - 1);
21 }
22
23 int main(int argc, char const *argv[])
24 {
25     int totcas;
26     scanf("%d", &totcas);
27     for (int cas = 1; cas <= totcas; ++cas)
28     {
29         scanf("%d", &n);
30         for (int i = 0; i < n; ++i)
31         {
32             scanf("%lld%lld", &p[i].x, &p[i].y);
33             p[i].id = i;
34         }
35         for (int i = 0; i < n; ++i)
36         {
37             m = 0;
38             base = p[i];
39             for (int j = 0; j < n; ++j)
40                 if (i != j)

```

```

41         {
42             tp[m] = p[j];
43             Point v = tp[m]-base;
44             tp[m++].theta = atan2(v.y,v.x);
45         }
46
47         sort(tp, tp + m, cmp);
48         for (int j = 0; j < m; ++j)
49             tp[m + j] = tp[j];
50
51         //calc cnt
52         for (int j = 0; j < m; ++j)
53             cnt[i][tp[j].id] = j;
54
55         //calc cntleft
56         for (int j = 0, k = 0, tot = 0; j < m; ++j)
57         {
58             while (k == j || (k < j + m && (tp[j] - base) * (
59                 tp[k] - base) > 0))
60                 k++, tot++;
61             cntleft[i][tp[j].id] = --tot;
62         }
63
64         printf("Case_□%d:\n", cas);
65         int q;
66         scanf("%d", &q);
67         for (int i = 0; i < q; ++i)
68         {
69             int x, y, z;
70             scanf("%d%d%d", &x, &y, &z);
71             if ((p[z] - p[x]) * (p[y] - p[x]) > 0)
72                 swap(y, z);
73             int res = cntleft[x][z] + cntleft[z][y] + cntleft[y][
74                 x];
75             res += calc(x, y, z) + calc(y, z, x) + calc(z, x, y);
76             res -= 2 * (n - 3);
77             printf("%d\n", res);
78         }
79         return 0;
80     }

```

7.11.2 有三点共线且点有类别之分

```

1  int n,n0,n1,m;
2  Point p[3000], tp[3000], base;
3
4  bool cmp(const Point &a, const Point &b)
5  {
6      if ((a-base)*(b-base) == 0)
7      {
8          return (a-base).getMol() < (b-base).getMol();

```

```

9      }
10     return a.theta < b.theta;
11 }
12
13 int cnt[100][100];
14 int cntleft[100][100];
15
16 int calc(int a,int b,int c)
17 {
18     Point p1 = p[b]-p[a],p2 = p[c]-p[a];
19     if (atan2(1.0*p1.y,1.0*p1.x) > atan2(1.0*p2.y,1.0*p2.x))
20         swap(b,c);
21     int res = cnt[a][c]-cnt[a][b];
22     if ((p[b]-p[a])*(p[c]-p[a]) > 0)
23         return res;
24     else
25         return n1-res;
26 }
27
28 int main()
29 {
30     int cas = 0;
31     while (scanf("%d%d",&n0,&n1) != EOF)
32     {
33         n = n1+n0;
34         for (int i = 0; i < n; i++)
35         {
36             scanf("%I64d%I64d",&p[i].x,&p[i].y);
37             p[i].id = i;
38         }
39         for (int i = 0; i < n0; ++i)
40         {
41             m = 0;
42             base = p[i];
43             for (int j = 0; j < n; ++j)
44                 if (i != j)
45                 {
46                     tp[m] = p[j];
47                     Point v = tp[m]-base;
48                     tp[m++].theta = atan2(1.0*v.y,1.0*v.x);
49                 }
50
51             sort(tp, tp + m, cmp);
52             for (int j = 0; j < m; ++j)
53                 tp[m + j] = tp[j];
54
55             for (int j = 0,tot = 0; j < m; ++j)
56             {
57                 if (tp[j].id < n0)
58                     cnt[i][tp[j].id] = tot;
59                 else
60                     tot++;

```



```

61         }
62
63         for (int j = 0, k = 0, tot = 0; j < m; ++j)
64         {
65             while (k == j || (k < j + m && (tp[j] - base) * (
66                 tp[k] - base) > 0))
67             {
68                 if (tp[k].id >= n0)
69                     tot++;
70                 k++;
71             }
72             if (tp[j].id >= n0)
73                 tot--;
74             else
75                 cntleft[i][tp[j].id] = tot;
76         }
77
78         int ans = 0;
79         for (int i = 0; i < n0; i++)
80             for (int j = i+1; j < n0; j++)
81                 for (int k = j+1; k < n0; k++)
82                 {
83                     int x = i, y = j, z = k;
84
85                     if ((p[z] - p[x]) * (p[y] - p[x]) > 0)
86                         swap(y, z);
87                     int res = cntleft[x][z] + cntleft[z][y] +
88                         cntleft[y][x];
89
90                     res += calc(x, y, z) + calc(y, z, x) + calc(z
91                         , x, y);
92
93                     res -= 2 * n1;
94
95                     //printf("%d %d %d %d\n", x, y, z, res);
96
97                     if (res%2 == 1)
98                         ans++;
99                 }
100         printf("Case %d: %d\n", ++cas, ans);
101     }
102     return 0;
103 }

```

7.12 最近点对

7.12.1 类快排算法

```

1 double calc_dis(Point &a ,Point &b) {
2     return sqrt((a.x-b.x)*(a.x-b.x) + (a.y-b.y)*(a.y-b.y));
3 }
4 //别忘了排序

```

```

5 | bool operator<(const Point &a ,const Point &b) {
6 |     if(a.y != b.y) return a.x < b.x;
7 |     return a.x < b.x;
8 | }
9 | double Gao(int l ,int r ,Point pnts[]) {
10 |     double ret = inf;
11 |     if(l == r) return ret;
12 |     if(l+1 ==r) {
13 |         ret = min(calc_dis(pnts[l],pnts[l+1]) ,ret);
14 |         return ret;
15 |     }
16 |     if(l+2 ==r) {
17 |         ret = min(calc_dis(pnts[l],pnts[l+1]) ,ret);
18 |         ret = min(calc_dis(pnts[l],pnts[l+2]) ,ret);
19 |         ret = min(calc_dis(pnts[l+1],pnts[l+2]) ,ret);
20 |         return ret;
21 |     }
22 |
23 |     int mid = l+r>>1;
24 |     ret = min (ret ,Gao(l ,mid,pnts));
25 |     ret = min (ret , Gao(mid+1, r,pnts));
26 |
27 |     for(int c = l ; c<=r; c++)
28 |         for(int d = c+1; d <=c+7 && d<=r; d++) {
29 |             ret = min(ret , calc_dis(pnts[c],pnts[d]));
30 |         }
31 |     return ret;
32 | }

```

7.12.2 随机增量法

```

1 | #include <iostream>
2 | #include <cstdio>
3 | #include <cstring>
4 | #include <map>
5 | #include <vector>
6 | #include <cmath>
7 | #include <algorithm>
8 | #define Point pair<double,double>
9 | using namespace std;
10 |
11 | const int step[9][2] =
12 |     {{-1,-1},{-1,0},{-1,1},{0,-1},{0,0},{0,1},{1,-1},{1,0},{1,1}};
13 | int n,x,y,nx,ny;
14 | map<pair<int,int>,vector<Point > > g;
15 | vector<Point > tmp;
16 | Point p[20000];
17 | double tx,ty,ans,nowans;
18 | vector<Point >::iterator it,op,ed;
19 | pair<int,int> gird;
20 | bool flag;
21 | double Dis(Point p0,Point p1)

```

```

22 {
23     return sqrt((p0.first-p1.first)*(p0.first-p1.first)+
24                (p0.second-p1.second)*(p0.second-p1.second));
25 }
26
27 double CalcDis(Point p0,Point p1,Point p2)
28 {
29     return Dis(p0,p1)+Dis(p0,p2)+Dis(p1,p2);
30 }
31
32 void build(int n,double w)
33 {
34     g.clear();
35     for (int i = 0;i < n;i++)
36         g[make_pair((int)floor(p[i].first/w),(int)floor(p[i].
37                    second/w))].push_back(p[i]);
38
39 int main()
40 {
41     int t;
42     scanf("%d",&t);
43     for (int ft = 1;ft <= t;ft++)
44     {
45         scanf("%d",&n);
46         for (int i = 0;i < n;i++)
47         {
48             scanf("%lf%lf",&tx,&ty);
49             p[i] = make_pair(tx,ty);
50         }
51         random_shuffle(p,p+n);
52         ans = CalcDis(p[0],p[1],p[2]);
53         build(3,ans/2.0);
54         for (int i = 3;i < n;i++)
55         {
56             x = (int)floor(2.0*p[i].first/ans);
57             y = (int)floor(2.0*p[i].second/ans);
58             tmp.clear();
59             for (int k = 0;k < 9;k++)
60             {
61                 nx = x+step[k][0];
62                 ny = y+step[k][1];
63                 gird = make_pair(nx,ny);
64                 if (g.find(gird) != g.end())
65                 {
66                     op = g[gird].begin();
67                     ed = g[gird].end();
68                     for (it = op;it != ed;it++)
69                         tmp.push_back(*it);
70                 }
71             }
72             flag = false;

```

```

73         for (int j = 0; j < tmp.size(); j++)
74             for (int k = j+1; k < tmp.size(); k++)
75                 {
76                     nowans = CalcDis(p[i], tmp[j], tmp[k]);
77                     if (nowans < ans)
78                         {
79                             ans = nowans;
80                             flag = true;
81                         }
82                 }
83         if (flag == true)
84             build(i+1, ans/2.0);
85         else
86             g[make_pair((int)floor(2.0*p[i].first/ans), (int)
87                         floor(2.0*p[i].second/ans))].push_back(p[i]);
88     }
89     printf("%.3f\n", ans);
90 }

```

7.13 多圆面积并

7.13.1 去重

有时候可能需要去掉不需要的圆

```

1  for (int i = 0; i < n; i++)
2  {
3      scanf("%lf%lf%lf", &c[i].c.x, &c[i].c.y, &c[i].r);
4      del[i] = false;
5  }
6  for (int i = 0; i < n; i++)
7      if (del[i] == false)
8          {
9              if (c[i].r == 0.0) del[i] = true;
10             for (int j = 0; j < n; j++)
11                 if (i != j)
12                     if (del[j] == false)
13                         if (cmp(Point(c[i].c, c[j].c).Len()+c[i].r, c[j]
14                             ].r) <= 0)
15                             del[i] = true;
16         }
17     tn = n;
18     n = 0;
19     for (int i = 0; i < tn; i++)
20         if (del[i] == false)
21             c[n++] = c[i];

```

7.13.2 圆并

$ans[i]$ 表示被覆盖*i*次的面积

```

1  const double pi = acos(-1.0);
2  const double eps = 1e-8;
3  struct Point

```

```

4 {
5     double x,y;
6     Point(){}
7     Point(double _x,double _y)
8     {
9         x = _x;
10        y = _y;
11    }
12    double Length()
13    {
14        return sqrt(x*x+y*y);
15    }
16 };
17 struct Circle
18 {
19     Point c;
20     double r;
21 };
22 struct Event
23 {
24     double tim;
25     int typ;
26     Event(){}
27     Event(double _tim,int _typ)
28     {
29         tim = _tim;
30         typ = _typ;
31     }
32 };
33
34 int cmp(const double& a,const double& b)
35 {
36     if (fabs(a-b) < eps)    return 0;
37     if (a < b)    return -1;
38     return 1;
39 }
40
41 bool Eventcmp(const Event& a,const Event& b)
42 {
43     return cmp(a.tim,b.tim) < 0;
44 }
45
46 double Area(double theta,double r)
47 {
48     return 0.5*r*r*(theta-sin(theta));
49 }
50
51 double xmult(Point a,Point b)
52 {
53     return a.x*b.y-a.y*b.x;
54 }
55

```

```

56 int n,cur,tote;
57 Circle c[1000];
58 double ans[1001],pre[1001],AB,AC,BC,theta,fai,a0,a1;
59 Event e[4000];
60 Point lab;
61
62 int main()
63 {
64     while (scanf("%d",&n) != EOF)
65     {
66         for (int i = 0;i < n;i++)
67             scanf("%lf%lf%lf",&c[i].c.x,&c[i].c.y,&c[i].r);
68         for (int i = 1;i <= n;i++)
69             ans[i] = 0.0;
70         for (int i = 0;i < n;i++)
71         {
72             tote = 0;
73             e[tote++] = Event(-pi,1);
74             e[tote++] = Event(pi,-1);
75             for (int j = 0;j < n;j++)
76                 if (j != i)
77                 {
78                     lab = Point(c[j].c.x-c[i].c.x,c[j].c.y-c[i].c
79                         .y);
80                     AB = lab.Length();
81                     AC = c[i].r;
82                     BC = c[j].r;
83                     if (cmp(AB+AC,BC) <= 0)
84                     {
85                         e[tote++] = Event(-pi,1);
86                         e[tote++] = Event(pi,-1);
87                         continue;
88                     }
89                     if (cmp(AB+BC,AC) <= 0) continue;
90                     if (cmp(AB,AC+BC) > 0) continue;
91                     theta = atan2(lab.y,lab.x);
92                     fai = acos((AC*AC+AB*AB-BC*BC)/(2.0*AC*AB));
93                     a0 = theta-fai;
94                     if (cmp(a0,-pi) < 0) a0 += 2*pi;
95                     a1 = theta+fai;
96                     if (cmp(a1,pi) > 0) a1 -= 2*pi;
97                     if (cmp(a0,a1) > 0)
98                     {
99                         e[tote++] = Event(a0,1);
100                         e[tote++] = Event(pi,-1);
101                         e[tote++] = Event(-pi,1);
102                         e[tote++] = Event(a1,-1);
103                     }
104                     else
105                     {
106                         e[tote++] = Event(a0,1);
107                         e[tote++] = Event(a1,-1);

```

```

107         }
108     }
109     sort(e,e+tote,Eventcmp);
110     cur = 0;
111     for (int j = 0;j < tote;j++)
112     {
113         if (cur != 0 && cmp(e[j].tim,pre[cur]) != 0)
114         {
115             ans[cur] += Area(e[j].tim-pre[cur],c[i].r);
116             ans[cur] += xmult(Point(c[i].c.x+c[i].r*cos(
117                                     Point(c[i].c.x+c[i].r*cos
118                                         (e[j].tim),c[i].c.y+c[
119                                         i].r*sin(e[j].tim)))
120                                     /2.0;
121             }
122             cur += e[j].typ;
123             pre[cur] = e[j].tim;
124         }
125     }
126     for (int i = 1;i < n;i++)
127         ans[i] -= ans[i+1];
128     for (int i = 1;i <= n;i++)
129         printf("[%d]_=%.3f\n",i,ans[i]);
130 }
131 return 0;
132 }

```

7.14 一个圆与多边形面积交

```

1 bool InCircle(Point a,double r)
2 {
3     return cmp(a.x*a.x+a.y*a.y,r*r) <= 0; //这里判断的时候EPS一定不要
      太小!!
4 }
5
6 double CalcArea(Point a,Point b,double r)
7 {
8     Point p[4];
9     int tot = 0;
10    p[tot++] = a;
11
12    Point tv = Point(a,b);
13    Line tmp = Line(Point(0,0),Point(tv.y,-tv.x));
14    Point near = LineToLine(Line(a,b),tmp);
15    if (cmp(near.x*near.x+near.y*near.y,r*r) <= 0)
16    {
17        double A,B,C;
18        A = near.x*near.x+near.y*near.y;
19        C = r;
20        B = C*C-A;
21        double tvl = tv.x*tv.x+tv.y*tv.y;

```

```

22     double tmp = sqrt(B/tv1); //这样做只用一次开根
23     p[tot] = Point(near.x+tmp*tv.x,near.y+tmp*tv.y);
24     if (OnSeg(Line(a,b),p[tot]) == true) tot++;
25     p[tot] = Point(near.x-tmp*tv.x,near.y-tmp*tv.y);
26     if (OnSeg(Line(a,b),p[tot]) == true) tot++;
27 }
28 if (tot == 3)
29 {
30     if (cmp(Point(p[0],p[1]).Length(),Point(p[0],p[2]).Length
31           ()) > 0)
32         swap(p[1],p[2]);
33 }
34 p[tot++] = b;
35 double res = 0.0,theta,a0,a1,sgn;
36 for (int i = 0;i < tot-1;i++)
37 {
38     if (InCircle(p[i],r) == true && InCircle(p[i+1],r) ==
39         true)
40     {
41         res += 0.5*xmult(p[i],p[i+1]);
42     }
43     else
44     {
45         a0 = atan2(p[i+1].y,p[i+1].x);
46         a1 = atan2(p[i].y,p[i].x);
47         if (a0 < a1) a0 += 2*pi;
48         theta = a0-a1;
49         if (cmp(theta,pi) >= 0) theta = 2*pi-theta;
50         sgn = xmult(p[i],p[i+1])/2.0;
51         if (cmp(sgn,0) < 0) theta = -theta;
52         res += 0.5*r*r*theta;
53     }
54 }
55 return res;
56 }

```

调用

```

1 area2 = 0.0;
2 for (int i = 0;i < resn;i++) //遍历每条边,按照逆时针
3     area2 += CalcArea(p[i],p[(i+1)%resn],r);

```

7.15 精度问题

7.15.1 浮点数为啥会有精度问题

浮点数(以C/C++为准),一般用的较多的是float、double。

8 搜索

8.1 Dancing Links

仰慕罗神。

```
1 void remove1(int col)
2 {
3     int i,j;
4     L[R[col]]=L[col];
5     R[L[col]]=R[col];
6     for(i=D[col];i!=col;i=D[i])
7     {
8         L[R[i]]=L[i];
9         R[L[i]]=R[i];
10    }
11 }
12 void remove2(int col)
13 {
14     int i,j;
15     L[R[col]]=L[col];
16     R[L[col]]=R[col];
17     for(i=D[col];i!=col;i=D[i])
18     {
19         for(j=R[i];j!=i;j=R[j])
20         {
21             U[D[j]]=U[j];
22             D[U[j]]=D[j];
23             --nk[C[j]];
24         }
25     }
26 }
27 void resume1(int col)
28 {
29     int i,j;
30     for(i=U[col];i!=col;i=U[i])
31     {
32         L[R[i]]=i;
33         R[L[i]]=i;
34     }
35     L[R[col]]=col;
36     R[L[col]]=col;
37 }
38 void resume2(int col)
39 {
40     int i,j;
41     for(i=U[col];i!=col;i=U[i])
42     {
43         for(j=L[i];j!=i;j=L[j])
44         {
45             ++nk[C[j]];
46             U[D[j]]=j;
```

```

47         D[U[j]]=j;
48     }
49 }
50 L[R[col]]=col;
51 R[L[col]]=col;
52 }
53 int h()
54 {
55     bool vis[100];
56     memset(vis,false,sizeof(vis));
57     int i,j,k,res=0,mi,col;
58     while(1)
59     {
60         mi=inf;
61         for(i=R[head];i!=head&&i<=2*n;i=R[i])
62             if(mi>nk[i]&&!vis[i])
63             {
64                 mi=nk[i];
65                 col=i;
66             }
67         if(mi==inf)
68             break;
69         res++;vis[col]=true;
70         for(j=D[col];j!=col;j=D[j])
71             for(k=R[j];k!=j;k=R[k])
72             {
73                 if(C[k]>2*n)
74                     continue;
75                 vis[C[k]]=true;
76             }
77     }
78     return res;
79 }
80 bool DLX(int d,int deep)
81 {
82     if(d+h(>deep) return false;
83     if(R[head]==head||R[head]>2*n)
84         return true;
85     if(d>=deep)
86         return false;
87     int col,ma=inf;
88     int i,j;
89     for(i=R[head];i!=head&&i<=2*n;i=R[i])
90         if(nk[i]<ma)
91         {
92             col=i;
93             ma=nk[i];
94         }
95     remove1(col);
96     for(i=D[col];i!=col;i=D[i])
97     {
98         int flag=1;

```

```

99         for(j=R[i];;j=R[j])
100     {
101         if(j==R[i]&&!flag)
102             break;
103         U[D[j]]=U[j];
104         D[U[j]]=D[j];
105         if(C[j]>2*n)
106             remove2(C[j]);
107         else
108             remove1(C[j]);
109         flag=0;
110     }
111     if(DLX(d+1,deep))
112         return true;
113     flag=1;
114     for(j=L[i];;j=L[j])
115     {
116         if(j==L[i]&&!flag)
117             break;
118         if(C[j]>2*n)
119             resume2(C[j]);
120         else
121             resume1(C[j]);
122         U[D[j]]=j;
123         D[U[j]]=j;
124         flag=0;
125     }
126 }
127 resume1(col);
128 return false;
129 }

```

9 杂物

9.1 高精度数

支持乘以整数和加法。

```
1 struct BigInt
2 {
3     const static int mod = 1000000000;
4     int a[600], len;
5     BigInt (){}
6     BigInt (int v)
7     {
8         len = 0;
9         do
10        {
11            a[len++] = v%mod;
12            v /= mod;
13        }while(v);
14    }
15    BigInt operator *(const int& b) const
16    {
17        BigInt res;
18        res.len = len;
19        for (int i = 0; i <= len; ++i)
20            res.a[i] = 0;
21        for (int i = 0; i < len; ++i)
22        {
23            res.a[i] += a[i]*b;
24            res.a[i+1] += res.a[i]/mod;
25            res.a[i] %= mod;
26        }
27        if (res.a[len] > 0) res.len++;
28        return res;
29    }
30    BigInt operator +(const BigInt& b) const
31    {
32        BigInt res;
33        res.len = max(len, b.len);
34        for (int i = 0; i <= res.len; ++i)
35            res.a[i] = 0;
36        for (int i = 0; i < res.len; ++i)
37        {
38            res.a[i] += ((i < len)?a[i]:0)+((i < b.len)?b.a[i]:0)
39                ;
40            res.a[i+1] += res.a[i]/mod;
41            res.a[i] %= mod;
42        }
43        if (res.a[res.len] > 0) res.len++;
44        return res;
45    }
46    void output()
```

```

46     {
47         printf("%d",a[len-1]);
48         for (int i = len-2; i >= 0; --i)
49             printf("%08d",a[i]);
50         printf("\n");
51     }
52 };

```

9.2 整数外挂

```

1  int wg;
2  char ch;
3  bool ng;
4
5  inline int readint()
6  {
7      ch = getchar();
8      while (ch != '-' && (ch < '0' || ch > '9')) ch = getchar();
9      if (ch == '-')
10     {
11         ng = true;
12         ch = getchar();
13     }
14     else
15         ng = false;
16     wg = ch-'0';
17     ch = getchar();
18     while (ch >= '0' && ch <= '9')
19     {
20         wg = wg*10+ch-'0';
21         ch = getchar();
22     }
23     if (ng == true) wg = -wg;
24     return wg;
25 }

```

9.3 Java

9.3.1 IO

9.3.2 优先队列

```

1  PriorityQueue queue = new PriorityQueue( 1, new Comparator()
2  {
3      public int compare( Point a, Point b )
4      {
5          if( a.x < b.x || a.x == b.x && a.y < b.y )
6              return -1;
7          else if( a.x == b.x && a.y == b.y )
8              return 0;
9          else
10             return 1;
11     }

```

```
12 | });
```

9.3.3 Map

```
1 | Map map = new HashMap();
2 | map.put("sa","dd");
3 | String str = map.get("sa").toString;
4 |
5 | for(Object obj : map.keySet()){
6 |     Object value = map.get(obj );
7 | }
```

9.3.4 sort

```
1 | static class cmp implements Comparator
2 | {
3 |     public int compare(Object o1,Object o2)
4 |     {
5 |         BigInteger b1=(BigInteger)o1;
6 |         BigInteger b2=(BigInteger)o2;
7 |         return b1.compareTo(b2);
8 |     }
9 | }
10 | public static void main(String[] args) throws IOException
11 | {
12 |     Scanner cin = new Scanner(System.in);
13 |     int n;
14 |     n=cin.nextInt();
15 |     BigInteger[] seg = new BigInteger[n];
16 |     for (int i=0;i<n;i++)
17 |         seg[i]=cin.nextBigInteger();
18 |     Arrays.sort(seg,new cmp());
19 | }
```

9.4 hashmap

```
1 | struct hash_map
2 | {
3 |     const static int mod=10007;
4 |     int head[mod];
5 |     struct hash_tables
6 |     {
7 |         int key;
8 |         int val;
9 |         int next;
10 |     } ele[10007];
11 |     int N;
12 |     int getHash(int x)
13 |     {
14 |         return x%mod;
15 |     }
16 |     void init()
17 |     {
18 |         memset(head,255,sizeof(head));
```

```

19         N=0;
20     }
21     void clear()
22     {
23         for (int i = 0; i < N; i++)
24             head[getHash(ele[i].key)] = -1;
25         N = 0;
26     }
27     int fint(int x)
28     {
29         for (int i=head[getHash(x)]; i!=-1; i=ele[i].next)
30             if (ele[i].key==x) return i;
31         return -1;
32     }
33     void insert(int x)
34     {
35         int tmp=getHash(x);
36         ele[N].key=x;
37         ele[N].val=0;
38         ele[N].next=head[tmp];
39         head[tmp]=N++;
40     }
41     int& operator [] (int x)
42     {
43         int tmp=fint(x);
44         if (tmp!=-1)
45         {
46             insert(x);
47             return ele[N-1].val;
48         }
49         else
50             return ele[tmp].val;
51     }
52 };

```

9.5 C++&STL常用函数

9.5.1 lower_bound/upper_bound

不解释

```

1 | iterator lower_bound(const key_type &key )\\返回一个迭代器，指向键值>=
   | key的第一个元素。
2 | iterator upper_bound(const key_type &key )\\返回一个迭代器，指向键值>
   | key的第一个元素。
3
4 | #include <iostream>
5 | #include <algorithm>
6 | #include <vector>
7 | using namespace std;
8
9 | int main () {
10 |     int myints[] = {10,20,30,30,20,10,10,20};

```

```

11 | vector<int> v(myints,myints+8);           // 10 20 30 30 20 10
    |    10 20
12 | vector<int>::iterator low,up;
13 |
14 | sort (v.begin(), v.end());               // 10 10 10 20 20 20
    |    30 30
15 |
16 | low=lower_bound (v.begin(), v.end(), 20); //
17 | up= upper_bound (v.begin(), v.end(), 20); //
    |    ^
18 |
19 | cout << "lower_bound at position " << int(low- v.begin()) <<
    |    endl;
20 | cout << "upper_bound at position " << int(up - v.begin()) <<
    |    endl;
21 |
22 | return 0;
23 | }

```

Output:

```

1 | lower_bound at position 3
2 | upper_bound at position 6

```

9.5.2 rotate

把数组后一半搬到前面

```

1 | template <class ForwardIterator>
2 |     void rotate ( ForwardIterator first, ForwardIterator middle,
3 |                   ForwardIterator last );

```

9.5.3 nth_element

```

1 | template <class RandomAccessIterator>
2 |     void nth_element ( RandomAccessIterator first,
    |                      RandomAccessIterator nth,
3 |                      RandomAccessIterator last );
4 |
5 | template <class RandomAccessIterator, class Compare>
6 |     void nth_element ( RandomAccessIterator first,
    |                      RandomAccessIterator nth,
7 |                      RandomAccessIterator last, Compare comp );

```

9.5.4 bitset

取用

```

1 | bitset<4> mybits;
2 |
3 | mybits[1]=1;           // 0010
4 | mybits[2]=mybits[1];   // 0110

```


翻转

```
1 | bitset<4> mybits (string("0001"));
2 |
3 | cout << mybits.flip(2) << endl;      // 0101
4 | cout << mybits.flip() << endl;      // 1010
```

运算

```
1 | bitset<4> first (string("1001"));
2 | bitset<4> second (string("0011"));
3 |
4 | cout << (first^=second) << endl;      // 1010 (XOR, assign)
5 | cout << (first&=second) << endl;      // 0010 (AND, assign)
6 | cout << (first|=second) << endl;      // 0011 (OR, assign)
7 |
8 | cout << (first<=2) << endl;           // 1100 (SHL, assign)
9 | cout << (first>>=1) << endl;          // 0110 (SHR, assign)
10 |
11 | cout << (~second) << endl;            // 1100 (NOT)
12 | cout << (second<<1) << endl;          // 0110 (SHL)
13 | cout << (second>>1) << endl;          // 0001 (SHR)
14 |
15 | cout << (first==second) << endl;      // false (0110==0011)
16 | cout << (first!=second) << endl;      // true  (0110!=0011)
17 |
18 | cout << (first&second) << endl;        // 0010
19 | cout << (first|second) << endl;        // 0111
20 | cout << (first^second) << endl;        // 0101
```

9.5.5 multimap

遍历

```
1 | multimap<char,int> mymm;
2 | multimap<char,int>::iterator it;
3 | char c;
4 |
5 | mymm.insert(pair<char,int>('x',50));
6 | mymm.insert(pair<char,int>('y',100));
7 | mymm.insert(pair<char,int>('y',150));
8 | mymm.insert(pair<char,int>('y',200));
9 | mymm.insert(pair<char,int>('z',250));
10 | mymm.insert(pair<char,int>('z',300));
11 |
12 | for (c='x'; c<='z'; c++)
13 | {
14 |     cout << "There are " << (int)mymm.count(c);
15 |     cout << " elements with key " << c << ":";
16 |     for (it=mymm.equal_range(c).first; it!=mymm.equal_range(c).
17 |         second; ++it)
18 |         cout << " " << (*it).second;
```

```

18     cout << endl;
19 }
20 /*
21 Output:
22
23 There are 1 elements with key x: 50
24 There are 3 elements with key y: 100 150 200
25 There are 2 elements with key z: 250 300
26 */

```

二分查找

```

1  multimap<char,int> mymultimap;
2  multimap<char,int>::iterator it,itlow,itup;
3
4  mymultimap.insert(pair<char,int>('a',10));
5  mymultimap.insert(pair<char,int>('b',121));
6  mymultimap.insert(pair<char,int>('c',1001));
7  mymultimap.insert(pair<char,int>('c',2002));
8  mymultimap.insert(pair<char,int>('d',11011));
9  mymultimap.insert(pair<char,int>('e',44));
10
11 itlow=mymultimap.lower_bound ('b');    // itlow points to b
12 itup=mymultimap.upper_bound ('d');    // itup points to e (not d)
13
14 // print range [itlow,itup):
15 for ( it=itlow ; it != itup; it++ )
16     cout << (*it).first << "=>" << (*it).second << endl;
17
18 /*
19 Output:
20
21 b => 121
22 c => 1001
23 c => 2002
24 d => 11011
25 */

```

删除

```

1  multimap<char,int> mymultimap;
2  multimap<char,int>::iterator it;
3
4  // insert some values:
5  mymultimap.insert(pair<char,int>('a',10));
6  mymultimap.insert(pair<char,int>('b',20));
7  mymultimap.insert(pair<char,int>('b',30));
8  mymultimap.insert(pair<char,int>('c',40));
9  mymultimap.insert(pair<char,int>('d',50));
10 mymultimap.insert(pair<char,int>('d',60));
11 mymultimap.insert(pair<char,int>('e',70));
12 mymultimap.insert(pair<char,int>('f',80));
13

```

```

14 | it=mymultimap.find('b');
15 | mymultimap.erase (it); // erasing by iterator
    | (1 element)
16 |
17 | mymultimap.erase ('d'); // erasing by key (2
    | elements)
18 |
19 | it=mymultimap.find ('e');
20 | mymultimap.erase ( it, mymultimap.end() ); // erasing by range
21 |
22 | // show content:
23 | for ( it=mymultimap.begin() ; it != mymultimap.end(); it++ )
24 |     cout << (*it).first << "=>" << (*it).second << endl;
25 |
26 | /*
27 | Output:
28 |
29 | a => 10
30 | b => 30
31 | c => 40
32 | */

```

9.6 其它

9.6.1 对跑脚本

```

1 | while true; do
2 |     ./gen > input
3 |     ./sol < input > output.sol
4 |     ./bf < input > output.bf
5 |
6 |     diff output.sol output.bf
7 |     if [ $? -ne 0 ] ; then break; fi
8 | done

```

9.6.2 枚举长为 n 含 k 个1的01串

```

1 | int n = 5,k = 3;
2 | for (int s = (1 << k)-1,u = 1 << n; s < u;)
3 | {
4 |     for (int i = 0;i < n;i++)
5 |         printf("%d",(((s>>(n-1-i))&1) == 1));
6 |     printf("\n");
7 |
8 |     int b = s & -s;
9 |     s = (s+b)|(((s^(s+b))>>2)/b);
10 | }

```